


Epitax Adjustable

ADJUSTABLE


EPI-RRWH-A-...-SP... Delivered Lumens - Spot			
		Diameter [Wattage]	
		25 [8 CC]	35 [15 CC]
CCT	92-27-	501	-
	92-30-	536	-
	92-35-	536	-
	92-40-	578	-
Polar Plot / Cone Of Light Multiplier			
		25 [8 CC]	35 [15 CC]
		1.00	-
UGR (3K)			
		25 [8 CC]	35 [15 CC]
		14.2	-



Beam Angle (0-180) = 14.6°
Beam Angle (90-270) = 15.0°

CONE OF LIGHT - 8W 3000K Spot EPI-RRWH-A-25-8-CC-92-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	1139	0.5
4	285	1.0
6	127	1.5
8	71	2.0
10	46	2.6
12	32	3.1
14	23	3.6
16	18	4.1
18	14	4.6
20	11	5.1


EPI-RRWH-A-...-NFL... Delivered Lumens - Narrow Flood			
		Diameter [Wattage]	
		25 [8 CC]	35 [15 CC]
CCT	92-27-	-	1110
	92-30-	-	1187
	92-35-	-	1187
	92-40-	-	1276
Polar Plot / Cone Of Light Multiplier			
		25 [8 CC]	35 [15 CC]
		-	1.00
UGR (3K)			
		25 [8 CC]	35 [15 CC]
		-	13.0



Beam Angle (0-180) = 23.4°
Beam Angle (90-270) = 23.0°

CONE OF LIGHT - 15W 3000K Narrow Flood EPI-RRWH-A-35-15-CC-92-30-NFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	1272	0.8
4	318	1.7
6	141	2.5
8	80	3.3
10	51	4.1
12	35	5.0
14	26	5.8
16	20	6.6
18	16	7.5
20	13	8.3


EPI-RRWH-A-...-FL... Delivered Lumens - Flood			
		Diameter [Wattage]	
		25 [8 CC]	35 [15 CC]
CCT	92-27-	412	1021
	92-30-	441	1092
	92-35-	441	1092
	92-40-	476	1175
Polar Plot / Cone Of Light Multiplier			
		25 [8 CC]	35 [15 CC]
		0.40	1.00
UGR (3K)			
		25 [8 CC]	35 [15 CC]
		16.8	15.9



Beam Angle (0-180) = 36.6°
Beam Angle (90-270) = 36.4°

CONE OF LIGHT - 15W 3000K Flood EPI-RRWH-A-35-15-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	599	1.3
4	150	2.6
6	67	4.0
8	37	5.3
10	24	6.6
12	17	7.9
14	12	9.3
16	9	10.6
18	7	11.9
20	6	13.2

EPI-RRWH-A-...-WFL... Delivered Lumens - Wide Flood			
		Diameter [Wattage]	
		25 [8 CC]	35 [15 CC]
CCT	92-27-	424	962
	92-30-	454	1029
	92-35-	454	1029
	92-40-	491	1107
Polar Plot / Cone Of Light Multiplier			
		25 [8 CC]	35 [15 CC]
		0.44	1.00
UGR (3K)			
		25 [8 CC]	35 [15 CC]
		19.6	19.5



Beam Angle (0-180) = 56.0°
Beam Angle (90-270) = 55.6°

CONE OF LIGHT - 15W 3000K Wide Flood EPI-RRWH-A-35-15-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	303	2.1
4	76	4.3
6	34	6.4
8	19	8.5
10	12	10.6
12	8	12.8
14	6	14.9
16	5	17.0
18	4	19.1
20	3	21.3

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

** Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.