


Warp_RJ | Downlight | powerLED | Damp Location | Driver remote | Adjustable | 8W 700mA



Balance - CRI 92

White	E81258	2700 K	689 lm	M	Spot	15
Black	E81259	3000 K	738 lm	W	Medium Flood	30
		3500 K	738 lm	T	Flood	60
		4000 K	796 lm	N		

Efficiency - CRI 80

White	E81260	2700 K	854 lm	M	Spot	15
Black	E81261	3000 K	854 lm	W	Medium Flood	30
		3500 K	854 lm	T	Flood	60
		4000 K	922 lm	N		

Power supply options (remote only)

ECO30W-700

0-10V EldoLED ECOdrive
30W for 1-3 fixtures


SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1-4 fixtures

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-8 fixtures

Warp_RJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 15W 400mA



Balance - CRI 92

White	E81262	2700 K	1568 lm	M	Spot	15
Black	E81263	3000 K	1677 lm	W	Medium Flood	30
		3500 K	1677 lm	T	Flood	60
		4000 K	1904 lm	N		

Efficiency - CRI 80

White	E81264	2700 K	1932 lm	M	Spot	15
Black	E81265	3000 K	1932 lm	W	Medium Flood	30
		3500 K	1932 lm	T	Flood	60
		4000 K	2078 lm	N		

Power supply options (remote only)

ECO30W-400

0-10V EldoLED ECOdrive
30W for 1 fixtures

SOLO50W-400

0-10V EldoLED SOLOdrive
50W for 1-2 fixtures

SOLO100W-400

0-10V EldoLED SOLOdrive
100W for 1-4 fixtures

technical
information