apache





The Apache standardized design in civil engineering is a source of inspiration for Studio RIGO for creative re-elaboration. The rigidity of the original profile is transformed into a bollard with minimal and curvy design with an entirely innovative emission: the source is positioned at the upper part of the product, facing downwards to create an asymmetric beam which eliminates glaring, generating a harmonic and efficient diffusion while maintaining integration in the architectural space at the same time.


Materials

Metal body with polyester powder coating and protective surface pre-treatment Transparent polycarbonate diffuser



Apache | Bollards | powerLED | Wet location | Driver remote | 7W





CRI 80

| BK Grey E64262 | 3000 K | 935 lm | W | General | 00 |
|-----------------------|--------|--------|---|---------|----|
| Gr BK E64263 | 4000 K | 978 lm | N | | |
| Cor-Ten E64264 | | | | | |
| Sand E64265 | | | | | |

Power supply options (remote only)

| Tower supply options (remote only) | | | | |
|---|---|--|--|--|
| ECO30W-180 | SOL050W-180 | SOL0100W-180 | | |
| 0-10V EldoLED ECOdrive 30W for 1 fixture | 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures | 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures | | |






E64210 Tie rods

Apache | Bollards | powerLED | Wet location | Driver remote | 9W





CRI 80

| BK Grey E64266 | 3000 K | 1207 lm | W | General | 00 |
|-----------------------|--------|---------|---|---------|----|
| Gr BK E64267 | 4000 K | 1266 lm | N | | |
| Cor-Ten E64268 | | | | | |
| Sand E64269 | _ | | | | |

Power supply options (remote only)

| ECO30W-220 | SOL050W-220 | SOL0100W-220 |
|------------------------|-------------------------|-------------------------|
| 0-10V EldoLED ECOdrive | 0-10V EldoLED SOLOdrive | 0-10V EldoLED SOLOdrive |
| 30W for 1 fixture | 50W for 1-2 fixtures | 100W for 1-4 fixtures |

Accessories




E64210 Tie rods

Bollards inter-lux.com 458



Apache | Bollards | powerLED | Wet location | Driver remote | 7W





CRI 80

| BK Grey E81972 | 3000 K | 935 lm | W | General | 00 |
|-----------------------|--------|--------|---|---------|----|
| Gr BK E81973 | 4000 K | 978 lm | N | | |
| Cor-Ten E81974 | | | | | |
| Sand E81975 | | | | | |

Power supply options (remote only)

| EC030W-180 | SOL050W-180 | SOL0100W-180 |
|------------------------|-------------------------|-------------------------|
| 0-10V EldoLED ECOdrive | 0-10V EldoLED SOLOdrive | 0-10V EldoLED SOLOdrive |
| 30W for 1 fixture | 50W for 1-2 fixtu es | 100W for 1-4 fixtu es |


Accessories



Tie rods

Apache | Bollards | powerLED | Wet location | Driver remote | 9W





CRI 80

| BK Grey E81976 | 3000 K | 1207 lm |
|-----------------------|--------|---------|
| Gr BK E81977 | 4000 K | 1266 lm |
| Cor-Ten E81978 | | |
| Sand E81979 | _ | |

Power supply options (remote only)

EC030W-220 SOL050W-220 SOL0100W-220 0-10V EldoLED SOLOdrive 0-10V EldoLED ECOdrive 0-10V EldoLED SOLOdrive 30W for 1 fixture 50W for 1-2 fixtu es 100W for 1-4 fixtu es

W

N

General

00

Accessories



459 inter-lux.com MAESTRO 2.0