

Archiline Stainless Steel Frame



General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (15 µm), Black finish
Trim: 316 Marine Grade Stainless Steel, Brushed. Extra clear glass - Tempered
Mounting/Housing: Galvanized Steel (required for in ground installations).
Drive-over: Walk-Over only.
Dimensions/Weight: 14.8" (3.31 lbs) – 22.2" (6.17 lbs) – 41.6" (10.6 lbs)

Driver: Integral 120-277V 5% 0-10V dimming, or Non-Dim.
Wattages: 15W (14.8") – 22W (22.2") – 44W (41.6")
Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).
Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.
IK rating: IK 10
ETL Certification: ETL, wet location

Optics: Fixed. Available in Narrow Spot – Spot – Flood – Wide Flood – Elliptic, Asymmetric Wall Washer. Most variants are also available with Dark Light (Anti-glare) system.
Color temperatures: 2700K – 3000K – 3500K – 4000K.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



14.8" (15W)
22.2" (22W)
41.6" (44W)

Delivered Lumens (Fixed + Adjustable)*	14.8"	22.2"	41.6"
Narrow Spot	1038	1545	2977
Spot	1048	1572	3185
Flood	974	1557	3067
Wide Flood	1085	1630	3363
Elliptic/Grazer	1009	1587	3176
Asymm/Wall Washer	1174	1779	3634

*Values shown for 3000K

Delivered Lumens (Dark Light)*	14.8"	22.2"	41.6"
Spot	783	1295	2578
Flood	702	1214	2509
Wide Flood	845	1439	2603
Elliptical	857	1508	2948

*Values shown for 3000K


Ordering Information									
AR	RSF				ID				
Product	Mounting/Frame	Type	Length	Wattage	Operation	Color Temp	Optic	+	Housing (Required) ² Cables ²
AR = Archiline	RSF = Recessed Stainless Steel Frame	F = Fixed FDL = Fixed DarkLight A = Adjustable	15 = 14.8"	15 = 15W	ID = Integral (0-10V dim)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	NSP = Narrow Spot ¹ SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer WW = Wall Washer ¹		E98671 (15) E98672 (22) E98673 (42)
			22 = 22.2"	22 = 22W					
			42 = 41.6"	44 = 44W					

¹ Not available for FDL

² See page 2



14.8" 15W ID




HOUSING

E98671
Outer Housing



22.2" 22W ID




HOUSING

E98672
Outer Housing



41.6" 44W ID



HOUSING

E98673
Outer Housing



Cables 0-10V

E99826	E99822	E99823	E99824	E99825
39.4" power supply cable +0-10V dimming F 5 pin	196.9" power supply cable +0-10V dimming F 5 pin	39.4" extension cable for power +0-10V dimming M+F 5 pin	196.9" extension cable for power +0-10V dimming M+F 5 pin	393.7 in extension cable for power +0-10V dimming M+F 5 pin