

cicada




Outdoor wall light available in single- or double-beam versions, with a choice of five optics to emphasise architectural details. Special black screenprinted glass reduces glare, while AquaStop® technology provides maximum durability.

Materials

Aluminum body

Cicada Single emission | Wall light | powerLED | Wet location | Driver remote | 6W 630mA



CRI 80


White	E97290	2700 K	657 lm	M	Spot	15
Black	E97291	3000 K	699 lm	W	Medium Flood	30
Grey	E97292	4000 K	747 lm	N	Flood	60
DarkBrown	E81355				Asymmetric	25
					General	00

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures



Cicada Double emission | Wall light | powerLED | Wet location | Driver remote | 12W 630mA



CRI 80


White	E97293	2700 K	1314 lm	M	Spot	15
Black	E97294	3000 K	1398 lm	W	Medium Flood	30
Grey	E97295	4000 K	1494 lm	N	Flood	60
DarkBrown	E81356				Asymmetric	25
					General	00

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures



Cicada Single emission | Wall light | powerLEDs | Wet location | Driver remote | 12W 630mA



CRI 80


White	E97302	2700 K	1314 lm	M	Spot	15
Black	E97303	3000 K	1398 lm	W	Medium Flood	30
Grey	E97304	4000 K	1494 lm	N	Flood	60
DarkBrown	E81357				Asymmetric	25
					General	00

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures



Cicada Double emission | Wall light | powerLEDs | Wet location | Driver remote | 24W 630mA



CRI 80

White	E97305	2700 K	2628 lm	M	Spot	15
Black	E97306	3000 K	2796 lm	W	Medium Flood	30
Grey	E97307	4000 K	2988 lm	N	Flood	60
DarkBrown	E81358				Asymmetric	25
					General	00

Power supply options (remote only)

SOLO50W-630	SOLO100W-630
0-10V EldoLED SOLOdrive 50W for 1 fixture	0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

