



Luminaire		Measurem.		Source	
Code	64794W07 X=-90 Z=0.29	Code	1	Code	LED Array Citizen
Name	Peak - Terreno - Finitura:RAL 9006 goffrato - mono	Name	Peak - Terreno - Finitura:RAL 9006 goffrato - mono	Name	Peak - Terreno - Finitura:RAL 9006 goffrato - mono
Line	Eulmdat	Date	17-10-2016	Position	
Luminaire Flux	575 lm	Luminaire Power	8.0 W	Efficacy	71.875 lm/W
Source Flux	575 lm	Maximum value	782.93 cd/klm	Position	C=85.00 G=45.00
				CG	Asymmetrical

US ROAD STANDARDS



Luminaire Classification System (LCS)			
LCS Zone		Lumens	%Lamp
FL	0° -- 30°	57.7 lm	10.0 %
FM	30° -- 60°	319.0 lm	55.5 %
FH	60° -- 80°	171.5 lm	29.8 %
FVH	80° -- 90°	5.2 lm	0.9 %
BL	0° -- 30°	7.9 lm	1.4 %
BM	30° -- 60°	8.6 lm	1.5 %
BH	60° -- 80°	4.4 lm	0.8 %
BVH	80° -- 90°	0.7 lm	0.1 %
UL	90° -- 100°	0.0 lm	0.0 %
UH	100° -- 180°	0.0 lm	0.0 %
TOTALS		575.0 lm	100.0 %
BUG B0 U0 G0 Type IV Very Short Asymmetrical			