



Luminaire		Measurem.		Source	
Code	64788N07	Code	1	Code	LED Array Citizen
Name	Peak - Terreno - Finitura:RAL 9006 goffrato - monoenergetico	Name	Peak - Terreno - Finitura:RAL 9006 goffrato - monoenergetico	Name	Peak - 11W
Line	Eulmdat	Date	13-04-2016	Position	
Luminaire Flux	555 lm	Luminaire Power	11.0 W	Efficacy	50.455 lm/W
Source Flux	555 lm	Maximum value	710.41 cd/klm	Position	C=95.00 G=55.00
				CG	Asymmetrical

US ROAD STANDARDS



Luminaire Classification System (LCS)			
LCS Zone		Lumens	%Lamp
FL	0° -- 30°	64.1 lm	11.5 %
FM	30° -- 60°	287.8 lm	51.9 %
FH	60° -- 80°	183.0 lm	33.0 %
FVH	80° -- 90°	13.6 lm	2.4 %
BL	0° -- 30°	1.4 lm	0.3 %
BM	30° -- 60°	2.5 lm	0.4 %
BH	60° -- 80°	2.1 lm	0.4 %
BVH	80° -- 90°	0.5 lm	0.1 %
UL	90° -- 100°	0.0 lm	0.0 %
UH	100° -- 180°	0.0 lm	0.0 %
TOTALS		555.0 lm	100.0 %
BUG B0 U0 G1 Type IV Very Short Asymmetrical			