



General: Myia represents a very particular solution for adding style to façade lighting and walls. Its triangular shape makes it aesthetically and functionally suited for corners and buildings with very defined geometrical lines.

Fixture Body: Open-pore Anodized and Powder Coated Die-Cast Aluminum.

Diffuser: Extra clear tempered glass.

Mounting details: Surface mounted.

Dimensions/Weight: 4.7" (1.64 lbs)

Driver: Remote, Constant Current 120-277V Dimmable 0-10V.

Wattage: 9W (4.7")

Cable: Fixture comes with 3.28' of power cable.

Safety features: Fixture is equipped with Electrostatic discharge protection and Surge Protection (4 KV).

IP rating: IP65 for protection against dust and water jets from any angle.

IK rating: IK 05

ETL Certification: ETL, wet location


Optics: Fixed with Wide Flood Distribution.

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



4.7" (9W)

Delivered Lumens*		4.7"
WFL		311


*Values shown for 3000K

Ordering Information

MYI		LE	47	9 - CC		WFL		
Product	Trim/Film	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver (Required) ¹
MYI = Myia	WH = White BL = Black GR = Gray	LE = Light Effects	47 = 4.7" Triangular	9 CC = 9W / Constant Current (630mA)	27 = 2700K 30 = 3000K 40 = 4000K	WFL = Wide Flood		ECO30W-630 SOLO50W-630 SOLO100W-630

¹ See page 2

4.7" 9W CC



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures