

Quara IP65



General: With an elegant opening shaped light a drop of water, Quara family of step lights offers a classy while efficient solution for steps, or could be used to emphasize any ground detail in a discrete way. Quara is available for both Indoor and Outdoor applications, round or square, recessed or semi-recessed, in multiple sizes and finishes, including stainless steel and nickel.

Fixture Body: Powder Coated Aluminum.

Diffuser: UV Resistant Polycarbonate.

Mounting details: Wall mounted, semi-flush. Black PVC housing.

Dimensions/Weight: 2.6" & 2.8" (0.42 lbs) – 5.0" x 4.8" (0.90 lbs)

Driver: Remote, Constant Current 120-277V, Dimmable 0-10V.

Wattage/Size: 2W (2.6" & 2.8") – 4W (5.0" x 4.8")

Cable: Fixture comes with 3.28' of power cable.

IP rating: IP65 for protection against dust and water jets from any angle.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed with Asymmetric distribution.

Color temperatures: 2700K – 3000K – 3500K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.


Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



2.6" Round (2W)



2.8" Square (2W)



5.0" x 4.8" Square (4W)

Round Delivered Lumens*	2.6" (2W)
AS	117

*Values shown for 3000K

Square Delivered Lumens*	2.8" (2W)	5.0" x 4.8" (4W)
AS	117	268

*Values shown for 3000K


Ordering Information							(Required) ¹		
Product	Trim	Type	Dimensions	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
QR65 = Quara IP65	RWH = Round White RGR = Round Gray RDB = Round Dark Brown	F = Fixed	26 = 2.6"	2 CC = 2W / Constant Current (630mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	AS = Asymmetric	+	E84338 ² E98050 ³	ECO30W-630 SOLO50W-630 SOLO100W-630
	SWH = Square White SGR = Square Gray SDB = Square Dark Brown		28 = 2.8"	2 CC = 2W / Constant Current (630mA)					
			50 = 5.0" x 4.8"	4 CC = 4W / Constant Current (630mA)					

¹ See page 2

² 26, 28 sizes only

³ 50 size only

2.6" Round (2W)



Housing

E84338
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures

2.8" Square (2W)



Housing

E84338
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures

5.0" x 4.8" Square (4W)



Housing

E98050
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures