

# quara65




A drop of light in a small casing, with AquaStop® protection. Installed close to the ground, Quara65 projects a circular pool of light into the space below, and can be used to decorate steps and outdoor flooring details.

## **Materials**

Aluminum or AISI 316 stainless steel body



**Quara65\_R | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA**



 2.1

CRI 80

White	<b>E85543</b>	2700 K	219 lm	<b>M</b>	Flood	<b>70</b>
Grey	<b>E85542</b>	3000 K	233 lm	<b>W</b>		
DarkBrown	<b>E87988</b>	4000 K	249 lm	<b>N</b>		

**Power supply options (remote only)**


ECO30W- 630	SOLO50W-630	SOLO100W-630
0-10V	0-10V	0-10V
EldoLED	EldoLED	EldoLED
ECODrive	SOLOdrive	SOLOdrive
30W for	50W for	100W for
1-10 fixtures	1-16 fixtures	1-32 fixtures

Recessed casing

 659  
**E84338**



**Quara65\_RI | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA**



 2.1

CRI 80

Steel	<b>E92671</b>	2700 K	219 lm	<b>M</b>	Flood	<b>70</b>
		3000 K	233 lm	<b>W</b>		
		4000 K	249 lm	<b>N</b>		

**Power supply options (remote only)**


ECO30W- 630	SOLO50W-630	SOLO100W-630
0-10V	0-10V	0-10V
EldoLED	EldoLED	EldoLED
ECODrive	SOLOdrive	SOLOdrive
30W for	50W for	100W for
1-10 fixtures	1-16 fixtures	1-32 fixtures

Recessed casing

 659  
**E84338**



**Quara65\_F | Path-marker | powerLED | Wet location | Driver remote | 1W 350mA**



CRI 80


White	<b>E86460</b>	2700 K	145 lm	<b>M</b>	Flood	<b>70</b>
		3000 K	155 lm	<b>W</b>		
		4000 K	236 lm	<b>N</b>		

**Power supply options (remote only)**

ECO30W- 350	SOLO50W-350	SOLO100W-350
0-10V	0-10V	0-10V
EldoLED	EldoLED	EldoLED
ECODrive	SOLOdrive	SOLOdrive
30W for	50W for	100W for
1-10 fixtures	1-20 fixtures	1-40 fixtures

Recessed casing

 659  
**E84338**



1\_ Wall-drilled hole



2\_ Wall installation




3\_ Finished result



4\_ Flush-mounted installation

technical information

**Quara65\_Q | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA**



 2.1

CRI 80

White	<b>E86563</b>	2700 K	219 lm	<b>M</b>	Flood	<b>70</b>
Grey	<b>E86562</b>	3000 K	233 lm	<b>W</b>		
DarkBrown	<b>E87989</b>	4000 K	249 lm	<b>N</b>		


**Power supply options (remote only)**

ECO30W- 630	SOLO50W-630	SOLO100W-630
0-10V	0-10V	0-10V
EldoLED	EldoLED	EldoLED
ECODrive	SOLOdrive	SOLOdrive
30W for	50W for	100W for
1-10 fixtures	1-16 fixtures	1-32 fixtures

Recessed casing

 659  
**E84338**

**Quara65\_QI | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA**



 2.1

CRI 80

Steel	<b>E92672</b>	2700 K	219 lm	<b>M</b>	Flood	<b>70</b>
		3000 K	233 lm	<b>W</b>		
		4000 K	249 lm	<b>N</b>		


**Power supply options (remote only)**

ECO30W- 630	SOLO50W-630	SOLO100W-630
0-10V	0-10V	0-10V
EldoLED	EldoLED	EldoLED
ECODrive	SOLOdrive	SOLOdrive
30W for	50W for	100W for
1-10 fixtures	1-16 fixtures	1-32 fixtures

Recessed casing

 659  
**E84338**

**Quara65\_QI | Path-marker | powerLED | Wet location | Driver remote | 4W 630mA**



CRI 80

White	<b>E92238</b>	2700 K	438 lm	<b>M</b>	Flood	<b>70</b>
Grey	<b>E92239</b>	3000 K	466 lm	<b>W</b>		
DarkBrown	<b>E92240</b>	4000 K	498 lm	<b>N</b>		

**Power supply options (remote only)**

ECO30W- 630	SOLO50W-630	SOLO100W-630
0-10V	0-10V	0-10V
EldoLED	EldoLED	EldoLED
ECODrive	SOLOdrive	SOLOdrive
30W for	50W for	100W for
1-10 fixtures	1-16 fixtures	1-32 fixtures

Recessed casing

 659  
**E98050**

technical  
information