


# SUELO Dual Optic Adjustable Vandal Resistant

## SUD-SFSTVR-A-...-SP-... Delivered Lumens - Spot

		Diameter [Wattage]	
		67 [14 IND]	91 [26 ID]
CCT	27	422	1674
	30	444	1763
	40	491	1862
		Diameter [Wattage]	
		67 [14 IND]	91 [26 ID]
		0.25	1.00




Beam Angle (0-180) = 14.5  
Beam Angle (90-270) = 14.8

## CONE OF LIGHT - 26W 3000K SPOT SUD-SFSTVR-A-91-26-ID-30-SP\*

Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	47	5.1
18	58	4.6
16	74	4.1
14	96	3.6
12	131	3.0
10	189	2.5
8	295	2.0
6	524	1.5
4	1178	1.0
2	4713	0.5

## SUD-SFSTVR-A-...-FL-... Delivered Lumens - Flood

		Diameter [Wattage]	
		67 [14 IND]	91 [26 ID]
CCT	27	437	1784
	30	460	1892
	40	508	1999
		Diameter [Wattage]	
		67 [14 IND]	91 [26 ID]
		0.24	1.00




Beam Angle (0-180) = 25.1  
Beam Angle (90-270) = 25.3

## CONE OF LIGHT - 26W 3000K FLOOD SUD-SFSTVR-A-91-26-ID-30-FL\*

Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	23	8.9
18	29	8.0
16	36	7.1
14	48	6.2
12	65	5.3
10	93	4.5
8	146	3.6
6	259	2.7
4	582	1.8
2	2329	0.9

## SUD-SFSTVR-A-...-WFL-... Delivered Lumens - Wide Flood

		Diameter [Wattage]	
		67 [14 IND]	91 [26 ID]
CCT	27	393	1637
	30	414	1724
	40	457	1821
		Diameter [Wattage]	
		67 [14 IND]	91 [26 ID]
		0.24	1.00



Beam Angle (0-180) = 51.2  
Beam Angle (90-270) = 50.8

## CONE OF LIGHT - 26W 3000K WIDE FLOOD SUD-SFSTVR-A-91-26-ID-30-WFL\*

Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	6	19.2
18	8	17.2
16	10	15.3
14	13	13.4
12	18	11.5
10	25	9.6
8	40	7.7
6	70	5.7
4	158	3.8
2	633	1.9

\*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.