



General: With its durable frosted polycarbonate diffuser, Sand family of small outdoor step lights creates a soft, comfortable illumination suitable for most applications.

Fixture Body: Brass.

Diffuser: UV resistant polycarbonate.

Mounting details: Wall mounted, semi-recessed. ABS housing available for both concrete and tile applications.

Dimensions/Weight: 1.6" (0.12 lbs).

Driver: Remote, Constant Current 120-277V, Dimmable 0-10V.

Wattage/Size: 1W (1.6")

Cable: Fixture comes with 3.28' of power cable.

Safety features: Fixture is equipped with Aqua-Stop technology (anti-wicking) and Over voltage protection.

IP rating: IP65 for protection against dust and water jets from any angle.

IK rating: IK 07

ETL Certification: ETL, wet location

Optics: Fixed with Blade distribution (line of light).

Color temperatures: 3000K – 4000K – 5000K – Blue.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



1.6" Round (1W)



1.6" Square (1W)


Delivered Lumens*	1.6"
GE	90

*Values shown for 3000K

Ordering Information							(Required) ¹		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
SAN = Sand	RWH = Round White SWH = Square White	FR = Frosted	16 = 1.6"	1 CC = 1W / Constant Current (350mA)	30 = 3000K 40 = 4000K 50 = 5000K BL = Blue	GE = General		E84915 E84336	ECO30W-350 SOLO50W-350 SOLO100W-350

¹ See page 2

1.6" Round (1W)



Housing

E84915
Recessed Housing



E84336
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures

1.6" Square (1W)



Housing

E84915
Recessed Housing



E84336
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures