

sub




This underwater point light features IP68 and AquaStop® protection and an ultrathin 0.35-inch flange. When positioned in series, it can be used to create attractive dot patterns to highlight the bottom of a fountain or architectural feature in contact with water.

Materials
Brass body



Sub_R | Underwater luminaires | powerLED | Submersible | Driver remote | Drive over | 1.5W 500mA



Recessed casings
▶ 623


CRI 80

Steel	E97315	2700 K	187 lm	M	Spot	15
		3000 K	199 lm	W	Medium Flood	30
		4000 K	213 lm	N	Flood	60
					General	00

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Sub_Q | Underwater luminaires | powerLED | Submersible | Driver remote | Drive over | 1.5W 500mA



Recessed casings
▶ 623

CRI 80

Steel	E97317	2700 K	187 lm	M	Spot	15
		3000 K	199 lm	W	Medium Flood	30
		4000 K	213 lm	N	Flood	60
					General	00

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures