

# suelo underwater




Suelo and Suelo PRO are also suitable for underwater environment thanks to the new IP68 versions equipped with the AquaStop® system.

Small and high-performing, these articles come with an anti-vandalism fixing screw thus making them suitable for installation in fountains or in other extremely deep environments as well as easy to reach depths.

## **Materials**

Aluminum body

AISI 316L stainless steel flange

**Suelo | Up-Light | 1W powerLED | Submersible | Driver remote | Driver over**


C.C. - 350mA

Steel	E80432	2700K	136 lm	M	Medium Flood	20
		3000K	145 lm	W	Medium Flood	35
		4000K	155 lm	N		

**Power supply options (remote only)**
**ECO30W-350**


 0-10V EldoLED ECOdrive  
 30W for 1-10 fixtures

**SOLO50W-350**

 0-10V EldoLED SOLOdrive  
 50W for 1-20 fixtures

**SOLO100W-350**

 0-10V EldoLED SOLOdrive  
 100W for 1-40 fixtures

**Suelo Pro | Up-Light | 1W powerLED | Submersible | Driver remote | Driver over**


C.C. - 350mA

Steel	E80433	2700K	136 lm	M	Medium Flood	20
		3000K	145 lm	W	Medium Flood	35
		4000K	155 lm	N		

**Power supply options (remote only)**
**ECO30W-350**

 0-10V EldoLED ECOdrive  
 30W for 1-10 fixtures

**SOLO50W-350**

 0-10V EldoLED SOLOdrive  
 50W for 1-20 fixtures

**SOLO100W-350**

 0-10V EldoLED SOLOdrive  
 100W for 1-40 fixtures

C.V. - 24V

Steel	E80434	2700K	136 lm	M	Medium Flood	20
		3000K	145 lm	W	Medium Flood	35
		4000K	155 lm	N		

**Power supply options (remote only)**
**OT96-D010**

 Osram, 10% 0-10V dim,  
 96W, 24V DC, 120-  
 277VAC, supplied in a  
 Dry location

**OT96-JBX**

 Osram, Non-dim 24V  
 DC, 120-277VAC, Wet  
 location