
4" ProTools DL Wall Wash

Square Wall Wash Cover







Recessed Plaster Trim




Recessed Bezel Trim





Cut Out: 24.75" / 121mm

Recessed Plaster Trim (RPT)



Cut Out: 24.75" / 121mm

Recessed Bezel Trim (RBT)

Ordering Information SWW WWL WG-100SPTDLWW CRI/ Model **Fixation** Power^{1,2} Driver^e Cover Finish Options⁶ Lens CCT WG-100SPTDLWW SWW WWL LP 927 Χ W CP **RBT** М 930 G^5 Η 935 D010 IC PEQ1 WL XΗ 940 PEQ0 **DFPN**

Luminaire

- 4" square downlight with 2" light aperture.
- 0.7" regressed aperture / lens providing asymmetric beam distribution optimized for even illumination of vertical surfaces.
- High-angle illumination.
- Luminaire and driver installed and maintained from below the ceiling.
- Minimum of 5.5" (127mm) ceiling void is required to install the fixture from below the ceiling (remodelling).
- Modular interchangeability throughout the entire ProTools range of products.

Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim

Power^{1,2}

- L = Low Power, 5.7W @ 350mA
- M = Mid Power, 8.4W @ 500mA
- H = High Power, 12.0W @ 700mA
- XH = Extra High Power, 17.8W @ 1050mA

CRI/CCT3

90+ CRI (Low/Medium/High/Extra High)

- \blacksquare 927 = 2700K, (720/999/1344/1884 lm)
- 930 = 3000K, (775/1075/1447/2027 lm)
- \blacksquare 935 = 3500K, (775/1075/1447/2027 lm)
- \blacksquare 940 = 4000K, (830/1151/1549/2171 lm)

Driver⁴

- X = Remote driver, ordered separately
- S = Standard non-dim driver, 120-277V
- D010 = EldoLED, 1%, 0-10V Driver, 120-277V
- PEQ1 = Lutron Hi-lume 1% EcoSystem, 120-277V
- PEQ0 = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
- DFPN = Lutron Forward Phase 1% 120VAC

Cover

■ SWW = Square Wall Wash

l ens

WWL = Regressed Wall Wash Spread Lens

Finish

- W = White
- G = Gray⁵

Options⁶

ProTools downlights require no additional options kits for remodel & new construction

- LP = Landing Pan
- CP = Chicago Plenum Housing
- IC = IC/NC Housing
- WL = Wet Location
- ¹ Other lumen packages available, consult factory.
- ² Wattage shown does not include power supplies/drivers. System wattage adds 10-20%.
- ³ See LED data sheet for delivered lumens.
- ⁴ See power supply page for details.
- ⁵ Plaster trim version includes white frame and gray cover.
- ⁶ To specify multiple options, select the appropriate grouped codes from the dropdown e.g. LP-WL.

