

# Envelope IP66 Rectangular Recessed Mount



**General:** With a simple, elegant, and minimalist design, Envelope is a family of round or square wall mounted step lights suitable for most projects (available for both indoor and outdoor applications). A recessed asymmetric optic that guarantees full cut-off while providing outstanding performances and a multitude of sizes and colors complete the range.

**Fixture Body:** Powder Coated Aluminum.

**Diffuser:** Extra clear glass, tempered.

**Mounting details:** Wall mounted, semi-recessed. Black or Blue PVC housing.

**Dimensions/Weight:** 6.7" x 6.6" (1.87 lbs) – 10.6" x 4.9" (2.21 lbs)

**Driver:** Remote, Constant Voltage 24V DC, 120-277VAC Dimmable 0-10V or Non-Dim.

**Wattage/Size:** 7W (6.7" x 6.6") – 11W & 17W (10.6" x 4.9")

**Cable:** Fixture comes with 0.98' of power cable.

**IP rating:** IP66 for protection against dust and water jets from any angle.

**IK rating:** IK 10

**ETL Certification:** ETL, wet location

**Optics:** Fixed, Asymmetric.

**Color temperatures:** 3000K – 4000K.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



6.7" x 6.6" (7W)



10.6" x 4.9" (11W / 17W)

Delivered Lumens <sup>1</sup>	67 (7W)	106 (11W)	106 (17W)
AS	483	743	1131


<sup>1</sup>Values shown for 3000K

Ordering Information							(Required)		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing <sup>1</sup>	Driver <sup>1</sup>
EN66 = Envelope IP66	SRWH = Surface Mount, Rectangular White SRWG = Surface Mount, Rectangular Grey SRBG = Surface Mount, Rectangular Black Grey SRDB = Surface Mount, Rectangular Dark Brown	ME = Mono Emission	67 = 6.7" x 6.6" 106 = 10.6" x 4.9"	7 CV = 7W / CV = Remote Constant Voltage 24V DC 11 CV = 11W / CV = Remote Const. Voltage 24V DC 17 CV = 17W / CV = Remote Constant Voltage 24V DC	30 = 3000K 40 = 4000K	AS = Asymmetric		E99744 (67) E99745 (106)	OT96-D010 OT96-JBX

<sup>1</sup> See page 2




## 6.7" x 6.6" (7W)



### Housing

**E99744**  
Recessed Housing  
for brickwork-mounted  
installation




### DRIVER OPTIONS (pick one)

#### C.V. Power supply options (remote only)

**OT96-D010**  
Osram, 10% 0-10V dim, 96W,  
24VDC, 120-277VAC, supplied  
in a Dry location enclosure


**OT96-JBX**  
Osram, Non-Dim, 96W,  
24VDC, 120-277VAC,  
Wet Location

## 10.6" x 4.9" (11W / 17W)



### Housing

**E99745**  
Recessed Housing  
for brickwork-mounted  
installation



### DRIVER OPTIONS (pick one)

#### C.V. Power supply options (remote only)

**OT96-D010**  
Osram, 10% 0-10V dim, 96W,  
24VDC, 120-277VAC, supplied  
in a Dry location enclosure

**OT96-JBX**  
Osram, Non-Dim, 96W,  
24VDC, 120-277VAC,  
Wet Location