

Envelope IP66 Wall Recessed Rectangular



General: With a simple, elegant, and minimalist design, Envelope is a family of round or square wall mounted step lights suitable for most projects (available for both indoor and outdoor applications). A recessed asymmetric optic that guarantees full cut-off while providing outstanding performances and a multitude of sizes and colors complete the range.

Fixture Body: Powder Coated Aluminum.

Diffuser: Extra clear glass, tempered.

Mounting details: Wall mounted, semi-recessed. Black or Blue PVC housing.

Dimensions/Weight: 6.7" x 6.6" (1.87 lbs) – 10.6" x 4.9" (2.21 lbs)

Driver: Remote, Constant Voltage 24V DC, 120-277VAC Dimmable 0-10V or Non-Dim.

Wattage/Size: 7W (6.7" x 6.6") – 11W & 17W (10.6" x 4.9")

Cable: Fixture comes with 0.98' of power cable.

IP rating: IP66 for protection against dust and water jets from any angle.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed, Asymmetric.

Color temperatures: 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



6.7" x 6.6" (7W)



10.6" x 4.9" (11W / 17W)


Delivered Lumens ¹	67 (7W)	106 (11W)	106 (17W)
AS	483	743	1131

¹Values shown for 3000K

Ordering Information							(Required)		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing ¹	Driver ¹
EN66 = Envelope IP66	RRWH = Recessed, Rectangular White RRWG = Recessed, Rectangular Grey RRBG = Recessed, Rectangular Black Grey RRDB = Recessed, Rectangular Dark Brown	ME = Mono Emission	67 = 6.7" x 6.6" 106 = 10.6" x 4.9"	7 CV = 7W / CV = Remote Constant Voltage 24V DC 11 CV = 11W / CV = Remote Const. Voltage 24V DC 17 CV = 17W / CV = Remote Constant Voltage 24V DC	30 = 3000K 40 = 4000K	AS = Asymmetric		E99744 (67) E99745 (106)	OT96-D010 OT96-JBX


¹ See page 2

6.7" x 6.6" (7W)



Housing

E99744
Recessed Housing
for brickwork-mounted
installation




DRIVER OPTIONS (pick one)

C.V. Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W,
24VDC, 120-277VAC, supplied
in a Dry location enclosure


OT96-JBX
Osram, Non-Dim, 96W,
24VDC, 120-277VAC,
Wet Location

10.6" x 4.9" (11W / 17W)



Housing

E99745
Recessed Housing
for brickwork-mounted
installation



DRIVER OPTIONS (pick one)

C.V. Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W,
24VDC, 120-277VAC, supplied
in a Dry location enclosure

OT96-JBX
Osram, Non-Dim, 96W,
24VDC, 120-277VAC,
Wet Location