Tour Pendant Vertical Square Inside

inter•lux

IP40

26.4" (45W)



General: Tour is a comprehensive family of large pendants created to become integral part of any architectural design. Tour is available in Round, Square or Rectangular shape, with multiple sizes to choose from, and several distributions (Direct, Indirect, Direct/Indirect, Inside). Lobby spaces, conference rooms, retail stores are just some of the many applications Tour could be the perfect fit for.

Fixture Body: Powder Coated Aluminum 6060 (superior corrosion resistance).
Diffuser: Opaline UV resistant Polycarbonate.
Mounting: Suspension.
Dimensions/Weight: 26.4" (6.61 lbs).

Driver: 120-277V. Integral inside canopy (0-10V Dimming), or Remote (0-10V Dimming or Non-Dim).
Operation: Constant Voltage, 24V DC (CV).
Wattages: 45W (26.4" sq.)
Suspension Cable Length: Max 196.9".

IP rating: IP40. Fixture is protected against solid objects greater than 0.04".
ETL Certification: ETL, dry location

Optics: Fixed, Inside Emission. General Illumination.
Color temperatures: 3000K – 3500K – 4000K.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Delivered Lumens*	26.4"
GE	2348

*Values shown for 3000K

Ordering Information

Product	Trim/Finish	Type	Diameter/ Size	Wattage/Operation	Color Temp	Optic	+	Fixing & Driver (Required)[1]
TOU		INS	26	45 CV		GE		
TOU = Tour	VSWH = Vertical Square White VSBL = Vertical Square Black	INS = Inside Distribution	26 = 26.4"	45 CV = 45W / Remote Constant Voltage 24VDC	30 = 3000K 35 = 3500K 40 = 4000K	GE = General Illumination		**Remote Driver:** E64270+OT96-D010 E64240+OT96-D010 **Driver in Canopy:** E64368 E64369

[1] See page 2

Tour Pendant Vertical Square Inside

inter•lux

Emissions range

Tour comes with three different emissions: direct, inside and direct-indirect. Three lighting effects that can be combined with each other in countless combinations to transform the environments with a minimal and contemporary light.



Direct emission

Inside emission (vertical only)

Direct-indirect emission

4-piece fixing kit (Remote Driver)



type

White	E64270
Black	E64240

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

Final result

Driver: ON/OFF 0-10V



4-coupling point ceiling canopy for one-side emission (Integral 0-10V dimming driver in canopy)



White	E64368
Black	E64369