# vuelta





The Vuelta spot offers maximum flexibility and precisely controlled illumination. The integral fixing bracket keeps it stably focused over time. Available in two sizes and a variety of beam types (symmetrical wide flood, asymmetrical wide flood, narrow spot, and flood), it can be fixed to a wall, the ground, or a pole. Vuelta also has an optional lamellar anti-glare grille.

#### Materials

Aluminum body Transparent glass diffuser



## vuelta lighting concept

#### **Construction details**

Diecasting aluminum case, oxidation treatment and polyester coating. Extra clear tempered glass 0.2 inch thickness with a black serigraphy used for diffuser. Silicone gasket and anticondensation valve guarantees long term protection against seepage and moisture. Integrated driver on/off.

#### Technology

ArrayLED / PowerLED









SP / FL



#### Narrow spot emission

Available only for the small version. This emission is perfect for particularly effectiveness lighting accent. Used for long distance (1181.1 inch) ensures high intensity values and a reduced energy consumption.



On demand, Vuelta NSP can be supplied with a special elliptical filter to ovalize the light beam, creating blade lighting effects, extremely precise and professional.

#### Asymmetric emission

Perfect for indirect vault and ceiling lighting; this configuration is the result of a long optics research to optimize depth flux distribution, not "soiled" with spurious light, the installation plan is obscured.



1181.1 in

1

#### Wideflood direct emission

Direct lighting illuminates objects frontally, reducing contrasts and maximizing volumes and textures' perception. It's a high performance configuration; arrayLED source uses the full emission and maximize lighting distribution, provided by aluminum high reflectance dedicated diffuser 120°.









Asymmetric

07

### Vuelta\_Y | Outdoor spotlights | 120-277 V | arrayLED | Wet location | Integral Driver | Tiltable | 16W

CRI 80

Grey **E64522** 

BK Grey **E64523** 

3000K

4000K

1631 lm

1746 lm

W

Ν







		5	

	2.9 4.6		
	Angular bracket		
E14931	Grey	E64538	



11.4 Ċ 9.6

E64534

Grid

Black

Accessories

Ø 5.1 11.9

Pegs

Black