

Quara IP65 Flush (Plaster-in)



General: With an elegant opening shaped light a drop of water, Quara family of step lights offers a classy while efficient solution for steps, or could be used to emphasize any ground detail in a discrete way. Quara is available for both Indoor and Outdoor applications, round or square, recessed or semi-recessed, in multiple sizes and finishes, including stainless steel and nickel.

Fixture Body: Powder Coated Aluminum.
Diffuser: UV Resistant Polycarbonate.
Mounting details: Wall mounted, recessed flush. Black PVC housing.
Dimensions/Weight: 2.0" (0.372 lbs)

Driver: Remote, Constant Current 120-277V, Dimmable 0-10V.
Wattage/Size: 1W (2.0")
Cable: Fixture comes with 3.28' of power cable.

IP rating: IP65 for protection against dust and water jets from any angle.
IK rating: IK 10
ETL Certification: ETL, wet location

Optics: Fixed with Asymmetric distribution.
Color temperatures: 2700K – 3000K – 4000K.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



2.0" (1W)

Delivered Lumens*	2.0" (1W)
WFL	72

*Values shown for 3000K


Ordering Information							(Required) ¹	
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Driver
QR65 = Quara IP65	RFWH = Round Flush White	F = Fixed	20 = 2.0"	1 CC = 1W / Constant Current (350mA)	27 = 2700K 30 = 3000K 40 = 4000K	AS = Asymmetric	+	ECO30W-350 SOLO50W-350 SOLO100W-350

¹ See page 2

Quara IP65 Flush (Plaster-in)



2.0" (1W)



Housing

E84338
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures