

# Quara IP65 Flush (Plaster-in)



**General:** With an elegant opening shaped light a drop of water, Quara family of step lights offers a classy while efficient solution for steps, or could be used to emphasize any ground detail in a discrete way. Quara is available for both Indoor and Outdoor applications, round or square, recessed or semi-recessed, in multiple sizes and finishes, including stainless steel and nickel.

**Fixture Body:** Powder Coated Aluminum.

**Diffuser:** UV Resistant Polycarbonate.

**Mounting details:** Wall mounted, recessed flush. Black PVC housing.

**Dimensions/Weight:** 2.0" (0.372 lbs)

**Driver:** Remote, Constant Current 120-277V, Dimmable 0-10V.

**Wattage/Size:** 1W (2.0")

**Cable:** Fixture comes with 3.28' of power cable.

**IP rating:** IP65 for protection against dust and water jets from any angle.

**IK rating:** IK 10

**ETL Certification:** ETL, wet location

**Optics:** Fixed with Asymmetric distribution.

**Color temperatures:** 2700K – 3000K – 3500K – 4000K.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



2.0" (1W)

Delivered Lumens*	2.0" (1W)
WFL	72



\*Values shown for 3000K

Ordering Information							(Required) <sup>1</sup>		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
QR65	RFWH	F	20	1 - CC		AS		E84338	
QR65 = Quara IP65	RFWH = Round Flush White	F = Fixed	20 = 2.0"	1 CC = 1W / Constant Current (350mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	AS = Asymmetric		E84338	ECO30W-350 SOLO50W-350 SOLO100W-350

<sup>1</sup> See page 2

# Quara IP65 Flush (Plaster-in)

## 2.0" (1W)



## Housing

### E84338

Recessed Housing



## DRIVER OPTIONS (pick one)

### C.C. Power supply options (remote only)

#### ECO30W-350

0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

#### SOLO50W-350

0-10V EldoLED  
SOLOdrive 50W  
for 1-20 fixtures

#### SOLO100W-350

0-10V EldoLED  
SOLOdrive 100W  
for 1-40 fixtures