

Quara IP65 Stainless Steel



General: With an elegant opening shaped light a drop of water, Quara family of step lights offers a classy while efficient solution for steps or could be used to emphasize any ground detail in a discrete way. Quara is available for both Indoor and Outdoor applications, round or square, recessed or semi-recessed, in multiple sizes and finishes, including stainless steel and nickel.

Fixture Body: 316L Stainless Steel (Marine Grade).

Diffuser: UV Resistant Polycarbonate.

Mounting details: Wall mounted, semi-flush. Black PVC housing.

Dimension/Weight: 2.8" (0.90 lbs)

Driver: Remote, Constant Current 120-277V, Dimmable 0-10V.

Wattage/Size: 2W (2.8")

Cable: Fixture comes with 3.28' of power cable.

IP rating: IP65 for protection against dust and water jets from any angle.

IK rating: IK 10

ETL Certification: ETL, wet location


Optics: Fixed with Asymmetric distribution.

Color temperatures: 2700K – 3000K – 3500K – 4000K.


CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



2.8" RST (2W)



2.8" SST (2W)


Delivered Lumens*		2.8" (2W)
WFL		85

*Values shown for 3000K

Ordering Information								(Required) ¹	
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic		Housing	Driver
QR65		F	28	2 - CC		AS		E84338	
QR65 = Quara IP65	RST = Round Stainless Steel SST = Square Stainless Steel	F = Fixed	28 = 2.8"	2 CC = 2W / Constant Current (630mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	AS = Asymmetric	+	E84338	ECO30W-630 SOLO50W-630 SOLO100W-630

¹ See page 2

2.8" RST (2W)



Housing

E84338
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures

2.8" SST (2W)



Housing

E84338
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures