


**Orma Flush Trim | Frosted | 2.1" Ø**



C.C. 1W DC - 350mA	Cct	lm S - D	Optic
Steel/Alu <b>E81217</b>	<b>M</b> 2700	136 - 17	<b>00</b> General (117°)
	<b>W</b> 3000	145 - 18	
	<b>N</b> 4000	155 - 19	





**Power supply options (remote only)**

EC030W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECODrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures


C.V. 1.5W DC - 24 VDC	Cct	lm S - D	Optic
Steel/Alu <b>E81218</b>	<b>M</b> 2700	136 - 17	<b>00</b> General (117°)
	<b>W</b> 3000	145 - 18	
	<b>N</b> 4000	155 - 19	

**Power supply options (remote only)**

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



**Orma Flush Trim | Frosted | 3.3" Ø**



C.C. 2W DC - 630 mA	Cct	lm S - D	Optic
Steel/Alu <b>E81219</b>	<b>M</b> 2700	249 - 25	<b>00</b> General (118°)
	<b>W</b> 3000	266 - 26	
	<b>N</b> 4000	284 - 28	






**Power supply options (remote only)**

EC030W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECODrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

C.V. 2.5W DC - 24 VDC	Cct	lm S - D	Optic
Steel/Alu <b>E81220</b>	<b>M</b> 2700	249 - 25	<b>00</b> General (118°)
	<b>W</b> 3000	266 - 26	
	<b>N</b> 4000	284 - 28	


**Power supply options (remote only)**

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



\*NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush\*. Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL). Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations. Inter-lux reserves the right to make technical changes without notice.

**Orma Flush Trim | Frosted | 4.9" Ø**



C.C. 4W DC - 350mA	Cct	lm S - D	Optic
Steel/Alu <b>E81221</b>	<b>M</b> 2700	490 - 90	<b>00</b> General (116°)
	<b>W</b> 3000	490 - 90	
	<b>N</b> 4000	529 - 97	




**Power supply options (remote only)**

<b>EC030W-350</b>	<b>SOLO50W-350</b>	<b>SOLO100W-350</b>
0-10V EldoLED ECODrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

C.V. 4.5W DC - 24 VDC	Cct	lm S - D	Optic
Steel/Alu <b>E81222</b>	<b>M</b> 2700	490 - 90	<b>00</b> General (116°)
	<b>W</b> 3000	490 - 90	
	<b>N</b> 4000	529 - 97	

**Power supply options (remote only)**

<b>OT96-D010</b>	<b>OT96-JBX</b>
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



\*NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush\*.  
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).  
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.  
NOT suitable for submersible installations.  
Inter-lux reserves the right to make technical changes without notice.

