


Orma Trim Flush Adjustable | Up-Light | powerLED



C.C. 4W DC - 350mA		Cct	lm S - D	Optic
Steel/Alu	E81205	M 2700	490 - 272	15 Spot (22°)
		W 3000	490 - 272	30 Flood (29°)
		N 4000	529 - 294	60 W.Flood (48°)




Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures


C.V. 5W DC - 24 VDC		Cct	lm S - D	Optic
Steel/Alu	E81206	M 2700	490 - 272	15 Spot (22°)
		W 3000	490 - 272	30 Flood (29°)
		N 4000	529 - 294	60 W.Flood (48°)

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



Orma Trim Flush Adjustable | Up-Light | arrayLED



C.C. - 8W DC - 220 mA		Cct	lm S - D	Optic
Steel/Alu	E81207	M 2700	1080 - 858	15 Spot (15°)
		W 3000	1126 - 894	30 Flood (31°)
		N 4000	1188 - 944	60 W.Flood (61°)

HC	Cct	lm S - D	Optic	
Steel/Alu	E82460	M 2700	1080 - 619	15 Spot -
		W 3000	1126 - 646	30 Flood -
		N 4000	1188 - 681	60 W.Flood -

Power supply options (remote only)

ECO30W-220	SOLO50W-220	SOLO100W-220
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures





C.V. 9W DC - 24 VDC		Cct	lm S - D	Optic
Steel/Alu	E81208	M 2700	1193 - 955	15 Spot (15°)
		W 3000	1244 - 997	30 Flood (31°)
		N 4000	1313 - 1052	60 W.Flood (61°)

HC	Cct	lm S - D	Optic	
Steel/Alu	E82461	M 2700	1193 - 687	15 Spot -
		W 3000	1244 - 716	30 Flood -
		N 4000	1313 - 761	60 W.Flood -

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure


OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location



NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.

Inter-lux reserves the right to make technical changes without notice.

Orma Trim Flush Adjustable | Up-Light | arrayLED






C.C. - 12W DC - 350 mA	Cct	lm S - D	Optic
Steel/Alu E81209	M 2700	1724 - 1317	15 Spot (22°)
	W 3000	1724 - 1317	30 Flood (34°)
	N 4000	1854 - 1417	60 W.Floos (61°)

HC	Cct	lm S - D	Optic
Steel/Alu E82462	M 2700	1724 - 935	15 Spot -
	W 3000	1724 - 935	30 Flood -
	N 4000	1854 - 1005	60 W.Flood -

Power supply options (remote only)

EC030W-350 0-10V EldoLED ECODrive 30W for 1 fixture	SOL050W-350 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	SOLO100W-350 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures
---	--	--



NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
 Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
 NOT suitable for submersible installations.
 Inter-lux reserves the right to make technical changes without notice.