



Orma Trimless Adjustable | Up-Light | powerLED



C.C. 4W DC - 350mA	Cct	lm S - D	Optic
Glass Alu E82663	M 2700	490 - 288	15 Spot -
	W 3000	490 - 288	30 Flood -
	N 4000	529 - 311	60 W.Flood -



Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures


C.V. 5W DC - 24 VDC	Cct	lm S - D	Optic
Glass Alu E82664	M 2700	490 - 288	15 Spot -
	W 3000	490 - 288	30 Flood -
	N 4000	529 - 311	60 W.Flood -

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



Orma Trimless Adjustable | Up-Light | ArrayLED



C.C. 8W DC - 220mA	Cct	lm S - D	Optic
Glass Alu E82675	M 2700	1080 - 693	15 Spot -
Glass Alu E82676 HC	W 3000	1126 - 722	30 Flood -
	N 4000	1188 - 763	60 W.Flood -



Power supply options (remote only)

ECO30W-220	SOLO50W-220	SOLO100W-220
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

C.V. 9W DC - 24 VDC	Cct	lm S - D	Optic
Glass Alu E82677	M 2700	1193 - 693	15 Spot -
Glass Alu E82678 HC	W 3000	1244 - 722	30 Flood -
	N 4000	1313 - 763	60 W.Flood -

Power supply options (remote only)


OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
 NOT suitable for submersible installations.

Inter-lux reserves the right to make technical changes without notice.



Orma Trimless Adjustable | Up-Light | ArrayLED



C.C. 12W DC - 350mA	Cct	Im S - D	Optic
Glass Alu E82689	M 2700	1724 - 1203	15 Spot -
Glass Alu E82690 HC	W 3000	1724 - 1203	30 Flood -
	N 4000	1854 - 1292	60 W.Flood -

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
 NOT suitable for submersible installations.
 Inter-lux reserves the right to make technical changes without notice.