





**Orma Trimless Fixed | Up-Light | powerLED**





| C.C. 1W DC - 350mA      | Cct           | lm S - D | Optic             |
|-------------------------|---------------|----------|-------------------|
| Glass Alu <b>E82697</b> | <b>M</b> 2700 | 136 - 71 | <b>20</b> Spot -  |
|                         | <b>W</b> 3000 | 145 - 76 | <b>35</b> Flood - |
|                         | <b>N</b> 4000 | 155 - 81 |                   |

**Power supply options (remote only)**

| ECO30W-350   | SOLO50W-350   | SOLO100W-350   |
|--|---|--|
| 0-10V EldoLED<br>ECOdrive 30W<br>for 1-10 fixtures | 0-10V EldoLED<br>SOLOdrive 50W<br>for 1-20 fixtures | 0-10V EldoLED<br>SOLOdrive 100W<br>for 1-40 fixtures |





**Orma Trimless Fixed | Up-Light | powerLED**





| C.V. 1.5W DC - 24 VDC   | Cct           | lm S - D | Optic             |
|-------------------------|---------------|----------|-------------------|
| Glass Alu <b>E82698</b> | <b>M</b> 2700 | 136 - 71 | <b>20</b> Spot -  |
|                         | <b>W</b> 3000 | 145 - 76 | <b>35</b> Flood - |
|                         | <b>N</b> 4000 | 155 - 81 |                   |

**Power supply options (remote only)**

| OT96-D010  | OT96-JBX                                       |
|--|--|
| Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure | Osram, Non-dim 24VDC, 120-277VAC, Wet location |



**Orma Trimless Fixed | Up-Light | powerLED**



| C.C. 4W DC - 350mA         | Cct           | lm S - D  | Optic                   |
|----------------------------|---------------|-----------|-------------------------|
| Glass Alu <b>E82657</b>    | <b>M</b> 2700 | 490 - 288 | <b>15</b> Spot -        |
| Glass Alu <b>E82658</b> HC | <b>W</b> 3000 | 490 - 288 | <b>25</b> Elliptical* - |
| Glass Alu <b>E82659</b> DL | <b>N</b> 4000 | 529 - 311 | <b>30</b> Flood -       |
|                            |               |           | <b>60</b> W.Flood -     |

\*Elliptical available with E82657 only.

**Power supply options (remote only)**



| ECO30W-350  | SOLO50W-350  | SOLO100W-350   |
|---|--|--|
| 0-10V EldoLED<br>ECOdrive 30W<br>for 1-3 fixtures | 0-10V EldoLED<br>SOLOdrive 50W<br>for 1-6 fixtures | 0-10V EldoLED<br>SOLOdrive 100W<br>for 1-12 fixtures |

| C.V. 5W DC - 24 VDC        | Cct           | lm S - D  | Optic                   |
|----------------------------|---------------|-----------|-------------------------|
| Glass Alu <b>E82660</b>    | <b>M</b> 2700 | 490 - 288 | <b>15</b> Spot -        |
| Glass Alu <b>E82661</b> HC | <b>W</b> 3000 | 490 - 288 | <b>25</b> Elliptical* - |
| Glass Alu <b>E82662</b> DL | <b>N</b> 4000 | 529 - 311 | <b>30</b> Flood -       |
|                            |               |           | <b>60</b> W.Flood -     |

\*Elliptical available with E82660 only.



**Power supply options (remote only)**

| OT96-D010  | OT96-JBX                                       |
|--|--|
| Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure | Osram, Non-dim 24VDC, 120-277VAC, Wet location |



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).  
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.  
 NOT suitable for submersible installations.  
 Inter-lux reserves the right to make technical changes without notice.

**Orma Trimless Fixed | Up-Light | ArrayLED**



| C.C. 8W DC - 220mA         | Cct           | lm S - D   | Optic               |
|----------------------------|---------------|------------|---------------------|
| Glass Alu <b>E82669</b>    | <b>M</b> 2700 | 1080 - 689 | <b>15</b> Spot -    |
| Glass Alu <b>E82670</b> HC | <b>W</b> 3000 | 1126 - 718 | <b>30</b> Flood -   |
| Glass Alu <b>E82671</b> DL | <b>N</b> 4000 | 1188 - 758 | <b>60</b> W.Flood - |



**Power supply options (remote only)**

| ECO30W-220                                     | SOLO50W-220  | SOLO100W-220  |
|--|--|---|
| 0-10V EldoLED<br>ECOdrive 30W<br>for 1 fixture | 0-10V EldoLED<br>SOLOdrive 50W<br>for 1-2 fixtures | 0-10V EldoLED<br>SOLOdrive 100W<br>for 1-4 fixtures |



| C.V. 9W DC - 24 VDC        | Cct           | lm S - D   | Optic               |
|----------------------------|---------------|------------|---------------------|
| Glass Alu <b>E82672</b>    | <b>M</b> 2700 | 1193 - 689 | <b>15</b> Spot -    |
| Glass Alu <b>E82673</b> HC | <b>W</b> 3000 | 1244 - 718 | <b>30</b> Flood -   |
| Glass Alu <b>E82674</b> DL | <b>N</b> 4000 | 1313 - 758 | <b>60</b> W.Flood - |

**Power supply options (remote only)**

| OT96-D010  | OT96-JBX  |
|--|---|
| Osram, 10% 0-10V dim, 96W,<br>24VDC, 120-277VAC, supplied<br>in a Dry location enclosure | Osram, Non-dim 24VDC,<br>120-277VAC, Wet location |





**Orma Trimless Fixed | Up-Light | ArrayLED**



| C.C. 12W - 350mA           | Cct           | lm S - D    | Optic               |
|----------------------------|---------------|-------------|---------------------|
| Glass Alu <b>E82683</b>    | <b>M</b> 2700 | 1724 - 1365 | <b>15</b> Spot -    |
| Glass Alu <b>E82684</b> HC | <b>W</b> 3000 | 1724 - 1365 | <b>30</b> Flood -   |
| Glass Alu <b>E82685</b> DL | <b>N</b> 4000 | 1854 - 1466 | <b>60</b> W.Flood - |

**Power supply options (remote only)**

| ECO30W-350                                     | SOLO50W-350  | SOLO100W-220  |
|--|--|---|
| 0-10V EldoLED<br>ECOdrive 30W<br>for 1 fixture | 0-10V EldoLED<br>SOLOdrive 50W<br>for 1-2 fixtures | 0-10V EldoLED<br>SOLOdrive 100W<br>for 1-4 fixtures |



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).  
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.  
NOT suitable for submersible installations.  
Inter-lux reserves the right to make technical changes without notice.