




Orma Trimless Frosted | Up-Light | powerLED




| C.C. 1W DC - 350mA | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82699 | M 2700 | 136 - 12 | 00 General - |
| | W 3000 | 145 - 13 | |
| | N 4000 | 155 - 14 | |

Power supply options (remote only)

| ECO30W-350 | SOLO50W-350 | SOLO100W-350 |
|--|---|--|
| 0-10V EldoLED ECOdrive 30W for 1-10 fixtures | 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures | 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures |





Orma Trimless Frosted | Up-Light | powerLED




| C.V. 1.5W DC - 24 VDC | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82700 | M 2700 | 136 - 12 | 00 General - |
| | W 3000 | 145 - 13 | |
| | N 4000 | 155 - 14 | |

Power supply options (remote only)

| OT96-D010 | OT96-JBX |
|--|---|
| Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure | Osram, Non-dim 24VDC, 120-277VAC, Wet location |



Orma Trimless Frosted | Path-Marker | powerLED



| C.C. 1W DC - 350mA | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82667 | M 2700 | 136 - 8 | 00 General - |
| | W 3000 | 145 - 8 | |
| | N 4000 | 155 - 9 | |


Power supply options (remote only)

| ECO30W-350 | SOLO50W-350 | SOLO100W-350 |
|--|---|--|
| 0-10V EldoLED ECOdrive 30W for 1-10 fixtures | 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures | 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures |

| C.V. 1.5W DC - 24 VDC | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82668 | M 2700 | 136 - 8 | 00 General - |
| | W 3000 | 145 - 8 | |
| | N 4000 | 155 - 9 | |


Power supply options (remote only)

| OT96-D010 | OT96-JBX |
|--|---|
| Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure | Osram, Non-dim 24VDC, 120-277VAC, Wet location |



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Trimless Frosted | Path-Marker | powerLED



| C.C. 2W DC- 630mA | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82681 | M 2700 | 249 - 15 | 00 General - |
| | W 3000 | 266 - 15 | |
| | N 4000 | 284 - 16 | |



Power supply options (remote only)

| ECO30W-630 | SOLO50W-630 | SOLO100W-630 |
|--|---|--|
| 0-10V EldoLED ECOdrive 30W for 1-10 fixtures | 0-10V EldoLED SOLOdrive 50W for 1-16 fixtures | 0-10V EldoLED SOLOdrive 100W for 1-32 fixtures |


| C.V. 2.5W DC - 24 VDC | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82682 | M 2700 | 249 - 15 | 00 General - |
| | W 3000 | 266 - 15 | |
| | N 4000 | 284 - 16 | |

Power supply options (remote only)

| OT96-D010 | OT96-JBX |
|--|--|
| Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure | Osram, Non-dim 24VDC, 120-277VAC, Wet location |



Orma Trimless Frosted | Path-Marker | powerLED



| C.C. 4W DC - 350mA | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82695 | M 2700 | 490 - 50 | 00 General - |
| | W 3000 | 490 - 50 | |
| | N 4000 | 529 - 54 | |



Power supply options (remote only)

| ECO30W-350 | SOLO50W-350 | SOLO100W-220 |
|---|--|--|
| 0-10V EldoLED ECOdrive 30W for 1-3 fixtures | 0-10V EldoLED SOLOdrive 50W for 1-6 fixtures | 0-10V EldoLED SOLOdrive 100W for 1-12 fixtures |

| C.V. 5W DC - 24 VDC | Cct | lm S - D | Optic |
|-------------------------|---------------|----------|---------------------|
| Glass Alu E82696 | M 2700 | 490 - 50 | 00 General - |
| | W 3000 | 490 - 50 | |
| | N 4000 | 529 - 54 | |

Power supply options (remote only)

| OT96-D010 | OT96-JBX |
|--|--|
| Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure | Osram, Non-dim 24VDC, 120-277VAC, Wet location |



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.