

# suelo underwater



AquaStop®



Suelo and Suelo PRO are also suitable for underwater environment thanks to the new IP68 versions equipped with the AquaStop® system.


Small and high-performing, these articles come with an anti-vandalism fixing screw thus making them suitable for installation in fountains or in other extremely deep environments as well as easy to reach depths.

## **Materials**

Aluminum body

AISI 316L stainless steel flange

Suelo | Up-Light | 1W powerLED | Submersible | Driver remote | Driver over




C.C. - 350mA

Steel	E80432	2700K	136 lm	M	Medium Flood	20
		3000K	145 lm	W	Medium Flood	35
		4000K	155 lm	N		

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Suelo Pro | Up-Light | 1W powerLED | Submersible | Driver remote | Driver over



C.C. - 350mA

Steel	E80433	2700K	136 lm	M	Medium Flood	20
		3000K	145 lm	W	Medium Flood	35
		4000K	155 lm	N		

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

C.V. - 24V

Steel	E80434	2700K	136 lm	M	Medium Flood	20
		3000K	145 lm	W	Medium Flood	35
		4000K	155 lm	N		

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120- 277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location