


**Orma Flush Trim | Blade | 2.5" Ø**



C.C. - 8W DC 630 mA	Cct	lm S - D	Optic
Steel/Alu <b>E83642</b>	<b>M</b> 2700	1080 - 219	<b>18</b> E.W.Flood -
	<b>W</b> 3000	1126 - 219	
	<b>N</b> 4000	1188 - 236	





**Power supply options (remote only)**

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. 9W DC 24VDC	Cct	lm S - D	Optic
Steel/Alu <b>E83643</b>	<b>M</b> 2700	1193 - 219	<b>18</b> E.W.Flood -
	<b>W</b> 3000	1244 - 219	
	<b>N</b> 4000	1313 - 236	

**Power supply options (remote only)**

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



technical information

\*NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush\*. Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL). Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations. Inter-lux reserves the right to make technical changes without notice.

