


Orma Semi-Flush Trim | Blade | 3.8" Ø



| C.C. - 8W DC 630 mA | Cct | lm S - D | Optic |
|-------------------------|---------------|------------|-----------------------|
| Steel/Alu E83644 | M 2700 | 1080 - 219 | 18 E.W.Flood - |
| Brass/Alu E84316 | W 3000 | 1126 - 219 | |
| | N 4000 | 1188 - 236 | |




Power supply options (remote only)

| ECO30W-630 | SOLO50W-630 | SOLO100W-630 |
|---|--|---|
| 0-10V EidoLED ECOdrive 30W for 1-3 fixtures | 0-10V EidoLED SOLOdrive 50W for 1-4 fixtures | 0-10V EidoLED SOLOdrive 100W for 1-8 fixtures |

| C.V. 9W DC 24VDC | Cct | lm S - D | Optic |
|-------------------------|---------------|------------|-----------------------|
| Steel/Alu E83645 | M 2700 | 1193 - 219 | 18 E.W.Flood - |
| Brass/Alu E84317 | W 3000 | 1244 - 219 | |
| | N 4000 | 1313 - 236 | |

Power supply options (remote only)

| OT96-D010 | OT96-JBX |
|--|--|
| Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure | Osram, Non-dim 24VDC, 120-277VAC, Wet location |



NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
 Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
 NOT suitable for submersible installations.
 Inter-lux reserves the right to make technical changes without notice.

