



Orma Semi-Flush Trim | Fixed | 3.8" Ø (RGBW)



Material	Part Number	Cct	Optic
Steel/Alu	E81321	Q RGBW natural white	06 N.Spot -
Brass/Alu	E84301	V RGBW warm white	15 Spot -
			45 W.Flood -
			00 General -

, Quad-chip LED

Power supply options (remote only)

PWR50W-630
DMX EldoLED
POWERdrive 50W
for 1-5 fixtures

E99651
Concrete casing
PVC



E83252
Tile casing
PVC



RTG E80588W30 / E81321V45

Feed Cables**

E99216	E89190	E98476	E98477
59 in. DC(+) power cable F 4 pin M12	196 in. DC(+) power cable F 4 pin M12	59 in. DC(-) power cable M 4 pin M12	196 in. DC(-) power cable M 4 pin M12

** One Female DC(+) and one Male DC(-) required per driver

Extension Cables***

E98437	E98149	E89188
39 in. Extension power cable M+F 4 pin M12	196.85 in. Extension for power cable M+F 4 pin M12	393.7 in. Extension for power cable M+F 4 pin M12

***Required between fixtures powered from the same driver

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

technical
information