



Orma Semi-Flush Trim | Fixed | 3.8" Ø (RGBW)



RGBW* - 8W DC - 630 mA	Cct	Optic
Steel/Alu E81321	Q RGBW natural white	06 N.Spot -
Brass/Alu E84301	V RGBW warm white	15 Spot -
		45 W.Flood -
		00 General -

, Quad-chip LED

Power supply options (remote only)

PWR50W-630

DMX EldoLED
POWERdrive 50W
for 1-5 fixtures


E99651

Concrete
casing
PVC



E83252

Tile
casing
PVC



RTG E80588W30 / E81321V45

Feed Cables**

E99216

59 in. DC(+) power cable
F 4 pin M12

E89190

196 in. DC(+) power cable
F 4 pin M12

E98476

59 in. DC(-) power cable
M 4 pin M12

E98477

196 in. DC(-) power cable
M 4 pin M12

** One Female DC(+) and one Male DC(-) required per driver

Extension Cables***

E98437

39 in. Extension power cable
M+F 4 pin M12

E98149

196.85 in. Extension for power cable
M+F 4 pin M12

E89188

393.7 in. Extension for power cable
M+F 4 pin M12

***Required between fixtures powered from the same driver

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Uplights and in-ground lamps

technical
information

inter-lux.com

K38