



**Orma Trim Semi-Flush Trim | Concentric | 1.6" Ø**




C.V. 1.5W DC - 24VDC		Cct	lm S - D	Optic
White	<b>E95474</b>	M 2700	136 - 54	00 General
Black	<b>E95475</b>	W 3000	145 - 60	
Grey	<b>E95476</b>	N 4000	155 - 63	

**Power supply options (remote only)**


**OT96-D010**  
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

**OT96-JBX**  
Osram, Non-dim 24VDC, 120-277VAC, Wet location


**E98291**  
Concrete casing



**E98292**  
Tile casing  
PVC



**Orma Trim Semi-Flush Trim | Concentric | 2.2" Ø**



C.V. 1W DC - 350mA		Cct	lm S - D	Optic
Black	<b>E82665</b>	M 2700	136 - 6	00 General -
		W 3000	145 - 6	
		N 4000	155 - 7	

**Power supply options (remote only)**

**EC030W-350**  
0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtu es

**SOLO50W-350**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-20 fixtu es

**SOLO100W-350**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-40 fixtu es

C.V. 1.5W DC - 24VDC		Cct	lm S - D	Optic
Black	<b>E82666</b>	M 2700	136 - 6	00 General -
		W 3000	145 - 6	
		N 4000	155 - 7	

**Power supply options (remote only)**


**OT96-D010**  
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

**OT96-JBX**  
Osram, Non-dim 24VDC, 120-277VAC, Wet location

**E83038**  
Concrete casing  
PVC



**E99922**  
Tile casing  
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).  
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.  
NOT suitable for submersible installations.  
Inter-lux reserves the right to make technical changes without notice.