



Orma Trim Semi-Flush Fixed | Up-Light | powerLED



C.C. 4W DC - 350mA		Cct	lm S - D	Optic
Steel Alu	E80582	M 2700	490 - 272	15 Spot (22°)
Brass Alu	E84289	W 3000	490 - 272	30 Flood (29°)
		N 4000	529 - 294	60 W.Flood (48°)
				25 Elliptical -

HC		Cct	lm S - D	Optic
Steel Alu	E80583	M 2700	490 - 187	15 Spot (20°)
Brass Alu	E84290	W 3000	490 - 187	30 Flood (25°)
		N 4000	529 - 202	60 Flood (37°)

DL		Cct	lm S - D	Optic
Steel Alu	E80584	M 2700	490 - 194	15 Spot (22°)
Brass Alu	E84291	W 3000	490 - 194	30 Flood (30°)
		N 4000	529 - 209	60 W.Flood (55°)

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECODrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures



C.V. 5W DC - 24 VDC		Cct	lm S - D	Optic
Steel Alu	E80585	M 2700	490 - 272	15 Spot (22°)
Brass Alu	E84292	W 3000	490 - 272	30 Flood (29°)
		N 4000	529 - 294	60 W.Flood (48°)
				25 Elliptical -

HC		Cct	lm S - D	Optic
Steel Alu	E80586	M 2700	490 - 187	15 Spot (20°)
Brass Alu	E84293	W 3000	490 - 187	30 Flood (25°)
		N 4000	529 - 202	60 Flood (37°)



DL		Cct	lm S - D	Optic
Steel Alu	E80587	M 2700	490 - 194	15 Spot (22°)
Brass Alu	E84294	W 3000	490 - 194	30 Flood (30°)
		N 4000	529 - 209	60 W.Flood (55°)

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



Orma Trim Semi-Flush Fixed | Up-Light | arrayLED



C.C. - 8W DC - 220 mA		Cct	lm S - D	Optic
Steel Alu	E80588	M 2700	1080 - 858	15 Spot (15°)
Brass Alu	E84295	W 3000	1126 - 894	30 Flood (31°)
		N 4000	1188 - 944	60 W.Flood (61°)

HC		Cct	lm S - D	Optic
Steel Alu	E80589	M 2700	1080 - 619	15 Spot (15°)
Brass Alu	E84296	W 3000	1126 - 646	30 Flood (27°)
		N 4000	1188 - 681	60 W.Flood (49°)

DL		Cct	lm S - D	Optic
Steel Alu	E80590	M 2700	1080 - 576	15 Spot (16°)
Brass Alu	E84297	W 3000	1126 - 600	30 Flood (29°)
		N 4000	1188 - 634	60 W.Flood (53°)

Power supply options (remote only)

ECO30W-220	SOLO50W-220	SOLO100W-220
0-10V EldoLED ECODrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

C.V. 9W DC - 24 VDC		Cct	lm S - D	Optic
Steel Alu	E81172	M 2700	1193 - 955	15 Spot (15°)
Brass Alu	E84298	W 3000	1244 - 997	30 Flood (31°)
		N 4000	1313 - 1052	60 W.Flood (61°)

HC		Cct	lm S - D	Optic
Steel Alu	E81173	M 2700	1193 - 687	15 Spot (15°)
Brass Alu	E84299	W 3000	1244 - 716	30 Flood (27°)
		N 4000	1313 - 756	60 W.Flood (49°)

DL		Cct	lm S - D	Optic
Steel Alu	E81174	M 2700	1193 - 639	15 Spot (16°)
Brass Alu	E84300	W 3000	1244 - 667	30 Flood (29°)
		N 4000	1313 - 704	60 W.Flood (53°)



Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
 NOT suitable for submersible installations.

Inter-lux reserves the right to make technical changes without notice.

Orma Trim Semi-Flush Fixed RGBW | Up-Light | arrayLED



RGBW - 8W DC - 630 mA	Cct	Optic
Steel/Alu E81321	Q RGBW natural white	06 N.Spot -
Brass/Alu E84301	V RGBW warm white	15 Spot -
		45 W.Flood -
		00 General -

Power supply options (remote only)

EC030W-630
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtures


SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtures

E99651
Recessed casing
PVC





E83201
Recessed casing
PVC



RTG E80588W30 / E81321V45

Orma Trim Semi-Flush Fixed | Up-Light | arrayLED



C.C. 12W DC - 350mA	Cct	lm S - D	Optic
Steel/Alu E81175	M 2700	1724 - 1379	15 Spot (14°)
Brass/Alu E84302	W 3000	1724 - 1379	30 Flood (31°)
	N 4000	1854 - 1485	60 W.Flood (60°)

HC	Cct	lm S - D	Optic
Steel/Alu E81176	M 2700	1724 - 981	15 Spot (14°)
Brass/Alu E84303	W 3000	1724 - 981	30 Flood (28°)
	N 4000	1854 - 1055	60 W.Flood (49°)

DL	Cct	lm S - D	Optic
Steel/Alu E81177	M 2700	1724 - 1094	15 Spot (14°)
Brass/Alu E84304	W 3000	1724 - 1094	30 Flood (30°)
	N 4000	1854 - 1178	60 W.Flood (52°)

Power supply options (remote only)

EC030W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixture

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtures

E99652
Recessed casing
PVC



E83202
Recessed casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.