


Orma Trimless Concentric (Rings) | Up-Light | powerLED



C.C. 1W DC - 350mA		Cct	lm S - D	Optic
Black	E82665	M 2700	136 - 6	00 General -
		W 3000	145 - 6	
		N 4000	155 - 7	

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

C.V. 1.5W DC - 24VDC		Cct	lm S - D	Optic
Black	E82666	M 2700	136 - 6	00 General -
		W 3000	145 - 6	
		N 4000	155 - 7	

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83038
Recessed casing
PVC




E99922
Recessed casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Trimless Concentric (Rings) | Up-Light | powerLED



C.C. 2W DC - 630mA	Cct	lm S - D	Optic
Black E82679	M 2700	249 - 13	00 General -
	W 3000	266 - 13	
	N 4000	284 - 14	



Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EidoLED ECOdrive 30W for 1-10 fixtures	0-10V EidoLED SOLOdrive 50W for 1-16 fixtures	0-10V EidoLED SOLOdrive 100W for 1-32 fixtures


C.V. 2.5W DC - 24 VDC	Cct	lm S - D	Optic
Black E82680	M 2700	249 - 13	00 General -
	W 3000	266 - 13	
	N 4000	284 - 14	

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



Orma Trimless Concentric (Rings) | Up-Light | powerLED



C.C. 4W DC - 350mA	Cct	lm S - D	Optic
Black E82693	M 2700	490 - 34	00 General -
	W 3000	490 - 34	
	N 4000	529 - 37	



Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-220
0-10V EidoLED ECOdrive 30W for 1-3 fixtures	0-10V EidoLED SOLOdrive 50W for 1-6 fixtures	0-10V EidoLED SOLOdrive 100W for 1-12 fixtures

C.V. 5W DC - 24 VDC	Cct	lm S - D	Optic
Black E82694	M 2700	490 - 34	00 General -
	W 3000	490 - 34	
	N 4000	529 - 37	

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.