



CIRCOLO LIGHT + ACOUSTIC

Housing: Aluminum profile with integrated opal diffuser and fabric covering as a light and acoustic diffuser.
Design: SATTLER



Housing in 1 part




fabric characteristics
o sound absorption coefficient $\alpha_w = 0,55$
In the range of 500 - 2.000 Hz relevant for human speech, an absorption maximum of up to 0.82 is reached.
o fire protection class B1
o fabric color white


Size: L x W x H mm	Inches	LED Watt	Lumen ¹⁾	Weight ²⁾ kg/ lbs	Item No.	LED	Dimming	LED	Finishes	Power supply cable	Mounting version	
Sizes												
Ø 750 / 29.5"	H 80 / 3.1" B 40 / 1.6"	48	3.009	8 / 17.6	1200	X X .	X X .	X X .	X X .	X X X .	X	
Ø 900 / 35.5"	H 80 / 3.1" B 40 / 1.6"	57	3.641	10 / 22.0	1201	X X .	X X .	X X .	X X .	X X X .	X	
Ø 1320 / 35.5"	H 80 / 3.1" B 40 / 1.6"	83	5.442	20 / 44.0	1202	X X .	X X .	X X .	X X .	X X X .	X	
Ø 1600 / 62.9"	H 80 / 3.1" B 40 / 1.6"	101	6.614	25 / 55.1	1203	X X .	X X .	X X .	X X .	X X X .	X	
Ø 1800 / 70.8"	H 80 / 3.1" B 40 / 1.6"	114	7.256	30 / 66.0	1204	X X .	X X .	X X .	X X .	X X X .	X	
LED 24V		Standard: Neutral-white	4000 K		X X X .	40.	X X .	X X .	X X .	X X X .	X	
CRI > 90		Optional:	Warm-white	3000 K	X X X .	30.	X X .	X X .	X X .	X X X .	X	
			Extra warm-white	2700 K	X X X .	27.	X X .	X X .	X X .	X X X .	X	
			Tunable white*	2700 - 6500 K	X X X .	80.	X X .	X X .	X X .	X X X .	X	
			RGB color control*		X X X .	60.	X X .	00.	X X .	X X X .	X	
			RGB + Neutral-White*	4000 K	X X X .	60.	X X .	40.	X X .	X X X .	X	
			*(only in combination with dimming DMX and CASAMBI) Combinations up to two stripes of LED possible									
Dimming		Standard: Without Dimmer			X X X .	X X .	01.	00.	X X .	X X X .	X	
		Optional:	DMX (not for mounting S,T)		X X X .	X X .	31.	00.	X X .	X X X .	X	
			0 - 10 V		X X X .	X X .	51.	00.	X X .	X X X .	X	
			CASAMBI		X X X .	X X .	81.	00.	X X .	X X X .	X	
Finish		Standard:	12 white, powder coated, similar RAL 9003	Optional (Powder coated):								
			11 white, similar RAL 9010	10 black fine textured	30 anthracite fine textured	32 crocodile black	33 sand silver fine textured					
			34 bronze satined	35 gold	36 brass	37 bronze fine textured	38 copper					
		Optional (Premium):	22 Aluminum polished	27 brush-finished Aluminum								
					XX Custom finish	X X X .	X X .	X X .	X X .	---	X X X .	X
Power supply cable		Standard:	Z 70 Silver	Optional:								
			Z 71 white	Z 72 grey	Z 73 black							
			Z 74 orange	Z 75 red	Z 76 green							
						Without power cable						
					000 Current-carrying F, R, T, K	X X X .	X X .	X X .	X X .	X X .	---	X

CIRCOLO LIGHT + ACOUSTIC

Housing: Aluminum profile with integrated opal diffuser and fabric covering as a light and acoustic diffuser.
Design: SATTLER




Housing in 1 part




fabric characteristics
 o sound absorption coefficient $\alpha_w = 0,55$
 In the range of 500 - 2.000 Hz relevant for human speech, an absorption maximum of up to 0.82 is reached.
 o fire protection class B1
 o fabric color white


Mounting Version




4-point suspension with external power supply unit in suspended ceiling




4-point suspension with external power supply unit in separate canopy




suspension through canopy




4 current-carrying steel cables. Only 1 stripe LED possible. Not in combination with RGB




Suspension with current-carrying steel cables and cavity wall box. Not in combination with RGB




Suspension with pendant canopy and steel cables (a) 5000 mm / 196.8" + (b) 3000 mm / 118.1"




Suspension with pendant canopy PB 366 and current-carrying steel cables.
 (a) 5000 mm / 196.8" + (b) 3000 mm / 118.1"
 Not in combination with RGB



Direct ceiling mounting 50mm / 1.9" with external power supply unit in suspended ceiling



Direct ceiling mounting (white) 50mm / 1.9" with external power supply unit in separate canopy



Suspension point as clamping unit with 4 current-carrying cables and remote technical unit in suspended ceiling.

Item No.	LED	Dimming	LED	Finishes	Power supply cable	Mounting version
X X X.	X X.	X X.	X X.	X X.	X X X	-

A, B, G, H, R = Distance of external power supply unit to light fixture max. 10m / 394".

S, T, K, E, F = Minimum suspension height half the diameter of light fixture, maximum suspension height two times diameter of light fixture

Including steel cable suspension 5000mm / 197" ; Version F, R, S, T 5000 / 3000mm / 197"/118" and/or power supply cable 5000mm / 197"



---	---	---	---	---	---	---
-----	-----	-----	-----	-----	-----	-----

Complete order number

Power supply units: (1 LED Stripe)		Protective rating
Type / Size mm / inch	For use with Mounting version	
DE 1F 360 x 150 x 85 mm / 14.2 x 5.9 x 3.3"	A,G,R,K	IP 20

Input voltage for all external power supply units and canopy is **90-277 VAC 47-63 Hz**

Canopy: (1 LED Stripe)		Protective rating
Type/ Size mm / inch	For use with Mounting version	
DB 290 Ø 290 / 260 / 60 mm / 11.4 x 10.2 / 2.3"	B, E, F, H	IP 20
PB 366 Ø 90 H 366 mm / 3.5 x 14.4"	S, T	IP 20 (up to Ø 1320)
PB 656 Ø 90 H 656 mm / 3.5 x 25.8"	S, T	IP 20 (up to Ø 1800)

Color: 12 white, similar RAL 9003, contact factory for other finishes
 USA/Canada: Canopy mounts to 4" octagonal junction box.

Optional




CASAMBI wall-switch

207. 00. 00. 00. 12. (white)

207. 00. 00. 00. 10 (black)

Casambi wall-switch is a wireless user interface that can be configured via the Casambi app. The four target buttons can control a scene or an animation of the user's choice or simply one luminaire, one luminaire group or all lights together if so desired. Up to 4 groups may be separately programmed. It comes with a wall mounting plate. The switch may be also used on its own as it is attached to the wall plate using magnets.



Ceiling fixation for mounting version A

200. 00. 00. 00. 12 (white)

Consisting of a cavity ceiling box with 80mm round metal cover. Applicable to mounting version A.