


ProTools 60 Linear Wall Wash Recessed

WG-60PTLWW-...-LML-WW-...-W-W Delivered Lumens Per Foot					
		Power			
		P1 [3 W/ft]	P2 [6 W/ft]	P3 [10 W/ft]	P4 [15 W/ft]
CCT	927	268	504	774	1141
	930	279	524	806	1188
	935	289	543	836	1244
	940	297	558	858	1278
		Power Multiplier			
		P1 [3 W/ft]	P2 [6 W/ft]	P3 [10 W/ft]	P4 [15 W/ft]
		0.24	0.44	0.68	1.00
		CCT Multiplier			
		927	930	935	940
		0.96	1.00	1.04	1.06



BEAM ANGLE (0-180) = 57.8
BEAM ANGLE (90-270) = 102

ILLUMINANCE - 24" LML-WW P4 3000K WG-60PTLWW-...-S-24-930-LML-WW-P4-...-W-W ¹		
Mounting Height [ft]	Illuminance [fc at nadir]	Beam Width [ft]
3	155	3.3
6	39	6.6
9	17	9.9
12	10	13.3
15	6	16.6
18	4	19.9
21	3	23.2
24	2	26.5
27	2	29.8
30	2	33.1

WG-60PTLWW-...-TW-LML-WW-... Delivered Lumens Per Foot			
		Power	
		P2 [6 W/ft]	P3 [10 W/ft]
CCT	2200	254	375
	4000	261	395

PROTOOLS 60 LINEAR UGR + FIXTURE EFFICIENCY					
		UGR ²			
		P1 [3W/ft]	P2 [6W/ft]	P3 [10W/ft]	P4 [15W/ft]
OPTIC - BEAM	LML-WW	31.1	33.3	34.8	36.1

1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
2 UGR value noted is the maximum UGR (crosswise) with 930 LEDs at noted Power level.