



3" ProTools Adjustable Square Recessed



Recessed Cone (SRC) / Bezel Trim (RBT)




Recessed Cone (SRC) / Plaster Trim (RPT)




Bezel Trim (RBT)

Plaster Trim (RPT)



Minimum of 5" (126mm) ceiling void is required to install the integral driver from below the ceiling.



Multiple luminaire configurations for plaster trim. See Multiple Luminaire specsheet for details.

Ordering Information										
Model	Fixation	Power ^{1,2}	CRI	CCT ^{2,3}	Driver ⁴	Cover	Beam	Trim Finish ⁵	Cover Finish ⁵	Options
WG-75SPTA										
WG-75SPTA	RBT RPT	L M H	92	27 30 35 40	S S010 PEQ0 SPH RD010 RPEQ1 RDFPN RPEQ0	SRC SRPH	25 36	W (std) S F	W (std) S F	CP IC NC LP WL RDL

Luminaire

- Part of a complete family of 3" aperture matching downlights.
- Multiple beam spreads to accommodate all applications.
- High lumen output and excellent color rendition for all applications.
- Installs from below the ceiling for new and retrofit installations.
- Very shallow ceiling depth required for both integral and remote drivers.
- Multiple luminaire configurations for plaster trim. See Multiple Luminaire specsheet for details.

Fixation

- RPT = Recessed Plaster Trim
- RBT = Recessed Bezel Trim

Power^{1,2}

- L = Low Power, 5.9W @ 350mA
- M = Mid Power, 8.6W @ 500mA
- H = High Power, 12.4W @ 700mA

CRI

- 92 = 92 CRI

CCT (Low/Mid/High Power)^{2,3}

- 27 = 2700K, (727/989/1306 lm)
- 30 = 3000K, (782/1064/1405 lm)
- 35 = 3500K, (782/1064/1405 lm)
- 40 = 4000K, (837/1139/1505 lm)

Integral Driver⁴

- S = Standard non-dim driver, 120-277V
- S010 = Standard 10% 0-10V dimming, 120-277V
- SPH = Standard 10% Phase Dimming, 120V only (available in low and mid power only)
- PEQ0 = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V

Remote Driver⁴

- RD010 = EldoLED, 1% 0-10V dimming, 120-277V
- RDFPN = Lutron Forward Phase 1%, 120V only
- RPEQ0 = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V

Cover

- SRC = Square Recessed Cone
- SRPH = Square Regressed Pinhole (available as 25° only)

Beam

- 25 = 25° Beam Angle
- 36 = 36° Beam Angle

Trim Finish⁵

- W = White, 15% gloss, Tiger Drylac 49/11350 (standard)
- S = Silver, 15% gloss, Tiger Drylac 49/90500
- F = Custom finish, specify RAL code

Cover Finish⁵

- W = White, 15% gloss, Tiger Drylac 49/11350 (standard)
- S = Silver, 15% gloss, Tiger Drylac 49/90500
- F = Custom finish, specify RAL code

Options

- CP = Chicago Plenum Housing
- IC = Insulated Ceiling Housing
- NC = New Construction Housing
- LP = Landing Pan (specify for Acoustic Ceiling Tile installation)
- WL = Wet Location (only available with SRC)
- RDL = Regressed Diffused Lens

Emergency Remote Only

- Emergency LED battery backup available, ordered separately

1. Wattage shown does not include power supplies/drivers. System wattage adds 10-20%.
2. Other lumen packages available, consult factory.
3. Source lumens shown, see IES files for delivered lumens.
4. See power supply page for details.
5. See Tiger Drylac color chart: inter-lux.com/tiger