


20 Linear Mini Edgeless Cove


WG-20MEC-...-SD-W					
Delivered Lumens Per Foot					
		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	248	495	867	-
	930	270	538	942	-
	935	319	640	1119	-
	940	380	760	1330	-
	WD ²	190	394	569	-
	RGBW ³	-	-	-	322
UGR ⁴		-	-	-	-



BEAM ANGLE (0-180) = 80.2
BEAM ANGLE (90-270) = 100.7

ILLUMINANCE - 48" SD H 3500K		
WG-20MEC-...-S-48-H-935-...-SD-W-... ¹		
Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	511	3.4
4	128	6.7
6	57	10.1
8	32	13.5
10	20	16.8
12	14	20.2
14	10	23.6
16	8	26.9
18	6	30.3
20	5	33.7

WG-20MEC-...-OD-W					
Delivered Lumens Per Foot					
		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	176	352	617	-
	930	192	383	670	-
	935	227	455	796	-
	940	270	540	946	-
	WD ²	135	280	405	-
	RGBW ³	-	-	-	229
UGR ⁴		-	-	-	-



BEAM ANGLE (0-180) = 110.1
BEAM ANGLE (90-270) = 110.1

ILLUMINANCE - 48" OD H 3500K		
WG-20MEC-...-S-48-H-935-...-OD-W-... ¹		
Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	277	5.7
4	69	11.4
6	31	17.2
8	17	22.9
10	11	28.6
12	8	34.3
14	6	40.1
16	4	45.8
18	3	51.5
20	3	57.2

Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.29	0.57	1.00	0.29
WD	0.17	0.35	0.51	-
CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.