



Advantages

- Available in multiple lengths to accommodate exacting installations
- Multiple wattages and lumen output for maximum flexibility within any application
- Four (4) standard color temperatures from 2700K-4000K; non-standard available
- Compatible with all common dimmer and control standards such as 0-10V, 3-wire, forwardphase w/neutral, DALI and DMX. For others, please contact factory
- High efficiency design delivers more lumens per watt
- Same LED technology used throughout all Whitegoods products for color and performance consistency
- 5-year warranty

Technical Data

- form linear
- circuitry parallel
- power (W/ft) 3W, 6W, 10W
- supply type CV
- operating voltage (VDC) 24
- color rendering index Ra 90+
- MacAdam 3 step
- viewing angle (°) 120
- LED (SMD) quantity (per foot) 70
- PCB substrate FR4
- lifetime-L70 (h)* 60,000
- working temperature -40°C - 100°C

*Tested to LM80

Power (w/ft)	CCT (k)	Lum.Flux (lm/ft)	lm/watt
3	2700	427	142
3	3000	427	142
3	3500	427	142
3	4000	427	142
6	2700	889	148
6	3000	889	148
6	3500	889	148
6	4000	889	148
10	2700	1491	149
10	3000	1491	149
10	3500	1491	149
10	4000	1491	149

Conformal coated boards for damp and wet location applications are available.