




ZTA.50.Bay



Order Code	ZTA.50.Bay.light source.beam.finish
------------	-------------------------------------

- Materials: Aluminum
- Mount type: Surface
- Light source: Osram Oslon Square LED
Xicato XOB COB LED

LED lifetime: L70, B0, F0 at 50,000hrs Col consistency: 1x2 SDCM
Luminus Tuneable White LED
- Output: See table on page 2
- Dimming: See table on page 2
- Finish: Anodized or painted to any RAL color (interior Matt Black)
Standard offering is RAL 9010 Pure White or Matt Black
- Supply: Remote constant current driver
- Cable: 2x0,34mm² (as standard: 500mm, black)
- Weight: 0.7lbs (0.3kg)
- Description: ZTA is a truly unconstrained new product range, be that in choice of light source, optic, paint finish, control system or how it's mounted. With a simpler aesthetic, it offers versatility and a product that is truly maintainable, re-manufacturable and ultimately recyclable.
- Beams: See table over page
- Accessories: Can accommodate up to 2 x Ø2" (50mm) lens or louver

High output, fixed optics	Low output, fixed optics and Zoom	Dedicated Very Narrow spot	Tuneable White																																						
Xicato XOB 0.39" (9.8mm)	Xicato XOB 0.24" (6mm)	Oslon Star	CTM-9-6527-90-36-TWD2																																						
Dimming Option	Dimming Option	Dimming Option	Dimming Option																																						
0-10V, DALI, Mains or Wireless (Xicato or Casambi)	0-10V, DALI, Mains or Wireless (Xicato or Casambi)	0-10V, DALI, Mains or Wireless (Xicato or Casambi)	0-10V, DALI, Mains or Wireless (Xicato or Casambi)																																						
<table border="0"> <tr> <td>CRI ≥ 90</td> <td>CRI ≥ 95</td> </tr> <tr> <td>1513lm</td> <td>1341lm</td> </tr> <tr> <td>(Initial @ 3000K)</td> <td>(Initial @ 3000K)</td> </tr> <tr> <td>11.9W at 350mA</td> <td>11.9W at 350mA</td> </tr> <tr> <td>Typ. 34Vf</td> <td>Typ. 34Vf</td> </tr> </table>	CRI ≥ 90	CRI ≥ 95	1513lm	1341lm	(Initial @ 3000K)	(Initial @ 3000K)	11.9W at 350mA	11.9W at 350mA	Typ. 34Vf	Typ. 34Vf	<table border="0"> <tr> <td>CRI ≥ 90</td> <td>CRI ≥ 95</td> </tr> <tr> <td>873lm</td> <td>798lm</td> </tr> <tr> <td>(Initial @ 3000K)</td> <td>(Initial @ 3000K)</td> </tr> <tr> <td>7.9W at 250mA</td> <td>7.9W at 250mA</td> </tr> <tr> <td>Typ. 31.6Vf</td> <td>Typ. 31.6Vf</td> </tr> </table>	CRI ≥ 90	CRI ≥ 95	873lm	798lm	(Initial @ 3000K)	(Initial @ 3000K)	7.9W at 250mA	7.9W at 250mA	Typ. 31.6Vf	Typ. 31.6Vf	<table border="0"> <tr> <td>CRI ≥ 90</td> <td></td> </tr> <tr> <td>252lm</td> <td></td> </tr> <tr> <td>(Initial @ 3000K)</td> <td></td> </tr> <tr> <td>3W at 1050mA</td> <td></td> </tr> <tr> <td>Typ. 3Vf</td> <td></td> </tr> </table>	CRI ≥ 90		252lm		(Initial @ 3000K)		3W at 1050mA		Typ. 3Vf		<table border="0"> <tr> <td>CRI ≥ 90</td> <td></td> </tr> <tr> <td>1128lm</td> <td>1320lm</td> </tr> <tr> <td>(Initial @ 2700K)</td> <td>(Initial @ 6500K)</td> </tr> <tr> <td colspan="2">10.2W at 300mA</td> </tr> </table>	CRI ≥ 90		1128lm	1320lm	(Initial @ 2700K)	(Initial @ 6500K)	10.2W at 300mA	
CRI ≥ 90	CRI ≥ 95																																								
1513lm	1341lm																																								
(Initial @ 3000K)	(Initial @ 3000K)																																								
11.9W at 350mA	11.9W at 350mA																																								
Typ. 34Vf	Typ. 34Vf																																								
CRI ≥ 90	CRI ≥ 95																																								
873lm	798lm																																								
(Initial @ 3000K)	(Initial @ 3000K)																																								
7.9W at 250mA	7.9W at 250mA																																								
Typ. 31.6Vf	Typ. 31.6Vf																																								
CRI ≥ 90																																									
252lm																																									
(Initial @ 3000K)																																									
3W at 1050mA																																									
Typ. 3Vf																																									
CRI ≥ 90																																									
1128lm	1320lm																																								
(Initial @ 2700K)	(Initial @ 6500K)																																								
10.2W at 300mA																																									
CCT	CCT	CCT	CCT																																						
2700K, 3000K, 3500K, or 4000K	2700K, 3000K, 3500K, or 4000K	2700K, 3000K, 3500K, or 4000K	2700K - 6500K																																						
Beam Options	Beam Options	Beam Options	Beam Options																																						
Narrow (15.1°) Medium (22°) Flood (31.2°) Flood 2 (44.3°) Wide Flood (64.5°)	Very Narrow (13.9°) Narrow (14.7°) Medium (24.1°) Flood (36.7°) Wide Flood (51.7°) Zoom (13.7°-48.1°)	Very Narrow (3.3°)	Narrow (19°) Medium (25°) Flood (34°) Wide Flood (42°)																																						

Accessories

