Updated 11.2022

Professional Architectural Lighting

MAESTRO 2.2

linea light group

MAESTRO 2.2

PROFESSIONAL ARCHITECTURAL LIGHTING

linealightgroup

indoor range index

click images to open product pages

Downlights

Vos

A7

Quantum

A23

Warp

A35

Epitax

A57

Giotto

A67

Loro

A71

Projectors

Creek

B3

Ceiling

Tour

C2

click images to open product pages

Path markers

Quara

E7

Laella

E10

Envelope

E12

Small spotlights

Bibok

F7

Crystals Elin

F11

Crystals Ture

F12

Crystals Gude

F13

Small projectors

Eyelet

G3

outdoor range index

click images to open product pages

Ceiling lamps

Orma_C

H7

Wall path markers

Envelope

J5

Sand

J11

Quara65

J13

Cut

J17

Uplights & inground lamps

Beret

K11

Orma

K15

Suelo

K51

click images to open product pages

Bollards

Ryo

L7

Joe

L13

Bond-pro

L17

Peak

L21

Apache

L29

Linear light

Paseo

M7

Xenia

M23

Archiline

M38

Dirigo

M72

Accent lighting

Eyelet65

N5

Periskop

N7

Iris67

N15

Light effects

Arcada

O5

Myia

O9

Loop66

O11

Paseo_Pixels

O15

outdoor range index

click images to open product pages

LED Strips

Ribbon	Dropper	Silicone_C	Rubber
			
P4	P6	P9	P39

DAMAC

DAMAC

A CREATIVE REALITY
IDEAS IN DESIGN

A DESIGNER'S IDEA ENCAPSULATED IN A QUALITY PRODUCT THAT WILL WITHSTAND THE TEST OF TIME.

IMAGINE A COMPANY CAPABLE OF CREATING LIGHTING DESIGN SOLUTIONS THAT ARE COMPLETELY TAILOR-MADE FOR YOUR PROJECTS. A REVOLUTIONARY KNOWLEDGE OF LED TECHNOLOGY TO GUARANTEE QUALITY, SUSTAINABILITY AND EFFICIENCY IN ANY SITUATION. A SINGLE GROUP CONSISTING OF SPECIALISED DEPARTMENTS TO RESPOND TO YOUR PROJECT'S EVERY NEED.

AT A TIME WHERE IDEAS ARE RESTRAINED BY THE LOGIC OF PRODUCTION AND UNIFORMITY, LINEA LIGHT GROUP HAS, OVER THE YEARS, SUCCEEDED IN DEVELOPING AN APPROACH IN THE MARKET AIMED AT BREATHING NEW LIFE INTO THE IMAGINATION AND RESTORING THE POWER OF CREATIVITY TO THE DESIGNER IN ANY WAY AND BY ANY MEANS. THE COMPANY'S SUCCESS IN THE WORLD OF LIGHTING IS FOUNDED ON REAL VALUES THAT MAKE ALL THE DIFFERENCE: EXPERIENCE AND INNOVATION; INTERNATIONAL VISION AND TYPICALLY ITALIAN DESIGN AND AVANT-GARDE TECHNOLOGY COMBINED WITH HANDCRAFTED PRECISION. THEIR PHILOSOPHY ADDRESSES THE COMPLEXITIES OF THE WORLD WE LIVE IN IN ORDER TO RESEARCH, DEVELOP AND CREATE SOLUTIONS FAR FROM THE EVERYDAY AND IN PERFECT HARMONY WITH ARCHITECTURE, NATURE AND PEOPLE.

Roma d+ design più INTERNATIONAL EXPODESIGN

reddot award

ADI COMPASSO D'ORO INTERNATIONAL AWARD


DESIGN
AWARD
2019

GLOBAL EXCELLENCE MADE IN ITALY

WORLDWIDE AVAILABILITY WITH PERSONALISED AND PUNCTUAL SERVICE

LINEA LIGHT GROUP IS A UNIQUE GROUP SPECIALIZED IN A DIVERSE RANGE OF DOMAINS WITHIN THE WORLD OF LIGHTING. IT IS INDEPENDENT YET COORDINATED AT THE SAME TIME. ITS FORMULA ALLOWS FOR THE CREATION OF COMPLETE, UNIQUE SOLUTIONS IN ANY GIVEN CONTEXT: FROM INTEGRATED SYSTEMS FOR LARGE RESIDENTIAL OR PUBLIC BUILDINGS TO OUTDOORS OR UNDERWATER LIGHTING; FROM HOME ENVIRONMENTS TO COMMERCIAL, INDUSTRIAL, INSTITUTIONAL OR PUBLIC SPACES.

LINEA LIGHT GROUP STANDS OUT THANKS TO A MARKET APPROACH THAT IS ATTENTIVE TO SPECIFIC REQUIREMENTS AND TO THE DEMANDS OF LOCAL PARTNERS. ITS “THINK GLOBAL, ACT LOCAL” VISION FOCUSSES ON MAKING CONNECTIONS BETWEEN DIFFERENT AREAS AND ON MANAGING SERVICES FROM A SHORTER DISTANCE. TODAY, LINEA LIGHT GROUP IS A COMPANY WITH A STRONG INTERNATIONAL PRESENCE AND AN EXTENSIVE NETWORK: WHEREVER THEIR PROJECTS MAY TAKE THEM, THEIR PARTNERS WILL BE RIGHT BY THEIR SIDE.

Shanghai
China
Beijing
China
Zhong Shan
China
Moscow
Russia
Singapore
New Delhi
India
Dubai
UAE
Doha
Qatar
Riyadh
Saudi Arabia
Czeladz
Poland
Athens
Greece
Mülheim a.d. Ruhr
Germany
Milan
Italy
Treviso
Italy
Rome
Italy
London
UK
Paris
France
Madrid
Spain
Wittelsheim
France
Baltimore
USA
Headquarters
Subsidiaries
Branches

ARCHI-TECH LIGHTING

A HARMONIOUS RELATIONSHIP WITH THE SURROUNDING ENVIRONMENT, A UNION WITH ARCHITECTURAL FEATURES.

TODAY, WE EXPECT LIGHTING TO INTEGRATE WITH ITS SURROUNDINGS, TO BE A VALUABLE ADDITION AND PROTAGONIST BUT NEVER THE PRIMA DONNA. LIGHTING TO ARCHITECTURE IS WHAT A GOOD COSTUME DESIGNER IS TO A PLAY: IT ADDS ATMOPSHERE TO EVERY SCENE.

MAESTRO 2.2 BRINGS TOGETHER FORMAL INNOVATION AND TECHNOLOGY BASED ON EXPERIENCE AND THE NEW DEMANDS OF ARCHITECTS AND LIGHTING DESIGNERS: THE PROPOSED SOLUTIONS CAN BE USED IN ANY GIVEN CIRCUMSTANCE, WITH PARTICULAR ATTENTION GIVEN TO INTEGRATION WITH ROOFS AND WALLS, ALL WHILE RETAINING A PROFESSIONAL STYLE. THIS ASPECT IS IN DIRECT OPPOSITION TO THE CURRENT FOCUS ON DESIGN AND A BALANCE BETWEEN THESE TWO CONCEPTS NEED TO BE STRUCK IN ORDER TO HIGHLIGHT WHAT IS TRULY IMPORTANT IN LIGHTING: THE LIGHT ITSELF.

THE PERFECT LIGHTING

RESEARCH AND DEVELOPMENT OF THE HIGHEST PERFORMING OPTICAL SYSTEMS

EACH LED IS CONFIGURED TO EMIT A SET AMOUNT OF LIGHT, BUT THE AMOUNT THAT IS ACTUALLY EMITTED IS DIFFERENT WHEN THE LAMP IS SUPPLIED WITH AN OPTICAL SYSTEM.

THE TASK OF FORMULATING THE EMISSION OF THE LIGHT BEAM FROM THE APPARATUS IS ENTRUSTED TO A DEDICATED OPTICAL SYSTEM, WHOSE PROVEN EFFICIENCY OPTIMISES THE LIGHT OUTPUT OF THE SOURCE.

THE ONGOING RESEARCH AND DEVELOPMENT OF LENSES AND REFLECTORS DESIGNED FOR AND PLANNED AROUND THE LED MEANS THAT, THANKS TO OUR KNOWLEDGE ACQUIRED OVER THE YEARS, WE CAN PROPOSE NEW TECHNICAL APPLICATIONS AIMED AT IMPROVING THE EXPERIENCE OF LIGHTING DESIGN IN A SIMPLE AND EFFICIENT WAY.

Narrow optics

Narrow Spot: 8°

Spot: 10°

Spot: 15°

Medium optics

Flood: 30°

Medium Flood: 45°

Medium Flood: 60°

Diffused optics

Wide Flood: 120°



General: 180°

Wall-mounted washing optics

Asymmetric Wall Washer: 27°

Elliptic: 25°

DESIGN COMPLETENESS




UGR<19
OptiLight technology
Directional spotlight
Fidelity
CRI 98
Indirect wall-lighting
Retail lighting
Specialty
CRI 98
General lighting
Pendant
architectural
luminaires
Cut-off optics
IP65
IK10

EVOLUTIONS IN ENGINEERING

MINIATURIZATION DOES NOT JUST MEAN MAKING PRODUCTS SMALLER.

THINKING OF IT IN THIS WAY MEANS THAT APECTS THAT ARE FUNDAMENTAL TO THIS PROCESS SUCH AS TECHNOLOGICAL INNOVATION, TOGETHER WITH THE STUDY OF MATERIALS, OPTICS AND APPLICATIONS, ARE OVERLOOKED. IN ADDITION, THE ADOPTION OF 'SPACESAVING' SOLUTIONS LIKE THE INTEGRATED AQUASTOP OR THE CV CONVERTER INCORPORATED WITHIN THE CABLE OR BODY OF THE LAMP ALLOWS US TO MAKE USE OF EACH PRECIOUS MILLIMETER IN THE MOST EFFECTIVE WAY. TO CREATE PRODUCTS THAT ARE SMALL BUT POWERFUL.

IN THE SAME WAY, INCREASING THE RANGE DOES NOT SIMPLY MEAN MAKING MORE PRODUCTS

IT IS ACTUALLY A PRODUCTION PHILOSOPHY TO WHICH LINEA LIGHT GROUP IS FULLY COMMITTED. A RESPONSE TO SPECIFIC PROJECT DEMANDS WHICH CANNOT BE MET BY A SINGLE PRODUCT. A DIVERSIFIED RANGE ALLOWS EACH STAGE OF A PROJECT TO BE COMPLETED, FROM ILLUMINATING THE TALLEST HEIGHTS TO LIGHTING FOOTPATHS, ALL WHILE ENSURING THAT STYLISTIC UNIFORMITY IS MAINTAINED. THE DESIGNER CAN MEET ALL OF A SINGLE FAMILY'S TECHNOLOGICAL NEEDS THANKS TO A DIVERSE RANGE OF APPLICATIONS WITH VARIOUS VERSIONS AND POWERS AVAILABLE.

ORMA_FJ 13W

Aquastop®

INTEGRATED AQUASTOP

CUSTOM ORIENTED

THE BEST TAILOR-MADE DRESS

FOR US, TAILOR-MADE FIRSTLY INVOLVES LOOKING BACK AT OUR LEARNED EXPERIENCES SO THAT WE CAN MOVE FORWARDS AND CREATE SOMETHING COMPLETELY DIFFERENT. THIS KNOW-HOW ALLOWS US TO MAKE 'TAILOR-MADE' PRODUCTS, SIMILAR TO A DRESS THAT AN EXPERIENCED TAILOR HAS SEWN FOR HIS CUSTOMER.

'TAILOR-MADE' MEANS ADAPTING LATEST GENERATION PRODUCTS TO FIT PRE-EXISTING AND IRREPLACEABLE SYSTEMS, AN OCCURRENCE THAT IS ANYTHING BUT RARE. IT CAN ALSO MEAN SELECTING SPECIFIC DIODES WITH DIFFERENT COLOR TEMPERATURES SUITABLE FOR A RANGE OF LIGHT SOURCES AND OPTICS ALLOWING FOR AN EXTREMELY DIVERSE RANGE OF USE. IN ADDITION, 'TAILOR-MADE', FOR US, MEANS CREATING ATTACHMENTS AND FIXTURES THAT ARE COMPATIBLE WITH IMPORTANT AND CORRODIBLE BUILDINGS OR ADAPTING A PRODUCT FOR PARTICULAR CLIMATIC CONDITIONS. LAST BUT NOT LEAST, 'TAILOR-MADE' MEANS KNOWING HOW TO ADAPT SINGLE PRODUCTS IN LENGTH, WIDTH AND SHAPE TO FULLY SATISFY MORE SPECIFIC LIGHTING NEEDS.

Detail of the profile designed specifically for the Curio Hotel project. The diffuser is painted in white to guarantee unobtrusive and scenic lighting. The LED circuits make use of Dynamic White technology and are managed by DMX protocol.

THE NEW LIGHTING ALPHABET

THE BEST LIGHTING ACCENTUATES THE ILLUMINATED OBJECT, ENHANCES ITS MOST ATTRACTIVE FEATURES AND PIQUES THE OBSERVER'S INTEREST.

THE SYNERGY BETWEEN CREE AND LINEA LIGHT GROUP HAS ALLOWED US TO REFINE NEW LIGHT SOURCES WITH THE AIM OF PROVIDING THE PERFECT LIGHTING FOR EVERY USE, WHETHER THAT BE IN AN OFFICE, MUSEUM OR FOR COMMERCIAL PURPOSES. BEHIND THIS IMPORTANT INNOVATION IS THE CLOSE ANALYSIS OF THE NEW PARAMETERS OUTLINED IN IES TM-30-15, A METHOD OF MEASURING THE MOST PRECISE LIGHTS AND MORE SPECIFICALLY, THE CRI. THE COMPARISON BETWEEN NATURAL LIGHT SOURCES AND LED FOR 99 COLOR SAMPLES (CES- COLOR EVALUATION SAMPLE), WITHIN SEVEN DIFFERENT CATEGORIES (NATURAL COLORS, SKIN TONE, MATERIAL, COLORS IN PAINTINGS, PLASTICS, PRINTED MATERIALS AND COLOR SYSTEMS) DETERMINES RF OR FIDELITY. THE RESULT IS DISPLAYED ON A SCALE BETWEEN 0 AND 100 WHERE THE MAXIMUM VALUE SHOWS COMPLETE FIDELITY.
THE OTHER VALUE TAKEN FROM TM-30-15 IS THE GAMUT OR RG, WHICH IS INDICATED BY A FIGURE BETWEEN 60 AND 140. THIS EXPRESSES THE DEGREE OF SATURATION OF THE COLORS ILLUMINATED BY THE LIGHT SOURCE.

CRI COLOR RANGE

The 99 samples used for determining TM-30 are the result of a logarithmic selection out of the 105,000 colors visible to the human eye.

TM-30 COLOR RANGE

FIDELITY

Rf - fidelity	97,8
RG - gamut	101
R9 - red	98
R12 - blue	95

(Values Detected)

SPECIALTY

Rf - fidelity	96
RG - gamut	103
R9 - red	96
R12 - blue	91

(Values Detected)

BALANCE

Rf - fidelity	93
RG - gamut	100
R9 - red	71
R12 - blue	87

(Values Detected)



FIDELITY

FIDELITY IN THE REPRESENTATION
OF A COLOR IN ALL OF ITS SHADES.

Mainly used in museums and in more prestigious retail spaces where the aim is to show the true depth of colors.

RF 93 - RG 99
CRI Ra 98
100 lm/W
2-step SDCM
(Typical Values)







SPECIALITY

RANGE OF CHROMATIC
SATURATION.

This selection is designed for all retail spaces where, rather than highlighting the colors, the aim is to create an ambiance that is not so much tied to the products on offer but to the overall experience.

RF 93 - RG 99
CRI Ra 98
100 lm/W
2-step SDCM
(Typical Values)







BALANCE

EFFICIENCY IN TERMS OF EMISSION AND OPTIMUM BALANCE BETWEEN FIDELITY AND GAMUT.

LED with high efficiency in terms of lumen/W which is suited to all applications where there are no specific requirements to emphasise color.

RF 92 - RG 100
CRI 92
115 lm/W
2-step SDCM (Typical Values)







ELECTRONIC CENTER

BETTER LONGEVITY GUARANTEED

ELECTRONICS, THE BEATING HEART OF ANY MODERN PIECE OF TECHNOLOGY, IS CENTRAL TO THE FIELD OF LED AND, CONSEQUENTLY, TO THE DEVELOPMENT OF LINEA LIGHT GROUP'S PROJECTS.
THIS IS BECAUSE, ALTHOUGH THIS TECHNOLOGY IS EXTREMELY ADAPTABLE, A UNIQUE CIRCUIT CREATED FOR A SPECIFIC PURPOSE IS BETTER ABLE TO FULLY EMPHASIZE THE LIGHTING QUALITY OF THE SELECTED DIODES AND HOW THEY FULFILL THE PURPOSE FOR WHICH THE LAMPS WERE DESIGNED AND CREATED.

COMPATIBILITY, SAFETY, PERFORMANCE: A TRIO OF EXCELLENCE ENABLING US TO GUARANTEE SAFE AND EFFICIENT PRODUCTS.



RELIABILITY AND PERFORMANCE

EACH DEVICE IS CONFIGURED AND DESIGNED TO HIGHLIGHT THE CAPACITY OF THE SOURCE AS MUCH AS POSSIBLE.

IN THE DESIGN STAGE, IT IS NOT JUST APPEARANCES THAT MATTER. THE MAIN ROLE OF THE BODY IS TO MAINTAIN A RUNNING TEMPERATURE LOWER THAN 60°C SO THAT THE PERFORMANCE OF THE LED AND THE LIFE CYCLE OF THE LAMP ARE NOT IMPACTED. TO ENSURE THE CORRECT THERMAL DISSIPATION, THE JUNCTION TEMPERATURE IS USED AS A REFERENCE POINT. THIS IS MEASURED WHERE THE DIODE SUBSTRATE AND THE PRINTED CIRCUIT MEET.
THIS ALLOWS US TO BE CERTAIN THAT NO LIGHT SOURCE USED WILL UNDERGO FLUCTUATIONS THAT COULD COMPROMISE THE QUALITY AND PERFORMANCE OF THE LAMP.





THE VALUES “L” AND “B” INDICATE, RESPECTIVELY, THE PERCENTAGE OF WASTE LIGHT FLOW AND THE PERCENTAGE OF LEDS THAT DO NOT COMPLY WITH THE SPECIFICATION OVER A PERIOD OF TIME INDICATED BY THE MANUFACTURER. AN AMBIENT TA TEMPERATURE IS CONSIDERED TO BE CONSTANT AT 25°C AND A CONTACT TEMPERATURE TC IS CONSIDERED TO BE 60°C.

A LED STATING L70B10=223,824 HOURS INDICATES THAT ONCE 223,824 HOURS IS REACHED, 90% (B10) OF THE DIODES DEMONSTRATE LOSS OF LUMENS EQUAL TO OR MORE THAN 70% OF THE INITIAL LUMENS (L70).

QUALITY CERTIFICATE

ALL TESTS ARE DEVELOPED INTERNALLY WITH THE ASSISTANCE OF SOPHISTICATED INSTRUMENTS, UNDER THE CONTROL OF HIGHLY QUALIFIED PERSONNEL AND IN COMPLIANCE WITH CURRENT REGULATORY STANDARDS.

- JUNCTION TEMPERATURE
- PHOTOMETRIC MEASURMENTS
- MECHANICAL RESISTANCE TO KNOCKS
- FIRE RESISTANCE
- SALT MIST
- RESISTANCE TO TRAMPLING/TRAFFICABILITY
- PROTECTION AGAINST SOLID AND LIQUID BODIES
- RESISTANCE TO SOLAR RADIATION
- RESISTANCE TO VIBRATIONS AND MECHANICAL STRESSES
- CLIMATIC CHAMBER

IN ADDITION TO GENERAL TESTING THERE IS ALSO ELECTRONIC TESTING:

- POWER SURGES
- ELECTROSTATIC DISCHARGE

WARRANTY

LINEA LIGHT GROUP OFFERS A 5-YEAR WARRANTY ON ITS PRODUCTS AGAINST MANUFACTURING DEFECTS, SUBJECT TO FILLING IN THE ACTIVATION FORM AVAILABLE AT WWW.LINEALIGHT.COM.

ALL POWER SUPPLY, WIRING AND ACCESSORIES USED FOR PRODUCT INSTALLATION SHALL BE ORIGINAL LINEA LIGHT GROUP PARTS OR APPROVED BY THE COMPANY. THE WARRANTY WILL BECOME VOID IF NON ORIGINAL OR NON APPROVED PARTS ARE USED.

FOR MORE INFORMATION
WWW.LINEALIGHT.COM

downlight range index

click images to open product pages

Vos

Vos_R

A11

Vos_RJ

A15

Vos_Q

A17

Vos_QJ

A21

Quantum

Quantum_R

A27

Quantum_RJ

A31

Warp

Warp_R

A39

Warp_RY

A45

Warp_RJ

A48

Warp_Q

A49

Warp_QY

A53

Epitax

Epitax

A61

Epitax_J

A64

Giotto

Giotto

A70

Loro

Loro_R

A75

Loro_RJ

A77

Loro_Q

A79

Loro_QJ

A81



VOS

A complete range of downlights conceived for modern lighting. Vos offers high performance, controlled UGR and minimum aesthetic impact due to the slim flange. Redesigned and expanded, the new range of Vos products comes in many variants and power.

Materials
Aluminum body
Steel flange
Black-painted optics compartment



	1.5 W	2 W	4 W	6 W	8 W	15 W	25 W
_R	Ø 0.8 in	Ø 1.4 in	Ø 1.4 in	Ø 1.7 in	Ø 2.8 in	Ø 4.1 in	Ø 5.3 in
_RJ	-	-	Ø 2.4 in	-	Ø 3 in	Ø 3.9 in	-
_Q	☐ 0.8 in	☐ 1.4 in	☐ 1.4 in	☐ 1.7 in	☐ 2.8 in	☐ 4.1 in	☐ 5.3 in
_QJ	-	-	☐ 2.4 in	-	☐ 3 in	☐ 3.9 in	-
Accessories	-	HC	HC	HC	HC	HC	HC
Finish	☐ ■	☐ ■	☐ ■	☐ ■	☐ ■	☐ ■	☐ ■
Balance CRI 92	2700K 3000K 3500K	2700K 3000K 3500K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Efficiency CRI 80	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Optics	Medium Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood
Driver	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V
	0.6 in	1.1 in	1.1 in 2.1 in (J)	1.4 in	2.5 in 2.8 in (J)	3.7 in	4.8 in

F.O.L.™

The optics group consists of a polycarbonate lens combined with F.O.L.™ (Filtering Optical Layers) filters: a 5-filter patented system made of polyethylene terephthalate with different levels of opacity to safeguard the clarity of the light beam and it guarantees optimal optical efficiency.

Visual comfort

The honeycomb-like filter integrated in the Honeycomb versions allows to shield the source further. The hexagonal microcells forming the grid contribute towards shielding the secondary light beam, thus almost eliminating glare altogether.

Pinhole

The optics compartment applies the pin-hole camera concept, thus guaranteeing reflectance control. The source is positioned on a receded plane with respect to the opening of the compartment: the photons forming the primary light beam project without being hindered; on the contrary, the outermost photons bounce in the compartment, painted black to obtain maximum degree of absorption, progressively dimming up to complete elimination.



Adjustable version

The Vos_RJ and Vos_QJ range of products come with a 360° rotation on the horizontal axis and a 35° tilt on the vertical axis.

Shielding of the optics compartment

The downlight structure was designed to avoid rear light dispersion and for shielding the plenum space.

Accessory

The luminaire can be directed using a special accessory key, provided at purchase, hence avoiding touching the optics with the fingers directly.

Vos_R | Downlight | powerLED | Damp location | Driver remote | 1.5W 500mA



Balance - CRI 92

White	**E90622**	2700 K	134 lm	**M**	Medium Flood	**20**
Black	**E90623**	3000 K	153 lm	**W**	Medium Flood	**35**
		3500 K	153 lm	**T**		

Efficiency - CRI 80

White	**E90408**	2700 K	187 lm	**M**	Medium Flood	**20**
Black	**E90409**	3000 K	199 lm	**W**	Medium Flood	**35**
		3500 K	199 lm	**T**		
		4000 K	213 lm	**N**		

power supply options (remote only)

ECO 30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Vos_R | Downlight | powerLED | Damp location | Driver remote | 2W 630mA



Balance - CRI 92

White	**E90626**	2700 K	157 lm	**M**	Spot	**15**
Black	**E90627**	3000 K	179 lm	**W**	Medium Flood	**30**
		3500 K	179 lm	**T**	Flood	**60**
HC White	**E90634**					
HC Black	**E90635**					

Efficiency - CRI 80

White	**E90412**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90413**	3000 K	233 lm	**W**	Medium Flood	**30**
		3500 K	233 lm	**T**	Flood	**60**
		4000 K	249 lm	**N**		
HC White	**E90632**					
HC Black	**E90633**					

power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

index
technical information

Vos_R | Downlight | powerLED | Damp location | Driver remote | 4W 350mA





Balance - CRI 92

White	**E90638**	2700 K	395 lm	**M**	Spot	**15**
Black	**E90639**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
		4000 K	456 lm	**N**		
HC White	**E90646**					
HC Black	**E90647**					

Efficiency - CRI 80

White	**E90416**	2700 K	490 lm	**M**	Spot	**15**
Black	**E90417**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
		4000 K	529 lm	**N**		
HC White	**E90644**					
HC Black	**E90645**					

power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Vos_R | Downlight | powerLED | Damp location | Driver remote | 6W 500mA





Balance - CRI 92

White	**E90650**	2700 K	532 lm	**M**	Spot	**15**
Black	**E90651**	3000 K	569 lm	**W**	Medium Flood	**30**
		3500 K	569 lm	**T**	Flood	**60**
		4000 K	614 lm	**N**		
HC White	**E90658**					
HC Black	**E90659**					

Efficiency - CRI 80

White	**E90420**	2700 K	659 lm	**M**	Spot	**15**
Black	**E90421**	3000 K	659 lm	**W**	Medium Flood	**30**
		3500 K	659 lm	**T**	Flood	**60**
		4000 K	711 lm	**N**		
HC White	**E90656**					
HC Black	**E90657**					

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

Vos_R | Downlight | powerLED | Damp location | Driver remote | 8W 700mA





Balance - CRI 92

White	**E90662**	2700 K	689 lm	**M**	Spot	**15**
Black	**E90663**	3000 K	738 lm	**W**	Medium Flood	**30**
		3500 K	738 lm	**T**	Flood	**45**
		4000 K	796 lm	**N**		
HC White	**E90670**					
HC Black	**E90671**					

Efficiency - CRI 80

White	**E90430**	2700 K	854 lm	**M**	Spot	**15**
Black	**E90431**	3000 K	854 lm	**W**	Medium Flood	**30**
		3500 K	854 lm	**T**	Flood	**45**
		4000 K	922 lm	**N**		
HC White	**E90668**					
HC Black	**E90669**					

power supply options (remote only)

ECO30W-700	SOLO50W-700	SOLO100W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Vos_R | Downlight | arrayLED | Damp location | Driver remote | 15W 400mA





Balance - CRI 92

White	**E90674**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E90675**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
		4000 K	1804 lm	**N**		
HC White	**E90682**					
HC Black	**E90683**					

Efficiency - CRI 80

White	**E90440**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E90441**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
		4000 K	2078 lm	**N**		
HC White	**E90680**					
HC Black	**E90681**					

power supply options (remote only)

ECO30W-400	SOLO50W-400	SOLO100W-400
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Vos_R | Downlight | arrayLED | Damp location | Driver remote | 25W 700mA





Balance - CRI 92

White	**E80722**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E80723**	3000 K	2794 lm	**W**	Medium Flood	**30**
		3500 K	2794 lm	**T**	Flood	**60**
		4000 K	2990 lm	**N**		
HC White	**E90690**					
HC Black	**E90691**					

Efficiency - CRI 80

White	**E80724**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E80725**	3000 K	3431 lm	**W**	Medium Flood	**30**
		3500 K	3431 lm	**T**	Flood	**60**
		4000 K	3431 lm	**N**		
HC White	**E90688**					
HC Black	**E90689**					

power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive 50W for 1 fixture

SOLO100W-700

0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index
technical information

Vos_RJ | Downlight | powerLED | Damp location | Driver remote | Adjustable | 4W 350mA





Balance - CRI 92

White	**E81266**	2700 K	395 lm	**M**	Spot	**15**
Black	**E81267**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
		4000 K	456 lm	**N**		
HC White	**E81114**					
HC Black	**E81115**					

Efficiency - CRI 80

White	**E81268**	2700 K	490 lm	**M**	Spot	**15**
Black	**E81269**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
		4000 K	529 lm	**N**		
HC White	**E81118**					
HC Black	**E81119**					

power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Vos_RJ | Downlight | powerLED | Damp locatoin | Driver remote | Adjustable | 8W 700mA





Balance - CRI 92

White	**E81274**	2700 K	689 lm	**M**	Spot	**15**
Black	**E81275**	3000 K	738 lm	**W**	Medium Flood	**30**
		3500 K	738 lm	**T**	Flood	**45**
		4000 K	796 lm	**N**		
HC White	**E81122**					
HC Black	**E81123**					

Efficiency - CRI 80

White	**E81276**	2700 K	854 lm	**M**	Spot	**15**
Black	**E81277**	3000 K	854 lm	**W**	Medium Flood	**30**
		3500 K	922 lm	**T**	Flood	**45**
		4000 K	922 lm	**N**		
HC White	**E81126**					
HC Black	**E81127**					

power supply options (remote only)

ECO30W-700	SOLO50W-700	SOLO100W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

index
technical information

Vos_RJ | Downlight | arrayLED | Damp location | Driver remote | Adjustable | 15W 400mA



Balance - CRI 92

White	**E81282**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E81283**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
		4000 K	1804 lm	**N**		

Efficiency - CRI 80

White	**E81320**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E81285**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	2078 lm	**T**	Flood	**60**
		4000 K	2078 lm	**N**		

power supply options (remote only)

ECO30W-400	**SOLO50W-400**	**SOLO100W-400**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Vos_Q | Downlight | powerLED | Damp location | Driver remote | 1.5W 500mA



Balance - CRI 92

White	**E90620**	2700 K	134 lm	**M**	Medium Flood	**20**
Black	**E90621**	3000 K	153 lm	**W**	Medium Flood	**35**
		3500 K	153 lm	**T**		

Efficiency - CRI 80

White	**E90406**	2700 K	187 lm	**M**	Medium Flood	**20**
Black	**E90407**	3000 K	199 lm	**W**	Medium Flood	**35**
		3500 K	199 lm	**T**		
		4000 K	213 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Vos_Q | Downlight | powerLED | Damp locatoin | Driver remote | 2W 630mA





Balance - CRI 92

White	**E90624**	2700 K	157 lm	**M**	Spot	**15**
Black	**E90625**	3000 K	179 lm	**W**	Medium Flood	**30**
		3500 K	179 lm	**T**	Flood	**60**
HC White	**E90630**					
HC Black	**E90631**					

Efficiency - CRI 80

White	**E90410**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90411**	3000 K	233 lm	**W**	Medium Flood	**30**
		3500 K	233 lm	**T**	Flood	**60**
		4000 K	249 lm	**N**		
HC White	**E90628**					
HC Black	**E90629**					

power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

index
technical information

Vos_Q | Downlight | powerLED | Damp locatoin | Driver remote | 4W 350mA





Balance - CRI 92

White	**E90636**	2700 K	395 lm	**M**	Spot	**15**
Black	**E90637**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
		4000 K	456 lm	**N**		
HC White	**E90642**					
HC Black	**E90643**					

Efficiency - CRI 80

White	**E90414**	2700 K	490 lm	**M**	Spot	**15**
Black	**E90415**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
		4000 K	529 lm	**N**		
HC White	**E90640**					
HC Black	**E90641**					

power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Vos_Q | Downlight | powerLED | Damp location | Driver remote | 6W 500mA





Balance - CRI 92

White	**E90648**	2700 K	532 lm	**M**	Spot	**15**
Black	**E90649**	3000 K	569 lm	**W**	Medium Flood	**30**
		3500 K	569 lm	**T**	Flood	**60**
		4000 K	614 lm	**N**		
HC White	**E90654**					
HC Black	**E90655**					

Efficiency - CRI 80

White	**E90418**	2700 K	659 lm	**M**	Spot	**15**
Black	**E90419**	3000 K	659 lm	**W**	Medium Flood	**30**
		3500 K	659 lm	**T**	Flood	**60**
		4000 K	711 lm	**N**		
HC White	**E90652**					
HC Black	**E90653**					

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

Vos_Q | Downlight | powerLED | Damp location | Driver remote | 8W 700mA





Balance - CRI 92

White	**E90660**	2700 K	689 lm	**M**	Spot	**15**
Black	**E90661**	3000 K	738 lm	**W**	Medium Flood	**30**
		3500 K	738 lm	**T**	Flood	**45**
		4000 K	796 lm	**N**		
HC White	**E90666**					
HC Black	**E90667**					

Efficiency - CRI 80

White	**E90428**	2700 K	854 lm	**M**	Spot	**15**
Black	**E90429**	3000 K	854 lm	**W**	Medium Flood	**30**
		3500 K	854 lm	**T**	Flood	**45**
		4000 K	922 lm	**N**		
HC White	**E90664**					
HC Black	**E90665**					

power supply options (remote only)

ECO30W-700	SOLO50W-700	SOLO100W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Vos_Q | Downlight | arrayLED | Damp location | Driver remote | 15W 400mA





Balance - CRI 92

White	**E90672**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E90673**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
		4000 K	1804 lm	**N**		
HC White	**E90678**					
HC Black	**E90679**					

Efficiency - CRI 80

White	**E90438**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E90439**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
		4000 K	2078 lm	**N**		
HC White	**E90676**					
HC Black	**E90677**					

power supply options (remote only)

ECO30W-400	SOLO50W-400	SOLO100W-400
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Vos_Q | Downlight | arrayLED | Damp location | Driver remote | 25W 700mA





Balance - CRI 92

White	**E80726**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E80727**	3000 K	2794 lm	**W**	Medium Flood	**30**
		3500 K	2794 lm	**T**	Flood	**60**
		4000 K	2990 lm	**N**		
HC White	**E90686**					
HC Black	**E90687**					

Efficiency - CRI 80

White	**E80728**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E80729**	3000 K	3431 lm	**W**	Medium Flood	**30**
		3500 K	3431 lm	**T**	Flood	**60**
		4000 K	3431 lm	**N**		
HC White	**E90684**					
HC Black	**E90685**					

power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1 fixture

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-3 fixtures

index
technical information

Vos_QJ | Downlight | powerLED | Damp location | Driver remote | Adjustable | 4W 350mA



Balance - CRI 92

White	**E81270**	2700 K	395 lm	**M**	Spot	**15**
Black	**E81271**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
		4000 K	456 lm	**N**		
HC White	**E80478**					
HC Black	**E80479**					

Efficiency - CRI 80

White	**E81272**	2700 K	490 lm	**M**	Spot	**15**
Black	**E81273**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
		4000 K	529 lm	**N**		
HC White	**E80476**					
HC Black	**E80477**					

power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Vos_QJ | Downlight | powerLED | Damp location | Driver remote | Adjustable | 8W 700mA



Balance - CRI 92

White	**E81278**	2700 K	689 lm	**M**	Spot	**15**
Black	**E81279**	3000 K	738 lm	**W**	Medium Flood	**30**
		3500 K	738 lm	**T**	Flood	**45**
		4000 K	796 lm	**N**		
HC White	**E80490**					
HC Black	**E80491**					

Efficiency - CRI 80

White	**E81280**	2700 K	854 lm	**M**	Spot	**15**
Black	**E81281**	3000 K	854 lm	**W**	Medium Flood	**30**
		3500 K	854 lm	**T**	Flood	**45**
		4000 K	922 lm	**N**		
HC White	**E80488**					
HC Black	**E80489**					

power supply options (remote only)

ECO30W-700	SOLO50W-700	SOLO100W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

index
technical information

Vos_QJ | Downlight | arrayLED | Damp location | Driver remote | Adjustable | 15W 400mA



Balance - CRI 92

White	**E81286**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E81287**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
		4000 K	1804 lm	**N**		

Efficiency - CRI 80

White	**E81288**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E81289**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
		4000 K	2078 lm	**N**		

power supply options (remote only)

ECO30W-400	**SOLO50W-400**	**SOLO100W-400**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

quantum

An organic-shaped downlight, with a deep optics compartment with soft and refined lines, winners of the prestigious RedDot Award.

Materials
Aluminum body

quantum range



	1.5 W	2 W	4 W	6 W	10 W	15 W	25 W
_R	Ø 0.7 in	Ø 0.9 in	Ø 1.4 in	Ø 1.7 in	Ø 2.4 in	Ø 3.3 in	Ø 5.3 in
_RJ	-	Ø 2 in	Ø 2 in	Ø 2.2 in	Ø 2.8 in	Ø 3.2 in	-
Accessories	-	HC (_RJ)	HC	HC	HC	HC	HC
Finish							
Balance CRI 92	2700K 3000K 3500K	2700K 3000K 3500K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Efficiency CRI 80	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Optics	Medium Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood
Driver	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V
	0.6 in	0.8 in (_R) 1.7 in (_RJ)	1.1 in (_R) 1.7 in (_RJ)	1.4 in (_R) 1.9 in (_RJ)	2.1 in (_R) 2.5 in (_RJ)	2.8 in (_R) 2.9 in (_RJ)	4.9 in

F.O.L.™

The optics group consists of a polycarbonate lens combined with F.O.L.™ (Filtering Optical Layers) filters: a 5-filter patented system made of polyethylene terephthalate with different levels of opacity to safeguard the clarity of the light beam and it guarantees optimal optical efficiency.

reddot award 2015
winner

HC Visual comfort

The honeycomb-like filter integrated in the Honeycomb versions allows to shield the source further. The hexagonal microcells forming the grid contribute towards shielding the secondary light beam, thus almost eliminating glare altogether.

Organic design

Tiltable

The Quantum_RJ range are adjusted by a 35° inclination on the vertical axis.

Quantum_R | Downlight | powerLED | Damp Location | Driver remote | 1.5W 500mA



Balance - CRI 92

White	**E80009**	2700 K	134 lm	**M**	Medium Flood	**20**
Black	**E80010**	3000 K	153 lm	**W**	Medium Flood	**35**
Gold	**E82011**	3500 K	153 lm	**T**		

Efficiency - CRI 80

White	**E90554**	2700 K	187 lm	**M**	Medium Flood	**20**
Black	**E90555**	3000 K	199 lm	**W**	Medium Flood	**35**
Gold	**E82012**	3500 K	199 lm	**T**		
		4000 K	213 lm	**N**		

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-500
0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Quantum_R | Downlight | powerLED | Damp Location | Driver remote | 2W 630mA



Balance - CRI 92

White	**E80011**	2700 K	157 lm	**M**	Spot	**15**
Black	**E80012**	3000 K	179 lm	**W**	Medium Flood	**30**
Gold	**E82013**	3500 K	179 lm	**T**	Flood	**45**

Efficiency - CRI 80

White	**E90556**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90557**	3000 K	233 lm	**W**	Medium Flood	**30**
Gold	**E82014**	3500 K	233 lm	**T**	Flood	**45**
		4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-16 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

index
technical information

Quantum_R | Downlight | powerLED | Damp Location | Driver remote | 4W 350mA





Balance - CRI 92

	White	E80017	2700 K	395 lm	M	Spot 15
	Black	E80018	3000 K	423 lm	W	Medium Flood 30
	Gold	E82015	3500 K	423 lm	T	Flood 45
			4000 K	456 lm	N	
HC	White	E80021				
HC	Black	E80022				
HC	Gold	E82016				

Efficiency - CRI 80

	White	E90558	2700 K	490 lm	M	Spot 15
	Black	E90559	3000 K	490 lm	W	Medium Flood 30
	Gold	E82017	3500 K	490 lm	T	Flood 45
			4000 K	529 lm	N	
HC	White	E80019				
HC	Black	E80020				
HC	Gold	E82018				

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Quantum_R | Downlight | powerLED | Damp Location | Driver remote | 6W 500mA





Balance - CRI 92

	White	E80023	2700 K	532 lm	M	Spot 15
	Black	E80024	3000 K	569 lm	W	Medium Flood 30
	Gold	E82019	3500 K	569 lm	T	Flood 45
			4000 K	614 lm	N	
HC	White	E80027				
HC	Black	E80028				
HC	Gold	E82020				

Efficiency - CRI 80

	White	E90560	2700 K	659 lm	M	Spot 15
	Black	E90561	3000 K	659 lm	W	Medium Flood 30
	Gold	E82021	3500 K	659 lm	T	Flood 45
			4000 K	711 lm	N	
HC	White	E80025				
HC	Black	E80026				
HC	Gold	E82022				

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Quantum_R | Downlight | powerLED | Damp Location | Driver remote | 10W 800mA





Balance - CRI 92

	White	E80029	2700 K	960 lm	M	Spot 15
	Black	E80030	3000 K	1034 lm	W	Medium Flood 30
	Gold	E82023	3500 K	1034 lm	T	Flood 45
			4000 K	1108 lm	N	
HC	White	E80033				
HC	Black	E80034				
HC	Gold	E82024				

Efficiency - CRI 80

	White	E90562	2700 K	1108 lm	M	Spot 15
	Black	E90563	3000 K	1194 lm	W	Medium Flood 30
	Gold	E82025	3500 K	1194 lm	T	Flood 45
			4000 K	1280 lm	N	
HC	White	E80031				
HC	Black	E80032				
HC	Gold	E82026				

Power supply options (remote only)

ECO30W-800
0-10V EldoLED ECOdrive 30W for 1-2 fixtures

SOLO100W-800
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Quantum_R | Downlight | arrayLED | Damp Location | Driver remote | 15W 400mA





Balance - CRI 92

	White	E80035	2700 K	1568 lm	M	Spot 15
	Black	E80036	3000 K	1677 lm	W	Medium Flood 30
	Gold	E82027	3500 K	1677 lm	T	Flood 45
			4000 K	1804 lm	N	
HC	White	E80039				
HC	Black	E80040				
HC	Gold	E82028				

Efficiency - CRI 80

	White	E90564	2700 K	1932 lm	M	Spot 15
	Black	E90565	3000 K	1932 lm	W	Medium Flood 30
	Gold	E82029	3500 K	1932 lm	T	Flood 45
			4000 K	2078 lm	N	
HC	White	E80037				
HC	Black	E80038				
HC	Gold	E82030				

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Quantum_R | Downlight | arrayLED | Damp Location | Driver remote | 25W 700mA





Balance - CRI 92

White	**E80041**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E80042**	3000 K	2794 lm	**W**	Medium Flood	**30**
Gold	**E82031**	3500 K	2794 lm	**T**	Flood	**45**
		4000 K	2990 lm	**N**		
HC White	**E80045**					
HC Black	**E80046**					
HC Gold	**E82032**					

Efficiency - CRI 80

White	**E90609**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E90610**	3000 K	3431 lm	**W**	Medium Flood	**30**
Gold	**E82033**	3500 K	3431 lm	**T**	Flood	**45**
		4000 K	3431 lm	**N**		
HC White	**E80043**					
HC Black	**E80044**					
HC Gold	**E82034**					

Power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive 50W for 1 fixtures

SOLO100W-700

0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index
technical information

Quantum_RJ | Downlight | powerLED | Damp Location | Driver remote | Tiltable | 2W 630mA





Balance - CRI 92

White	**E80047**	2700 K	157 lm	**M**	Spot	**15**
Black	**E80048**	3000 K	179 lm	**W**	Medium Flood	**30**
Gold	**E82035**	3500 K	179 lm	**T**	Flood	**45**

HC

White	**E80051**
Black	**E80052**
Gold	**E82036**

Efficiency - CRI 80

White	**E90566**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90567**	3000 K	233 lm	**W**	Medium Flood	**30**
Gold	**E82037**	3500 K	233 lm	**T**	Flood	**45**
		4000 K	249 lm	**N**		

HC

White	**E80049**
Black	**E80050**
Gold	**E82038**

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-16 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Quantum_RJ | Downlight | powerLED | Damp Location | Driver remote | Tiltable | 4W 350mA





Balance - CRI 92

White	**E80053**	2700 K	395 lm	**M**	Spot	**15**
Black	**E80054**	3000 K	423 lm	**W**	Medium Flood	**30**
Gold	**E82039**	3500 K	423 lm	**T**	Flood	**45**
		4000 K	456 lm	**N**		

HC

White	**E80057**
Black	**E80058**
Gold	**E82040**

Efficiency - CRI 80

White	**E90568**	2700 K	490 lm	**M**	Spot	**15**
Black	**E90569**	3000 K	490 lm	**W**	Medium Flood	**30**
Gold	**E82041**	3500 K	490 lm	**T**	Flood	**45**
		4000 K	529 lm	**N**		

HC

White	**E80055**
Black	**E80056**
Gold	**E82042**

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-6 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

Quantum_RJ | Downlight | powerLED | Damp Location | Driver remote | Tiltable | 6W 500mA





Balance - CRI 92

	White	E80059	2700 K	532 lm	M	Spot 15
	Black	E80060	3000 K	569 lm	W	Medium Flood 30
	Gold	E82043	3500 K	569 lm	T	Flood 45
			4000 K	614 lm	N	
HC	White	E80063				
HC	Black	E80064				
HC	Gold	E82044				

Efficiency - CRI 80

	White	E90570	2700 K	659 lm	M	Spot 15
	Black	E90571	3000 K	659 lm	W	Medium Flood 30
	Gold	E82045	3500 K	659 lm	T	Flood 45
			4000 K	711 lm	N	
HC	White	E80061				
HC	Black	E80062				
HC	Gold	E82046				

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive
30W for 1-3 fixtures

SOLO50W-500
0-10V EldoLED SOLOdrive
50W for 1-6 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive
100W for 1-12 fixtures

Quantum_RJ | Downlight | powerLED | Damp Location | Driver remote | Tiltable | 10W 800mA





Balance - CRI 92

	White	E80065	2700 K	960 lm	M	Spot 15
	Black	E80066	3000 K	1034 lm	W	Medium Flood 30
	Gold	E82047	3500 K	1034 lm	T	Flood 45
			4000 K	1108 lm	N	
HC	White	E80069				
HC	Black	E80070				
HC	Gold	E82048				

Efficiency - CRI 80

	White	E90572	2700 K	1108 lm	M	Spot 15
	Black	E90573	3000 K	1194 lm	W	Medium Flood 30
	Gold	E82049	3500 K	1194 lm	T	Flood 45
			4000 K	1280 lm	N	
HC	White	E80067				
HC	Black	E80068				
HC	Gold	E82050				

Power supply options (remote only)

ECO30W-800
0-10V EldoLED ECOdrive
30W for 1-2 fixtures

SOLO100W-800
0-10V EldoLED SOLOdrive
100W for 1-4 fixtures

index
technical information

Quantum_RJ | Downlight | arrayLED | Damp Location | Driver remote | Tiltable | 15W 400mA





Balance - CRI 92

	White	**E80071**	2700 K	1568 lm	**M**	Spot **15**
	Black	**E80072**	3000 K	1677 lm	**W**	Medium Flood **30**
	Gold	**E82051**	3500 K	1677 lm	**T**	Flood **45**
			4000 K	1804 lm	**N**	
HC	White	**E80075**				
HC	Black	**E80076**				
HC	Gold	**E82052**				

Efficiency - CRI 80

	White	**E90574**	2700 K	1932 lm	**M**	Spot **15**
	Black	**E90575**	3000 K	1932 lm	**W**	Medium Flood **30**
	Gold	**E82053**	3500 K	1932 lm	**T**	Flood **45**
			4000 K	2078 lm	**N**	
HC	White	**E80073**				
HC	Black	**E80074**				
HC	Gold	**E82054**				

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

warp

This downlight comes with an extremely slim flange that perfectly blends with the ceiling: its design was specifically conceived to optimise lighting efficiency, while the source was particularly receded to offer maximum visual comfort.

Materials
Aluminum body

warp range



	2 W	4 W	6 W	8 W	10 W	15 W	25 W	45 W
_R ○	Ø 1.4 in	Ø 1.4 in	Ø 1.7 in	-	Ø 2.8 in	Ø 3.9 in	Ø 5.3 in	Ø 5.3 in
_RY ○	Ø 2 in	Ø 2 in	-	-	Ø 2.8 in	Ø 3.9 in	Ø 5.3 in	-
_RJ ○	-	-	-	Ø 3.2 in	-	Ø 4.7 in	-	-
_Q □	□ 1.4 in	□ 1.4 in	□ 1.7in	-	□ 2.8in	□ 3.9 in	□ 5.3 in	-
_QY □	□ 2 in	□ 2 in	-	-	□ 2.8 in	□ 3.9 in	□ 5.3 in	-
Accessories	HC	HC	HC	-	HC	-	HC	HC
Finish	□ ■	□ ■	□ ■	□ ■	□ ■	□ ■	□ ■	□ ■
Balance CRI 92	2700K 3000K 3500K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Efficiency CRI 80	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Optics	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood
Driver	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V
	1.1 in (_R / _Q) 1.8 in (_RY / _QY)	1.1 in (_R / _Q) 1.8 in (_RY / _QY)	1.4 in (_R) 1.4 in (_Q)	2.7 in (_RJ)	2.5 in (_R / _RY) 2.5 in (_Q / _QY)	3.6 in (_R / _RY) 4.1 in (_RJ) 3.6 in (_Q / _QY)	5 in (_R / _RY) 5 in (_Q / _QY)	5 in

F.O.L.™

The optics group consists of a polycarbonate lens combined with F.O.L.™ (Filtering Optical Layers) filters: a 5-filter patented system made of polyethylene terephthalate with different levels of opacity to safeguard the clarity of the light beam and it guarantees optimal optical efficiency.

Visual comfort

The honeycomb-like filter integrated in the Honeycomb versions allows to shield the source further. The hexagonal microcells forming the grid contribute towards shielding the secondary light beam, thus almost eliminating glare altogether.



Minimale frame

Asymmetric version

The Warp_RY and Warp_QY range of products are slanted by 25° and offer an asymmetric emission, ideal for the uniform distribution of light on lateral surfaces. The slanted configuration of the lamp body allows to conceal the light source, thus eliminating direct glare.

Adjustable version

The Warp_RJ range of products come with a 360° rotation on the horizontal axis and a 25° tilt on the vertical axis.

Warp_R | Downlight | powerLED | Damp Location | Driver remote | 2W 630mA





Balance - CRI 92

White	**E90542**	2700 K	157 lm	**M**	Spot	**15**
Black	**E90543**	3500 K	179 lm	**T**	Medium Flood	**30**
		3000 K	179 lm	**W**	Flood	**60**
HC White	**E90722**					
HC Black	**E90723**					

Efficiency - CRI 80

White	**E90544**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90545**	3000 K	233 lm	**W**	Medium Flood	**30**
		3500 K	233 lm	**T**	Flood	**60**
HC White	**E90720**	4000 K	249 lm	**N**		
HC Black	**E90721**					

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Warp_R | Downlight | powerLED | Damp Location | Driver remote | 4W 350mA





Balance - CRI 92

White	**E90740**	2700 K	395 lm	**M**	Spot	**15**
Black	**E90741**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
HC White	**E90744**	4000 K	456 lm	**N**		
HC Black	**E90745**					

Efficiency - CRI 80

White	**E90546**	2700 K	490 lm	**M**	Spot	**15**
Black	**E90547**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
HC White	**E90742**	4000 K	529 lm	**N**		
HC Black	**E90743**					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

Warp_R | Downlight | powerLED | Damp Location | Driver remote | 6W 500mA



1.4

HC

Balance - CRI 92

White	**E90748**	2700 K	532 lm	**M**	Spot	**15**
Black	**E90749**	3000 K	569 lm	**W**	Medium Flood	**30**
		3500 K	569 lm	**T**	Flood	**60**
White	**E90752**	4000 K	614 lm	**N**		
Black	**E90753**					

Efficiency - CRI 80

White	**E90548**	2700 K	659 lm	**M**	Spot	**15**
Black	**E90549**	3000 K	659 lm	**W**	Medium Flood	**30**
		3500 K	659 lm	**T**	Flood	**60**
White	**E90750**	4000 K	711 lm	**N**		
Black	**E90751**					

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-500
0-10V EldoLED SOLOdrive 50W for 1-6 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Warp_R | Downlight | powerLED | Damp Location | Driver remote | 10W 800mA



2.5

HC

Balance - CRI 92

White	**E90762**	2700 K	960 lm	**M**	Spot	**15**
Black	**E90763**	3000 K	1034 lm	**W**	Medium Flood	**30**
		3500 K	1034 lm	**T**	Flood	**60**
White	**E90766**	4000 K	1108 lm	**N**		
Black	**E90767**					

Efficiency - CRI 80

White	**E90550**	2700 K	1108 lm	**M**	Spot	**15**
Black	**E90551**	3000 K	1194 lm	**W**	Medium Flood	**30**
		3500 K	1194 lm	**T**	Flood	**60**
White	**E90764**	4000 K	1280 lm	**N**		
Black	**E90765**					

Power supply options (remote only)

ECO30W-800
0-10V EldoLED ECOdrive 30W for 1-2 fixtures

SOLO100W-800
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Warp_R | Downlight | arrayLED | Damp Location | Driver remote | 15W 400mA



3.6

HC

Balance - CRI 92

White	**E90776**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E90777**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
White	**E90780**	4000 K	1804 lm	**N**		
Black	**E90781**					

Efficiency - CRI 80

White	**E90552**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E90553**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
White	**E90778**	4000 K	2078 lm	**N**		
Black	**E90779**					

Power supply options (remote only)

ECO30W-400	SOLO50W-400	SOLO100W-400
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Warp_R | Downlight | arrayLED | Damp Location | Driver remote | 25W 700mA



5

HC

Balance - CRI 92

White	**E90790**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E90791**	3000 K	2794 lm	**W**	Medium Flood	**30**
		3500 K	2794 lm	**T**	Flood	**60**
White	**E90794**	4000 K	2990 lm	**N**		
Black	**E90795**					

Efficiency - CRI 80

White	**E90612**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E90613**	3000 K	3431 lm	**W**	Medium Flood	**30**
		3500 K	3431 lm	**T**	Flood	**60**
White	**E90792**	4000 K	3431 lm	**N**		
Black	**E90793**					

Power supply options (remote only)

SOLO50W-700	SOLO100W-700
0-10V EldoLED SOLOdrive 50W for 1 fixture	0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index
technical information

Warp_R | Downlight | arrayLED | Damp Location | Driver remote | 45W 1250mA





Balance - CRI 92

White	**E81487**	2700 K	5033 lm	**M**	Spot	**15**
Black	**E81488**	3000 K	5383 lm	**W**	Medium Flood	**30**
		3500 K	5383 lm	**T**	Flood	**60**
HC White	**E81491**	4000 K	5784 lm	**N**		
HC Black	**E81492**					

Efficiency - CRI 80

White	**E81485**	2700 K	6185 lm	**M**	Spot	**15**
Black	**E81486**	3000 K	6185 lm	**W**	Medium Flood	**30**
		3500 K	6185 lm	**T**	Flood	**60**
HC White	**E81489**	4000 K	6649 lm	**N**		
HC Black	**E81490**					

Power supply options (remote only)

SOLO100W-1250

0-10V EldoLED SOLOdrive
100W for 1 fixture

index
technical information

CORALLO
LOBSTER BAR
milano
copenaghen
CORALLO

Warp_RY | Downlight | powerLED | Damp Location | Driver remote | Asymmetric | 2W 630mA



HC

Balance - CRI 92

White	**E90814**	2700 K	157 lm	**M**	Spot	**15**
Black	**E90815**	3000 K	179 lm	**W**	Medium Flood	**30**
		3500 K	179 lm	**T**	Flood	**60**
HC White	**E90818**					
HC Black	**E90819**					

Efficiency - CRI 80

White	**E90812**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90813**	3000 K	233 lm	**W**	Medium Flood	**30**
		3500 K	233 lm	**T**	Flood	**60**
HC White	**E90816**	4000 K	249 lm	**N**		
HC Black	**E90817**					

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Warp_RY | Downlight | powerLED | Damp Location | Driver remote | Asymmetric | 4W 350mA



HC

Balance - CRI 92

White	**E90830**	2700 K	395 lm	**M**	Spot	**15**
Black	**E90831**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
HC White	**E90834**	4000 K	456 lm	**N**		
HC Black	**E90835**					

Efficiency - CRI 80

White	**E90828**	2700 K	490 lm	**M**	Spot	**15**
Black	**E90829**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
HC White	**E90832**	4000 K	529 lm	**N**		
HC Black	**E90833**					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

Warp_RY | Downlight | powerLED | Damp Location | Driver remote | Asymmetric | 10W 800mA



HC

Balance - CRI 92

White	**E90846**	2700 K	1054 lm	**M**	Spot	**15**
Black	**E90847**	3000 K	1135 lm	**W**	Medium Flood	**30**
		3500 K	1135 lm	**T**	Flood	**60**
White	**E90850**	4000 K	1216 lm	**N**		
Black	**E90851**					

HC

Efficiency - CRI 80

White	**E90844**	2700 K	1216 lm	**M**	Spot	**15**
Black	**E90845**	3000 K	1310 lm	**W**	Medium Flood	**30**
		3500 K	1310 lm	**T**	Flood	**60**
White	**E90848**	4000 K	1405 lm	**N**		
Black	**E90849**					

HC

Power supply options (remote only)

ECO30W-800
0-10V EldoLED ECOdrive 30W for 1-2 fixtures

SOLO100W-800
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Warp_RY | Downlight | arrayLED | Damp Location | Driver remote | Asymmetric | 15W 400mA



HC

Balance - CRI 92

White	**E90862**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E90863**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
White	**E90866**	4000 K	1804 lm	**N**		
Black	**E90867**					

HC

Efficiency - CRI 80

White	**E90860**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E90861**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
White	**E90864**	4000 K	2078 lm	**N**		
Black	**E90865**					

HC

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Warp_RY | Downlight | arrayLED | Damp Location | Driver remote | Asymmetric | 25W 700mA





Balance - CRI 92

White	**E90878**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E90879**	3000 K	2794 lm	**W**	Medium Flood	**30**
		3500 K	2794 lm	**T**	Flood	**60**
HC White	**E90882**	4000 K	2990 lm	**N**		
HC Black	**E90883**					

Efficiency - CRI 80

White	**E90876**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E90877**	3000 K	3341 lm	**W**	Medium Flood	**30**
		3500 K	3341 lm	**T**	Flood	**60**
HC White	**E90880**	4000 K	3431 lm	**N**		
HC Black	**E90881**					

Power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1 fixtures

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-3 fixtures

E90876W30



Photometric curve



Light beam

Floor plan



100 LUX	250 LUX	300 LUX	500 LUX	1000 LUX

index
technical information

Warp_RJ | Downlight | powerLED | Damp Location | Driver remote | Adjustable | 8W 700mA



Balance - CRI 92

White	**E81258**	2700 K	689 lm	**M**	Spot	**15**
Black	**E81259**	3000 K	738 lm	**W**	Medium Flood	**30**
		3500 K	738 lm	**T**	Flood	**60**
		4000 K	796 lm	**N**		

Efficiency - CRI 80

White	**E81260**	2700 K	854 lm	**M**	Spot	**15**
Black	**E81261**	3000 K	854 lm	**W**	Medium Flood	**30**
		3500 K	854 lm	**T**	Flood	**60**
		4000 K	922 lm	**N**		

Power supply options (remote only)

ECO30W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-700
0-10V EldoLED SOLOdrive 50W for 1-4 fixtures

SOLO100W-700
0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Warp_RJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 15W 400mA



Balance - CRI 92

White	**E81262**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E81263**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
		4000 K	1904 lm	**N**		

Efficiency - CRI 80

White	**E81264**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E81265**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
		4000 K	2078 lm	**N**		

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixtures

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Warp_Q | Downlight | powerLED | Damp Location | Driver remote | 2W 630mA





Balance - CRI 92

White	**E90726**	2700 K	157 lm	**M**	Spot	**15**
Black	**E90727**	3000 K	179 lm	**W**	Medium Flood	**30**
		3500 K	179 lm	**T**	Flood	**60**
HC White	**E90730**					
HC Black	**E90731**					

Efficiency - CRI 80

White	**E90724**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90725**	3000 K	233 lm	**W**	Medium Flood	**30**
		3500 K	233 lm	**T**	Flood	**60**
HC White	**E90728**	4000 K	249 lm	**N**		
HC Black	**E90729**					

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Warp_Q | Downlight | powerLED | Damp Location | Driver remote | 4W 350mA





Balance - CRI 92

White	**E90734**	2700 K	395 lm	**M**	Spot	**15**
Black	**E90735**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
HC White	**E90738**	4000 K	456 lm	**N**		
HC Black	**E90739**					

Efficiency - CRI 80

White	**E90732**	2700 K	490 lm	**M**	Spot	**15**
Black	**E90733**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
HC White	**E90736**	4000 K	529 lm	**N**		
HC Black	**E90737**					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

Warp_Q | Downlight | powerLED | Damp Location | Driver remote | 6W 500mA





Balance - CRI 92

White	**E90756**	2700 K	532 lm	**M**	Spot	**15**
Black	**E90757**	3000 K	569 lm	**W**	Medium Flood	**30**
		3500 K	569 lm	**T**	Flood	**60**
HC White	**E90760**	4000 K	614 lm	**N**		
HC Black	**E90761**					

Efficiency - CRI 80

White	**E90754**	2700 K	659 lm	**M**	Spot	**15**
Black	**E90755**	3000 K	659 lm	**W**	Medium Flood	**30**
		3500 K	659 lm	**T**	Flood	**60**
HC White	**E90758**	4000 K	711 lm	**N**		
HC Black	**E90759**					

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Warp_Q | Downlight | powerLED | Damp Location | Driver remote | 10W 800mA





Balance - CRI 92

White	**E90770**	2700 K	960 lm	**M**	Spot	**15**
Black	**E90771**	3000 K	1034 lm	**W**	Medium Flood	**30**
		3500 K	1034 lm	**T**	Flood	**60**
HC White	**E90774**	4000 K	1108 lm	**N**		
HC Black	**E90775**					

Efficiency - CRI 80

White	**E90768**	2700 K	1108 lm	**M**	Spot	**15**
Black	**E90769**	3000 K	1194 lm	**W**	Medium Flood	**30**
		3500 K	1194 lm	**T**	Flood	**60**
HC White	**E90772**	4000 K	1280 lm	**N**		
HC Black	**E90773**					

Power supply options (remote only)

ECO30W-800	SOLO100W-800
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Warp_Q | Downlight | arrayLED | Damp Location | Driver remote | 15W 400mA





Balance - CRI 92

White	**E90784**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E90785**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
White	**E90788**	4000 K	1804 lm	**N**		
Black	**E90789**					

HC

Efficiency - CRI 80

White	**E90782**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E90783**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
White	**E90786**	4000 K	2078 lm	**N**		
Black	**E90787**					

HC

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Warp_Q | Downlight | arrayLED | Damp Location | Driver remote | 25W 700mA





Balance - CRI 92

White	**E90798**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E90799**	3000 K	2794 lm	**W**	Medium Flood	**30**
		3500 K	2794 lm	**T**	Flood	**60**
White	**E90802**	4000 K	2990 lm	**N**		
Black	**E90803**					

HC

Efficiency - CRI 80

White	**E90796**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E90797**	3000 K	3431 lm	**W**	Medium Flood	**30**
		3500 K	3431 lm	**T**	Flood	**60**
White	**E90800**	4000 K	3431 lm	**N**		
Black	**E90801**					

HC

Power supply options (remote only)

SOLO50W-700
0-10V EldoLED SOLOdrive 50W for 1 fixture

SOLO100W-700
0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index
technical information



Warp_QY | Downlight | powerLED | Damp Location | Driver remote | Asymmetric | 2W 630mA





Balance - CRI 92

White	**E90822**	2700 K	157 lm	**M**	Spot	**15**
Black	**E90823**	3000 K	179 lm	**W**	Medium Flood	**30**
		3500 K	179 lm	**T**	Flood	**60**
HC White	**E90826**					
HC Black	**E90827**					

Efficiency - CRI 80

White	**E90820**	2700 K	219 lm	**M**	Spot	**15**
Black	**E90821**	3000 K	233 lm	**W**	Medium Flood	**30**
		3500 K	233 lm	**T**	Flood	**60**
HC White	**E90824**	4000 K	249 lm	**N**		
HC Black	**E90825**					

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Warp_QY | Downlight | powerLED | Damp Location | Driver remote | Asymmetric | 4W 350mA





Balance - CRI 92

White	**E90838**	2700 K	395 lm	**M**	Spot	**15**
Black	**E90839**	3000 K	423 lm	**W**	Medium Flood	**30**
		3500 K	423 lm	**T**	Flood	**60**
HC White	**E90842**	4000 K	456 lm	**N**		
HC Black	**E90843**					

Efficiency - CRI 80

White	**E90836**	2700 K	490 lm	**M**	Spot	**15**
Black	**E90837**	3000 K	490 lm	**W**	Medium Flood	**30**
		3500 K	490 lm	**T**	Flood	**60**
HC White	**E90840**	4000 K	529 lm	**N**		
HC Black	**E90841**					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

Warp_QY | Downlight | powerLED | Damp Location | Driver remote | Asymmetric | 10W 800mA



HC

Balance - CRI 92

White	**E90854**	2700 K	960 lm	**M**	Spot	**15**
Black	**E90855**	3000 K	1034 lm	**W**	Medium Flood	**30**
		3500 K	1034 lm	**T**	Flood	**60**
White	**E90858**	4000 K	1108 lm	**N**		
Black	**E90859**					

HC

Efficiency - CRI 80

White	**E90852**	2700 K	1108 lm	**M**	Spot	**15**
Black	**E90853**	3000 K	1194 lm	**W**	Medium Flood	**30**
		3500 K	1194 lm	**T**	Flood	**60**
White	**E90856**	4000 K	1280 lm	**N**		
Black	**E90857**					

HC

Power supply options (remote only)

ECO30W-800
0-10V EldoLED ECOdrive 30W for 1-2 fixtures

SOLO100W-800
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Warp_QY | Downlight | arrayLED | Damp Location | Driver remote | Asymmetric | 15W 400mA



HC

Balance - CRI 92

White	**E90870**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E90871**	3000 K	1677 lm	**W**	Medium Flood	**30**
		3500 K	1677 lm	**T**	Flood	**60**
White	**E90874**	4000 K	1804 lm	**N**		
Black	**E90875**					

HC

Efficiency - CRI 80

White	**E90868**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E90869**	3000 K	1932 lm	**W**	Medium Flood	**30**
		3500 K	1932 lm	**T**	Flood	**60**
White	**E90872**	4000 K	2078 lm	**N**		
Black	**E90873**					

HC

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixtures

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Warp_QY | Downlight | arrayLED | Damp Location | Driver remote | Asymmetric | 25W 700mA





Balance - CRI 92

White	**E90886**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E90887**	3000 K	2794 lm	**W**	Medium Flood	**30**
		3500 K	2794 lm	**T**	Flood	**60**
HC White	**E90890**	4000 K	2990 lm	**N**		
HC Black	**E90891**					

Efficiency - CRI 80

White	**E90884**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E90885**	3000 K	3431 lm	**W**	Medium Flood	**30**
		3500 K	3431 lm	**T**	Flood	**60**
HC White	**E90888**	4000 K	3431 lm	**N**		
HC Black	**E90889**					

Power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1 fixture

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-3 fixtures

E90884W60



Photometric curve



Light beam

25 LUX | 300 LUX | 500 LUX | 700 LUX | 750 LUX | 900 LUX | 1000 LUX



Floor plan

Note: Source lumens shown

epitax

A removable downlight designed for complete integration with the architecture. It can be recessed into the ceiling, enhancing the light in its purest form; or, it can be fixed semi-recessed, with a classy “warm & chic” gold finish optics compartment”.

Materials
Polycarbonate body (vers. 8W and 15W)
Aluminum body (other versions)

epitax range

	2 W	4 W	6 W	8 W	10 W	15 W
_R	Ø 1.1 in	Ø 1.1 in	Ø 1.4 in	-	Ø 2.5 in	Ø 3.5 in
_RJ	-	-	-	Ø 2.5 in	-	Ø 3.5 in
Finish						
Balance CRI 92	2700K 3000K 3500K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Efficiency CRI 80	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Optics	Narrow Spot Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood
Driver	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V
	1.5 in	1.5 in	1.6 in	3 in	3 in	4.1 in

F.O.L.™

The optics group consists of a polycarbonate lens combined with F.O.L.™ (Filtering Optical Layers) filters: a 5-filter patented system made of polyethylene terephthalate with different levels of opacity to safeguard the clarity of the light beam and it guarantees optimal optical efficiency.

Trimless

Part of the Epitax range of products, these downlights can be flush-mounted or extracted by 0.39 in , even with the installation already in place: this option considerably simplifies the removal operations and makes Epitax a product that is versatile and easy to configure.

Receded source

Being particularly receded, this light source allows obtaining a defined emission, hence reducing the impact of the secondary light beam while drastically reducing glare at the same time.



Adjustable version

The Epitax_J range of products come with a 360° mobility on the horizontal axis and a 30° tilt on the vertical axis.

Epitax | Downlight | powerLED | Damp Location | Driver remote | 2W 630mA





Balance - CRI 92

White	**E80632**	2700 K	157 lm	**M**	Narrow Spot	**8**
Black	**E80633**	3000 K	179 lm	**W**	Spot	**15**
Gold	**E80745**	3500 K	179 lm	**T**	Medium Flood	**30**
					Flood	**60**

Efficiency - CRI 80

White	**E80630**	2700 K	219 lm	**M**	Narrow Spot	**8**
Black	**E80631**	3000 K	233 lm	**W**	Spot	**15**
Gold	**E80744**	3500 K	233 lm	**T**	Medium Flood	**30**
		4000 K	249 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-16 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing required



E98501
Trimless casing



White	**E98527**
Black	**E98528**
Gold	**E98529**

Trim casing

Epitax | Downlight | powerLED | Damp Location | Driver remote | 4W 350mA





Balance - CRI 92

White	**E80636**	2700 K	395 lm	**M**	Spot	**15**
Black	**E80637**	3000 K	423 lm	**W**	Medium Flood	**30**
Gold	**E80747**	3500 K	423 lm	**T**	Flood	**60**
		4000 K	456 lm	**N**		

Efficiency - CRI 80

White	**E80634**	2700 K	490 lm	**M**	Spot	**15**
Black	**E80635**	3000 K	490 lm	**W**	Medium Flood	**30**
Gold	**E80746**	3500 K	490 lm	**T**	Flood	**60**
		4000 K	529 lm	**N**		

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-6 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Recessed casing required



E98501
Trimless casing



White	**E98527**
Black	**E98528**
Gold	**E98529**

Trim casing

index
technical information

Epitax | Downlight | powerLED | Damp Location | Driver remote | 6W 500mA





Balance - CRI 92

White	**E80640**	2700 K	532 lm	**M**	Spot	**15**
Black	**E80641**	3000 K	569 lm	**W**	Medium Flood	**30**
Gold	**E80749**	3500 K	569 lm	**T**	Flood	**60**
		4000 K	614 lm	**N**		

Efficiency - CRI 80

White	**E80638**	2700 K	659 lm	**M**	Spot	**15**
Black	**E80639**	3000 K	659 lm	**W**	Medium Flood	**30**
Gold	**E80748**	3500 K	659 lm	**T**	Flood	**60**
		4000 K	711 lm	**N**		

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-500
0-10V EldoLED SOLOdrive 50W for 1-6 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Recessed casing required

E98502
Trimless casing



White	**E98530**
Black	**E98531**
Gold	**E98532**

Trim casing

Epitax | Downlight | powerLED | Damp Location | Driver remote | 10W 800mA





Balance - CRI 92

White	**E80595**	2700 K	960 lm	**M**	Spot	**15**
Black	**E80596**	3000 K	1034 lm	**W**	Medium Flood	**30**
Gold	**E80751**	3500 K	1034 lm	**T**	Flood	**45**
		4000 K	1108 lm	**N**		

Efficiency - CRI 80

White	**E80591**	2700 K	1108 lm	**M**	Spot	**15**
Black	**E80592**	3000 K	1194 lm	**W**	Medium Flood	**30**
Gold	**E80750**	3500 K	1194 lm	**T**	Flood	**45**
		4000 K	1280 lm	**N**		

Power supply options (remote only)

ECO30W-800
0-10V EldoLED ECOdrive 30W for 1-2 fixtures

SOLO100W-800
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Recessed casing required



E98499
Trimless casing



White	**E98533**
Black	**E98534**
Gold	**E98535**

Trim casing

index
technical information

Epitax | Downlight | powerLED | Damp Location | Driver remote | 15W 400mA





Balance - CRI 92

White	**E80603**	2700 K	1568 lm	**M**	Spot	**15**
Black	**E80604**	3000 K	1677 lm	**W**	Medium Flood	**30**
Gold	**E80753**	3500 K	1677 lm	**T**	Flood	**60**
		4000 K	1804 lm	**N**		

Efficiency - CRI 80

White	**E80599**	2700 K	1932 lm	**M**	Spot	**15**
Black	**E80600**	3000 K	1932 lm	**W**	Medium Flood	**30**
Gold	**E80752**	3500 K	1932 lm	**T**	Flood	**60**
		4000 K	2078 lm	**N**		

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Recessed casing required



E98500
Trimless casing



White	**E98536**
Black	**E98537**
Gold	**E98538**

Trim casing

index
technical information

Epitax_J | Downlight | powerLED | Damp Location | Driver remote | Adjustable | 8W 700mA



Balance - CRI 92

White	E80644	2700 K	689 lm	M	Spot	15
Black	E80645	3000 K	738 lm	W	Medium Flood	30
Gold	E80758	3500 K	738 lm	T	Flood	60
		4000 K	796 lm	N		

Efficiency - CRI 80

White	E80642	2700 K	854 lm	M	Spot	15
Black	E80643	3000 K	854 lm	W	Medium Flood	30
Gold	E80757	3500 K	854 lm	T	Flood	60
		4000 K	922 lm	N		

Power supply options (remote only)

ECO30W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-700
0-10V EldoLED SOLOdrive 50W for 1-4 fixtures

SOLO100W-700
0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Recessed casing required



E98499
Trimless casing



White	E98533
Black	E98534
Gold	E98535

Trim casing

Epitax_J | Downlight | powerLED| Damp Location | Driver remote | Adjustable | 15W 400mA



Balance - CRI 92

White	E80648	2700 K	1568 lm	M	Spot	15
Black	E80649	3000 K	1677 lm	W	Medium Flood	30
Gold	E80760	3500 K	1677 lm	T	Flood	60
		4000 K	1804 lm	N		

Efficiency - CRI 80

White	E80646	2700 K	1932 lm	M	Spot	15
Black	E80647	3000 K	1932 lm	W	Medium Flood	30
Gold	E80759	3500 K	1932 lm	T	Flood	60
		4000 K	2078 lm	N		

Power supply options (remote only)

ECO30W-400
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-400
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-400
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Recessed casing required



E98500
Trimless casing



White	E98536
Black	E98537
Gold	E98538

Trim casing

index
technical information

giotto

The renowned Italian artist proved his prowess to Pope Boniface VIII by drawing a perfect circle, without any instrument. A tribute to his legend, Giotto is a compact ceiling-recessed downlight, which exposes itself with just a small round hole. The light beam is rather defined and surprisingly ample.

Materials
Aluminum body


05
07

In a class of its own

Due to the 1.7 in of source and the surprising controlled diffusion in two 30° and 60° optical variants, Giotto ushers an innovative solution in the lighting industry, unrivalled for its ratio between the slim diameter of the beam output hole and the super efficient lighting technique.

Scale 1:1

1.7 in

Cross Optics Technology ™

This technology exploits the positioning of two convex lenses arranged facing each other: the first gathers the light on the surface, conveying it into a small point for a flawless definition; the second lens opens the beam again, now without the secondary component, creating a clear-cut and clean light circle on the lit surface.





30° → Ø 90.55 in

60° → Ø 126.77 in

Recess and suspension

Thanks to the recessed or suspension double application, Giotto perfectly fits into various environments, due to the greater range of application and the option to combine products of the same range featuring the same technological and lighting technology distinctive traits. The Giotto range of products fully blends with the environment, offers great efficiency and harmony as well as installation coherence across the entire range.

Giotto_R | Downlight | powerLED | Dry Location | Driver remote | 4W 350mA



Balance - CRI 92

White	E84199	2700 K	395 lm	M	Spot	10
Black	E84200	3000 K	423 lm	W	Medium Flood	30
		3500 K	423 lm	T	Flood	60
		4000 K	456 lm	N		

Efficiency - CRI 80

White	E84201	2700 K	490 lm	M	Spot	10
Black	E84202	3000 K	490 lm	W	Medium Flood	30
		3500 K	490 lm	T	Flood	60
		4000 K	529 lm	N		

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Giotto_R | Downlight | powerLED | Dry Location | Driver remote | 6W 500mA



Balance - CRI 92

White	E84203	2700 K	532 lm	M	Spot	10
Black	E84204	3000 K	569 lm	W	Medium Flood	30
		3500 K	569 lm	T	Flood	60
		4000 K	614 lm	N		

Efficiency - CRI 80

White	E84205	2700 K	659 lm	M	Spot	10
Black	E84206	3000 K	659 lm	W	Medium Flood	30
		3500 K	659 lm	T	Flood	60
		4000 K	712 lm	N		

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Giotto_P | Pendant | powerLED | Dry Location | Driver remote | 7.5W 630mA



Balance - CRI 92

White	E81477	2700 K	614 lm	M	Medium Flood	30
Black	E81478	3000 K	657 lm	W	Flood	60
		3500 K	657 lm	T		
		4000 K	709 lm	N		

Efficiency - CRI 80

White	E81479	2700 K	760 lm	M	Medium Flood	30
Black	E81480	3000 K	760 lm	W	Flood	60
		3500 K	760 lm	T		
		4000 K	821 lm	N		

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

index
technical information

loro

Designed with a curved heat sink, typical “parrot-shape”, Loro fits best in dropped ceilings with little room for maneuver. A solution that allows maximum versatility, alongside a minimal design, wide range of versions and finishes as well as optimal visual comfort.

Materials
Aluminum body

loro range



	4 W	8 W	13 W	25 W
_R	-	Ø 3 in	Ø 3 in	Ø 4.1 in
_RJ	Ø 2.7 in	Ø 3.9 in	Ø 3.9 in	Ø 5.5 in
_Q	-	☐ 2.8 in	☐ 2.8 in	☐ 3.9 in
_QJ	-	☐ 3.9 in	☐ 3.9 in	☐ 5.5 in
Accessories	HC	HC	HC	HC
Finish				
Balance **CRI 92**	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Efficiency **CRI 80**	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K
Optics	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood
Driver	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V	On/Off 0 -10V
	2.6 in (_RJ)	2.7 in (_R) 3.6 in (_RJ) 2.5 in (_Q) 3.6 in (_QJ)	2.7 in (_R) 3.6 in (_RJ) 2.5 in (_Q) 3.6 in (_QJ)	3.7 in (_R) 5 in (_RJ) 3.7 in (_Q) 4.9 in (_QJ)

Minimal size

Using a curved rear Heat sink reduces the recess depth and allows the Loro range of products (except for the 25W) versions to adapt to the installation on ceilings with height lesser than 3.94 in.

UGR<19

The optics group, consisting of a chrome-plated reflector and a transparent polycarbonate diffuser offers an optimal reflectance control and a UGR index below 19. i.e. the threshold value for the correct lighting of offices and environments with video terminals (UNI-EN 12464-1 standard).

Wet location O.C.

The optics group offers IP65 front protection, i.e. full protection against entry of dust and extremely fine particles, as well as sprays and water jets.
WARNING the value exclusively refers to the optics section and NOT the lamp body (Damp protection).



Finishes

Four finishes available:

- white RAL9003
- black RAL9005
- grey RAL9006
- warm & chic gold

Adjustable version

The Loro_RJ and Loro_QJ range of products come with a 360° rotation on the horizontal axis and a 35° tilt on the vertical axis.



Loro_R | Downlight | arrayLED | Damp Location | Driver remote | 8W 220mA



2.7

HC

>16 optics 30°
>19 optics 15°, 60°
UGR

Balance - CRI 92

White	E97920	2700 K	883 lm	M	Spot	15
Black	E97921	3000 K	943 lm	W	Medium Flood	30
Grey	E97924	3500 K	943 lm	T	Flood	60
Gold	E97925	4000 K	1016 lm	N		

HC

White	E80791
Black	E80792
Grey	E80793
Gold	E80794

Efficiency - CRI 80

White	E97695	2700 K	1088 lm	M	Spot	15
Black	E97696	3000 K	1088 lm	W	Medium Flood	30
Grey	E97697	3500 K	1088 lm	T	Flood	60
Gold	E97698	4000 K	1173 lm	N		

HC

White	E80787
Black	E80788
Grey	E80789
Gold	E80790

Power supply options (remote only)

ECO30W-220	SOLO50W-220	SOLO100W-220
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Loro_R | Downlight | arrayLED | Damp Location | Driver remote | 13W 350mA



2.7

HC

UGR< 22

Balance - CRI 92

White	E91749	2700 K	1399 lm	M	Spot	15
Black	E91750	3000 K	1496 lm	W	Medium Flood	30
Grey	E91751	3500 K	1496 lm	T	Flood	60
Gold	E91752	4000 K	1610 lm	N		

HC

White	E80799
Black	E80800
Grey	E80801
Gold	E80802

Efficiency - CRI 80

White	E91204	2700 K	1724 lm	M	Spot	15
Black	E91205	3000 K	1724 lm	W	Medium Flood	30
Grey	E91206	3500 K	1724 lm	T	Flood	60
Gold	E91207	4000 K	1854 lm	N		

HC

White	E80795
Black	E80796
Grey	E80797
Gold	E80798

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Loro_R | Downlight | arrayLED | Damp Location | Driver remote | 25W 700mA



HC

UGR< 22

Balance - CRI 92

White	**E80672**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E80673**	3000 K	2794 lm	**W**	Medium Flood	**30**
Grey	**E80704**	3500 K	2794 lm	**T**	Flood	**60**
Gold	**E80705**	4000 K	2990 lm	**N**		

HC

White	**E80807**
Black	**E80808**
Grey	**E80809**
Gold	**E80810**

Efficiency - CRI 80

White	**E80670**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E80671**	3000 K	3431 lm	**W**	Medium Flood	**30**
Grey	**E80702**	3500 K	3431 lm	**T**	Flood	**60**
Gold	**E80703**	4000 K	3431 lm	**N**		

HC

White	**E80803**
Black	**E80804**
Grey	**E80805**
Gold	**E80806**

Power supply options (remote only)

SOLO50W-700	**SOLO100W-700**
0-10V EldoLED SOLOdrive 50W for 1 fixture	0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index
technical information

Loro_RJ | Downlight | powerLED | Damp Location | Driver remote | Adjustable | 4W 350mA





2.6

Balance - CRI 92

White	**E80710**	2700 K	395 lm	**M**	Spot	**15**
Black	**E80711**	3000 K	423 lm	**W**	Medium Flood	**30**
Grey	**E80712**	3500 K	423 lm	**T**	Flood	**60**
Gold	**E80713**	4000 K	456 lm	**N**		

HC

White	**E80847**
Black	**E80848**
Grey	**E80849**
Gold	**E80850**

Efficiency - CRI 80

White	**E80706**	2700 K	490 lm	**M**	Spot	**15**
Black	**E80707**	3000 K	490 lm	**W**	Medium Flood	**30**
Grey	**E80708**	3500 K	490 lm	**T**	Flood	**60**
Gold	**E80709**	4000 K	529 lm	**N**		

HC

White	**E80843**
Black	**E80844**
Grey	**E80845**
Gold	**E80846**

Power supply options (remote only)

ECO30W-350	**SOLO50W-350**	**SOLO100W-350**
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Loro_RJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 8W 220mA





3.6

Balance - CRI 92

White	**E93443**	2700 K	883 lm	**M**	Spot	**15**
Black	**E93444**	3000 K	943 lm	**W**	Medium Flood	**30**
Grey	**E93446**	3500 K	943 lm	**T**	Flood	**60**
Gold	**E93449**	4000 K	1016 lm	**N**		

HC

White	**E80855**
Black	**E80856**
Grey	**E80857**
Gold	**E80858**

Efficiency - CRI 80

White	**E93407**	2700 K	1088 lm	**M**	Spot	**15**
Black	**E93411**	3000 K	1088 lm	**W**	Medium Flood	**30**
Grey	**E93413**	3500 K	1088 lm	**T**	Flood	**60**
Gold	**E93418**	4000 K	1173 lm	**N**		

HC

White	**E80851**
Black	**E80852**
Grey	**E80853**
Gold	**E80854**

Power supply options (remote only)

ECO30W-220	**SOLO50W-220**	**SOLO100W-220**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Loro_RJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 13W 350mA





Balance - CRI 92

White	**E93450**	2700 K	1724 lm	**M**	Spot	**15**
Black	**E93451**	3000 K	1724 lm	**W**	Medium Flood	**30**
Grey	**E93452**	3500 K	1724 lm	**T**	Flood	**60**
Gold	**E93460**	4000 K	1854 lm	**N**		

HC

White	**E80863**
Black	**E80864**
Grey	**E80865**
Gold	**E80866**

Efficiency - CRI 80

White	**E93422**	2700 K	1399 lm	**M**	Spot	**15**
Black	**E93428**	3000 K	1496 lm	**W**	Medium Flood	**30**
Grey	**E93429**	3500 K	1496 lm	**T**	Flood	**60**
Gold	**E93431**	4000 K	1610 lm	**N**		

HC

White	**E80859**
Black	**E80860**
Grey	**E80861**
Gold	**E80862**

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Loro_RJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 25W 700mA





Balance - CRI 92

White	**E80370**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E80371**	3000 K	2794 lm	**W**	Medium Flood	**30**
Grey	**E80372**	3500 K	2794 lm	**T**	Flood	**60**
Gold	**E80373**	4000 K	2990 lm	**N**		

HC

White	**E80871**
Black	**E80872**
Grey	**E80873**
Gold	**E80874**

Efficiency - CRI 80

White	**E80374**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E80375**	3000 K	3431 lm	**W**	Medium Flood	**30**
Grey	**E80376**	3500 K	3431 lm	**T**	Flood	**60**
Gold	**E80377**	4000 K	3431 lm	**N**		

HC

White	**E80867**
Black	**E80868**
Grey	**E80869**
Gold	**E80870**

Power supply options (remote only)

SOLO50W-700
0-10V EldoLED SOLOdrive 50W for 1 fixture

SOLO100W-700
0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index
technical information

Loro_Q | Downlight | arrayLED | Damp Location | Driver remote | 8W 220mA





UGR

>16 optics 30°
>19 optics 15°, 60°

Balance - CRI 92

White	**E97940**	2700 K	883 lm	**M**	Spot	**15**
Black	**E97941**	3000 K	943 lm	**W**	Medium Flood	**30**
Grey	**E97944**	3500 K	943 lm	**T**	Flood	**60**
Gold	**E97945**	4000 K	1016 lm	**N**		

HC

White	**E80823**
Black	**E80824**
Grey	**E80825**
Gold	**E80826**

Efficiency - CRI 80

White	**E97699**	2700 K	1088 lm	**M**	Spot	**15**
Black	**E97700**	3000 K	1088 lm	**W**	Medium Flood	**30**
Grey	**E97701**	3500 K	1088 lm	**T**	Flood	**60**
Gold	**E97702**	4000 K	1173 lm	**N**		

HC

White	**E80819**
Black	**E80820**
Grey	**E80821**
Gold	**E80822**

Power supply options (remote only)

ECO30W-220	SOLO50W-220	SOLO100W-220
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Loro_Q | Downlight | arrayLED | Damp Location | Driver remote | 13W 350mA





UGR< 22

Balance - CRI 92

White	**E91753**	2700 K	1724 lm	**M**	Spot	**15**
Black	**E91754**	3000 K	1724 lm	**W**	Medium Flood	**30**
Grey	**E91755**	3500 K	1724 lm	**T**	Flood	**60**
Gold	**E91756**	4000 K	1854 lm	**N**		

HC

White	**E80831**
Black	**E80832**
Grey	**E80833**
Gold	**E80834**

Efficiency - CRI 80

White	**E91208**	2700 K	1399 lm	**M**	Spot	**15**
Black	**E91209**	3000 K	1496 lm	**W**	Medium Flood	**30**
Grey	**E91210**	3500 K	1496 lm	**T**	Flood	**60**
Gold	**E91211**	4000 K	1810 lm	**N**		

HC

White	**E80827**
Black	**E80828**
Grey	**E80829**
Gold	**E80830**

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1 fixtures	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Loro_Q | Downlight | arrayLED | Damp Location | Driver remote | 25W 700mA





UGR< 22

Balance - CRI 92

White	**E80660**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E80661**	3000 K	2794 lm	**W**	Medium Flood	**30**
Grey	**E80690**	3500 K	2794 lm	**T**	Flood	**60**
Gold	**E80691**	4000 K	2990 lm	**N**		

HC

White	**E80839**
Black	**E80840**
Grey	**E80841**
Gold	**E80842**

Efficiency - CRI 80

White	**E80658**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E80659**	3000 K	3341 lm	**W**	Medium Flood	**30**
Grey	**E80688**	3500 K	3341 lm	**T**	Flood	**60**
Gold	**E80689**	4000 K	3341 lm	**N**		

HC

White	**E80835**
Black	**E80836**
Grey	**E80837**
Gold	**E80838**

Power supply options (remote only)

SOLO50W-700	**SOLO100W-700**
0-10V EldoLED SOLOdrive 50W for 1 fixture	0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index
technical information

Loro_QJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 8W 220mA





Balance - CRI 92

White	**E80346**	2700 K	883 lm	**M**	Spot	**15**
Black	**E80347**	3000 K	943 lm	**W**	Medium Flood	**30**
Grey	**E80348**	3500 K	943 lm	**T**	Flood	**60**
Gold	**E80349**	4000 K	1016 lm	**N**		

HC

White	**E80887**
Black	**E80888**
Grey	**E80889**
Gold	**E80890**

Efficiency - CRI 80

White	**E80350**	2700 K	1088 lm	**M**	Spot	**15**
Black	**E80351**	3000 K	1088 lm	**W**	Medium Flood	**30**
Grey	**E80352**	3500 K	1088 lm	**T**	Flood	**60**
Gold	**E80353**	4000 K	1173 lm	**N**		

HC

White	**E80883**
Black	**E80884**
Grey	**E80885**
Gold	**E80886**

Power supply options (remote only)

ECO30W-220	SOLO50W-220	SOLO100W-220
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Loro_QJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 13W 350mA





Balance - CRI 92

White	**E80354**	2700 K	1724 lm	**M**	Spot	**15**
Black	**E80355**	3000 K	1724 lm	**W**	Medium Flood	**30**
Grey	**E80356**	3500 K	1724 lm	**T**	Flood	**60**
Gold	**E80357**	4000 K	1854 lm	**N**		

HC

White	**E80895**
Black	**E80896**
Grey	**E80897**
Gold	**E80898**

Efficiency - CRI 80

White	**E80358**	2700 K	1399 lm	**M**	Spot	**15**
Black	**E80359**	3000 K	1496 lm	**W**	Medium Flood	**30**
Grey	**E80360**	3500 K	1496 lm	**T**	Flood	**60**
Gold	**E80361**	4000 K	1610 lm	**N**		

HC

White	**E80891**
Black	**E80892**
Grey	**E80893**
Gold	**E80894**

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1 fixtures	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

index
technical information

Loro_QJ | Downlight | arrayLED | Damp Location | Driver remote | Adjustable | 25W 700mA





Balance - CRI 92

White	**E80362**	2700 K	2598 lm	**M**	Spot	**15**
Black	**E80363**	3000 K	2794 lm	**W**	Medium Flood	**30**
Grey	**E80364**	3500 K	2794 lm	**T**	Flood	**60**
Gold	**E80365**	4000 K	2990 lm	**N**		

HC

White	**E80903**
Black	**E80904**
Grey	**E80905**
Gold	**E80906**

Efficiency - CRI 80

White	**E80366**	2700 K	3210 lm	**M**	Spot	**15**
Black	**E80367**	3000 K	3431 lm	**W**	Medium Flood	**30**
Grey	**E80368**	3500 K	3431 lm	**T**	Flood	**60**
Gold	**E80369**	4000 K	3461 lm	**N**		

HC

White	**E80899**
Black	**E80900**
Grey	**E80901**
Gold	**E80902**

Power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive 50W for 1 fixture

SOLO100W-700

0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

index

technical information

E91204W60



Photometric curve



Light beam

50 LUX | 75 LUX | 100 LUX | 125 LUX | 200 LUX | 250 LUX | 300 LUX | 350 LUX



Floor plan

projectors range index

Creek

Creek_Optus

B3

creek

Materials
Structure in EPS
Aluminium projector

creek range



	Creek Optus
16W	2.6 inch
24W	3.5 inch
34W	4.1 inch
Accessories	
Finish	White Black
Balance CRI 92	2700K - 3000K - 4000K
Optics	Spot - Flood - Wide Flood

index
technical information



Integrated architecture solutions

1 | Linear profiles (19.7 inch)
2 | Linear profiles (39.4 inch)
3 | Linear profiles (59 inch)
4 | Mechanical joint*
5 | Final guard
6 | Linear guard (19.7 inch)
7 | Linear guard (139.4 inch)
8 | Duct Tape

*item supplied by the installer, or available from any building material retailer.

Structure size

The new structure of Creek adapts perfectly to the standard center distance of the uprights of the plasterboard structure with a hole of just 14.6 inch. The linear profiles, made up of standard uprights combined with ESP panels, can be easily combined in line thanks to the mechanical joint. Once the linear profile has been positioned and fixed, it will be possible to fill and paint the EPS panel, which, thanks to its characteristics, will ensure uniformity with the plasterboard of the ceiling.



EPS panel

The EPS panel mates directly with the plasterboard false ceiling with the possibility of being sanded and treated in the same way. When finished, there will be no difference in finish.



Product installation phase

PHASE 1

Once the structure has been set up in the false ceiling, the lighting body is positioned in the linear casing.

PHASE 2

The fixing is done by interlocking, inserting the end of the base in the internal seat of the profile.

PHASE 3

The process is completed by pressing down on the base near the point where the articulated arm starts..

Upper cover guard



code	type	L inch
E99927	Black	19.7
E99928	Black	39.4

Sealing head



code	type
E99929	Black

Linear Profile _P (pair)



code	type	L inch
E82728	White	19.7
E82729	White	39.4
E82730	White	59

index
technical information

Creek Optus | powerLED 16 W DC 450mA

IP20 NEW



	Balance - CRI 92	Cct	lm S - D CRI 92	Optic	
White	**E82731**	**M** 2700	1939 - On req	**15** Spot	(12°)
Black	**E82732**	**W** 3000	2030 - On req	**30** Flood	(26°)
		N 4000	2182 - On req	**60** W.Flood	(51°)

Remote power supply options (required/ordered separately)

ECO30W-450

0-10V EldoLED
ECOdrive 30W
for 1 fixture

SOLO50W-450

0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtures

SOLO100W-450

0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtures

Optics & accessories Page B9

Creek Optus | powerLED 24 W DC 700mA

IP20 NEW



	Balance - CRI 92	Cct	lm S - D CRI 92	Optic	
White	**E82733**	**M** 2700	3033 - On req	**15** Spot	(12°)
Black	**E82734**	**W** 3000	3177 - On req	**30** Flood	(26°)
		N 4000	3416 - On req	**60** W.Flood	(51°)

Remote power supply options (required/ordered separately)

SOLO30W-700

0-10V EldoLED
SOLOdrive 30W
for 1 f xtures

SOLO100W-700

0-10V EldoLED
SOLOdrive 100W
for 1-3 f xtures

Optics & accessories Page B9

Creek Optus | arrayLED 34 W DC 950mA

IP20 NEW



	Balance - CRI 92	Cct	lm S - D CRI 92	Optic	
White	**E82735**	**M** 2700	3930 - On req	**15** Spot	(12°)
Black	**E82736**	**W** 3000	4117 - On req	**30** Flood	(26°)
		N 4000	4426 - On req	**60** W.Flood	(51°)

Remote power supply options (required/ordered separately)

SOLO50W-950

0-10V EldoLED
SOLOdrive 50W
for 1 fixtures

SOLO100W-950

0-10V EldoLED
SOLOdrive 100W
for 1-2 fixtures

Optics & accessories Page B9

index
technical information

Optics

	description
E99827	Spot

suitable for: Creek Optus 16W

	description
E99828	Flood

suitable for: Creek Optus 16W

	description
E99829	Wide Flood

suitable for: Creek Optus 16W

	description
E99844	Focal Kit

suitable for: Creek Optus 16W

	description
E99808	Spot

suitable for: Creek Optus 24W / 34W

	description
E99809	Flood

suitable for: Creek Optus 24W / 34W

	description
E99810	Wide Flood

suitable for: Creek Optus 24W / 34W

	description
E99843	Focal Kit

suitable for: Creek Optus 24W / 34W

Accessories

	description
E99781	Elliptical filter

suitable for: Creek Optus 16W

	description
E99780	Honeycomb

suitable for: Creek Optus 16W

	description
E99779	Cross louvre

suitable for: Creek Optus 16W

	description
E99783	Cylindrical screen

suitable for: Navata_Optus 16W

	description
E99782	45° Cylindrical screen

suitable for: Creek Optus 16W

	description
E99841	Honeycomb

suitable for: Kit focale **99844**

	description
E99797	Elliptical filter

suitable for: Creek Optus 24W / 34W

	description
E99798	Honeycomb

suitable for: Creek Optus 24W / 34W



	description
E99799	Cross louvre

suitable for: Creek Optus 24W / 34W

	description
E99796	Cylindrical screen

suitable for: Creek Optus 24W / 34W

	description
E99795	45° Cylindrical screen

suitable for: Creek Optus 24W / 34W



	description
E99842	Honeycomb

suitable for: Kit focale **E99843**

index
technical information

FKT | Venice, Italy

ceiling and pendant lamps range index

click images to open product pages

Tour

Tour_PD

C6

Tour_PI

C7

Tour_PU

C8

Tour_D

C10

Tour_Q

C12

Tour_QD

C13

Tour_QV

C13

Tour_R

C18

Tour_CD

C20

Tour_CI

C21

tour

Essential and practical, Tour allows redefining the lighting of large spaces: whether transit areas, retail contexts or open spaces designated for co-working, the various versions of direct light, indirect light with internal lateral or ceiling-mounted recessed emission revolutionize an iconic shape with redesigned applications, refined finishes and new installation technologies.

Materials
Calendered aluminum body
Opaline polycarbonate diffuser

tour range

	_P	_Q	_D	_QD	_R	_C
Profile	1.5” W x 1.5” H	1.5” W x 1.5” H	1.5” W x 3” H	1.5” W x 3” H	1.5” W x 1.5” H	1.5” W x 1.5” H
26.2 x 26.2 in	-	Q - QV 45 W	-	90 W	-	-
29.1 in	PD - PU 37.5 W	-	75 W	-	37.5 W	37.5 W
29.5 in	PI 29 W	-	-	-	-	-
35.8 in	PD - PU 45 W	-	90 W	-	-	-
37 in	-	-	-	-	45 W	-
37.2 in	PI 36.5 W	-	-	-	-	36.5 W
49.4 x 49.4 in		Q 90 W	-	180 W	-	-
56.3 in	PD 70 W	-	140 W	-	-	-
57.9 in	-	-	-	-	70 W	-
58.1 in	PI 57.5 W	-	-	-	-	57.5 W
65.2 x 49.4 in		Q 105 W	-	210 W	-	-
96.5 in	PD - PU 114 W	-	224 W	-	-	-
Finish						
CRI 92	3000K 3500K 4000K	3000K 3500K 4000K	3000K 3500K 4000K	3000K 3500K 4000K	3000K 3500K 4000K	3000K 3500K 4000K
Emission						
Driver	On/Off 0-10 V	On/Off 0-10 V	On/Off 0-10 V	On/Off 0-10 V	On/Off 0-10 V	On/Off 0-10 V

Application versatility

Tour's development process created the product as an application solution capable of adapting to any architectural need. In the suspension version, the support cables are the same that power-supply the product and they come 196.85 inch long on the four dimensions. Lastly, thanks to the ceiling-mounted version and recess, Tour becomes a dynamic element provided with a clean design without interfering with the style it is made of.



The ring

Tour comes with an extruded aluminum profile which places it in a class of its own due to its almost imperceptible size. Due to its prestigious six finishes, Tour becomes an all-around element suitable for any architectural solution.



Emissions range

Tour comes with four different emissions: direct, indirect, internal lateral and dual-side emission. Four lighting effects that can be combined with each other in countless combinations to transform the environments with a minimal and contemporary light.



Harmonic diffusion

The opaline polycarbonate screen guarantees visual comfort and a perfect diffusion. Is easily removable thanks to a system equipped with a spring, patented and specially designed to perfectly adapt to the extruded element.

Tour_PD | Pendant Luminaires | 24 V | topLED | Driver remote | 37.5W



White	E64570	3000 K	4678 lm	W	General	00
Black	E65112	3500 K	4678 lm	T		
Nickel	E65113	4000 K	5006 lm	N		
Gold	E63726					
Bronze	E65115					
Rosegold	E65128					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PD | Pendant Luminaires | 24 V | topLED | Driver remote | 45W



White	E64571	3000 K	5847 lm	W	General	00
Black	E65116	3500 K	5847 lm	T		
Nickel	E65117	4000 K	6139 lm	N		
Gold	E63727					
Bronze	E65119					
Rosegold	E65129					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PD | Pendant Luminaires | 24 V | topLED | Driver remote | 70W



White	E64572	3000 K	9355 lm	W	General	00
Black	E65120	3500 K	9355 lm	T		
Nickel	E65121	4000 K	9823 lm	N		
Gold	E63728					
Bronze	E65123					
Rosegold	E65130					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PD | Pendant Luminaires | 24 V | topLED | Driver remote | 114W



White	E64573	3000 K	15588 lm	W	General	00
Black	E65124	3500 K	15588 lm	T		
Nickel	E65125	4000 K	16367 lm	N		
Gold	E63729					
Bronze	E65127					
Rosegold	E65131					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PI | Pendant Luminaires | 24 V | stripLED | Driver remote | 29W



White	**E64577**	3000 K	3000 lm	**W**	General	**00**
Black	**E65100**	3500 K	3000 lm	**T**		
Nickel	**E65101**	4000 K	3220 lm	**N**		
Gold	**E63736**					
Bronze	**E65103**					
Rose gold	**E65132**					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PI | Pendant Luminaires | 24 V | stripLED | Driver remote | 36.5W



White	**E64579**	3000 K	3785 lm	**W**	General	**00**
Black	**E65104**	3500 K	3785 lm	**T**		
Nickel	**E65105**	4000 K	4060 lm	**N**		
Gold	**E63737**					
Bronze	**E65107**					
Rose gold	**E65133**					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PI | Pendant Luminaires | 24 V | stripLED | Driver remote | 57.5W



White	**E64581**	3000 K	6000 lm	**W**	General	**00**
Black	**E65108**	3500 K	6000 lm	**T**		
Nickel	**E65109**	4000 K	6440 lm	**N**		
Gold	**E63738**					
Bronze	**E65111**					
Rose gold	**E65134**					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

index
technical information

Tour_PU | Pendant Luminaires | 24 V | topLED | Driver remote | 37.5W



White	E64583	3000 K	4678 lm	W	General	00
Black	E64682	3500 K	4678 lm	T		
Nickel	E64683	4000 K	5006 lm	N		
Gold	E63731					
Bronze	E64685					
Rose gold	E65135					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PU | Pendant Luminaires | 24 V | topLED | Driver remote | 45W



White	E64584	3000 K	5847 lm	W	General	00
Black	E64686	3500 K	5847 lm	T		
Nickel	E64687	4000 K	6139 lm	N		
Gold	E63732					
Bronze	E64689					
Rose gold	E65136					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PU | Pendant Luminaires | 24 V | topLED | Driver remote | 70W



White	E64585	3000 K	9355 lm	W	General	00
Black	E64690	3500 K	9355 lm	T		
Nickel	E64691	4000 K	9823 lm	N		
Gold	E63733					
Bronze	E64693					
Rose gold	E65137					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_PU | Pendant Luminaires | 24 V | topLED | Driver remote | 114W



White	E64587	3000 K	15588 lm	W	General	00
Black	E64694	3500 K	15588 lm	T		
Nickel	E64695	4000 K	16367 lm	N		
Gold	E63734					
Bronze	E64697					
Rose gold	E65138					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

CODICE MENDINI
Eames design

Tour_D | Pendant Luminaires | 24 V | topLED | Driver remote | 75W



Use a dual driver for dual lighting

White	**E65300**	3000 K	9356 lm	**W**	General	**00**
Black	**E65301**	3500 K	9356 lm	**T**		
Nickel	**E65302**	4000 K	10012 lm	**N**		
Gold	**E63711**					
Bronze	**E65304**					
Rose gold	**E65305**					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_D | Pendant Luminaires | 24 V | topLED | Driver remote | 90W



Use a dual driver for dual lighting

White	**E65306**	3000 K	11894 lm	**W**	General	**00**
Black	**E65307**	3500 K	11894 lm	**T**		
Nickel	**E65308**	4000 K	12278 lm	**N**		
Gold	**E63712**					
Bronze	**E65310**					
Rose gold	**E65311**					

Requires 2 Drivers

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_D | Pendant Luminaires | 24 V | topLED | Driver remote | 140W



Use a dual driver for dual lighting

White	**E65312**	3000 K	18710 lm	**W**	General	**00**
Black	**E65313**	3500 K	18710 lm	**T**		
Nickel	**E65314**	4000 K	19646 lm	**N**		
Gold	**E63713**					
Bronze	**E65316**					
Rose gold	**E65317**					

Requires 2 Drivers

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

index
technical information

Tour_Q | Pendant Luminaires | 24 V | topLED | Driver remote | 45W



White	**E64360**	3000 K	4810 lm	**W**	General	**00**
Black	**E64370**	3500 K	4810 lm	**T**		
		4000 K	5040 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_Q | Pendant Luminaires | 24 V | topLED | Driver remote | 90W



White	**E64361**	3000 K	9619 lm	**W**	General	**00**
Black	**E64371**	3500 K	9619 lm	**T**		
		4000 K	10080 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_Q | Pendant Luminaires | 24 V | topLED | Driver remote | 105W



White	**E64362**	3000 K	11222 lm	**W**	General	**00**
Black	**E64372**	3500 K	11222 lm	**T**		
		4000 K	11760 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

index
technical information

Tour_QD | Pendant Luminaires | 24 V | topLED | Driver remote | 90W



White	**E64363**	3000 K	9619 lm	**W**	General	**00**
Black	**E64373**	3500 K	9619 lm	**T**		
		4000 K	10080 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_QD | Pendant Luminaires | 24 V | topLED | Driver remote | 180W



White	**E64364**	3000 K	18437 lm	**W**	General	**00**
Black	**E64374**	3500 K	18437 lm	**T**		
		4000 K	19320 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_QV | Pendant Luminaires | 24 V | topLED | Driver remote | 45W



White	**E64260**	3000 K	4810 lm	**W**	General	**00**
Black	**E64250**	3500 K	4810 lm	**T**		
		4000 K	5040 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

index
technical information

Single lighting remote driver configuration

Providing a Tour_PD composition with remote driver.

Selection Tour model



Selection suspension kit

Selection driver / controller

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Final result



Ordering example:

n.1 art. E64570W00 (Tour_PD1) + n.1 art. E64575 (Suspensions)

Dual lighting remote driver configuration

Providing a Tour_D composition with remote driver which commands dual lighting.

One driver for uplight, one for downlight

Selection Tour model



Selection suspension kit

Selection driver / controller

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Final result



Ordering example:

n.1 art. E65312W00 (Tour_D3) + n.1 art. E64575 (Suspensions)

3-cone fixing kit Tour_R



For version Ø 96.46 requires 2x fixing kit with 3 cones each

type

White	E64575	Gold	E63700
Black	E64670	Bronze	E64673
Nickel	E64671	Rose gold	E65141

3-cone fixing kit Tour_Q



type

White	E64270
Black	E64240

3-coupling point ceiling rose for one-side emission Tour R



White	E64578
Black	E65142
Nickel	E65144
Gold	E63706
Bronze	E65148
Rose gold	E65150

4-coupling point ceiling rose for one-side emission Tour Q



White	E64368
Black	E64369

6-point coupling ceiling rose for 96.46 inch-long one-side emission Tour R



White	E64580
Black	E65152
Nickel	E65154
Gold	E63708
Bronze	E65158
Rose gold	E65160

Configuration with 96.46 dual-side emission central ceiling rose

Providing a Tour_D composition with central ceiling rose.

Selection
Tour model



Selection of
central ceiling rose



Final result



Ordering example:

n.1 art. E64570W00
(Tour_PD1)

+

n.1 art. E64578
(ON/OFF)

Coupling ceiling rose for dual-side emission Tour R



White	**E65324**
Black	**E65326**
Nickel	**E65328**
Gold	**E63701**
Bronze	**E65332**
Rose gold	**E65334**

Coupling ceiling rose for dual-side emission Tour Q



White	**E64358**
Black	**E64359**

Configuration with central ceiling rose for compositions

Providing a Tour_PD, PU and D composition with central ceiling rose.

Selection
Tour model



Selection of
central ceiling rose



Final result



Ordering example:

n.1 art. E64570W00
n.1 art. E64584W00
n.1 art. E65312W00

+

n.1 art. E65412
(ON/OFF)

6-point ceiling rose for 3 tour fixing





White	**E65412**
Black	**E65413**
Nickel	**E65414**
Gold	**E63716**
Bronze	**E65416**
Rose gold	**E65417**

Tour_R | Integrated Luminaires | 24 V | topLED | Driver remote | 37.5W



White	E65420	3000 K	4678 lm	W	General	00
Black	E65421	3500 K	4678 lm	T		
Nickel	E65422	4000 K	5006 lm	N		
Gold	E63710					
Bronze	E65424					
Rose gold	E65425					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_R | Integrated Luminaires | 24 V | topLED | Driver remote | 45W



White	E65426	3000 K	5847 lm	W	General	00
Black	E65427	3500 K	5847 lm	T		
Nickel	E65428	4000 K	6139 lm	N		
Gold	E63720					
Bronze	E65430					
Rose gold	E65431					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_R | Integrated Luminaires | 24 V | topLED | Driver remote | 70W



White	E65432	3000 K	9355 lm	W	General	00
Black	E65433	3500 K	9355 lm	T		
Nickel	E65434	4000 K	9823 lm	N		
Gold	E63730					
Bronze	E65436					
Rose gold	E65437					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Removal steps of the EPS element



Dropped ceiling section | Product insertion | Removing cap | Painting and positioning the cap

Tour_CD | Ceiling Light | 24 V | topLED | Driver remote | 37.5W



White	E65350	3000 K	4678 lm	W	General	00
Black	E65351	3500 K	4678 lm	T		
Nickel	E65352	4000 K	5006 lm	N		
Gold	E63740					
Bronze	E65354					
Rose gold	E65355					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_CD | Ceiling Light | 24 V | topLED | Driver remote | 45W



White	E65356	3000 K	5847 lm	W	General	00
Black	E65357	3500 K	5847 lm	T		
Nickel	E65358	4000 K	6139 lm	N		
Gold	E63750					
Bronze	E65360					
Rose gold	E65361					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_CD | Ceiling Light | 24 V | topLED | Driver remote | 70W



White	E65362	3000 K	9355 lm	W	General	00
Black	E65363	3500 K	9355 lm	T		
Nickel	E65364	4000 K	9823 lm	N		
Gold	E63760					
Bronze	E65366					
Rose gold	E65367					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Spacer kit for Tour_C



White	E65386
Black	E65387
Nickel	E65389
Gold	E63724
Bronze	E65390
Rose gold	E65391

The Tour_C version comes with 0.9 inch-long spacers included.

index
technical information

Tour_CI | Ceiling_Wall Light | 24 V | stripLED | Driver remote | 29W

White	E65368	3000 K	3000 lm	W	General	00
Black	E65369	3500 K	3000 lm	T		
Nickel	E65370	4000 K	3220 lm	N		
Gold	E63721					
Bronze	E65372					
Rosegold	E65373					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_CI | Ceiling_Wall Light | 24 V | stripLED | Driver reomte | 36.5W



White	E65374	3000 K	3785 lm	W	General	00
Black	E65375	3500 K	3785 lm	T		
Nickel	E65376	4000 K	4060 lm	N		
Gold	E63722					
Bronze	E65378					
Rosegold	E65379					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Tour_CI | Ceiling_Wall Light | 24 V | stripLED | Driver remote | 57.5W



White	E65380	3000 K	6000 lm	W	General	00
Black	E65381	3500 K	6000 lm	T		
Nickel	E65382	4000 K	6440 lm	N		
Gold	E63723					
Bronze	E65384					
Rosegold	E65385					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Spacer kit for Tour_C



White	E65386
Black	E65387
Nickel	E65389
Gold	E63724
Bronze	E65390
Rosegold	E65391

The Tour_C version comes with 0.9 inch-long spacers included.

index
technical information

Configuration of Tour_C with spacer kit

Providing an ON/OFF composition. Tour_CI, CD with spacer kit. Tour_C is distributed including 0.9 inch spacers which can be possibly replaced by the suspension kit to extend the distance from the ceiling.

Selection Tour model



Selection suspension kit

Selection driver / controller

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Final result



Ordering example:

n.1 art. E65368W00
n.1 art. E65356W00
+
n.1 art. E65386 (spacer kit)
+
n.1 art. E99374 (driver ON/OFF)

Recess Tour configuration

Providing an ON/OFF configuration with Tour_R.

Selection Tour model



Selection driver / controller

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Final result



Ordering example:

n.1 art. E65420W00
+
n.1 art. E99374 (driver ON/OFF)

GABIN
ORATORIC

path markers range index

click images to open product pages

Quara

Quara_R

E8

Quara_Q

E8

Laella

Laella_R

E11

Laella_Q

E11

Envelope

Envelope_1

E13

Envelope_2

E13

Envelope_4

E13

Envelope_R

E14





PARIS

quara

A light drop excavated in a square or round-shaped lamp body: here comes Quara, a step light installed in proximity of the floor. It offers a classy lighting and decoration thanks to the radial optics and ovalized emission.

Materials
Aluminum body

Quara_R | Path-marker | powerLED | Damp location | Driver remote | Asymmetric | 2W 630mA

659 Recessed casing
E84338

1.7

Ø 2.6

2.1

Efficiency - CRI 80

Nickel	**E86402**	2700 K	219 lm	**M**	Flood **70**
		3000 K	233 lm	**W**	
		3500 K	233 lm	**T**	
		4000 K	249 lm	**N**	

Power supply options (remote only)

ECO30W-630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Quara_Q | Path-marker | powerLED | Damp location | Driver remote | Asymmetric | 2W 630mA

659 Recessed casing
E84338

1.7

□ 2.8

2.1

Efficiency - CRI 80

Nickel	**E86564**	2700 K	219 lm	**M**	Flood **70**
		3000 K	233 lm	**W**	
		3500 K	233 lm	**T**	
		4000 K	249 lm	**N**	

Power supply options (remote only)

ECO30W-630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

index
technical information

Private residence | Italy

laella



Laella is the prototype of then minimal step light with refined finishes, an extremely narrow emission and ovalized, capable of emitting a captivating light with defined contours. Also suitable for outdoor installations.

Materials
Aluminum or AISI 316 stainless steel body

Laella_R | Path-marker | powerLED | Damp location | Driver remote | Asymmetric | 1W 350mA

P63 Recessed casing
E98950



0.8

Efficiency - CRI 80

White	**E93508**	2700 K	100 lm	**M**	Asymmetric	**07**
Grey	**E93513**	3000 K	107 lm	**W**		
DarkBrown	**E93515**	3500 K	107 lm	**T**		
Steel	**E93516**	4000 K	114 lm	**N**		

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Laella_Q | Path-marker | powerLED | Damp location | Driver remote | Asymmetric | 1W 350mA

P63 Recessed casing
E98950



0.8

Efficiency - CRI 80

White	**E93517**	2700 K	100 lm	**M**	Asymmetric	**07**
Grey	**E93518**	3000 K	107 lm	**W**		
DarkBrown	**E93519**	3500 K	107 lm	**T**		
Steel	**E93520**	4000 K	114 lm	**N**		

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

envelope

Aquastop®

A versatile and aesthetically minimal applique resembling a small envelope. Coming with single (fit for indoor installation), double or quadruple emission, Envelope allows to obtain light effects capable of lighting and furnishing all at once.

Materials
Aluminum body

Envelope_1 | Path-marker | powerLED | Wet location | Driver remote | 1W 350mA



Efficiency - CRI 80

White	E96976	2700 K	136 lm	M	Asymmetric	07
Grey	E96978	3000 K	145 lm	W		
BK Grey	E80605	3500 K	145 lm	T		
DarkBrown	E96979	4000 K	155 lm	N		
Black	E96977					
Brass	E83613					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

E84336
Masonry outer casing

E84915
Poured-concrete outer casing

Envelope_2 | Path-marker | powerLED | Driver remote | 1W 350mA



Efficiency - CRI 80

White	E96971	2700 K	136 lm	M	180°	18
Grey	E96973	3000 K	145 lm	W		
DarkBrown	E96974	3500 K	145 lm	T		
		4000 K	155 lm	N		

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

E84336
Masonry outer casing

E84915
Poured-concrete outer casing

Envelope_4 | Path-marker | powerLED | Driver remote | 1W 350mA



Efficiency - CRI 80

White	E96966	2700 K	136 lm	M	180°	18
Grey	E96968	3000 K	145 lm	W		
DarkBrown	E96969	3500 K	145 lm	T		
		4000 K	155 lm	N		

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

E84336
Masonry outer casing

E84915
Poured-concrete outer casing

Envelope_R | Path-marker | powerLED | Wet location | Driver remote | 1W 350mA



Efficiency - CRI 80

White	**E83601**	2700 K	136 lm	**M**	Asymmetric	**07**
Grey	**E83603**	3000 K	145 lm	**W**		
BK Gre	**E84071**	3500 K	145 lm	**T**		
DarkBrow	**E83604**	4000 K	155 lm	**N**		
Black	**E83602**					
Brass	**E84072**					

Power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-350

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

E84336
Masonry outer casing

E84915
Poured-concrete outer casing

small spotlights range index

click images to open product pages

Bibok

Bibok

F7

Crystals

Elin

F11

Ture

F12

Gude

F13



bibok

With a flange measuring just 0.4 in, Bibok allows to obtain captivating lighting effects without affecting the architecture. With its ultra-minimalist design, fit for plasterboard-installation thanks to the recessed casing, this recessed spotlight enhances spaces with refined bright spots.

Materials
Brass body

Bibok | Decorative spotlight | 24 V | 5mmLED | Damp location | Driver remote | 0.5W



0.3

White	**E91366**	3000 K	**W**	Medium Flood	**30**
Chrome	**E85335**	3500 K	**T**		
		5000 K	**C**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Bibok | Decorative spotlight | powerLED | Damp location | Driver remote | 1W 350mA

P63 Recessed casing
E84916



0.5

White	**E91348**	3000 K	107 lm	**W**	Flood	**70**
Chrome	**E85976**	3500 K	107 lm	**T**		
		4000 K	114 lm	**N**		
		5000 K	139 lm	**C**		
White	**E91350**	3000 K	107 lm	**W**	Wide Flood	**12**
Chrome	**E85575**	3500 K	107 lm	**T**		
		4000 K	114 lm	**N**		
		5000 K	139 lm	**C**		

Power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-350

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Bibok | Decorative spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA

P63 Recessed casing
E84917



0.5

White	**E91349**	3000 K	143 lm	**W**	Flood	**70**
Chrome	**E85979**	3500 K	143 lm	**T**		
		4000 K	152 lm	**N**		
		5000 K	185 lm	**C**		

Power supply options (remote only)

ECO30W-500

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-500

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-500

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

index
technical information

crystals

Each and every article of the Crystals range of products comes with unique distinctive features: the normal imperfections due to hadcrafted processing of the crystal enhance these spotlights even further. Plasterboard-installable using recessed casings, they come with various CCTs of white light or RGB, with easy serial connection thanks to quick couplers.

Materials
Brass body
Transparent prismatic ground crystal diffuser

Note: Source lumens shown

Elin | Crystal spotlight | 5mmLED | Driver remote | 0.5W 24V



P63 Recessed casing
E84916 / E84335

Chrome	E87337	3000 K	W	General	00
		3500 K	T		
		5000 K	C		
		R - G - B - Y on request			

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Elin | Crystal spotlight | 5mmLED | Driver remote | 0.5W 24V



P63 Recessed casing
E84916

Chrome	E87340	RGB	Z	General	00

Power supply options (remote only)

EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/order separately.

Elin | Crystal spotlight | powerLED | Driver remote | 1W 350mA



P63 Recessed casing
E84916 / E84335

Efficiency - CRI 80

Chrome	E91200	3000 K	107 lm	W	General	00
		3500 K	107 lm	T		
		4000 K	114 lm	N		
		5000 K	139 lm	C		

Power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-350

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Elin | Crystal spotlight | powerLED | Driver remote | 1.5W 500mA



P63 Recessed casing
E84917

Efficiency - CRI 80

Chrome	E87323	3000 K	143 lm	W	General	00
		3500 K	143 lm	T		
		4000 K	152 lm	N		
		5000 K	185 lm	C		

Power supply options (remote only)

ECO30W-500

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-500

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-500

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Ture | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA

P63 Recessed casing
E84917



Efficiency - CRI 80

Chrome **E87350**	3000 K	143 lm	**W**	General	**00**
	3500 K	143 lm	**T**		
	4000 K	152 lm	**N**		
	5000 K	185 lm	**C**		

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Ture | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA

P63 Recessed casing
E84954



Efficiency - CRI 80

Chrome **E87353**	3000 K	199 lm	**W**	General	**00**
	3500 K	199 lm	**T**		
	4000 K	213 lm	**N**		
	5000 K	227 lm	**C**		

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Ture | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA

P63 Recessed casing
E84901



Efficiency - CRI 80

Chrome **E87356**	3000 K	199 lm	**W**	General	**00**
	3500 K	199 lm	**T**		
	4000 K	213 lm	**N**		
	5000 K	227 lm	**C**		

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

index
technical information

Gude | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA

P63 Recessed casing
E84917



Efficiency - CRI 80

Chrome **E87330**	3000 K	143 lm	**W**	General	**00**
	3500 K	143 lm	**T**		
	4000 K	152 lm	**N**		
	5000 K	185 lm	**C**		

Power supply options (remote only)

ECO30W-500	**SOLO50W-500**	**SOLO100W-500**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Gude | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA

P63 Recessed casing
E84954



Efficiency - CRI 80

Chrome **E87332**	3000 K	199 lm	**W**	General	**00**
	3500 K	199 lm	**T**		
	4000 K	213 lm	**N**		
	5000 K	227 lm	**C**		

Power supply options (remote only)

ECO30W-500	**SOLO50W-500**	**SOLO100W-500**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Gude | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA

P63 Recessed casing
E84901



Efficiency - CRI 80

Chrome **E87335**	3000 K	199 lm	**W**	General	**00**
	3500 K	199 lm	**T**		
	4000 K	213 lm	**N**		
	5000 K	227 lm	**C**		

Power supply options (remote only)

ECO30W-500	**SOLO50W-500**	**SOLO100W-500**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

index
technical information

small projectors range index

click images to open product pages

Eyelet

Eyelet_R

G4

Eyelet_Q

G4

eyelet

Eyelet is perfect for enhancing display in shelves, niches and shop windows. Installation is simple and easy due to the practical orientable bracket, while very small in size: Eyelet can be directed at will and offers discrete lighting.

Materials
Aluminum body

Eyelet_R | Movable spotlight | powerLED | Driver remote | Tiltable | 2W 630mA



Efficiency - CRI 80

White	**E96984**	2700 K	219 lm	**M**	Spot	**15**
Black	**E96985**	3000 K	233 lm	**W**	Medium Flood	**30**
Grey	**E96986**	3500 K	233 lm	**T**	Flood	**60**
		4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-16 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Eyelet_Q | Movable spotlight | powerLED | Driver remote | Tiltable | 2W 630mA



Efficiency - CRI 80

White	**E97336**	2700 K	219 lm	**M**	Spot	**15**
Black	**E97337**	3000 K	233 lm	**W**	Medium Flood	**30**
Grey	**E97338**	3500 K	233 lm	**T**	Flood	**60**
		4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-16 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

index
technical information

ceiling lamps range index

click images to open product pages

Orma_C

Orma_C

H11

Orma_CJ

H11





orma_C

Aquastop®

Orma_C is designed for small outdoor spaces: just a few centimetres deep, this high-tech downlight combines a minimal footprint with advanced lighting performance, a wide range of models and accessories to limit emissions.

Materials
Anodized aluminum body, or AISI 316 stainless steel

orma_c range

	4W	8W / 9W	12W
_C	Ø 2.5in	Ø 3.8 in	Ø 5.4 in
_CJ	Ø 2.5 in	Ø 3.8 in	Ø 5.4 in
Optic control Options	HC DL	HC DL	HC DL
Finish	Stainless Steel/Black	Stainless Steel/Black	Stainless Steel/Black
CRI 80	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K
Optics	15° 30° 60° Asymmetric	15° 30° 60°	15° 30° 60°
Driver	Remote	Remote	Remote
Current	C.C.	C.C. 8 W C.V. 9 W	C.C.
	2.2 in	3.4 in	5 in

Small overall dimensions

A small-footprint downlight, from 1.8 to barely 2 inch, with a small flange and helical optics designed to fit inside the body. This smart solution makes the product easier to install.

Visual comfort

Depending on how the light is positioned, its beam can be optimised using the appropriate accessory. The honeycomb filter screens secondary light and reduces direct glare, while maintaining the same high and diffuse quality.
If the light is installed in a grazing position and you wish to light only part of the wall, you can use the darklight filter to section part of the beam and prevent direct glare even close to the source.

Orma

Orma
+ honeycomb

Orma
+ darklight

The range

A wide range of lighting options, including four optics: spot, medium flood, flood and elliptical. There are also three sizes.
The Orma_C downlight range includes CJ tiltable versions, which can be adjusted with a screwdriver on the body of the luminaire.



Orma_C | Downlight | arrayLED | Wet location | Driver remote | 4W 350mA





3.4

C.C. - 350mA

Steel Alu **E81223**	2700 K	490 lm	**M**	Spot	**15**
	3000 K	490 lm	**W**	Medium Flood	**30**
	4000 K	529 lm	**N**	Flood	**60**
				Asymmetric	**25**
HC Steel Alu **E81224**	2700 K	490 lm	**M**	Spot	**15**
	3000 K	490 lm	**W**	Medium Flood	**30**
	4000 K	529 lm	**N**	Flood	**60**
DL Steel Alu **E81225**	2700 K	490 lm	**M**	Spot	**15**
	3000 K	490 lm	**W**	Medium Flood	**30**
	4000 K	529 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdriver 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Orma_CJ | Downlight | arrayLED | Wet location | Driver remote | Adjustable | 4W 350mA



3.4

C.C. - 350mA

Steel Alu **E81241**	2700 K	490 lm	**M**	Spot	**15**
	3000 K	490 lm	**W**	Medium Flood	**30**
	4000 K	529 lm	**N**	Flood	**60**



Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdriver 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

index
technical information

pixartprinting

Orma_C | Downlight | arrayLED | Wet location | Driver remote | 8W





C.V. version with converter integrated in the lamp body

3.4

C.C. - 220mA

	Steel Alu **E81229**	2700 K	1088 lm	**M**	Spot	**15**
		3000 K	1088 lm	**W**	Medium Flood	**30**
		4000 K	1173 lm	**N**	Flood	**60**
HC	Steel Alu **E81230**	2700 K	1088 lm	**M**	Spot	**15**
		3000 K	1088 lm	**W**	Medium Flood	**30**
		4000 K	1173 lm	**N**	Flood	**60**
DL	Steel Alu **E81231**	2700 K	1088 lm	**M**	Spot	**15**
		3000 K	1088 lm	**W**	Medium Flood	**30**
		4000 K	1173 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-220
0-10V EldoLED ECOdriver 30W for 1 fixture

SOLO50W-220
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-220
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

C.V. - 24V (9W)

	Steel Alu **E81232**	2700 K	1209 lm	**M**	Spot	**15**
		3000 K	1209 lm	**W**	Medium Flood	**30**
		4000 K	1303 lm	**N**	Flood	**60**
HC	Steel Alu **E81233**	2700 K	1209 lm	**M**	Spot	**15**
		3000 K	1209 lm	**W**	Medium Flood	**30**
		4000 K	1303 lm	**N**	Flood	**60**
DL	Steel Alu **E81234**	2700 K	1209 lm	**M**	Spot	**15**
		3000 K	1209 lm	**W**	Medium Flood	**30**
		4000 K	1303 lm	**N**	Flood	**60**

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX
Osram, Non-dim 24V DC, 120-277VAC, Wet location

Orma_CJ | Downlight | arrayLED | Wet location | Driver remote | Adjustable | 8W





C.V. version with converter integrated in the lamp body



3.4

C.C. - 220mA

	Steel Alu **E81243**	2700 K	1088 lm	**M**	Spot	**15**
		3000 K	1088 lm	**W**	Medium Flood	**30**
		4000 K	1173 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-220
0-10V EldoLED ECOdriver 30W for 1 fixture

SOLO50W-220
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-220
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

C.V. - 24V (9W)

	Steel Alu **E81244**	2700 K	1209 lm	**M**	Spot	**15**
		3000 K	1209 lm	**W**	Medium Flood	**30**
		4000 K	1303 lm	**N**	Flood	**60**

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX
Osram, Non-dim 24V DC, 120-277VAC, Wet location

index
technical information

Orma_C | arrayLED | Wet location | Driver remote | 12W





C.V. version with converter integrated in the lamp body

C.C. - 350mA

	Steel Alu **E81235**	2700 K	1724 lm	**M**	Spot	**15**
		3000 K	1724 lm	**W**	Medium Flood	**30**
		4000 K	1854 lm	**N**	Flood	**60**
HC	Steel Alu **E81236**	2700 K	1724 lm	**M**	Spot	**15**
		3000 K	1724 lm	**W**	Medium Flood	**30**
		4000 K	1854 lm	**N**	Flood	**60**
DL	Steel Alu **E81237**	2700 K	1724 lm	**M**	Spot	**15**
		3000 K	1724 lm	**W**	Medium Flood	**30**
		4000 K	1854 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdriver 30W for 1 fixture

SOLO50W-350

0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Orma_CJ | arrayLED | Wet location | Driver remote | Adjustable | 12W



C.V. version with converter integrated in the lamp body



C.C. - 350mA

Steel Alu **E81245**	2700 K	1724 lm	**M**	Spot	**15**
	3000 K	1724 lm	**W**	Medium Flood	**30**
	4000 K	1854 lm	**N**	Flood	**60**

Power supply options (remote only)

index
technical information

wall path-markers range index

click images to open product pages

Envelope

Envelope

J9

Envelope_W

J9

Envelope W-recessed

J10

Sand

Sand_R

J12

Sand_Q

J12

Quara65

Quara65_R

J15

Quara65_F

J15

Quara65_Q

J16

Quara65_QI

J16

Cut

Cut_R

J18

Cut_Q

J18





envelope_w

Named for its shape, the Envelope path marker's elegant lines and finish make it particularly suitable for foot traffic areas, and provide an attractive addition to walls.

Materials
Aluminum body



envelope_W range

	Envelope_1	Envelope_W	Envelope_W Recessed
1 W	1.6 x 1.6 in	4.7 x 3.5 in	
7 W	-	-	6.7 x 6.6 in
11 W / 17 W	-	-	10.6 x 4.9 in
Finish	☐ ■ ■ ■	☐ ■ ■ ■	☐ ■ ■ ■
topLED	2700K 3000K 4000K	3000K 4000K	3000K 4000K
Optics	Asymmetric	Asymmetric	Asymmetric
Driver	Remote 0-10V or Non-dim	Tgo qvg"2/32X"qt"Pqp/f lo	Tgo qvg"2/32X"qt"Pqp/f lo

Simple, elegant and minimalist

Envelope consists of a single compact element, with the screws hidden from view. The bayonet fitting makes it quick and easy to install, and the casing can be concealed for even greater aesthetic impact. Can also be fitted using a bracket.

DESIGN AWARD 2019

Finishes

Choice of four:

- white RAL9003
- classic grey RAL9006
- anthracite grey RAL7021
- dark brown

Recessed optic, asymmetric design

The recessed source is hidden from view, so the unit offers full cutoff: all you see is the clean, attractive beam. The slightly asymmetric design directs it towards the path.





25 lux | 100 lux | 250 lux | 500 lux | Floor plan

Envelope_1 | Path-marker | powerLED | Wet location | Driver remote | 1W 350mA



Efficiency - CRI 80

White	**E96976**	2700 K	136 lm	**M**	Asymmetric	**07**
Grey	**E96978**	3000 K	145 lm	**W**		
BK Grey	**E80605**	3500 K	145 lm	**T**		
DarkBrown	**E96979**	4000 K	155 lm	**N**		
Black	**E96977**					
Brass	**E83613**					

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

E84336
Masonry outer casing

E84915
Poured-concrete outer casing

Envelope_W Surface Mounted | Path-marker | 24 V | topLED | Wet location | Driver remote | 1W



CRI 80

White	**E97170**	3000 K	54 lm	**W**	Asymmetric	**07**
Grey	**E97172**	4000 K	60 lm	**N**		
BK Grey	**E81341**					
DarkBrown	**E81342**					

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Mounts to a 2"x4" j-box (by others)

index
technical information

Envelope_W Wall-Recessed | Path-marker | 24 V | topLED | Wet location | Driver remote | 7W



CRI 80

White	**E81343**	3000 K	619 lm	**W**	Asymmetric	**07**
Grey	**E81291**	4000 K	643 lm	**N**		
BK Grey	**E81290**					
DarkBrown	**E81292**					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Recessed casing



E99744
Outer casing for brickwork-mounted installation

Envelope_W Wall-Recessed | Path-marker | 24 V | topLED | Wet location | Driver remote



CRI 80 - 11W

White	**E81344**	3000 K	1032 lm	**W**	Asymmetric	**07**
Grey	**E81294**	4000 K	1073 lm	**N**		
BK Grey	**E81293**					
DarkBrown	**E81295**					

CRI 80 - 17W

White	**E81512**	3000 K	1600 lm	**W**	Asymmetric	**07**
Grey	**E81510**	4000 K	1684 lm	**N**		
BK Grey	**E81509**					
DarkBrown	**E81511**					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Solution with outer casing





Recessed casing



E99745
Outer casing for brickwork-mounted installation

index
technical information

sand

Aquastop®

A tough, reliable path marker with patented AquaStop® water and humidity protection, Sand has a durable polycarbonate diffuser for soft ambient illumination.

Materials
Brass body
Opalescent polycarbonate diffuser

Sand_R | Path-marker | powerLED | Wet locatoin | Driver remote | 1W 350mA



1.1

CRI 80

White	**E92260**	3000 K	136 lm	**W**	General **00**
		4000 K	145 lm	**N**	
		5000 K	155 lm	**C**	
		Blue		**B**	
		R - G - Y on request			

Recessed casing

P63

E84915 / E84336

Power supply options (remote only)

ECO30W- 350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Sand_Q | Path-marker | powerLED | Wet locatoin | Driver remote | 1W 350mA



1.1

CRI 80

White	**E92262**	3000 K	136 lm	**W**	General **00**
		4000 K	145 lm	**N**	
		5000 K	155 lm	**C**	
		Blue		**B**	
		R - G - Y on request			

Recessed casing

P63

E84915 / E84336

Power supply options (remote only)

ECO30W- 350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

index

technical information

quara65

Aquastop®

A drop of light in a small casing, with AquaStop® protection. Installed close to the ground, Quara65 projects a circular pool of light into the space below, and can be used to decorate steps and outdoor flooring details.

Materials
Aluminum or AISI 316 stainless steel body

Quara65_R | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA



CRI 80

White	**E85543**	2700 K	219 lm	**M**	Flood	**70**
Grey	**E85542**	3000 K	233 lm	**W**		
DarkBrown	**E87988**	4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W- 630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84338

Quara65_RI | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA



CRI 80

Steel	**E92671**	2700 K	219 lm	**M**	Flood	**70**
		3000 K	233 lm	**W**		
		4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W- 630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84338

Quara65_F | Path-marker | powerLED | Wet location | Driver remote | 1W 350mA



CRI 80

White	**E86460**	2700 K	145 lm	**M**	Flood	**70**
		3000 K	155 lm	**W**		
		4000 K	236 lm	**N**		

Power supply options (remote only)

ECO30W- 350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

P63

E84338



1_ Wall-drilled hole

2_ Wall installation

3_ Finished result

4_ Flush-mounted installation

index
technical information

Quara65_Q | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA



CRI 80

White	**E86563**	2700 K	219 lm	**M**	Flood	**70**
Grey	**E86562**	3000 K	233 lm	**W**		
DarkBrown	**E87989**	4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W- 630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84338

Quara65_QI | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA



CRI 80

Steel	**E92672**	2700 K	219 lm	**M**	Flood	**70**
		3000 K	233 lm	**W**		
		4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W- 630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84338

Quara65_QI | Path-marker | powerLED | Wet location | Driver remote | 4W 630mA



CRI 80

White	**E92238**	2700 K	438 lm	**M**	Flood	**70**
Grey	**E92239**	3000 K	466 lm	**W**		
DarkBrown	**E92240**	4000 K	498 lm	**N**		

Power supply options (remote only)

ECO30W- 630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84338

index
technical information

cut

Aquastop®

This small recessed narrow spot provides an elegant slit of light and creates a delicately attractive effect. It features AquaStop® technology, offering superior moisture protection for power cables.

Materials
Aluminum body

Cut_R | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA



2.1

CRI 80

White	**E92513**	2700 K	219 lm	**M**	Narrow Spot	**05**
Grey	**E92514**	3000 K	233 lm	**W**		
		4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W- 630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84338

Cut_Q | Path-marker | powerLED | Wet location | Driver remote | 2W 630mA



2.1

CRI 80

White	**E92558**	2700 K	219 lm	**M**	Narrow Spot	**05**
Grey	**E92559**	3000 K	233 lm	**W**		
		4000 K	249 lm	**N**		

Power supply options (remote only)

ECO30W- 630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84338

Almar Hotel | Jesolo, Italy



index
technical information

uplights and in-ground lamps range index

click images to open product pages

Beret

Beret_R

K13

Beret_X

K13

Beret_2R

K13

Beret_Q

K14

Beret_2Q

K14

Orma

Orma Trimless Flush Fixed

K21

Orma Trimless Flush Adjustable

K23

Orma Trimless Flush Frosted

K25

Orma Trim Semi-Flush Trim Concentric

K27

Orma Trimless Flush Concentric

K29

Orma Flush Trim Fixed

K31

Orma Flush Trim Adjustable

K33

Orma Flush Trim Frosted

K35

Orma Semi-Flush Trim Fixed

K37

Orma Semi-Flush Trim Adjustable

K39

Orma Semi-Flush Trim Frosted

K41

Orma Flush Trim Wall Washer

K46

Orma Semi-Flush Trim Wall Washer

K47

Orma Flush Trim Blade

K50

Orma Semi-Flush Trim Blade

K50

Suelo

Suelo_R

K55

SueloPRO_R

K55

Suelo_RJ

K58

SueloPRO_RX

K64

Suelo_RX

K68

Suelo_RXJ

K69

Suelo_RX Double

K70

Suelo Telescopic

K71



Uplights and in-ground lamps

K4

KULTURZ
OGÓLNOPOLSKI
KONKURS

I SZTUCE

Engineering innovation

Our new families of recessed uplights use high-quality materials such as aluminum for the body, AISI 316 stainless steel for the flange (providing added durability in high-salinity environments), and tempered glass for the optical compartment. These, combined with miniaturized components, have played a key role in the engineering design process, and made the Linea Light Group uplight range perfect for every need.

Drive-over capability

Ultra-hardwearing materials and the specific positioning of the casing mean that each range will support a weight of up to five tons.

Safety systems

We have developed specific safety systems to protect the uplights against corrosion and make them very durable. They also incorporate overvoltage and electrostatic discharge protection, and systems to protect the integrity of the circuits from moisture and internal condensation (AquaStop®) formation.

IP68

A combination of technology know-how, carefully chosen materials and advanced safety systems offer IP68 protection against dust and solid particles, spray, and short-term immersion in water.

Lasting quality

Linea Light Group products with topLED sources have a lifespan of over 72.000 hours! And that doesn't mean the LEDs go out after that time, but only that they reached 70% of the initial luminous flux with a 90% reliability of compliance. Even more impressively, array LED and powerLED modules have a tested and guaranteed life of over 223.000 hours, and a zero failure rate.

LED i-LèD B10
90% reliability
of the L parameter



Common LEDs on the market B50
50% reliability
of the L parameter

MacAdam step <2

To ensure that colors remain uniform over time and between different products used for the same project, we choose the best LED manufacturers to maintain consistency.

Olur standard of quality is a MacAdam step of less than 2. meaning that differences between LEDs are not visible to the human eye.



i-LèD- MacAdam < 2



Chromatic inhomogeneity - competitors

color range

LEDs give you access to a wide range of color temperatures, from warm white (2.700K) to daylight tones (5.000K), for total design versatility. As well as white light, the RGB range offers static or dynamic colored effects, and the introduction of RGBW, in which white is separate from red, green and blue in the diode, lets you obtain the right mix for your project alongside a very pure white.

2700° K 3000° K 4000° K RGBW

uplights and in-ground comfort

Comfort

Standard and pro optics

Linea Light Group recessed lights have an optionally deeper-positioned source than the standard version. The increased screening angle offers greater visual comfort.





Honeycomb

The hexagonal microcells making up the mesh of the Honeycomb filter help to screen the light beam, reducing glare while leaving the light quality unaltered.



With Honeycomb



Without Honeycomb



Darklight

The darklight filter attenuates the light so that it shines only on a specific area of the surface. This accessory sections the beam so that only a part of it shines on the wall, and prevents glare even close to the source.



With Darklight



Without Darklight

uplights and in-ground optic range

Narrow optics

Narrow Spot: 8°

Spot: 10°

Spot: 15°

Medium optics

Flood: 30°

Medium Flood: 45°

Medium Flood: 60°

Diffused optics

Wide Flood: 120°



General: 180°

Ground-mounting washing optics

Asymmetric Wall Washer: 27°

Elliptic: 25°

beret

Aquastop®

A compact, rugged and reliable walk-on uplight featuring AquaStop® technology, the Beret is perfect for columns and external architectural details.

Materials
Brass or aluminum body
Brass or steel flange

Beret_R | Walk-over spotlight | powerLED | Wet location | Driver remote | Walk over | 1W 350mA

White	**E92065**	2700K	136 lm	**M**	Spot	**15**
Grey	**E92061**	3000K	145 lm	**W**	Medium Flood	**30**
Chrome	**E92066**	4000K	155 lm	**N**	Flood	**60**
Nickel	**E92067**				General	**00**
Steel	**E92068**					
Brass	**E81469**					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

P63

E84915 / E84336

Beret_X Anti-glaring silk-screen | Walk-over spotlight | powerLED | Wet location | Driver remote | Walk over | 1W 350mA



White	**E97800**	2700K	136 lm	**M**	Spot	**15**
Grey	**E97801**	3000K	145 lm	**W**	Medium Flood	**30**
Chrome	**E97797**	4000K	155 lm	**N**	Flood	**60**
Nickel	**E97798**					
Steel	**E97799**					
Brass	**E81471**					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

P63

84915 / E84336

Beret_2R | Walk-over spotlight | powerLED | Wet location | Driver remote | Walk over | 2W 630mA



Chrome	**E93126**	2700K	219 lm	**M**	Narrow Spot	**08**
Nickel	**E93127**	3000K	233 lm	**W**	Spot	**15**
Steel	**E93128**	4000K	249 lm	**N**	Medium Flood	**30**
Brass	**E81470**				Flood	**60**
					Wide Flood	**12**
					General	**00**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84918

index
technical information

Beret_Q | Walk-over spotlight | powerLED | Wet location | Driver remote | Walk over | 1W 350mA



White	**E92088**	2700K	136 lm	**M**	Spot	**15**
Grey	**E92092**	3000K	145 lm	**W**	Medium Flood	**30**
Chrome	**E92069**	4000K	155 lm	**N**	Flood	**60**
Nickel	**E92076**				General	**00**
Steel	**E92077**					

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

Recessed casing

P63

E84915 / E84336

Beret_2Q | Walk-over spotlight | powerLED | Wet location | Driver remote | Walk over | 2W 630mA



Chrome	**E93132**	2700K	219 lm	**M**	Narrow Spot	**08**
Nickel	**E93133**	3000K	233 lm	**W**	Spot	**15**
Steel	**E93134**	4000K	249 lm	**N**	Medium Flood	**30**
					Flood	**60**
					Wide Flood	**12**
					General	**00**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84918

Beret_2Q | Walk-over spotlight | powerLED | Wet location | Driver remote | Walk over | 2W 630mA

Chrome	**E93138**	2700K	219 lm	**M**	Narrow Spot	**08**
Nickel	**E93139**	3000K	233 lm	**W**	Spot	**15**
Steel	**E93140**	4000K	249 lm	**N**	Medium Flood	**30**
					Flood	**60**
					Wide Flood	**12**
					General	**00**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casing

P63

E84918

index
technical information

linea light i-LED

orma

Materials
Aluminium body
Extra-clear tempered glass diffuser

orma range

	OR-TL-F	OR-TL-A	OR-TL-FR	OR-TL-CO	OR-FT-F	OR-FT-A	OR-FT-WW
							
	Orma Trimless Flush Fixed	**Orma Trimless Flush Adjustable**	**Orma Trimless Flush Frosted**	**Orma Trimless Flush Concentric**	**Orma Flush Trim Fixed**	**Orma Flush Trim Adjustable**	**Orma Flush Trim Wall Washer**
Ø0.9”	1W CC 1.5W CV	-	1W CC 1.5W CV	-	-	-	-
Ø1.7”	-	-	-	1.5W CV	-	-	-
Ø2.1 - Ø2.2”	4W CC 5W CV	4W CC 5W CV	1W CC 1.5W CV	1W CC 1.5W CV	4W CC 5W CV	4W CC 5W CV	4W CC 5W CV
Ø2.5”	-	-	-	-	-	-	-
Ø3.3” - Ø3.4”	8W CC 9W CV	8W CC 9W CV	2W CC 2.5W CV	2W CC 2.5W CV	8W CC - 9W CV 8W RGBW	8W CC 9W CV	8W CC 9W CV
Ø3.8”	-	-	-	-	-	-	-
Ø4.9” - Ø5”	12W CC	12W CC	4W CC 5W CV	4W CC 5W CV	12W CC	12W CC	12W CC
Ø5.4”	-	-	-	-	-	-	-
Accessories	HC DL	HC	-	-	HC DL	HC	-
Finish	Glass Alu	Glass Alu	Glass Alu	Black White Grey	Steel Alu	Steel Alu	Steel Alu
CRI 80	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K RGBW	2700K 3000K 4000K	2700K 3000K 4000K
Optic	Spot Flood Wide Flood	Spot Flood Wide Flood	General	General	Spot Flood Wide Flood Elliptical	Spot Flood Wide Flood	Asymmetric

	OR-SFST/BT-BL	OR-FT-FR	OR-SFST/BT-F	OR-SFST/BT-A	OR-SFST/BT-WW	OR-FT-BL	OR-SFST/BT-FR
	Orma Semi-Flush Trim Blade	**Orma Flush Trim Frosted**	**Orma Semi-Flush Trim Fixed**	**Orma Semi-Flush Trim Adjustable**	**Orma Semi-Flush Trim Wall Washer**	**Orma Flush Trim Blade**	**Orma Semi-Flush Trim Frosted**
Ø0.9”	-	-	-	-	-	-	-
Ø1.7”	-	-	-	-	-	-	-
Ø2.1” - Ø2.2”	-	1W CC 1.5W CV	-	-	-	-	-
Ø2.5”	-	-	4W CC 5W CV	4W CC 5W CV	4W CC 5W CV	-	1W CC 1.5W CV
Ø3.3” - Ø3.4”	-	2W CC 2.5W CV	-	-	-	8W CC 9W CV	-
Ø3.8”	8W CC 9W CV	-	8W CC - 9W CV 8W RGBW	8W CC 9W CV	8W CC 9W CV	-	2W CC 2.5W CV
Ø4.9” - Ø5”	-	4W CC 4.5W CV	-	-	-	-	-
Ø5.4”	-	-	12W CC	12W CC	12W CC	-	4W CC 5W CV
Accessories	-	-	HC DL	HC	-	-	-
Finish	Steel Alu Brass Alu	Steel Alu	Steel Alu Brass Alu	Steel Alu Brass Alu	Steel Alu Brass Alu	Steel Alu	Steel Alu Brass Alu
CRI 80	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K RGBW	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K
Optic	Extra Wide Flood	General	Spot Flood Wide Flood Elliptical	Spot Flood Wide Flood	Asymmetric	Extra Wide Flood	General

Broad Range

Orma is a complete recess-mounted family with compact sizes, and sturdy, reliable materials with high grades of protection: temporary IK10 and IP68[1], ideal for tight installation spaces.
In addition to the embossed steel flange, the range is enriched by the new Brass finish. The recess-mounted steel flange is completed by the brand new version with an all-glass front flush with the floor and a path-marker with concentric optics.
The adjustable version can be easily and quickly aimed through the screw system on the side of the fixture body, without have to open and remove the top trim/glass. This breakthrough concept entirely remove the risk of water infiltration during the on site aiming process.
Orma was conceived with a unique application versatility which provides the designer with a vast range of possible beams, finish and optics combinations. Flush, all-glass or in metal, Orma can adapt to any setting, even the most unusual one, thanks to the possibility of choosing from no less than eight diameters and square-shaped flange. On a technical lighting level, new optics packages are introduced: Spot, Flood, Wide Flood, Extra Wide Flood, General, Elliptical, asymmetrical swing with Wall Washer optics.

1 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
2 Fixtures have an overall depth of 3" including casing. 1" variants are deeper than 3".

Blade Optics

The Blade optics let you light windows, arches and architraves, emphasising the architecture and its details. The entirely recess-mounted structure lets the window or door open and close without interference.
The light beam is very narrow laterally and then opens up to almost 180° at the front, enhancing the inner face of the openings without glare or light pollution.







Concentric Optics

An exclusive design, recess-mounted path marker, flush with the pavement, it is capable of creating beautiful effects and giving the paths correct directionality with a sturdy structure capable of withstanding traffic weighing up to 4400 lb. The family includes four diameters: 1.7 in, 2.2 in, 3.4 in, 5 in and 5 power versions: 1 W, 1.5 W, 2 W, 2.5 W, 4 W, 5 W. A diverse and vast range available to professionals and their creativity.

Wall Washer Optics

Optics conceived for wall and floor recessed installation, they allow the creation of perfectly marked and visible luminous paths. The particular Washer optics allow the luminous cone to be sectioned in favour of high visual comfort and to be easily directed so that the positioning is not restricted in the installation phase.



Thanks to the tilting system built into the optics compartment, Orma Wall Washer is able to adapt to different installation heights, defining the diffusion of the light up the 9.8 feet away from the source.



Orma Trimless Flush | Fixed | 0.9” Ø (CC)

4400 lb



C.C. 1W DC - 350mA		Cct	lm S - D	Optic	
Glass Alu **E82697**		**M** 2700	136 - 71	**20** Spot	-
		W 3000	145 - 76	**35** Flood	-
		N 4000	155 - 81		

Power supply options (remote only)

E83036
Concrete casing
PVC

E99925
Tile casing
PVC

Orma Trimless Flush | Fixed | 0.9” Ø (CV)

4400 lb



C.V. 1.5W DC - 24 VDC		Cct	lm S - D	Optic	
Glass Alu **E82698**		**M** 2700	136 - 71	**20** Spot	-
		W 3000	145 - 76	**35** Flood	-
		N 4000	155 - 81		

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83037
Concrete casing
PVC

E99925
Tile casing
PVC

Orma Trimless Flush | Fixed | 2.2” Ø

4400 lb



C.C. 4W DC - 350mA		Cct	lm S - D	Optic	
Glass Alu **E82657**		**M** 2700	490 - 288	**15** Spot	-
Glass Alu **E82658**	HC	**W** 3000	490 - 288	**25** Elliptical*	-
Glass Alu **E82659**	DL	**N** 4000	529 - 311	**30** Flood	-
				60 W.Flood	-

*Elliptical available with E82657 only.

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtu es

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-6 fixtu es

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-12 fixtu es

C.V. 5W DC - 24 VDC		Cct	lm S - D	Optic	
Glass Alu **E82660**		**M** 2700	490 - 288	**15** Spot	-
Glass Alu **E82661**	HC	**W** 3000	490 - 288	**25** Elliptical*	-
Glass Alu **E82662**	DL	**N** 4000	529 - 311	**30** Flood	-
				60 W.Flood	-

*Elliptical available with E82660 only.

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83038
Concrete casing
PVC

E99922
Tile casing
PVC

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Trimless Flush | Fixed | 3.4" Ø



C.C. 8W DC - 220mA			Cct	lm S - D	Optic	
Glass Alu	**E82669**		**M** 2700	1080 - 689	**15** Spot	-
Glass Alu	**E82670**	HC	**W** 3000	1126 - 718	**30** Flood	-
Glass Alu	**E82671**	DL	**N** 4000	1188 - 758	**60** W.Flood	-

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixtu e

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtu es

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtu es

C.V. 9W DC - 24 VDC			Cct	lm S - D	Optic	
Glass Alu	**E82672**		**M** 2700	1193 - 689	**15** Spot	-
Glass Alu	**E82673**	HC	**W** 3000	1244 - 718	**30** Flood	-
Glass Alu	**E82674**	DL	**N** 4000	1313 - 758	**60** W.Flood	-

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83039
Concrete casing
PVC

E99923
Tile casing
PVC



Orma Trimless Flush | Fixed | 5.0" Ø



C.C. 12W - 350mA			Cct	lm S - D	Optic	
Glass Alu	**E82683**		**M** 2700	1724 - 1365	**15** Spot	-
Glass Alu	**E82684**	HC	**W** 3000	1724 - 1365	**30** Flood	-
Glass Alu	**E82685**	DL	**N** 4000	1854 - 1466	**60** W.Flood	-

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixtu e

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtu es

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtu es

E83040
Concrete casing
PVC



E99924
Tile casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Trimless Flush | Adjustable | 2.2" Ø



C.C. 4W DC - 350mA		Cct	lm S - D	Optic	
Glass Alu	**E82663**	**M** 2700	490 - 288	**15** Spot	-
		W 3000	490 - 288	**30** Flood	-
		N 4000	529 - 311	**60** W.Flood	-

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtu es

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtu es

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtu es

C.V. 5W DC - 24 VDC		Cct	lm S - D	Optic	
Glass Alu	**E82664**	**M** 2700	490 - 288	**15** Spot	-
		W 3000	490 - 288	**30** Flood	-
		N 4000	529 - 311	**60** W.Flood	-

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83038
Concrete casing
PVC



E99922
Tile casing
PVC

Orma Trimless Flush | Adjustable | 3.4" Ø



C.C. 8W DC - 220mA		Cct	lm S - D	Optic	
Glass Alu	**E82675**	**M** 2700	1080 - 693	**15** Spot	-
Glass Alu	**E82676** HC	**W** 3000	1126 - 722	**30** Flood	-
		N 4000	1188 - 763	**60** W.Flood	-

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixtu e

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtu es

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtu es

C.V. 9W DC - 24 VDC		Cct	lm S - D	Optic	
Glass Alu	**E82677**	**M** 2700	1193 - 693	**15** Spot	-
Glass Alu	**E82678** HC	**W** 3000	1244 - 722	**30** Flood	-
		N 4000	1313 - 763	**60** W.Flood	-

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83039
Concrete casing
PVC

E99923
Tile casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Trimless Flush | Adjustable | 5.0" Ø



C.C. 12W DC - 350mA		Cct	lm S - D	Optic	
Glass Alu **E82689**		**M** 2700	1724 - 1203	**15** Spot	-
Glass Alu **E82690**	HC	**W** 3000	1724 - 1203	**30** Flood	-
		N 4000	1854 - 1292	**60** W.Flood	-

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixtu e

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtu es

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtu es

E83040
Concrete casing
PVC

E99924
Tile casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Trimless Flush | **Frosted** | 0.9” Ø (CC)

4400 lb



C.C. 1W DC - 350mA	Cct	lm S - D	Optic
Glass Alu **E82699**	**M** 2700	136 - 12	**00** General -
	W 3000	145 - 13	
	N 4000	155 - 14	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtu es

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtu es

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtu es

E83036
Concrete casing
PVC

E99925
Tile casing
PVC

Orma Trimless Flush | **Frosted** | 0.9” Ø (CV)

4400 lb



C.V. 1.5W DC - 24 VDC	Cct	lm S - D	Optic
Glass Alu **E82700**	**M** 2700	136 - 12	**00** General -
	W 3000	145 - 13	
	N 4000	155 - 14	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83037
Concrete casing
PVC

E99925
Tile casing
PVC

Orma Trimless Flush | **Frosted** | 2.2” Ø

4400 lb



C.C. 1W DC - 350mA	Cct	lm S - D	Optic
Glass Alu **E82667**	**M** 2700	136 - 8	**00** General -
	W 3000	145 - 8	
	N 4000	155 - 9	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtu es

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtu es

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtu es

C.V. 1.5W DC - 24 VDC	Cct	lm S - D	Optic
Glass Alu **E82668**	**M** 2700	136 - 8	**00** General -
	W 3000	145 - 8	
	N 4000	155 - 9	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83038
Concrete casing
PVC

E99922
Tile casing
PVC

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Trimless Flush | Frosted | 3.4" Ø



C.C. 2W DC- 630mA	Cct	lm S - D	Optic
Glass Alu **E82681**	**M** 2700	249 - 15	**00** General -
	W 3000	266 - 15	
	N 4000	284 - 16	

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtu es

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-16 fixtu es

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtu es

C.V. 2.5W DC - 24 VDC	Cct	lm S - D	Optic
Glass Alu **E82682**	**M** 2700	249 - 15	**00** General -
	W 3000	266 - 15	
	N 4000	284 - 16	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83039
Concrete casing
PVC

E99923
Tile casing
PVC



Orma Trimless Flush | Frosted | 5.0" Ø



C.C. 4W DC - 350mA	Cct	lm S - D	Optic
Glass Alu **E82695**	**M** 2700	490 - 50	**00** General -
	W 3000	490 - 50	
	N 4000	529 - 54	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtu es

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-6 fixtu es

SOLO100W-220
0-10V EldoLED SOLOdrive 100W for 1-12 fixtu es

C.V. 5W DC - 24 VDC	Cct	lm S - D	Optic
Glass Alu **E82696**	**M** 2700	490 - 50	**00** General -
	W 3000	490 - 50	
	N 4000	529 - 54	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83040
Concrete casing
PVC

E99924
Tile casing
PVC

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Trim Semi-Flush Trim | Concentric | 1.6” Ø

C.V. IK09 IP67 4400 lb



C.V. 1.5W DC - 24VDC		Cct	lm S - D	Optic
White	**E95474**	**M** 2700	136 - 54	**00** General
Black	**E95475**	**W** 3000	145 - 60	
Grey	**E95476**	**N** 4000	155 - 63	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E98291
Concrete casing



E98292
Tile casing
PVC



Orma Trim Semi-Flush Trim | Concentric | 2.2” Ø

IK10 IP68 4400 lb



C.C. 1W DC - 350mA		Cct	lm S - D	Optic
Black	**E82665**	**M** 2700	136 - 6	**00** General -
		W 3000	145 - 6	
		N 4000	155 - 7	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1-10 fixtu es

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-20 fixtu es

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-40 fixtu es

C.V. 1.5W DC - 24VDC		Cct	lm S - D	Optic
Black	**E82666**	**M** 2700	136 - 6	**00** General -
		W 3000	145 - 6	
		N 4000	155 - 7	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83038
Concrete casing
PVC

E99922
Tile casing
PVC

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Trimless Flush | Concentric | 3.4" Ø



C.C. 2W DC - 630mA	Cct	lm S - D	Optic
Black **E82679**	**M** 2700	249 - 13	**00** General -
	W 3000	266 - 13	
	N 4000	284 - 14	

Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtu es

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtu es

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtu es

C.V. 2.5W DC - 24 VDC	Cct	lm S - D	Optic
Black **E82680**	**M** 2700	249 - 13	**00** General -
	W 3000	266 - 13	
	N 4000	284 - 14	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83039
Concrete casing
PVC

E99923
Tile casing
PVC



Orma Trimless Flush | Concentric | 5.0" Ø



C.C. 4W DC - 350mA	Cct	lm S - D	Optic
Black **E82693**	**M** 2700	490 - 34	**00** General -
	W 3000	490 - 34	
	N 4000	529 - 37	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtu es

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtu es

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtu es

C.V. 5W DC - 24 VDC	Cct	lm S - D	Optic
Black **E82694**	**M** 2700	490 - 34	**00** General -
	W 3000	490 - 34	
	N 4000	529 - 37	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E83040
Concrete casing
PVC

E99924
Tile casing
PVC

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Flush Trim | Fixed | 2.1” Ø



C.C. 4W DC - 350mA	Cct	lm S - D	Optic	
Steel Alu **E81181**	**M** 2700	490 - 272	**15** Spot	(22°)
	W 3000	490 - 272	**30** Flood	(29°)
	N 4000	529 - 294	**60** W.Flood	(48°)
			25 Elliptical	-

HC	Cct	lm S - D	Optic	
Steel Alu **E81182**	**M** 2700	490 - 187	**15** Spot	(20°)
	W 3000	490 - 187	**30** Flood	(25°)
	N 4000	529 - 202	**60** Flood	(37°)

DL	Cct	lm S - D	Optic	
Steel Alu **E81183**	**M** 2700	490 - 194	**15** Spot	(22°)
	W 3000	490 - 194	**30** Flood	(30°)
	N 4000	529 - 209	**60** W.Flood	(55°)

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtu es

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtu es

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtu es

C.V. 5W DC - 24 VDC	Cct	lm S - D	Optic	
Steel Alu **E81184**	**M** 2700	490 - 272	**15** Spot	(22°)
	W 3000	490 - 272	**30** Flood	(29°)
	N 4000	529 - 294	**60** W.Flood	(48°)
			25 Elliptical	-

HC	Cct	lm S - D	Optic	
Steel Alu **E81185**	**M** 2700	490 - 187	**15** Spot	(20°)
	W 3000	490 - 187	**30** Flood	(25°)
	N 4000	529 - 202	**60** Flood	(37°)

DL	Cct	lm S - D	Optic	
Steel Alu **E81186**	**M** 2700	490 - 194	**15** Spot	(22°)
	W 3000	490 - 194	**30** Flood	(30°)
	N 4000	529 - 209	**60** W.Flood	(55°)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete casing
PVC

E99560*
Round Vandal Resistant Casing
PVC

E99855*
Square Vandal Resistant casing
PVC



E83251
Tile casing
PVC

RTG **E81181W15 / E81181W30**

Orma Flush Trim | Fixed | 3.3” Ø



C.C. - 8W DC - 220 mA	Cct	lm S - D	Optic	
Steel Alu **E81187**	**M** 2700	1080 - 858	**15** Spot	(15°)
	W 3000	1126 - 894	**30** Flood	(31°)
	N 4000	1188 - 944	**60** W.Flood	(61°)

HC	Cct	lm S - D	Optic	
Steel Alu **E81188**	**M** 2700	1080 - 619	**15** Spot	(15°)
	W 3000	1126 - 646	**30** Flood	(27°)
	N 4000	1188 - 681	**60** W.Flood	(49°)

DL	Cct	lm S - D	Optic	
Steel Alu **E81189**	**M** 2700	1080 - 576	**15** Spot	(16°)
	W 3000	1126 - 600	**30** Flood	(29°)
	N 4000	1188 - 634	**60** W.Flood	(53°)

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixtu e

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtu es

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtu es

C.V. 9W DC - 24 VDC	Cct	lm S - D	Optic	
Steel Alu **E81190**	**M** 2700	1193 - 955	**15** Spot	(15°)
	W 3000	1244 - 997	**30** Flood	(31°)
	N 4000	1313 - 1052	**60** W.Flood	(61°)

HC	Cct	lm S - D	Optic	
Steel Alu **E81191**	**M** 2700	1193 - 687	**15** Spot	(15°)
	W 3000	1244 - 716	**30** Flood	(27°)
	N 4000	1313 - 756	**60** W.Flood	(49°)

DL	Cct	lm S - D	Optic	
Steel Alu **E81192**	**M** 2700	1193 - 639	**15** Spot	(15°)
	W 3000	1244 - 667	**30** Flood	(29°)
	N 4000	1313 - 704	**60** W.Flood	(53°)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

index
technical information

NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Flush Trim | Fixed | 3.3” Ø (RGBW)



RGBW* - 8W DC - 630 mA	Cct	Optic
Steel Alu **E81322**	**Q** RGBW natural white	**06** N.Spot -
, Quad-chip LED	**V** RGBW warm white	**15** Spot -
		45 W.Flood -
		00 General -

Power supply options (remote only)

PWR50W-630
DMX EldoLED
POWERdrive 50W
for 1-5 fixtures

E99651
Concrete casing
PVC

E99563*
Round Vandal Resistant casing
PVC

E99856*
Square Vandal Resistant casing
PVC



E83252
Tile casing
PVC



Feed Cables**

E99216	E89190	E98476	E98477
59 in. DC(+) power cable F 4 pin M12	196 in. DC(+) power cable F 4 pin M12	59 in. DC(-) power cable M 4 pin M12	196 in. DC(-) power cable M 4 pin M12

** One Female DC(+) and one Male DC(-) required per driver

Extension Cables***

E98437	E98149	E89188
39 in. Extension power cable M+F 4 pin M12	196.85 in Extension for power cable M+F 4 pin M12	393.7 in Extension for power cable M+F 4 pin M12

***Required between fixtures powered from the same driver

RTG **E81187W30**

NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Flush Trim | Fixed | 4.9” Ø



C.C. 12W DC - 350mA	Cct	lm S - D	Optic
Steel Alu **E81193**	**M** 2700	1724 - 1379	**15** Spot (14°)
	W 3000	1724 - 1379	**30** Flood (31°)
	N 4000	1854 - 1485	**60** W.Flood (60°)

HC	Cct	lm S - D	Optic
Steel Alu **E81194**	**M** 2700	1724 - 981	**15** Spot (14°)
	W 3000	1724 - 981	**30** Flood (28°)
	N 4000	1854 - 1055	**60** W.Flood (49°)

DL	Cct	lm S - D	Optic
Steel Alu **E81195**	**M** 2700	1724 - 1094	**15** Spot (14°)
	W 3000	1724 - 1094	**30** Flood (30°)
	N 4000	1854 - 1178	**60** W.Flood (52°)

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

E99652
Concrete casing
PVC

E99564*
Round Vandal Resistant Casing
PVC



E99857*
Square Vandal Resistant Casing
PVC



E83253
Tile casing
PVC



Orma Flush Trim | Adjustable | 2.1" Ø



C.C. 4W DC - 350mA	Cct	lm S - D	Optic	
Steel Alu **E81205**	**M** 2700	490 - 272	**15** Spot	(22°)
	W 3000	490 - 272	**30** Flood	(29°)
	N 4000	529 - 294	**60** W.Flood	(48°)

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtures

C.V. 5W DC - 24 VDC	Cct	lm S - D	Optic	
Steel Alu **E81206**	**M** 2700	490 - 272	**15** Spot	(22°)
	W 3000	490 - 272	**30** Flood	(29°)
	N 4000	529 - 294	**60** W.Flood	(48°)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete casing
PVC

E99560*
Round Vandal Resistant Casing
PVC

E99855*
Square Vandal Resistant Casing
PVC



E83251
Tile Casing
PVC

Orma Flush Trim | Adjustable | 3.3" Ø



C.C. - 8W DC - 220 mA	Cct	lm S - D	Optic	
Steel Alu **E81207**	**M** 2700	1080 - 858	**15** Spot	(15°)
	W 3000	1126 - 894	**30** Flood	(31°)
	N 4000	1188 - 944	**60** W.Flood	(61°)

HC	Cct	lm S - D	Optic	
Steel Alu **E82460**	**M** 2700	1080 - 619	**15** Spot	-
	W 3000	1126 - 646	**30** Flood	-
	N 4000	1188 - 681	**60** W.Flood	-

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixture

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtures

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtures

C.V. 9W DC - 24 VDC	Cct	lm S - D	Optic	
Steel Alu **E81208**	**M** 2700	1193 - 955	**15** Spot	(15°)
	W 3000	1244 - 997	**30** Flood	(31°)
	N 4000	1313 - 1052	**60** W.Flood	(61°)

HC	Cct	lm S - D	Optic	
Steel Alu **E82461**	**M** 2700	1193 - 687	**15** Spot	-
	W 3000	1244 - 716	**30** Flood	-
	N 4000	1313 - 761	**60** W.Flood	-

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Concrete casing
PVC

E99563*
Round Vandal Resistant Casing
PVC

E99856*
Square Vandal Resistant Casing
PVC



E83252
Tile Casing
PVC



*NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush".
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Flush Trim | Adjustable | 4.9" Ø



C.C. - 12W DC - 350 mA	Cct	lm S - D	Optic	
Steel Alu **E81209**	**M** 2700	1724 - 1317	**15** Spot	(22°)
	W 3000	1724 - 1317	**30** Flood	(34°)
	N 4000	1854 - 1417	**60** W.Flood	(61°)

HC	Cct	lm S - D	Optic	
Steel Alu **E82462**	**M** 2700	1724 - 935	**15** Spot	-
	W 3000	1724 - 935	**30** Flood	-
	N 4000	1854 - 1005	**60** W.Flood	-

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

E99652
Concrete casing
PVC

E99564*
Round Vandal Resistant Casing
PVC



E99857*
Square Vandal Resistant Casing
PVC



E83253
Tile Casing
PVC



NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Flush Trim | Frosted | 2.1” Ø



C.C. 1W DC - 350mA	Cct	lm S - D	Optic
Steel Alu **E81217**	**M** 2700	136 - 17	**00** General (117°)
	W 3000	145 - 18	
	N 4000	155 - 19	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtutes

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtutes

C.V. 1.5W DC - 24 VDC	Cct	lm S - D	Optic
Steel Alu **E81218**	**M** 2700	136 - 17	**00** General (117°)
	W 3000	145 - 18	
	N 4000	155 - 19	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete casing
PVC

E99560*
Round Vandal Resistant Casing
PVC

E99855*
Square Vandal Resistant Casing
PVC

E83251
Tile Casing
PVC



Orma Flush Trim | Frosted | 3.3” Ø



C.C. 2W DC - 630 mA	Cct	lm S - D	Optic
Steel Alu **E81219**	**M** 2700	249 - 25	**00** General (118°)
	W 3000	266 - 26	
	N 4000	284 - 28	

Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtutes

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtutes

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtutes

C.V. 2.5W DC - 24 VDC	Cct	lm S - D	Optic
Steel Alu **E81220**	**M** 2700	249 - 25	**00** General (118°)
	W 3000	266 - 26	
	N 4000	284 - 28	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Concrete Casing
PVC

E99563*
Round Vandal Resistant Casing
PVC

E99856*
Square Vandal Resistant Casing
PVC



E83252
Tile Casing
PVC



*NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush".
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Flush Trim | Frosted | 4.9” Ø



C.C. 4W DC - 350mA	Cct	lm S - D	Optic
Steel Alu **E81221**	**M** 2700	490 - 90	**00** General (116°)
	W 3000	490 - 90	
	N 4000	529 - 97	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtutgs

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtutes

C.V. 4.5W DC - 24 VDC	Cct	lm S - D	Optic
Steel Alu **E81222**	**M** 2700	490 - 90	**00** General (116°)
	W 3000	490 - 90	
	N 4000	529 - 97	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99652
Concrete Casing
PVC

E99564*
Round Vandal Resistant Casing
PVC



E99857*
Square Vandal Resistant Casing
PVC



E83253
Tile Casing
PVC



NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15’ depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Semi-Flush Trim | Fixed | 2.5” Ø

4400 lb



C.C. 4W DC - 350mA		Cct	lm S - D	Optic	
Steel Alu	**E80582**	**M** 2700	490 - 272	**15** Spot	(22°)
Brass Alu	**E84289**	**W** 3000	490 - 272	**30** Flood	(29°)
		N 4000	529 - 294	**60** W.Flood	(48°)
				25 Elliptical	-

HC		Cct	lm S - D	Optic	
Steel Alu	**E80583**	**M** 2700	490 - 187	**15** Spot	(20°)
Brass Alu	**E84290**	**W** 3000	490 - 187	**30** Flood	(25°)
		N 4000	529 - 202	**60** Flood	(37°)

DL		Cct	lm S - D	Optic	
Steel Alu	**E80584**	**M** 2700	490 - 194	**15** Spot	(22°)
Brass Alu	**E84291**	**W** 3000	490 - 194	**30** Flood	(30°)
		N 4000	529 - 209	**60** W.Flood	(55°)

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtutes

C.V. 5W DC - 24 VDC		Cct	lm S - D	Optic	
Steel Alu	**E80585**	**M** 2700	490 - 272	**15** Spot	(22°)
Brass Alu	**E84292**	**W** 3000	490 - 272	**30** Flood	(29°)
		N 4000	529 - 294	**60** W.Flood	(48°)
				25 Elliptical	-

HC		Cct	lm S - D	Optic	
Steel Alu	**E80586**	**M** 2700	490 - 187	**15** Spot	(20°)
Brass Alu	**E84293**	**W** 3000	490 - 187	**30** Flood	(25°)
		N 4000	529 - 202	**60** Flood	(37°)

DL		Cct	lm S - D	Optic	
Steel Alu	**E80587**	**M** 2700	490 - 194	**15** Spot	(22°)
Brass Alu	**E84294**	**W** 3000	490 - 194	**30** Flood	(30°)
		N 4000	529 - 209	**60** W.Flood	(55°)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete Casing
PVC

E83251
Tile Casing
PVC

Orma Semi-Flush Trim | Fixed | 3.8” Ø



C.C. - 8W DC - 220 mA		Cct	lm S - D	Optic	
Steel Alu	**E80588**	**M** 2700	1080 - 858	**15** Spot	(15°)
Brass Alu	**E84295**	**W** 3000	1126 - 894	**30** Flood	(31°)
		N 4000	1188 - 944	**60** W.Flood	(61°)

HC		Cct	lm S - D	Optic	
Steel Alu	**E80589**	**M** 2700	1080 - 619	**15** Spot	(15°)
Brass Alu	**E84296**	**W** 3000	1126 - 646	**30** Flood	(27°)
		N 4000	1188 - 681	**60** W.Flood	(49°)

DL		Cct	lm S - D	Optic	
Steel Alu	**E80590**	**M** 2700	1080 - 576	**15** Spot	(16°)
Brass Alu	**E84297**	**W** 3000	1126 - 600	**30** Flood	(29°)
		N 4000	1188 - 634	**60** W.Flood	(53°)

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-220
0-10V EldoLED
SOLOdrive
100W for 1-4
fixtutes

C.V. 9W DC - 24 VDC		Cct	lm S - D	Optic	
Steel Alu	**E81172**	**M** 2700	1193 - 955	**15** Spot	(15°)
Brass Alu	**E84298**	**W** 3000	1244 - 997	**30** Flood	(31°)
		N 4000	1313 - 1052	**60** W.Flood	(61°)

HC		Cct	lm S - D	Optic	
Steel Alu	**E81173**	**M** 2700	1193 - 687	**15** Spot	(15°)
Brass Alu	**E84299**	**W** 3000	1244 - 716	**30** Flood	(27°)
		N 4000	1313 - 756	**60** W.Flood	(49°)

DL		Cct	lm S - D	Optic	
Steel Alu	**E81174**	**M** 2700	1193 - 639	**15** Spot	(16°)
Brass Alu	**E84300**	**W** 3000	1244 - 667	**30** Flood	(29°)
		N 4000	1313 - 704	**60** W.Flood	(53°)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Semi-Flush Trim | Fixed | 3.8” Ø (RGBW)



RGBW* - 8W DC - 630 mA		Cct		Optic	
Steel Alu	**E81321**	**Q**	RGBW natural white	**06** N.Spot	-
Brass Alu	**E84301**	**V**	RGBW warm white	**15** Spot	-
				45 W.Flood	-
				00 General	-

, Quad-chip LED

Power supply options (remote only)

PWR50W-630
DMX EldoLED
POWERdrive 50W
for 1-5 fixtutes

E99651
Concrete casing
PVC

E83252
Tile casing
PVC



RTG **E80588W30 / E81321V45**

Feed Cables**

E99216	E89190	E98476	E98477
59 in. DC(+) power cable F 4 pin M12	196 in. DC(+) power cable F 4 pin M12	59 in. DC(-) power cable M 4 pin M12	196 in. DC(-) power cable M 4 pin M12

** One Female DC(+) and one Male DC(-) required per driver

Extension Cables***

E98437	E98149	E89188
39 in. Extension power cable M+F 4 pin M12	196.85 in Extension for power cable M+F 4 pin M12	393.7 in Extension for power cable M+F 4 pin M12

***Required between fixtures powered from the same driver

Orma Semi-Flush Trim | Fixed | 5.4” Ø



C.C. 12W DC - 350mA		Cct		Im S - D	Optic	
Steel Alu	**E81175**	**M**	2700	1724 - 1379	**15** Spot	(14°)
Brass Alu	**E84302**	**W**	3000	1724 - 1379	**30** Flood	(31°)
		N	4000	1854 - 1485	**60** W.Flood	(60°)

HC		Cct		Im S - D	Optic	
Steel Alu	**E81176**	**M**	2700	1724 - 981	**15** Spot	(14°)
Brass Alu	**E84303**	**W**	3000	1724 - 981	**30** Flood	(28°)
		N	4000	1854 - 1055	**60** W.Flood	(49°)

DL		Cct		Im S - D	Optic	
Steel Alu	**E81177**	**M**	2700	1724 - 1094	**15** Spot	(14°)
Brass Alu	**E84304**	**W**	3000	1724 - 1094	**30** Flood	(30°)
		N	4000	1854 - 1178	**60** W.Flood	(52°)

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

E99652
Concrete casing
PVC

E83253
Tile casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15’ depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Semi-Flush Trim | Adjustable | 2.5” Ø



C.C. 4W DC - 350mA		Cct	lm S - D	Optic	
Steel Alu	**E81199**	**M** 2700	490 - 272	**15** Spot	(22°)
Brass Alu	**E82521**	**W** 3000	490 - 272	**30** Flood	(29°)
		N 4000	529 - 294	**60** W.Flood	(48°)

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtutes

C.V. 5W DC - 24 VDC		Cct	lm S - D	Optic	
Steel Alu	**E81200**	**M** 2700	490 - 272	**15** Spot	(22°)
Brass Alu	**E82522**	**W** 3000	490 - 272	**30** Flood	(29°)
		N 4000	529 - 294	**60** W.Flood	(48°)

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete casing
PVC

E83251
Tile casing
PVC

Orma Semi-Flush Trim | Adjustable | 3.8” Ø



C.C. - 8W DC - 220mA		Cct	lm S - D	Optic	
Steel Alu	**E81201**	**M** 2700	1080 - 858	**15** Spot	(15°)
Brass Alu	**E82523**	**W** 3000	1126 - 894	**30** Flood	(31°)
		N 4000	1188 - 944	**60** W.Flood	(61°)

HC		Cct	lm S - D	Optic	
Steel Alu	**E82456**	**M** 2700	1080 - 619	**15** Spot	-
Brass Alu	**E82934**	**W** 3000	1126 - 646	**30** Flood	-
		N 4000	1188 - 681	**60** W.Flood	-

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

C.V. 9W DC - 24 VDC		Cct	lm S - D	Optic	
Steel Alu	**E81202**	**M** 2700	1193 - 955	**15** Spot	(15°)
Brass Alu	**E82524**	**W** 3000	1244 - 997	**30** Flood	(31°)
		N 4000	1313 - 1052	**60** W.Flood	(61°)

HC		Cct	lm S - D	Optic	
Steel Alu	**E82457**	**M** 2700	1193 - 687	**15** Spot	-
Brass Alu	**E82935**	**W** 3000	1244 - 716	**30** Flood	-
		N 4000	1313 - 756	**60** W.Flood	-

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Concrete casing
PVC

E83252
Tile casing
PVC

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Semi-Flush Trim | Adjustable | 5.4" Ø



C.C. - 12W DC - 350mA		Cct	lm S - D	Optic	
Steel Alu	**E81203**	**M** 2700	1724 - 1317	**15** Spot	(22°)
Brass Alu	**E82525**	**W** 3000	1724 - 1317	**30** Flood	(34°)
		N 4000	1854 - 1417	**60** W.Flood	(61°)

HC		Cct	lm S - D	Optic	
Steel Alu	**E82458**	**M** 2700	1724 - 935	**15** Spot	-
Brass Alu	**E84308**	**W** 3000	1724 - 935	**30** Flood	-
		N 4000	1854 - 1005	**60** W.Flood	-

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

E99652
Concrete casing
PVC



E83253
Tile Casing
PVC

Orma Trim Semi-Flush Adjustable Brass

Orma Trim Semi-Flush Adjustable Steel

index
technical information

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Semi-Flush Trim | Frosted | 2.5" Ø

4400 lb



C.C. 1W DC - 350mA		Cct	lm S - D	Optic
Steel Alu	**E81211**	**M** 2700	136 - 17	**00** General (117°)
Brass Alu	**E84318**	**W** 3000	145 - 18	
		N 4000	155 - 19	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtu es

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtu es

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtu es

C.V. 1.5W DC - 24 VDC		Cct	lm S - D	Optic
Steel Alu	**E81212**	**M** 2700	136 - 17	**00** General (117°)
Brass Alu	**E84319**	**W** 3000	145 - 18	
		N 4000	155 - 19	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete Casing
PVC

E83251
Tile Casing
PVC

Orma Semi-Flush Trim | Frosted | 3.8" Ø



C.C. 2W DC - 630mA		Cct	lm S - D	Optic
Steel Alu	**E81213**	**M** 2700	249 - 25	**00** General (118°)
Brass Alu	**E84320**	**W** 3000	266 - 26	
		N 4000	284 - 28	

Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtu es

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtu es

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtu es

C.V. 2.5W DC - 24 VDC		Cct	lm S - D	Optic
Steel Alu	**E81214**	**M** 2700	249 - 25	**00** General (118°)
Brass Alu	**E84321**	**W** 3000	266 - 26	
		N 4000	284 - 28	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Concrete Casing
PVC

E83252
Tile Casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

index
technical information

Orma Semi-Flush Trim | Frosted | 5.4" Ø



C.C. 4W DC - 350mA	Cct	lm S - D	Optic
Steel Alu **E81215**	**M** 2700	490 - 90	**00** General (116°)
Brass Alu **E84322**	**W** 3000	490 - 90	
	N 4000	529 - 97	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtutes

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtutes

C.V. 5W DC - 24 VDC	Cct	lm S - D	Optic
Steel Alu **E81216**	**M** 2700	490 - 90	**00** General (116°)
Brass Alu **E84323**	**W** 3000	490 - 90	
	N 4000	529 - 97	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99652
Concrete Casing
PVC

E83253
Tile Casing
PVC



Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

INSTALLATION

Installation in a few quick steps **(Recessed casing E99563 + Orma Trim Flush Adjustable E81207W15)**



LOCKING SYSTEM

Technologically advanced outer casings that offer maximum aiming stability when using the adjustable version of the equipment thanks to the special grooves that stabilise the screw and prevent rotation thereof over time.



Maximum aiming stability when using the tilting version (Orma Trim Flush Adjustable)

orma

Materials
Aluminium body
AISI 316L stainless steel flange

Orma Flush Trim | Wall Washer | 2.1" Ø



C.C. 4W DC 350 mA	Cct	lm S - D	Optic
Steel Alu **E83631**	**M** 2700	490 - 129	**07** Asymm. -
	W 3000	490 - 129	
	N 4000	529 - 140	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtutes

C.V. 24 V - 5W DC	Cct	lm S - D	Optic
Steel Alu **E83633**	**M** 2700	490 - 129	**07** Asymm. -
	W 3000	490 - 129	
	N 4000	529 - 140	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete Casing
PVC

E99560*
Round Vandal Resistant Casing
PVC

E99855*
Square Vandal Resistant Casing
PVC



E83251
Tile Casing
PVC



Orma Flush Trim | Wall Washer | 3.3" Ø



C.C. - 8W DC 220 mA	Cct	lm S - D	Optic
Steel Alu **E83635**	**M** 2700	1080 - 300	**07** Asymm. -
	W 3000	1126 - 313	
	N 4000	1188 - 330	

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

C.V. 24 V - 9W DC	Cct	lm S - D	Optic
Steel Alu **E83637**	**M** 2700	1193 - 333	**07** Asymm. -
	W 3000	1244 - 347	
	N 4000	1313 - 366	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Concrete Casing
PVC

E99563*
Round Vandal Resistant Casing
PVC

E99856*
Square Vandal Resistant Casing
PVC



E83252
Tile Casing
PVC



Orma Flush Trim | Wall Washer | 4.9" Ø



C.C. - 12W DC 350 mA	Cct	lm S - D	Optic
Steel Alu **E83639**	**M** 2700	1724 - 598	**07** Asymm. -
	W 3000	1724 - 598	
	N 4000	1854 - 643	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixtutg

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

E99652
Concrete Casing
PVC

E99564
Round Vandal Resistant Casing
PVC



E99857*
Square Vandal Resistant Casing
PVC



E83253
Tile casing
PVC



index
technical information

*NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush".
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Semi-Flush Trim | Wall Washer | 2.5” Ø

4400 lb



C.C. 4W DC 350 mA		Cct	lm S - D	Optic
Steel Alu	**E83630**	**M** 2700	490 - 129	**07** Asymm. -
Brass Alu	**E84310**	**W** 3000	490 - 129	
		N 4000	529 - 140	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-6 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-12 fixtu es

C.V. 24 V - 5W DC		Cct	lm S - D	Optic
Steel Alu	**E83632**	**M** 2700	490 - 129	**07** Asymm. -
Brass Alu	**E84311**	**W** 3000	490 - 129	
		N 4000	529 - 140	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99650
Concrete Casing
PVC

E83251
Tile Casing
PVC



Orma Semi-Flush Trim | Wall Washer | 3.8” Ø



C.C. - 8W DC 220 mA		Cct	lm S - D	Optic
Steel Alu	**E83634**	**M** 2700	1080 - 300	**07** Asymm. -
Brass Alu	**E84312**	**W** 3000	1126 - 313	
		N 4000	1188 - 330	

Power supply options (remote only)

ECO30W-220
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-220
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-220
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

C.V. 24 V - 9W DC		Cct	lm S - D	Optic
Steel Alu	**E83636**	**M** 2700	1193 - 333	**07** Asymm. -
Brass Alu	**E84313**	**W** 3000	1244 - 347	
		N 4000	1313 - 366	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Concrete Casing
PVC

E83252
Tile Casing
PVC



Orma Semi-Flush Trim | Wall Washer | 5.4” Ø



C.C. - 12W DC 350 mA		Cct	lm S - D	Optic
Steel Alu	**E83638**	**M** 2700	1724 - 598	**07** Asymm. -
Brass Alu	**E84314**	**W** 3000	1724 - 598	
		N 4000	1854 - 643	

Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1 fixtute

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-2 fixtutes

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-4 fixtutes

E99652
Concrete casing
PVC

E83253
Tile casing
PVC



index
technical information

Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min. NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Wall Washer Optics

Optics conceived for wall and floor recessed installation, they allow the creation of perfectly marked and visible luminous paths. The particular Washer optics allow the luminous cone to be sectioned in favour of high visual comfort and to be easily directed so that the positioning is not restricted in the installation phase.



Thanks to the tilting system built into the optics compartment, Orma Wall Washer is able to adapt to different installation heights, defining the diffusion of the light up the 9.8 feet away from the source.



orma

Materials
Aluminum body
AISI 316L stainless steel flange

Orma Flush Trim | Blade | 2.5" Ø



C.C. - 8W DC 630 mA		Cct	lm S - D	Optic
Steel Alu	**E83642**	**M** 2700	1080 - 219	**18** E.W.Flood -
		W 3000	1126 - 219	
		N 4000	1188 - 236	

Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtutes

SOLO100W-630
0-10V EldoLED
SOLOdrive
100W for 1-8
fixtutes

C.V. 9W DC 24VDC		Cct	lm S - D	Optic
Steel Alu	**E83643**	**M** 2700	1193 - 219	**18** E.W.Flood -
		W 3000	1244 - 219	
		N 4000	1313 - 236	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Recessed casing
PVC

E99563
Recessed casing
PVC

E99856*
Recessed casing
PVC



E83252
Recessed casing
PVC



index

technical information

NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
NOT suitable for submersible installations.
Inter-lux reserves the right to make technical changes without notice.

Orma Semi-Flush Trim | Blade | 3.8" Ø



C.C. - 8W DC 630 mA		Cct	lm S - D	Optic
Steel Alu	**E83644**	**M** 2700	1080 - 219	**18** E.W.Flood -
Brass Alu	**E84316**	**W** 3000	1126 - 219	
		N 4000	1188 - 236	

Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-3 fixtutes

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-4 fixtutes

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-8 fixtues

C.V. 9W DC 24VDC		Cct	lm S - D	Optic
Steel Alu	**E83645**	**M** 2700	1193 - 219	**18** E.W.Flood -
Brass Alu	**E84317**	**W** 3000	1244 - 219	
		N 4000	1313 - 236	

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-dim 24VDC, 120-277VAC, Wet location

E99651
Recessed casing
PVC

E83252
Recessed casing
PVC



suelo



The real strength of the Suelo range is its sheer variety. Efficient, versatile, and safe, with a hardwearing flange, a black silkscreened protective screen for increased visual comfort, and the AquaStop® patented protection system, Suelo has been completely redesigned, with drive-over uplights offering unmistakeable Linea Light Group quality.

Materials
Aluminum body
AISI 316L stainless steel flange

suelo range

	2 W	4.2 W	7.2 W	13 W	30 W
Suelo_R	Ø 1.2 in	Ø 2.5 in	Ø 3.6 in	-	-
Suelo_RJ	-	Ø 2.5 in	Ø 3.6 in	-	-
Suelo_RX	-	-	Ø 4.7 in	Ø 6.7 in	Ø 9.1 in
Suelo_RXJ	-	-	Ø 4.7 in	Ø 6.7 in	-
SueloPRO_R	Ø 1.4 in	Ø 2.5 in	Ø 3.6 in	-	-
SueloPRO_RX	Ø 2 in	-	Ø 4.7 in	Ø 6.7 in	-
Suelo_RX Double	-	-	-	Ø 6.7 in (12W)	Ø 9.1 in (24W)
Suelo Telescopic	-	-	-	Ø 7.9 in	Ø 7.9 in (25W)
Options	HC PRO_R, PRO_RX	HC _R, PRO_R DL PRO_R	HC _R, _RX, PRO_R, _PRO_RX DL PRO_R, _PRO_RX	HC _RX, PRO_R, _PRO_RX DL _RX, _PRO_RX	HC _RX DL _RX
CRI 80	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K RGBW (_RX)	2700K 3000K 4000K RGBW (_RX)	2700K 3000K 4000K RGBW (_RX)
Optics – **Standard**	08° 15° 30° 60° 90° Diffused	10° 20° 30° 60° 90° Diffused Elliptic Asymmetric	06° 15° 20° 30° 60° 105° Diffused Elliptic Asymmetric	06° 15° 30° 35° 45° 60° Diffused Asymmetric	06° 15° 30° 35° 60° Asymmetric
Optics – **Pro**	15° 30° 60° Elliptic Diffused	20° 30° 50°	06° 15° 30° 60°	15° 30° 60° Asymmetric	-
Driver	Remote	Remote	Remote	Remote 120-277V On/Off (PRO_RX, _RX Double)	Remote 120-277V On/Off (_RX, _RX Double)
Current	C.C. C.V.	C.C. C.V.	C.C. C.V.	C.C.	C.C.

The range

The Suelo family offers a variety of solutions for every design need: fixed and tiltable versions, small-flanged flush-mount uplights. There are PRO models with recessed optics. RGBW engines and beam control filters are also available. All models have the exclusive AquaStop® protection systems, and there are versions with 24V converters.

RGBW

Visual comfort

Suelo fixtures with honeycomb louver, screen secondary light and reduce glare, maintaining a high-quality light. A darklight filter directs the illumination onto the intended part of the wall by sectioning part of the beam, and prevents glare even close to the source.

For full beam control and a drastically reduced glare risk, choose the Suelo PRO versions, in which the recessed source increases the screening angle, totally skimming off the secondary flow to give a cleaner, more concentrated and efficient light.



Suelo PRO

Suelo + Honeycomb

Suelo + Darklight

Performance and control

Six outputs to choose from, ranging from 1 to 30 watts, three color temperatures including warm light at 2700 and 3000K, and daylight at 4000K.
The uniquely wide spectrum of optics includes an elliptical, a wall wash for high, narrow walls, and an asymmetric version that gives an even, homogeneous wash.

Spot

Flood



Diffused



Asymmetric



Suelo_R | Up-Light | powerLED | Wet location | Driver remote | Walk over | 2W 630mA

Chrome **E93141**	2700K	219 lm	**M**	Narrow Spot	**08**
	3000K	233 lm	**W**	Spot	**15**
	4000K	249 lm	**N**	Medium Flood	**30**
				Flood	**60**
				General	**00**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Recessed casings

E84918
Outer casing for ground-mounting installation

SueloPRO_R | Up-Light | powerLED | Wet location | Driver remote | Driver over | 2W





Comfort

C.C. - 630mA

Steel Alu **E80439**	2700K	205 lm	**M**	Spot	**15**
	3000K	233 lm	**W**	Medium Flood	**30**
	4000K	249 lm	**N**	Flood	**60**
				Elliptic	**88**
				General	**00**
HC Steel Alu **E80440**	2700K	205 lm	**M**	Spot	**15**
	3000K	233 lm	**W**	Medium Flood	**30**
	4000K	249 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

C.V. - 24V

Steel Alu **E80441**	2700K	205 lm	**M**	Spot	**15**
	3000K	233 lm	**W**	Medium Flood	**30**
	4000K	249 lm	**N**	Flood	**60**
				Elliptic	**88**
				General	**00**
HC Steel Alu **E80442**	2700K	205 lm	**M**	Spot	**15**
	3000K	233 lm	**W**	Medium Flood	**30**
	4000K	249 lm	**N**	Flood	**60**

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E99684
Outer casing for ground-mounting installation IP67/68

index
technical information

Suelo_R | Up-Light | powerLED | Wet location | Driver remote | Driver over | 4.2W

E80443 / E80444 / E80445 / E80446



Recessed casings

E84936
Outer casing for ground-mounting installation

E81089 / E81090



Recessed casings

E84935
Outer casing for ground-mounting installation



C.C. - 350mA

Steel Alu **E80443**	2700K	490 lm	**M**	Spot	**10**
	3000K	490 lm	**W**	Medium Flood	**20**
	4000K	529 lm	**N**	Medium Flood	**30**
				Flood	**60**
				Elliptic	**88**
				General	**00**
Steel Alu **E81089**	2700K	490 lm	**M**	Asymmetric	**07**
	3000K	490 lm	**W**		
	4000K	529 lm	**N**		
HC Steel Alu **E80444**	2700K	490 lm	**M**	Medium Flood	**20**
	3000K	490 lm	**W**	Medium Flood	**30**
	4000K	529 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

C.V. - 24V

Steel Alu **E80445**	2700K	490 lm	**M**	Spot	**10**
	3000K	490 lm	**W**	Medium Flood	**20**
	4000K	529 lm	**N**	Medium Flood	**30**
				Flood	**60**
				Elliptic	**88**
				General	**00**
Steel Alu **E81090**	2700K	490 lm	**M**	Asymmetric	**07**
	3000K	490 lm	**W**		
	4000K	529 lm	**N**		
HC Steel Alu **E80446**	2700K	490 lm	**M**	Medium Flood	**20**
	3000K	490 lm	**W**	Medium Flood	**30**
	4000K	529 lm	**N**	Flood	**60**

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location

index
technical information

SueloPRO_R | Up-Light | powerLED | Wet location | Driver remote | Driver over | 4.2W





C.C. - 350mA

	Steel Alu **E80449**	2700K	490 lm	**M**	Medium Flood	**20**
		3000K	490 lm	**W**	Medium Flood	**30**
		4000K	529 lm	**N**	Flood	**50**
HC	Steel Alu **E80450**					
DL	Steel Alu **E80451**					

Power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-350

0-10V EldoLED SOLOdrive 50W for 1-6 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

C.V. - 24V

	Steel Alu **E80452**	2700K	490 lm	**M**	Medium Flood	**20**
		3000K	490 lm	**W**	Medium Flood	**30**
		4000K	529 lm	**N**	Flood	**50**
HC	Steel Alu **E80453**					
DL	Steel Alu **E80454**					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E84935
Outer casing for ground-mounting installation

index
technical information

Suelo_RJ | Up-Light | powerLED | Wet location | Driver remote | Adjustable | Driver over | 4.2W



C.C. - 350mA

Steel Alu **E80455**	2700K	490 lm	**M**	Medium Flood	**20**
	3000K	490 lm	**W**	Medium Flood	**30**
	4000K	529 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-350

0-10V EldoLED SOLOdrive 50W for 1-6 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

C.V. - 24V

Steel Alu **E80456**	2700K	490 lm	**M**	Medium Flood	**20**
	3000K	490 lm	**W**	Medium Flood	**30**
	4000K	529 lm	**N**	Flood	**60**

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E84936
Outer casing for ground-mounting installation

index
technical information

Suelo_R | Up-Light | powerLED | Wet location | Driver remote | Driver over | 7.2W





C.C. - 7.2W - 630mA

Steel Alu **E80546**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**
				Elliptic	**88**
				General	**00**
				Asymmetric	**07**

HC

Steel Alu **E80547**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**

Power supply options (remote only)

ECO30W-630

0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-630

0-10V EldoLED SOLOdrive 50W for 1-4 fixtures

SOLO100W-630

0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. - 7.2W - 24V

Steel Alu **E80550**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**
				Elliptic	**88**
				General	**00**
				Asymmetric	**07**

HC

Steel Alu **E80551**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

RGBW
Quad-chip LED

RGBW - 8W - 630mA

Steel Alu **E81717**	RGBW natural white		**Q**	Narrow Spot	**06**
	RGBW warm white		**V**	Medium Flood	**15**
				Flood	**45**

Power supply options (remote only)

PWR50W-630

DMX driver, EldoLED POWERdrive 50W
Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately
50W for 1-4 Fixtures

Recessed casings

E99680
Outer casing for ground-mounting installation

index
technical information

SueloPRO_R | Up-Light | powerLED | Wet location | Driver remote | Driver over | 7.2W





C.C. - 630mA

HC	Steel Alu	**E80558**	2700K	877 lm	**M**	Narrow Spot **06**
HC	Steel Alu	**E80559**	3000K	945 lm	**W**	Spot **15**
DL	Steel Alu	**E80560**	4000K	1013 lm	**N**	Medium Flood **30**
						Flood **60**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. - 24V

HC	Steel Alu	**E80564**	2700K	877 lm	**M**	Narrow Spot **06**
HC	Steel Alu	**E80565**	3000K	945 lm	**W**	Spot **15**
DL	Steel Alu	**E80566**	4000K	1013 lm	**N**	Medium Flood **30**
						Flood **60**

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E99680
Outer casing for ground-mounting installation

Suelo_RJ | Up-Light | powerLED | Wet location | Driver remote | Adjustable | Driver over | 7.2W



C.C. - 630mA

Steel Alu **E80576**	2700K	709 lm	**M**	Medium Flood **20**
	3000K	760 lm	**W**	Medium Flood **30**
	4000K	821 lm	**N**	Flood **60**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. - 24V

Steel Alu **E80578**	2700K	709 lm	**M**	Medium Flood **20**
	3000K	760 lm	**W**	Medium Flood **30**
	4000K	821 lm	**N**	Flood **60**

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E99680
Outer casing for ground-mounting installation

index
technical information

SueloPRO_RX | Screw-in | Up-Light | powerLED | Wet location | Driver remote | Driver over | 2W





C.C. - 600mA

Steel Alu **E80435**	2700K	205 lm	**M**	Spot	**15**
	3000K	233 lm	**W**	Medium Flood	**30**
	4000K	249 lm	**N**	Flood	**60**
				General	**00**

HC	Steel Alu **E80436**	2700K	205 lm	**M**	Spot	**15**
		3000K	233 lm	**W**	Medium Flood	**30**
		4000K	249 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-600

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-600

0-10V EldoLED SOLOdrive 50W for 1-16 fixtures

SOLO100W-600

0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

C.V. - 24V

Steel Alu **E80437**	2700K	205 lm	**M**	Spot	**15**
	3000K	233 lm	**W**	Medium Flood	**30**
	4000K	249 lm	**N**	Flood	**60**
				General	**00**

HC	Steel Alu **E80438**	2700K	205 lm	**M**	Spot	**15**
		3000K	233 lm	**W**	Medium Flood	**30**
		4000K	249 lm	**N**	Flood	**60**

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E99685
Outer casing for ground-mounting installation
IP67/68

index
technical information

Suelo_RX | Screw-in | Up-Light | powerLED | Wet location | Driver remote | Driver over | 7.2W





C.C. - 7.2W - 630mA

Steel Alu **E80548**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**
				Elliptic	**88**
				General	**00**
				Asymmetric	**07**

HC

Steel Alu **E80549**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**

Power supply options (remote only)

ECO30W-630

0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-630

0-10V EldoLED SOLOdrive 50W for 1-4 fixtures

SOLO100W-630

0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. - 7.2W - 24V

Steel Alu **E80552**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**
				Elliptic	**88**
				General	**00**
				Asymmetric	**07**

HC

Steel Alu **E80553**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

RGBW
Quad-chip LED

RGBW - 8W - 630mA

Steel Alu **E81718**	RGBW natural white	**Q**		Narrow Spot	**06**
	RGBW warm white	**V**		Medium Flood	**15**
				Flood	**45**

Power supply options (remote only)

PWR50W-630

DMX driver, EldoLED POWERdrive 50W
Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately
50W for 1-4 Fixtures

Recessed casings



E98121
Outer casing for ground-mounting installation

index
technical information

SueloPRO_RX | Screw-in | Up-Light | powerLED | Wet location | Driver remote | Driver over | 7.2W





C.C. - 630 mA

	Steel Alu **E80561**	2700K	877 lm	**M**	Narrow Spot	**06**
		3000K	945 lm	**W**	Spot	**15**
HC	Steel Alu **E80562**	4000K	1013 lm	**N**	Medium Flood	**30**
					Flood	**60**
DL	Steel Alu **E80563**					

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-4 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. - 24V

	Steel Alu **E80567**	2700K	877 lm	**M**	Narrow Spot	**06**
		3000K	945 lm	**W**	Spot	**15**
HC	Steel Alu **E80568**	4000K	1013 lm	**N**	Medium Flood	**30**
					Flood	**60**
DL	Steel Alu **E80569**					

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX
Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings



E98121
Outer casing for ground-mounting installation

Suelo_RXJ | Screw-in | Up-Light | powerLED | Wet location | Driver remote | Adjustable | Driver over | 7.2W



C.C. - 630 mA

Steel Alu **E80577**	2700K	709 lm	**M**	Medium Flood	**20**
	3000K	760 lm	**W**	Medium Flood	**30**
	4000K	821 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for 1-4 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. - 24V

Steel Alu **E80579**	2700K	709 lm	**M**	Medium Flood	**20**
	3000K	760 lm	**W**	Medium Flood	**30**
	4000K	821 lm	**N**	Flood	**60**

Power supply options (remote only)

OT96-D010
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX
Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E98121
Outer casing for ground-mounting installation

index
technical information

Suelo_RX | Screw-in | Up-Light | arrayLED | Wet location | Driver remote | Driver over | 13W 350mA





Steel Alu	**E80607**	2700K	1724 lm	**M**	Spot	**15**
		3000K	1724 lm	**W**	Medium Flood	**35**
		4000K	1854 lm	**N**	Flood	**60**
Steel Alu	**E81109**	2700K	1683 lm	**M**	Asymmetric	**07**
		3000K	1808 lm	**W**		
		4000K	1949 lm	**N**		
Steel Alu	**E80608**	2700K	1470 lm	**M**	Narrow Spot	**06**
		3000K	1470 lm	**W**		
		4000K	1587 lm	**N**		
HC Steel Alu	**E81740**	2700K	1724 lm	**M**	Spot	**15**
DL Steel Alu	**E81741**	3000K	1724 lm	**W**	Medium Flood	**35**
		4000K	1854 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

RGBW
Quad-chip LED

RGBW - 16W - 350mA

Steel Alu	**E81719**	RGBW natural white	**Q**	Spot	**15**
		RGBW warm white	**V**	Medium Flood	**30**
				Flood	**60**

Power supply options (remote only)

PWR50W-350

DMX driver, EldoLED POWERdrive 50W Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately for 1-2 Fixtures

Recessed casings

E84933
Outer casing for ground-mounting installation

SueloPRO_RX | Screw-in | Up-Light | arrayLED | 120-277V | Wet location | Integral Driver | Driver over | 15W 350mA





Comfort

On/Off

Steel Alu	**E80611**	2700K	1724 lm	**M**	Spot	**15**
		3000K	1724 lm	**W**	Medium Flood	**35**
		4000K	1854 lm	**N**	Flood	**60**
Steel Alu	**E80612**	2700K	1743 lm	**M**	Asymmetric	**07**
		3000K	1863 lm	**W**		
		4000K	1863 lm	**N**		
HC Steel Alu	**E81744**	2700K	1470 lm	**M**	Spot	**15**
DL Steel Alu	**E81745**	3000K	1470 lm	**W**	Medium Flood	**35**
		4000K	1587 lm	**N**	Flood	**60**

Recessed casings

E84932
Outer casing for ground-mounting installation

index
technical information

Suelo_RXJ | Screw-in | Up-Light | arrayLED | Wet location | Driver remote | Adjustable | Driver over | 13W



Steel Alu **E80613**	2700K	1724 lm	**M**	Spot	**15**
	3000K	1724 lm	**W**	Medium Flood	**35**
	4000K	1854 lm	**N**	Flood	**45**

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Recessed casings

E84933
Outer casing for ground-mounting installation

Suelo_RX | Screw-in | Up-Light | 120-277V | arrayLED | Wet location | Integral Driver | Driver over | 840mA





On/Off 33.6W

Steel Alu **E80614**	2700K	4088 lm	**M**	Spot	**15**
	3000K	4372 lm	**W**	Medium Flood	**35**
	4000K	4702 lm	**N**	Flood	**60**
Steel Alu **E80615**	2700K	3428 lm	**M**	Narrow Spot	**06**
	3000K	3428 lm	**W**		
	4000K	3700 lm	**N**		
Steel Alu **E80616**	2700K	3999 lm	**M**	Asymmetric	**07**
	3000K	4294 lm	**W**		
	4000K	4631 lm	**N**		
HC / DL Steel Alu **E81746** / Steel Alu **E81747**	2700K	4088 lm	**M**	Spot	**15**
	3000K	4372 lm	**W**	Medium Flood	**35**
	4000K	4702 lm	**N**	Flood	**60**

RGBW
Quad-chip LED

RGBW - 30W - 630mA

Steel Alu **E81737**	RGBW natural white	**Q**	Spot	**15**
	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**60**

Power supply options (remote only)

PWR50W-630

DMX driver, EldoLED POWERdrive 50W
Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately
50W for 1 Fixture

Recessed casings



E99794
Outer casing for ground-mounting installation

index
technical information

Suelo_RX Double | Screw-in | Up-Light | arrayLED | 120-277V | Wet location | Integral Driver | Adjustable | Driver over | 13.5W 350mA



On/Off

Steel Alu **E81619**	2700K	1114 lm	**M**	Spot	**15**
	3000K	1176 lm	**W**	Medium Flood	**30**
	4000K	1300 lm	**N**	Flood	**60**

Recessed casings

E84932
Outer casing for ground-mounting installation

Suelo_RX Double | Screw-in | Up-Light | arrayLED | 120-277V | Wet location | Integral Driver | Adjustable | Driver over | 26W 700mA



CRI 80

Steel Alu **E81620**	2700K	2207 lm	**M**	Spot	**15**
	3000K	2377 lm	**W**	Medium Flood	**30**
	4000K	2547 lm	**N**	Flood	**60**

Recessed casings

E99794
Outer casing for ground-mounting installation



index
technical information

Suelo Telescopic | Up-Light | arrayLED | 120-277V | Wet location | Driver on-board | 13.5W 350mA



CRI 80

DarkBrown **E81475**	2700K	1743 lm	**M**	Spot	**15**
	3000K	1863 lm	**W**	Medium Flood	**30**
	4000K	1863 lm	**N**	Flood	**60**

Recessed casings

E99747
Outer casing for ground-mounting installation

Suelo Telescopic | Up-Light | arrayLED | 120-277V | Wet location | Driver remote | 26W 700mA



CRI 80

DarkBrown **E81476**	2700K	3580 lm	**M**	Spot	**15**
	3000K	3847 lm	**W**	Medium Flood	**30**
	4000K	3847 lm	**N**	Flood	**60**

Recessed casings

E99747
Outer casing for ground-mounting installation

index
technical information

bollards range index

click images to open product pages

Ryo

Ryo

L11

Ryo

L11

Ryo

L11

Ryo

L12

Ryo

L12

Ryo

L12

Joe

Joe

L16

Joe

L16

Joe

L16

Joe

L16

Bond-pro

Bond-Pro

L20

Bond-Pro

L20

Bond-Pro

L20

Peak

Peak

L25

Peak

L26

Apache

Apache

L28

Apache

L29



L3

MAESTRO 2.2



Bollards

bollards features



High-quality construction

Linea Light Group bollards are corrosion proofed for maximum durability. Open-pore anodization provides total protection for the aluminum components. Before being fixed in place, the bollards are powder coated in polyester to give them a high level of protection against atmospheric agents. The diffusers are given an anti-UV treatment to prevent yellowing and ensure the product provides high-quality illumination for the longest possible time.



Elegant finishes

The finishes reflect the latest in outdoor design trends. Classic gray, anthracite and corten steel provide a bold and sophisticated look for public and private spaces including parks, suares, paths, and gardens.



Long-term reliability

Linea Light Group bollards for public spaces have an impact rating that exceeds IK08. The body and diffuser are made from hardwearing aluminum, steel, tempered glass and anti-impact polycarbonate in simple, robust designs. Vandalproof screws and other protection systems mean they'll continue to do their job for a long time to come.

Reducing light pollution

Many bollards' optics are specifically designed to combat light pollution. This has important benefits: as well as letting you see more stars with your naked eye, it minimises the environmental impact of electric lighting, improves the safety, health and welfare of humans and wild animals, and reduces energy consumption.



ryo

Ryo's strengths are its extremely pleasant lighting and original design. The optics are designed to prevent dispersion above the horizon, and the light from the LED source is directed throughout the length of the bollard. Like a river (rio, hence the product's name), it channels light, distributing it downwards through a 180-degree radius to prevent light pollution.

Materials
Polyester powder-coated aluminum body and protective surface treatment
Transparent polycarbonate diffuser

ryo range

	Ryo_1	Ryo_2
4 W	9.8 x 5.9 in	-
8.4 W	-	9.8 x 5.9 in
9 W	32.3 x 5.9 in 44.1 x 5.9 in	-
18 W	-	32.3 x 5.9 in 44.1 x 5.9 in
Finish		
topLED	3000K 4000K	3000K 4000K
Optics	General	General
Driver	0-10V	0-10V

ryo lighting concept

Concept

The Ryo name indicates its peculiar character: during the night the stem's concave profile comes alive and flooded by decorative and functional light. The vertical plan lighting provides a reference point during the night, using coating surface fixture's luminance to reduce consumptions. Light distribution on path results smooth and deep, perfect for public and residential projects.

Unidirectional emission

Ideal for pathway lighting, this solution provides a great visual orientation and creates a certain rhythm inside the pathways, also outlining the walking areas through light and shade.

E64736N00



Photometric curve



Light beam



25 LUX | 100 LUX | 300 LUX | 1000 LUX



Floor plan

Bidirectional emission

This type of emission is particularly functional to light up large areas or gardens, since they require a diffusive light coming from both sides of the bollard.

E64735W00



Photometric curve



Light beam



25 LUX | 100 LUX | 500 LUX | 1000 LUX



Floor plan

Ryo | Bollards | arrayLED | 120-277V | Wet location | Integral Driver | 4.2W | 5.2W | 0-10V



CRI 80

Grey	**E64761**	3000 K	728 lm	**W**	General **00**
BK Grey	**E64759**	4000 K	778 lm	**N**	
DarkBrown	**E64760**				

Accessories

E64758

Anchor

Ryo | Bollards | arrayLED | 120-277V | Wet location | Integral Driver | 10W | 0-10V



CRI 80

Grey	**E64734**	3000 K	1208 lm	**W**	General **00**
BK Grey	**E64721**	4000 K	1294 lm	**N**	
DarkBrown	**E64726**				

Accessories

E64758

Anchor Bolts

Ryo | Bollards | arrayLED | 120-277V | Wet location | Integral Driver | 10W | 0-10V



CRI 80

Grey	**E64736**	3000 K	1208 lm	**W**	General **00**
BK Grey	**E64723**	4000 K	1294 lm	**N**	
DarkBrown	**E64728**				

Accessories

E64758

Anchor Bolts

index
technical information

Ryo | Bollards | arrayLED | 120-277V | Wet location | Integral Driver | 10W | 0-10V





CRI 80

Grey	**E64764**	3000 K	1456 lm	**W**	General **00**
BK Grey	**E64762**	4000 K	1556 lm	**N**	
DarkBrown	**E64763**				

Accessories

E64758

Anchor Bolts

Ryo | Bollards | arrayLED | 120-277V | Wet location | Integral Driver | 20W | 0-10V





CRI 80

Grey	**E64735**	3000 K	2416 lm	**W**	General **00**
BK Grey	**E64722**	4000 K	2588 lm	**N**	
DarkBrown	**E64727**				

Accessories

E64758

Anchor Bolts

Ryo | Bollards | arrayLED | 120-277V | Wet location | Integral Driver | 20W | 0-10V





CRI 80

Grey	**E64737**	3000 K	2416 lm	**W**	General **00**
BK Grey	**E64724**	4000 K	2588 lm	**N**	
DarkBrown	**E64729**				

Accessories

E64758

Anchor Bolts

index
technical information

joe

A simple, elegant range of path markers and bollards designed for paths and other urban spaces.
The head encloses and protects the optics, and the light emerges from the rear-facing aperture for perfect glare-free control.

Materials
Polyester powder-coated aluminum body and protective surface treatment
Transparent polycarbonate diffuser

joe lighting concept

Optics design

The peculiar Joe emission derives by integrated optical group studies. The high performance ArrayLED source combined with a metallized transparent polycarbonate semi-circular reflector. The light chamber lower part is wrapped with a microcell pad in semi-glossy black polycarbonate, for the direct luminance perfect control.



Robust design

The special spherical cap shape of Joe profile makes this product particularly robust and resistant, ideal for both public and private outdoor applications. The total absence of raw edges makes it particularly safe for users.



reddot award 2015
winner

Grazing light

The distribution of the light on the walking area creates an interesting shade effect, which is perfectly parallel to the walking direction. This effect can be used to outline night paths and highlight green areas with accent lighting.

E59165W00



Photometric curve



Light beam



25 LUX | 100 LUX | 300 LUX | 500 LUX | 1000 LUX



Floor plan

Joe | Bollards | 120-277V | arrayLED | Wet location | Integral Driver | 11W | 0-10V

CRI 80

Grey	**E59165**	3000 K	1208 lm	**W**	General **00**
DarkBrown	**E59166**	4000 K	1294 lm	**N**	

Accessories

E14931
Anchor

Joe | Bollards | 120-277V | arrayLED | Wet location | Integral Driver | 11W | 0-10V



CRI 80

Grey	**E59175**	3000 K	1208 lm	**W**	General **00**
DarkBrown	**E59176**	4000 K	1294 lm	**N**	

Accessories

E59950
Anchor

Joe | Bollards | 120-277V | topLED | Wet location | Remote Driver | 9W



CRI 80

Grey	**E64635**	3000 K	1060 lm	**W**	General **00**
DarkBrown	**E64636**	4000 K	1124 lm	**N**	

Accessories

E14931
Anchor

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Joe | Bollards | 120-277V | topLED | Wet location | Remote Driver | 9W



CRI 80

Grey	**E59170**	3000 K	1060 lm	**W**	General **00**
DarkBrown	**E59171**	4000 K	1124 lm	**N**	

Accessories

E59950
Anchor

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-2 fixtures	0-10V EldoLED SOLOdrive 50 for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

index
technical information

bond PRO

Bond PRO is designed to fit in with its environment.
It's discreetly elegant, yet won't pass unnoticed.
The head screens the light source completely for maximum visual comfort.

Materials
Polyester powder-coated aluminum body with protective surface treatment
Opalescent white polyethylene diffuser

bond PRO lighting concept

Ergonomic design

The light source in the top of the bollard is screened by the circular flange to create a total cutoff, so that the light is never invasive and fits perfectly with its environment.

The light emitted illuminates the portion of the area below. The Bond PRO range offers three different sizes that allow the product to be declined in a variety of application contexts.

E81099W00



Photometric curve



Light beam



25 LUX | 100 LUX | 500 LUX | 1000 LUX



Floor plan

E81107W00



Photometric curve



Light beam



25 LUX | 100 LUX | 500 LUX | 1000 LUX



Floor plan

Bond_PRO | Bollards | topLED | Wet location | Driver remote | 10.8W



12 W - CRI 80

Black	**E81098**	3000 K	1350 lm	**W**	General	**00**
DarkBrown	**E81099**	4000 K	1460 lm	**N**		
Steel	**E81100**					
Grey	**E81097**					

Power supply options (remote only)

ECO30W-300	**SOLO50W-300**	**SOLO100W-300**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Accessories

E14931

Anchor Bolts

Bond_PRO | Bollards | topLED | Wet location | Driver remote | 10.8W





12 W - CRI 80

Black	**E81102**	3000 K	1350 lm	**W**	General	**00**
DarkBrown	**E81103**	4000 K	1460 lm	**N**		
Steel	**E81104**					
Grey	**E81101**					

Power supply options (remote only)

ECO30W-300	**SOLO50W-300**	**SOLO100W-300**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Accessories

E14931

Anchor Bolts

Bond_PRO | Bollards | topLED | Wet location | Driver remote | 10.8W



12 W - CRI 80

Black	**E81106**	3000 K	1350 lm	**W**	General	**00**
DarkBrown	**E81107**	4000 K	1460 lm	**N**		
Steel	**E81108**					
Grey	**E81105**					

Power supply options (remote only)

ECO30W-300	**SOLO50W-300**	**SOLO100W-300**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Accessories

E14931

Anchor Bolts

index
technical information

peak



More and more cities are realising the importance of lighting in providing an attractive environment for people to relax and enjoy their surroundings after the sun goes down. Peak offers a wide range of solutions designed to bring streets and other public places to life at night.

Materials
Polyester powder-coated aluminum body with protective surface treatment
Extra-clear glass diffuser

peak range



	Peak	Peak_L	
6.5 W	13.8 x 3.5 in	-	
9.5 W	29.5 x 3.5 in	29.5 x 3.5 in	
12 W	-	-	
Finish			
topLED	3000K 4000K	3000K 4000K	
Optics	Asymmetric	Asymmetric	
Driver	0-10V	0-10V	

Optics design

The peculiar optical group conformation provides a lighting emission only on bollard front, eliminating every secondary light dispersion on the back. The light emission is deep, clear and defined.



Control and performance

Luminous unit equipped with dedicated lens managing light distribution with maximum control. Asymmetric effects able to light up secondary roads, squares, parks and gardens.

Every needs answer

Wall mounted version, different dimensions and power bollards, ensures a solution for every installation needs. Peak provides easier installation also in the urban context, its great flexibility ensures a professional lighting and architecture project approach.

Peak | Bollards | 120-277V | arrayLED | Wet location | Integral Driver | Asymmetric | 8W | 0-10V



CRI 80

Grey	**E64794**	3000 K	988 lm	**W**	Asymmetric **07**
BK Grey	**E64795**	4000 K	1058 lm	**N**	
DarkBrown	**E64796**				

Accessories



E65082
Anchor Bolts

Peak | Bollards | 120-277V | arrayLED | Wet location | Integral Driver | Asymmetric | 11W | 0-10V



CRI 80

Grey	**E64791**	3000 K	1208 lm	**W**	Asymmetric **07**
BK Grey	**E64792**	4000 K	1294 lm	**N**	
DarkBrown	**E64793**				

Accessories



E65082
Anchor Bolts

index
technical information

E64794W07



Photometric curve



Light beam



25 LUX | 100 LUX | 500 LUX | 1000 LUX



Floor plan

Peak_L | Bollards | 120-277V | Wet location | Integral Driver | Asymmetric | 11W | 0-10V



CRI 80

Grey	**E64788**	3000 K	1208 lm	**W**	Asymmetric **07**
BK Grey	**E64789**	4000 K	1294 lm	**N**	
DarkBrown	**E64790**				

Accessories



E65082

Anchor Bolts

index
technical information

apache

The Apache standardized design in civil engineering is a source of inspiration for Studio RIGO for creative re-elaboration. The rigidity of the original profile is transformed into a bollard with minimal and curvy design with an entirely innovative emission: the source is positioned at the upper part of the product, facing downwards to create an asymmetric beam which eliminates glare, generating a harmonic and efficient diffusion while maintaining integration in the architectural space at the same time.

Materials
Metal body with polyester powder coating and protective surface pre-treatment
Transparent polycarbonate diffuser

Apache | Bollards | powerLED | Wet location | Driver remote | 7W 180mA



CRI 80

BK Grey	**E64262**	3000 K	935 lm	**W**	General **00**
Gr BK	**E64263**	4000 K	978 lm	**N**	
DarkBrown	**E64264**				
Sand	**E64265**				

Power supply options (remote only)

ECO30W-180	**SOLO50W-180**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures

Accessories

E64210
Tie rods

Apache | Bollards | powerLED | Wet location | Driver remote | 9W 220mA



CRI 80

BK Grey	**E64266**	3000 K	1207 lm	**W**	General **00**
Gr BK	**E64267**	4000 K	1266 lm	**N**	
DarkBrown	**E64268**				
Sand	**E64269**				

Power supply options (remote only)

ECO30W-220	**SOLO50W-220**	**SOLO100W-220**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Accessories

E64210
Tie rods

index
technical information

Apache | Bollards | powerLED | Wet location | Driver remote | 7W 180mA



CRI 80

BK Grey	**E81972**	3000 K	935 lm	**W**	General **00**
Gr BK	**E81973**	4000 K	978 lm	**N**	
DarkBrown	**E81974**				
Sand	**E81975**				

Power supply options (remote only)

ECO30W-180	**SOLO50W-180**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive50W for 1-2 fixtures

Accessories

E64210
Tie rods

Apache | Bollards | powerLED | Wet location | Driver remote | 9W 220mA



CRI 80

BK Grey	**E81976**	3000 K	1207 lm	**W**	General **00**
Gr BK	**E81977**	4000 K	1266 lm	**N**	
DarkBrown	**E81978**				
Sand	**E81979**				

Power supply options (remote only)

ECO30W-220	**SOLO50W-220**	**SOLO100W-220**
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Accessories

E64210
Tie rods

index
technical information

linear lights range index

Paseo

Paseo_L

M11

Paseo_X

M17

Xenia

Xenia_W

M27

Xenia_W Pro

M31

Xenia_A

M34

Xenia_A PRO

M36

Archiline

Archiline_F

M44

Archiline_FL



M47

Archiline_A

M50

Archiline_I

M53

Archiline PRO_I



M57

Archiline W



M64

Archiline PRO_W



M68

Dirigo

Dirigo

M72





linear lighting features

High-quality construction

The new linear light ranges feature:

- Very high-quality materials, including EN AW-6060 aluminum alloy, 316L stainless steel, tempered glass, and special silicone resins;

- Proven resistance to vibration, stress and impact, tolerating temperatures of -20C to +60C and other extremes of climate, overvoltage, electric discharge and moisture protection, and AquaStop® conductor waterproofing.

Less than two MacAdam steps

We choose the best manufacturers to ensure that LEDs maintain consistency of color over time and within lighting projects. Our standard of quality is less than two MacAdam steps, meaning that differences between LEDs are not visible to the naked eye, and the LEDs are regarded as being of excellent quality.

MacAdam < 2

Chromatic inhomogeneity

Color range

LEDs give you access to a wide range of color temperatures, from warm white (2.700K) to daylight tones (5.000K), for total design versatility. As well as white light, the RGB range offers static or dynamic colored effects, and the introduction of RGBW, in which white is separate from red, green and blue in the diode, lets you obtain the right mix for your project alongside a very pure white.

Perfect mixing





Performance for every need

Each family of lights includes different outputs to meet the largest possible range of requirements. Paseo, Xenia, Archiline and Archiline PRO offer a particularly wide selection. It's worth remembering that all linear lights can be dimmed using, 0-10V, DMX and RDM protocols, using bidirectional communication to achieve total control of DMX parameters.



Optical range

The Linear Lights series offers specific products for every context, and lighting solutions that vary depending on the optics you choose. There are spots, narrow spots for small or very small angles, various floods, and diffuse and wall washer lights. The Elliptic 20°x50° gives an oval grazing wash for tall narrow walls, and Asymmetric provides a directional beam that washes the wall evenly.

paseo

Paseo is a highly functional and versatile range of lights. Paseo_L, with a topLED source and antiglare and RGBW versions, is designed for positioning illumination. It has a range of optics, from flood to asymmetric and diffuse. Paseo_X has a powerLED source for high-output illumination, and and is available with flood, medium flood, asymmetric, elliptic optics and a wide selection of control options in the standard and RGBW version.

Materials
Transparent or opalescent polycarbonate body

paseo range



	_L	_L Anti-glare	L_RGBW	_X	_X RGBW
20.2 in	6 W	6 W	6 W	-	-
22.7 in	-	-	-	7 W	9 W
45.4 in	13 W	13 W	13 W	17 W	19 W
57.2 in	19 W	-	19 W	-	-
Finish	Transparent Opaline	Transparent	Opaline	Transparent	Transparent
topLED	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K	RGBW	-	-
powerLED	-	-	-	2700K 3000K 3500K 4000K	RGBW
Optics	Medium Flood Asymmetric General	Medium Flood Asymmetric	General	Narrow Spot Spot MediumFlood Flood Elliptical Asymmetric	Elliptical
Driver remote	24V	24V	24V	-	-
Integral Driver	120V On/Off	120V On/Off	DMX interface	120V On/Off 120V + 0-10V	120V + DMX interface

Minimal size

The new Paseo models are even thinner and more versatile, with heights of 0.9 to 1.5 inch that adapt easily to any design need. Their very small size is combined with simple, minimalist aesthetics.

Real sizes

The Paseo range comes with a wide choice of optics, lengths, color temperatures, and controls. These include 0-10V, and RGBW DMX and RGB pixel for dynamic lighting management and spectacular architectural illumination. The housings and numerous accessories mean Paseo can be recessed or fitted to a wall, ceiling or floor.



Maximum protection

An electrostatic discharge occurs when there's a transfer of charges between two bodies that are close or in contact with each other. This often damages electronics and LED modules. Paseo fixtures with integral drivers come with an up to 4KV electrostatic discharge (ESD) protection.

ESD PROTECTION 4KV

Ultrasonic-welded caps offer perfect mechanical resistance and light continuity

Thermoplastic PUR cables with IP67 4 pin or 5-pin M12 quick-connectors

Steel spring clips allow you to easily install the Paseo profile into the outer casing

TCS® valve, to avoid the formation of humidity in the profile

Paseo_L | Linear profiles | 24V | topLED | Wet location | Driver remote | Walk over | 3.7W/ft



6W - CRI 80

Transp. **E97673**	2700K	662 lm	**M**	Medium Flood	**20**
	3000K	720 lm	**W**	Asymmetric	**07**
	3500K	720 lm	**T**		
	4000K	749 lm	**N**		
Opaline **E81328**	2700K	662 lm	**M**	General	**00**
	3000K	720 lm	**W**		
	3500K	720 lm	**T**		
	4000K	749 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location



13W - CRI 80

Transp. **E97674**	2700K	1208 lm	**M**	Medium Flood	**20**
	3000K	1313 lm	**W**	Asymmetric	**07**
	3500K	1313 lm	**T**		
	4000K	1365 lm	**N**		

13W - CRI 80

Opaline **E81329**	2700K	1208 lm	**M**	General	**00**
	3000K	1313 lm	**W**		
	3500K	1313 lm	**t**		
	4000K	1365 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location



19W - CRI 80

Transp. **E97675**	2700K	1913 lm	**M**	Medium Flood	**20**
	3000K	2079 lm	**W**	Asymmetric	**07**
	3500K	2079 lm	**T**		
	4000K	2162 lm	**N**		
Opaline **E81330**	2700K	1913 lm	**M**	General	**00**
	3000K	2079 lm	**W**		
	3500K	2079 lm	**T**		
	4000K	2162 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Cables

E99216	**E89190**	**E98437**	**E98149**	**E89188**
59 in. low volt. power feed cable F 4 pin M12	196 in. low volt. power feed cable F 4 pin M12	39 in. low volt. power extension cable M+F 4 pin M12	196 in. low volt. power extension cable M+F 4 pin M12	393 in. low volt. power extension cable M+F 4 pin M12

Installation accessories (Required / Ordered separately)

Outer casings and fixing systems

See pages M19-M22

index
technical information

Paseo_L ON/OFF | Linear profiles | 120V | topLED |Wet location | Integral Driver | Walk over



7.4W - CRI 80

Transp. **E96150**	2700K	662 lm	**M**	Medium Flood	**20**
	3000K	720 lm	**W**	Asymmetric	**07**
	3500K	720 lm	**T**		
	4000K	749 lm	**N**		
Opaline **E81331**	2700K	662 lm	**M**	General	**00**
	3000K	720 lm	**W**		
	3500K	720 lm	**T**		
	4000K	749 lm	**N**		



15.2W - CRI 80

Transp. **E96151**	2700K	1208 lm	**M**	Medium Flood	**20**
	3000K	1313 lm	**W**	Asymmetric	**07**
	3500K	1313 lm	**T**		
	4000K	1365 lm	**N**		
Opaline **E81332**	2700K	1208 lm	**M**	General	**00**
	3000K	1313 lm	**W**		
	3500K	1313 lm	**T**		
	4000K	1365 lm	**N**		



21.8W - CRI 80

Transp. **E96152**	2700K	1913 lm	**M**	Medium Flood	**20**
	3000K	2079 lm	**W**	Asymmetric	**07**
	3500K	2079 lm	**T**		
	4000K	2162 lm	**N**		
Opaline **E81333**	2700K	1913 lm	**M**	General	**00**
	3000K	2079 lm	**W**		
	3500K	2079 lm	**T**		
	4000K	2162 lm	**N**		

Cables

E83043	**E83044**	**E83045**	**E83046**	**E83047**
59 in. line volt. power feed cable F 3 pin M12	196 in. line volt. power feed cable F 3 pin M12	39 in. line volt. power extension cable M+F 3 pin M12	196 in. line volt. power extension cable M+F 3 pin M12	393 in. line volt. power extension cable M+F 3 pin M12

Installation accessories (Required / Ordered separately)

Outer casings and fixing systems

See pages M19-M22

index
technical information

Paseo_L Anti-glare | Linear profiles | 24V | topLED | Wet location | Driver remote | Walk Over | 3.7W/ft



6W - CRI 80

Transp.	**E94021**	2700K	662 lm	**M**	Medium Flood	**20**
		3000K	720 lm	**W**	Asymmetric	**07**
		3500K	720 lm	**T**		
		4000K	749 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location



12W - CRI 80

Transp.	**E94022**	2700K	1208 lm	**M**	Medium Flood	**20**
		3000K	1313 lm	**W**	Asymmetric	**07**
		3500K	1313 lm	**T**		
		4000K	1365 lm	**N**		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Cables

E99216	E89190	E98437	E98149	E89188
59 in. low volt. power feed cable F 4 pin M12	196 in. low volt. power feed cable F 4 pin M12	39 in. low volt. power extension cable M+F 4 pin M12	196 in. low volt. power extension cable M+F 4 pin M12	393 in. low volt. power extension cable M+F 4 pin M12

Paseo_L ON/OFF Anti-glare | Linear profiles | 120V | topLED | Integral Driver | Asymmetric | Walk Over | 3.7W/ft



7W - CRI 80

Transp.	**E93994**	2700K	662 lm	**M**	Medium Flood	**20**
		3000K	720 lm	**W**	Asymmetric	**07**
		3500K	720 lm	**T**		
		4000K	749 lm	**N**		



15W - CRI 80

Transp.	**E93995**	2700K	1208 lm	**M**	Medium Flood	**20**
		3000K	1313 lm	**W**	Asymmetric	**07**
		3500K	1313 lm	**T**		
		4000K	1365 lm	**N**		



Modules are equipped with a shield that reduces the direct glare without significantly reducing the light output.

Cables

E83043	E83044	E83045	E83046	E83047
59 in. line volt. power feed cable F 3 pin M12	196 in. line volt. power feed cable F 3 pin M12	39 in. line volt. power extension cable M+F 3 pin M12	196 in. line volt. power extension cable M+F 3 pin M12	393 in. line volt. power extension cable M+F 3 pin M12

Installation accessories (Required / Ordered separately)

Outer casings and fixing systems

See pages M19-M22

index
technical information

Paseo_L RGBW DMX 24V | Linear profiles | 24V + Integral RDM DMX Interface | topLED | Wet location | Driver remote | Walk Over | 3.7W/ft



6.6W - CRI 80

Opaline	E84055	RGBW 4000K	Q	General	00
		RGBW 3000K	V		

OT96-D010*
Osram, *wired as non -dim, 96W, 24VDC 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location



13.6W - CRI 80

Opaline	E84056	RGBW 4000K	Q	General	00
		RGBW 3000K	V		

OT96-D010*
Osram, *wired as non -dim, 96W, 24VDC 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location



19.5W - CRI 80

Opaline	E84057	RGBW 4000K	Q	General	00
		RGBW 3000K	V		

OT96-D010*
Osram, *wired as non -dim, 96W, 24VDC 120-277VAC, supplied in a Dry location enclosure

OT96-JBX
Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Cables

E99216	E89190	E98437	E98149	E89188	E89189
59 in. low volt. power feed cable F 4 pin M12	196 in. low volt. power feed cable F 4 pin M12	39 in. low volt. power extension cable M+F 4 pin M12	196 in. low volt. power extension cable M+F 4 pin M12	393 in. low volt. power extension cable M+F 4 pin M12	196 in. low volt. DMX cable M 5 pin M12
E89186	**E98494**	**E98493**	**E98994**	**E98993**	**E89187**
196 in DMX cable M 5 pin M12 + M 3 pin XLR	196 in DMX cable M 5 pin M12 + F 3 pin XLR	196 in DMX cable M 5 pin M12 + M 5 pin XLR	39 in DMX extension 0-10V M+F 5 pin M12	196 in DMX extension 0-10V M+F 5 pin M12	393 in DMX extension 0-10V M+F 5 pin M12

Installation accessories (Required / Ordered separately)

Outer casings and fixing systems

See pages M19-M22

index
technical information

Paseo_X ON/OFF | Linear profiles | 120V | powerLED | Wet location | Integral Driver | Walk over



7.7W - CRI 80

Transp.					
E96196	2700K	970 lm	**M**	Narrow Spot	**08**
12 LEDs	3000K	1033 lm	**W**	Spot	**15**
	3500K	1033 lm	**T**	Medium Flood	**30**
	4000K	1105 lm	**N**	Flood	**60**
				Elliptical	**25**

19.4W - CRI 80

Transp.					
E96197	2700K	2392 lm	**M**	Narrow Spot	**08**
24 LEDs	3000K	2549 lm	**W**	Spot	**15**
	3500K	2726 lm	**T**	Medium Flood	**30**
	4000K	2726 lm	**N**	Flood	**60**
				Elliptical	**25**

Cables

E83043	E83044	E83045	E83046	E83047
59 in. line volt. power feed cable F 3 pin M12	196 in. line volt. power feed cable F 3 pin M12	39 in. line volt. power extension cable M+F 3 pin M12	196 in. line volt. power extension cable M+F 3 pin M12	393 in. line volt. power extension cable M+F 3 pin M12

Paseo_X 0-10V | Linear profiles | 120V | powerLED | Wet location | Integral Driver | Walk over



7.7W - CRI 80

Transp.					
E97255	2700K	1056 lm	**M**	Narrow Spot	**08**
12 LEDs	3000K	1128 lm	**W**	Spot	**15**
	3500K	1128 lm	**T**	Medium Flood	**30**
	4000K	1212 lm	**N**	Flood	**60**
				Elliptical	**25**

19.4 W - CRI 80

Transp.					
E97611	2700K	2112 lm	**M**	Narrow Spot	**08**
24 LEDs	3000K	2256 lm	**W**	Spot	**15**
	3500K	2256 lm	**T**	Medium Flood	**30**
	4000K	2424 lm	**N**	Flood	**60**
				Elliptical	**25**

Cables

E83043	E83044	E83045	E83046	E83047
59 in. line volt. power feed cable F 3 pin M12	196 in. line volt. power feed cable F 3 pin M12	39 in. line volt. power extension cable M+F 3 pin M12	196 in. line volt. power extension cable M+F 3 pin M12	393 in. line volt. power extension cable M+F 3 pin M12

E89189	E98994	E98993	E89187
196.9 in 0-10V cable M 5 pin M12	39.4 in 0-10V extension M+F 5 pin M12	196.9 in 0-10V extension M+F 5 pin M12	393.7 in 0-10V extension M+F 5 pin M12

Installation accessories (Required / Ordered separately)

Outer casings and fixing systems

See pages M19-M22

index
technical information

Paseo_X RGBW DMX | Linear profiles | 120V + Integral RDM DMX Interface | powerLED | Wet location | Integral Driver | Walk over | 5.5W/ft





9W - CRI 80

Transp.	**E84058**	RGBW 4000K	**Q**	Elliptical	**25**
16 LEDs		RGBW 3000K	**V**		

19W - CRI 80

Transp.	**E84059**	RGBW 4000K	**Q**	Elliptical	**25**
32 LEDs		RGBW 3000K	**V**		

Cables

E83043
59 in. line volt. power feed cable F 3 pin M12

E83044
196 in. line volt. power feed cable F 3 pin M12

E83045
39 in. line volt. power extension cable M+F 3 pin M12

E83046
196 in. line volt. power extension cable M+F 3 pin M12

E83047
393 in. line volt. power extension cable M+F 3 pin M12

E89189
196 in DMX cable M 5 pin M12

E89186
196 in DMX cable M 5 pin M12 + M 3 pin XLR

E98494
196 in DMX cable M 5 pin M12 + F 3 pin XLR

E98493
196 in DMX cable M 5 pin M12 + M 5 pin XLR

E98994
39 in DMX extension 0-10V M+F 5 pin M12

E98993
196 in DMX extension 0-10V M+F 5 pin M12

E89187
393 in DMX extension 0-10V M+F 5 pin M12

Installation accessories (Required / Ordered separately)

Outer casings and fixing systems

See pages M19-M22

Paseo | Floor with trim outer casing

Top casing

Bottom cable gland casing





		Top Outer casing	Bottom Cable gland
Anod. Al.	20.2 in x Paseo 20.2 in	**E98355**	**E98471**
Anod. Al.	22.7 in x Paseo 22.7 in	**E98430**	**E98472**
Anod. Al.	45.4 in x Paseo 45.4 in	**E98356**	**E98473**
Anod. Al.	57.2 in x Paseo 57.2 in	**E98357**	**E98474**



Installation accessories



E98876
2 x end caps

Paseo | Floor trimless / Surface mount outer casing

Top casing

Bottom cable gland casing





		Top Outer casing	Bottom Cable gland
Anod. Al.	20.2 in x Paseo 20.2 in	**E98467**	**E98471**
Anod. Al.	22.7 in x Paseo 22.7 in	**E98468**	**E98472**
Anod. Al.	45.4 in x Paseo 45.4 in	**E98469**	**E98473**
Anod. Al.	57.2 in x Paseo 57.2 in	**E98470**	**E98474**



Installation accessories



E98466
2 x end caps

Paseo | Ceiling with trim outer casing



Anod. Al.	20.2 in x Paseo 20.2 in	**E98374**
Anod. Al.	22.7 in x Paseo 22.7 in	**E98435**
Anod. Al.	45.4 in x Paseo 45.4 in	**E98375**
Anod. Al.	57.2 in x Paseo 57.2 in	**E98376**



Installation accessories



E98465
2 x end caps

Paseo | Ceiling trimless outer casing



Anod. Al.	20.2 in x Paseo 20.2 in	**E98367**
Anod. Al.	22.7 in x Paseo 22.7 in	**E98434**
Anod. Al.	45.4 in x Paseo 45.4 in	**E98368**
Anod. Al.	57.2 in x Paseo 57.2 in	**E98369**



Installation accessories



E98464
2 x end caps

Paseo | Surface 3D outer casing



Anod. Al.	20.2 in x Paseo 20.2 in	**E98836**
Anod. Al.	22.7 in x Paseo 22.7 in	**E98839**
Anod. Al.	45.4 in x Paseo 45.4 in	**E98837**
Anod. Al.	57.2 in x Paseo 57.2 in	**E98838**



Installation accessories



E98840
2 x end caps

Paseo | Surface adjustable outer casing

Outer casing



Anod. Al.	20.4 in x Paseo 20.2 in	**E98842**
Anod. Al.	22.9 in x Paseo 22.7 in	**E98843**
Anod. Al.	45.6 in x Paseo 45.4 in	**E98844**
Anod. Al.	57.4 in x Paseo 57.2 in	**E98845**



Installation accessories



Included
2 x end caps
included.

Paseo | Adjustable mounting clips

Adjustable mounting clips



E98771

Pair of fastening clips made of transparent polycarbonate to install the fixture in an even horizontal mounting surface. A directional accessory that allows Paseo tilt movement from + 90° to -90°.

Mounting plate for uneven horizontal surfaces (ordered separately)



L inches	L1 inches	
11.8 in	7.9 in	**E98772**
Plate for 20.2 or 20.7" Paseo fixtures		
L inches	L1 inches	
37.4 in	33.5 in	**E98773**
Plate for 45.4 or 57.2" Paseo fixtures		

The plate, without fixing it to the surface, can be used as a mobile support for the adjustable clips and fixture.
Clips not included in codes E98772 - E98773 (ordered separately)

Paseo | Extraction key



E98475

The Paseo extraction key (ordered separately) allows its removal from the outer casing.
Compatible with all Paseo outer casings.

index
technical information

xenia

The new Xenia family comprises a very wide range of linear lights, with numerous configurations for every lighting need. They provide a high-performance solution for lighting professionals, offering reliable safety technology including OVP, ESD, TCS® and AcquaStop®. There is also a wide choice of topLED and powerLED outputs, and optics. The range is available in warm white, natural white, and RGBW versions.

Materials
Anodized 6060 aluminum alloy body

xenia lighting concept



Xenia_W TopLED 24V

Xenia_W PowerLED 24V

Xenia_W PRO PowerLED 24V

	_W	_W Pro	_A	_A Pro
length	14.4 --> 60.2 in	14.4 --> 60.2 in	14.1 --> 59.8 in	14.1 --> 59.8 in
topLED	2700K - 3000K 3500K - 4000K RGBW+W - RGBW+N	-	2700K - 3000K 3500K - 4000K RGBW+W - RGBW+N	
powerLED	-	2700K - 3000K 3500K - 4000K RGBW+W - RGBW+N		2700K - 3000K 3500K - 4000K RGBW+W - RGBW+N
Optics	Narrow Flood - Flood Wide Flood - Asymmetric General	Narrow Spot - Narrow Flood Flood - Wide Flood Asymmetric - Elliptical	Narrow Flood - Flood Wide Flood - Asymmetric	Narrow Spot - Spot Narrow Flood - Flood Wide Flood - Asymmetric General - Wall Grazing
Finish				
Driver remote	0-10V DMX (RGBW)	0-10 V DMX (RGBW)	0-10V DMX (RGBW)	0-10 V DMX (RGBW)
Integral Driver	On/Off	On/Off 0-10V	DMX	DMX
Mounting	Surface mounted with brackets	Surface mounted with brackets	In-grade / Ceiling or wall recessed	In-grade / Ceiling or wall recessed

index
technical information

High-quality construction

Xenia is made from very high-quality materials and components. Because of the way in which they are manufactured, these lights are able to maintain their performance in temperatures ranging from a glacial -4°F to a sultry +140°C. They are also highly corrosion resistant, thanks to their use of 6060 aluminum alloy and 10-micron anodization.

Safety systems

We have developed a variety of corrosion protection technology to maximize the lifespan of our lights. They also have overtension and electrical discharge protection, TCS® to protect their circuits from moisture.



Wall-mounted versions

- Multiple fixing sizes for grazing installations
- Graduated body rotation
- Antiglare shade
- Five sizes, from 14.2 to 59.1 inch
- Optics: flood, Narrow Flood , wide flood, asymmetric, general



Recessed versions

- Extra-thin housing: frame only 0.12 inch thick
- Individual fixtures don't have end caps, allowing multiple lights to be installed back to back to create a continuous run.
- End caps can then be placed at the end of the run and adapted to the housing so that the whole body of the luminaire is enclosed.
- Anti-glare shade (darklight)
- Five lengths available, from nominal 14" to 60"
- Variety of optics: from narrow spot to wide flood, asymmetric, and general illumination

Xenia_W | Linear profiles | 24V | topLED | Wet location | Driver remote











6.5W

Anod. Al.	**E93786**	2700K 764 lm	**M**	Narrow Flood	**20**
		3000K 801 lm	**W**	Flood	**50**
		3500K 801 lm	**T**	Wide Flood	**90**
		4000K 838 lm	**N**	Asymmetric	**07**
				General	**00**

13W

Anod. Al.	**E93825**	2700K 1528 lm	**M**	Narrow Flood	**20**
		3000K 1602 lm	**W**	Flood	**50**
		3500K 1602 lm	**T**	Wide Flood	**90**
		4000K 1676 lm	**N**	Asymmetric	**07**
				General	**00**

20W

Anod. Al.	**E93828**	2700K 2292 lm	**M**	Narrow Flood	**20**
		3000K 2403 lm	**W**	Flood	**50**
		3500K 2403 lm	**T**	Wide Flood	**90**
		4000K 2514 lm	**N**	Asymmetric	**07**
				General	**00**

26W

Anod. Al.	**E93829**	2700K 3056 lm	**M**	Narrow Flood	**20**
		3000K 3204 lm	**W**	Flood	**50**
		3500K 3204 lm	**T**	Wide Flood	**90**
		4000K 3352 lm	**N**	Asymmetric	**07**
				General	**00**

33W

Anod. Al.	**E81696**	2700K 3820 lm	**M**	Narrow Flood	**20**
		3000K 4005 lm	**W**	Flood	**50**
		3500K 4005 lm	**T**	Wide Flood	**90**
		4000K 4190 lm	**N**	Asymmetric	**07**
				General	**00**

Steel fixing brackets

1.8-2.6 in	**E98949**
3.5 in	**E89045**
5.9 in	**E89046**
11.8 in	**E89047**

Anti-glaring accessory

14.4 in	**E98782**
24.8 in	**E98783**
36.6 in	**E98784**
48.4 in	**E98785**
60.2 in	**E99778**

Cables

E99216	**E89190**	**E98437**	**E98149**	**E89188**
59 in. line volt. power feed cable F 7 pin M12	196 in. line volt. power feed cable F 7 pin M12	39 in. line volt. power extension cable M+F 7 pin M12	196 in. line volt. power extension cable M+F 7 pin M12	393 in. line volt. power extension cable M+F 7 pin M12

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

index
technical information

Xenia_W ON/OFF | Linear pro iles | 120/277V | topLED | Wet location | Integral Driver











7.2W

Anod. Al.	On/Off	**E93688**	2700K	764 lm	**M**	Narrow Flood **20**
			3000K	801 lm	**W**	Medium Flood **50**
			3500K	801 lm	**T**	Flood **90**
			4000K	838 lm	**N**	Asymmetric **07**
						General **00**

14.2W

Anod. Al.	On/Off	**E93689**	2700K	1528 lm	**M**	Narrow Flood **20**
			3000K	1602 lm	**W**	Medium Flood **50**
			3500K	1602 lm	**T**	Flood **90**
			4000K	1676 lm	**N**	Asymmetric **07**
						General **00**

21.4W

Anod. Al.	On/Off	**E94020**	2700K	2292 lm	**M**	Narrow Flood **20**
			3000K	2403 lm	**W**	Medium Flood **50**
			3500K	2403 lm	**T**	Flood **90**
			4000K	2514 lm	**N**	Asymmetric **07**
						General **00**

27.8W

Anod. Al.	On/Off	**E94023**	2700K	3056 lm	**M**	Narrow Flood **20**
			3000K	3204 lm	**W**	Medium Flood **50**
			3500K	3204 lm	**T**	Flood **90**
			4000K	3352 lm	**N**	Asymmetric **07**
						General **00**

37W

Anod. Al.	On/Off	**E81695**	2700K	3820 lm	**M**	Narrow Flood **20**
			3000K	4005 lm	**W**	Medium Flood **50**
			3500K	4005 lm	**T**	Flood **90**
			4000K	4190 lm	**N**	Asymmetric **07**
						General **00**

Steel fixing brackets

1.8-2.6 in	**E98949**
3.5 in	**E89045**
5.9 in	**E89046**
11.8 in	**E89047**

Anti-glaring accessory

14.4 in	**E98782**
24.8 in	**E98783**
36.6 in	**E98784**
48.4 in	**E98785**
60.2 in	**E99778**

Cables

E83043	**E83044**	**E83045**	**E83046**	**E83047**
59 in. line volt. power feed cable F 3 pin M12	196 in. line volt. power feed cable F 3 pin M12	39 in. line volt. power extension cable M+F 3 pin M12	196 in. line volt. power extension cable M+F 3 pin M12	393 in. line volt. power extension cable M+F 3 pin M12

index
technical information

Xenia_W RGBW DMX | Linear profiles | 24V + Integral DMX Interface | topLED | Wet location | Driver remote

RGBW
Quad-chip LED





13W

Anod. Al.	**E84047**	RGBW natural white	**Q**	Narrow Flood	**20**
		RGBW warm white	**V**	Flood	**50**
				Wide Flood	**90**
				Asymmetric	**07**
				General	**00**

24W

Anod. Al.	**E84048**	RGBW natural white	**Q**	Narrow Flood	**20**
		RGBW warm white	**V**	Flood	**50**
				Wide Flood	**90**
				Asymmetric	**07**
				General	**00**

Power supply options (remote only. DMX control required/by others)

OT96-D010*

Osram, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure. *Must be wired as non-dim.

OT96-JBX

Osram, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure.

Steel fixing brackets

1.8-2.6 in	**E98949**
3.5 in	**E89045**
5.9 in	**E89046**
11.8 in	**E89047**

Anti-glaring accessory

19.7 in	**E98953**
46.5 in	**E98952**

Cables

E99216
59 in. low volt. power feed cable F 4 pin M12

E89190
196 in. low volt. power feed cable F 4 pin M12

E98437
39 in. low volt. power extension cable M+F 4 pin M12

E98149
196 in. low volt. power extension cable M+F 4 pin M12

E89188
393 in. low volt. power extension cable M+F 4 pin M12

E89189
196 in DMX cable M 5 pin M12

E89186
196 in DMX cable M 5 pin M12 + M 3 pin XLR

E98494
196 in DMX cable M 5 pin M12 + F 3 pin XLR

E98493
196 in DMX cable M 5 pin M12 + M 5 pin XLR

E98994
39 in DMX extension 0-10V M+F 5 pin M12

E98993
196 in DMX extension 0-10V M+F 5 pin M12

E89187
393 in DMX extension 0-10V M+F 5 pin M12

index
technical information

Xenia_W PRO | Linear profiles | 120/277V | powerLED | Wet location | Integral Driver



9W

Anod. Al.	On/Off	**E81702**	2700K 956 lm	**M**	Narrow Spot	**08**
			3000K 1025 lm	**W**	Narrow Flood	**20**
			3500K 1025 lm	**T**	Flood	**50**
			4000K 1164 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



17.1W

Anod. Al.	On/Off	**E81703**	2700K 1835 lm	**M**	Narrow Spot	**08**
			3000K 1964 lm	**W**	Narrow Flood	**20**
			3500K 1964 lm	**T**	Flood	**50**
			4000K 2238 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



26.2W

Anod. Al.	On/Off	**E81704**	2700K 2753 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E81709**	3000K 2946 lm	**W**	Narrow Flood	**20**
			3500K 2946 lm	**T**	Flood	**50**
			4000K 3357 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



35.4W

Anod. Al.	On/Off	**E81705**	2700K 3671 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E81710**	3000K 3928 lm	**W**	Narrow Flood	**20**
			3500K 3928 lm	**T**	Flood	**50**
			4000K 4476 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



44W

Anod. Al.	On/Off	**E81706**	2700K 4588 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E81711**	3000K 4910 lm	**W**	Narrow Flood	**20**
			3500K 4910 lm	**T**	Flood	**50**
			4000K 5594 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**

On/Off



0-10V

Steel fixing brackets

1.8-2.6 in	**E98949**
3.5 in	**E89045**
5.9 in	**E89046**
11.8 in	**E89047**

Anti-glaring accessory

14.4 in	**E98782**
24.8 in	**E98783**
36.6 in	**E98784**
48.4 in	**E98785**
60.2 in	**E99778**

Cables

E83043	**E83044**	**E83045**	**E83046**	**E83047**
59 in. line volt. power feed cable F 3 pin M12	196 in. line volt. power feed cable F 3 pin M12	39 in. line volt. power extension cable M+F 3 pin M12	196 in. line volt. power extension cable M+F 3 pin M12	393 in. line volt. power extension cable M+F 3 pin M12

E89189	**E98994**	**E98993**	**E89187**
196.9 in 0-10V cable M 5 pin M12	39.4 in 0-10V extension M+F 5 pin M12	196.9 in 0-10V extension M+F 5 pin M12	393.7 in 0-10V extension M+F 5 pin M12

index
technical information

Xenia_W Pro RGBW DMX | Linear profiles | 120/277V + Integral DMX Interface | powerLED | Wet location





8.5 W

Anod. Al.	**E84049**	RGBW natural white	**Q**	Elliptic	**25**
3 x 4 LEDs		RGBW warm white	**V**		

22.6 W

Anod. Al.	**E84050**	RGBW natural white	**Q**	Elliptic	**25**
8 x 4 LEDs		RGBW warm white	**V**		

Steel fixing brackets

1.8-2.6 in	**E98949**
3.5 in	**E89045**
5.9 in	**E89046**
11.8 in	**E89047**

Anti-glaring accessory

19.7 in	**E98951**
46.5 in	**E98952**

Cables

E83043
59 in. line volt. power feed cable F 3 pin M12

E83044
196 in. line volt. power feed cable F 3 pin M12

E83045
39 in. line volt. power extension cable M+F 3 pin M12

E83046
196 in. line volt. power extension cable M+F 3 pin M12

E83047
393 in. line volt. power extension cable M+F 3 pin M12

E89189
196.9 in DMX cable M 5 pin M12

E89186
196.9 in DMX cable M 5 pin M12 + M 3 pin XLR

E98494
196.9 in DMX cable M 5 pin M12 + F 3 pin XLR

E98493
196.9 in DMX cable M 5 pin M12 + M 5 pin XLR

E98994
39.4 in DMX extension 0-10V M+F

E98993
196.9 in DMX extension 0-10V M+F

E89187
393.7 in DMX extension 0-10V M+F

index
technical information

Xenia_A | Linear profiles | 24V | topLED | Wet location | Driver remote | Drive over | 6.1W/ft



6.5W

Anod. Al.	**E81453**	2700K	764 lm	**M**	Narrow Flood	**20**
		3000K	801 lm	**W**	Flood	**50**
		3500K	801 lm	**T**	Wide Flood	**90**
		4000K	838 lm	**N**	Asymmetric	**07**



13W

Anod. Al.	**E81454**	2700K	1528 lm	**M**	Narrow Flood	**20**
		3000K	1602 lm	**W**	Flood	**50**
		3500K	1602 lm	**T**	Wide Flood	**90**
		4000K	1676 lm	**N**	Asymmetric	**07**



19.5W

Anod. Al.	**E81455**	2700K	2292 lm	**M**	Narrow Flood	**20**
		3000K	2403 lm	**W**	Flood	**50**
		3500K	2403 lm	**T**	Wide Flood	**90**
		4000K	2514 lm	**N**	Asymmetric	**07**



26W

Anod. Al.	**E81456**	2700K	3056 lm	**M**	Narrow Flood	**20**
		3000K	3204 lm	**W**	Flood	**50**
		3500K	3204 lm	**T**	Wide Flood	**90**
		4000K	3352 lm	**N**	Asymmetric	**07**



32.5W

Anod. Al.	**E81621**	2700K	3820 lm	**M**	Narrow Flood	**20**
		3000K	4005 lm	**W**	Flood	**50**
		3500K	4005 lm	**T**	Wide Flood	**90**
		4000K	4190 lm	**N**	Asymmetric	**07**

In-grade outer casings

14.17 in	**E99761**
24.4 in	**E99762**
36.2 in	**E99763**
48 in	**E99764**
59.8 in	**E99765**

End caps(pair)
One pair required per in-grade run

E99766

Ceiling or wall recessed installation spring

E99818

Cables

E99216	**E89190**	**E98437**	**E98149**	**E89188**
59 in. low volt. power feed cable F 4 pin M12	196 in. low volt. power feed cable F 4 pin M12	39 in. low volt. power extension cable M+F 4 pin M12	196 in. low volt. power extension cable M+F 4 pin M12	393 in. low volt. power extension cable M+F 4 pin M12

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

index
technical information

Xenia_A RGBW DMX | Linear profiles | 120/277V + Integral DMX interface | topLED | Wet location | Integral Driver | Drive over



RGBW
Quad-chip LED



13W

Anod. Al. **E84051**

RGBW natural white	**Q**	Narrow Flood	**20**
RGBW warm white	**V**	Flood	**50**
		Wide Flood	**90**
		Asymmetric	**07**

24W

Anod. Al. **E84052**

RGBW natural white	**Q**	Narrow Flood	**20**
RGBW warm white	**V**	Flood	**50**
		Wide Flood	**90**
		Asymmetric	**07**

Cables

E83043
59 in. line volt. power feed cable F 3 pin M12

E83044
196 in. line volt. power feed cable F 3 pin M12

E83045
39 in. line volt. power extension cable M+F 3 pin M12

E83046
196 in. line volt. power extension cable M+F 3 pin M12

E83047
393 in. line volt. power extension cable M+F 3 pin M12

E89189
196 in DMX cable M 5 pin M12

E89186
196 in DMX cable M 5 pin M12 + M 3 pin XLR

E98494
196 in DMX cable M 5 pin M12 + F 3 pin XLR

E98493
196 in DMX cable M 5 pin M12 + M 5 pin XLR

E98994
39 in DMX extension 0-10V M+F 5 pin M12

E98993
196 in DMX extension 0-10V M+F 5 pin M12

E89187
393 in DMX extension 0-10V M+F 5 pin M12

In-grade Outer casings

14.17 in	**E99761**
24.4 in	**E99762**
36.2 in	**E99763**
48 in	**E99764**
59.8 in	**E99765**

End caps(pair)
One pair required per in-grade run

E99766

Ceiling or wall recessed installation spring

E99818

Cables

E99216
59 in. low volt. power feed cable F 4 pin M12

E89190
196 in. low volt. power feed cable F 4 pin M12

E98437
39 in. low volt. power extension cable M+F 4 pin M12

E98149
196 in. low volt. power extension cable M+F 4 pin M12

E89188
393 in. low volt. power extension cable M+F 4 pin M12

E89189
196 in DMX cable M 5 pin M12

E89186
196.9 in DMX cable M 5 pin M12 + M 3 pin XLR

E98494
196.9 in DMX cable M 5 pin M12 + F 3 pin XLR

E98493
196.9 in DMX cable M 5 pin M12 + M 5 pin XLR

E98994
39.4 in DMX extension M+F 5 pin M12

E98993
196.9 in DMX extension M+F 5 pin M12

E89187
393.7 in DMX extension M+F 5 pin M12

index
technical information

Xenia_A PRO | Linear profiles | 120/277V | powerLED | Wet location | Integral Driver | Drive over | 7.7W/ft



8.3W

Anod. Al.	On/Off	**E81465**	2700K 764 lm	**M**	Narrow Spot	**08**
			3000K 801 lm	**W**	Narrow Flood	**20**
*120V ONLY			3500K 801 lm	**T**	Flood	**50**
			4000K 838 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



16.5W

Anod. Al.	On/Off	**E81466**	2700K 1528 lm	**M**	Narrow Spot	**08**
			3000K 1602 lm	**W**	Narrow Flood	**20**
*120V ONLY			3500K 1602 lm	**T**	Flood	**50**
			4000K 1676 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



26.2W

Anod. Al.	On/Off	**E81467**	2700K 2292 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E81683**	3000K 2403 lm	**W**	Narrow Flood	**20**
			3500K 2403 lm	**T**	Flood	**50**
			4000K 2514 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



35.4W

Anod. Al.	On/Off	**E81468**	2700K 3056 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E81684**	3000K 3204 lm	**W**	Narrow Flood	**20**
			3500K 3204 lm	**T**	Flood	**50**
			4000K 3352 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**



44W DC

Anod. Al.	On/Off	**E81624**	2700K 3820 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E81685**	3000K 4005 lm	**W**	Narrow Flood	**20**
			3500K 4005 lm	**T**	Flood	**50**
			4000K 4190 lm	**N**	Wide Flood	**90**
					Elliptic	**25**
					Asymmetric	**07**

On/Off



0-10V

In-grade outer casings

14.17 in	**E99761**
24.4 in	**E99762**
36.2 in	**E99763**
48 in	**E99764**
59.8 in	**E99765**

End cap (pair)
One pair required per in-grade run

E99766

Ceiling-or wall recessed installation spring

E99818

Cables

E83043
59 in. line volt. power feed cable F 3 pin M12

E83044
196 in. line volt. power feed cable F 3 pin M12

E83045
39 in. line volt. power extension cable M+F 3 pin M12

E83046
196 in. line volt. power extension cable M+F 3 pin M12

E83047
393 in. line volt. power extension cable M+F 3 pin M12

E89189
196 in 0-10V cable M 5 pin M12

E98994
39 in 0-10V extension M+F 5 pin M12

E98993
196 in 0-10V extension M+F 5 pin M12

E89187
393 in 0-10V extension M+F 5 pin M12

index
technical information

Xenia_A PRO RGBW DMX | Linear profiles | 120/277V + Integral DMX interface | powerLED | Wet location | Integral Driver | Drive over

RGBW





8.5W

Anod. Al.	**E84053**	RGBW natural white	**Q**	Elliptic	**25**
		RGBW warm white	**V**		

22.6W

Anod. Al.	**E84054**	RGBW natural white	**Q**	Elliptic	**25**
		RGBW warm white	**V**		

In-grade outer casings

20.9 in	**E99820**
46.1 in	**E99821**

End cap (pair)
One pair required per in-grade run

E99766

Ceiling-mounted recessed installation spring

E99818

Cables

E83043 59 in. line volt. power feed cable F 3 pin M12	**E83044** 196 in. line volt. power feed cable F 3 pin M12	**E83045** 39 in. line volt. power extension cable M+F 3 pin M12	**E83046** 196 in. line volt. power extension cable M+F 3 pin M12	**E83047** 393 in. line volt. power extension cable M+F 3 pin M12	**E89189** 196.9 in DMX cable M 5 pin M12

E89186 196.9 in DMX cable M 5 pin M12 + M 3 pin XLR	**E98494** 196.9 in DMX cable M 5 pin M12 + F 3 pin XLR	**E98493** 196.9 in DMX cable M 5 pin M12 + M 5 pin XLR	**E98994** 39.4 in DMX extension M+F 5 pin M12	**E98993** 196.9 in DMX extension M+F 5 pin M12	**E89187** 393.7 in DMX extension M+F 5 pin M12

index
technical information

archiline

Archiline is a linear outdoor light offering a high level of luminosity and flexibility. This extremely wide and competitive range is the result of many years' research. Each item is precision engineered using top-quality materials, and each Archiline family offers a range of outputs, with dedicated narrow, wide, eliptical and asymmetric wallwasher beams and optical compartments designed to ensure a uniquely pure beam, easy to plug connectors for simpler installation, various dimming protocols, a choice of monochrome warm and natural white or RGBW, with the colors being mixed in the optic.

Recessed model materials
Anodized 6060 aluminum alloy or AISI 316L stainless steel flange
Extra-clear tempered glass or white ceramic varnished tempered glass diffuser

Wall/ceiling model materials
Anodized 6060 aluminum alloy or AISI 316L stainless steel body
Extra-clear tempered glass diffuser

archiline range

Archiline_F

Archiline_FL

	_F	_F Darklight	_FL
12.6 in	14.5 W	13.5 W	3.6 W
20.1in	22 W	22 W	6 W
39.4 in	44 W	43.5 W	12 W
Finish			
powerLED	2700K 3000K 3500K 4000K RGBW (3K) RGBW (4K)	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K RGBW (3K) RGBW (4K)
Optics	Narrow S. Spot Medium Fl. Flood Elliptical Asymmetric	Spot Medium Fl. Flood Elliptical	General
Driver	120/277VAC On/Off, 0-10V, DMX	120/277VAC On/Off, 0-10V	120/277VAC On/Off, 0-10V, DMX
Fixture	Trimless	Trimless/Draklight Louver	Trimless/Diffused
Continuous runs	Ok	Ok	Ok

Archiline_A

Archiline_I

	_A	_A Darklight	_I	_I Darklight
14.6 in	13.2 W	12 W	-	-
14.8 in	-	-	13 W	12 W
22.1 in	20 W	20 W	-	-
22.2 in	-	-	20 W	20 W
41.4 in	40 W	40 W	-	-
41.9 in	-	-	40 W	40 W
Finish				
powerLED	2700K 3000K 3500K 4000K RGB+W RGB+N	2700K 3000K 3500K 4000K	2700K 3000K 3500K 4000K RGB+W RGB+N	2700K 3000K 3500K 4000K
Optics	Narrow S. Spot Medium Fl. Flood Elliptical Asymmetric	Spot Medium Fl. Flood Elliptical	Narrow S. Spot Medium Fl. Flood Elliptical Asymmetric	Spot Medium Fl. Flood Elliptical
Driver	120/277VAC On/Off, 0-10V, DMX	120/277VAC On/Off, 0-10V	120/277VAC On/Off, 0-10V, DMX	120/277VAC On/Off, 0-10V
Fixture	Alluminum Flange	Alluminum Flange/Draklight Louver	Stainless Steel Flange	Stainless Steel Flange/ Draklight Louver
Continuous runs	Not recommended	Not recommended	Not recommended	Not recommended

High-quality construction

Archiline bodies are made from extruded 6060 aluminum alloy Anodized to 10 microns.

These two processes provide superior passive heat dissipation and, most importantly, higher corrosion resistance.

The caps are diecast.



RGBW

Safety systems

We have developed a variety of corrosion protection technology to maximize the lifespan of our lights.

They also have overtension and electrical discharge protection, TCS® to shield their circuits from moisture, and AquaStop® water protection.

AquaStop

The range

The Archiline range comprises four subranges of recessed mountings.

- ARCHILINE_F: trimless with extra-clear 0.5-inch tempered glass and black-screenprinted optical compartment, with or without darklight or in RGBW. Designed for wall illumination, and can be placed in continuous runs.

- ARCHILINE_FL: trimless with extra-clear 0.5-inch tempered glass and white ceramic varnish, monochrome or RGBW versions. Designed for path marking in parks, squares, drives, and public spaces. Can be placed in continuous runs.

- ARCHILINE_A: 6060 aluminum alloy flange with extra-clear 0.5-inch tempered glass and black-screenprinted optical compartment, with or without darklight or in darklight+RGBW. Designed for wall illumination. Not recommended for continuous runs.

- ARCHILINE_I: AISI 316L stainless steel flange with extra-clear 0.5-inch tempered glass and black-screenprinted optical compartment, with or without darklight or in darklight+RGBW. Designed for wall illumination. Not recommended for continuous runs.



Optics

The Archiline range has optics for every type of design need.
- SPOT and NARROW SPOT for accent lighting
- FLOOD and MEDIUM FLOOD for soft lighting of parts of walls
- ELLIPTIC 20°x50°, which projects an oval beam, ideal for grazing illumination of high and narrow walls
- ASYMMETRIC for a wallwasher effect.

Other features:
- Darklight versions, which section the beam by eliminating the direct component to the exterior and lighting only the wall
- Ability to create continuous lines without affecting the evenness of the light near the ends of each module. In the Archiline_F no-darklight versions, the diodes are arranged so as to maintain the same distance between each one, and between the last ones at each end.

ARCHILINE standard

ARCHILINE darklight



Archiline_F | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Drive over Max. 11,203lbs | 13W/ft



On/Off 13W

Anod. Bk.	On/Off	**E92127**	2700K	1686 lm	**M**	Narrow Spot	**08**
Anod. Bk.	0-10V	**E83530**	3000K	1686 lm	**W**	Spot	**15**
6 LEDs			3500K	1806 lm	**T**	Medium Flood	**30**
			4000K	1806 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98724
Outer casing



On/Off 20W

Anod. Bk.	On/Off	**E92128**	2700K	2529 lm	**M**	Narrow Spot	**08**
Anod. Bk.	0-10V	**E83531**	3000K	2529 lm	**W**	Spot	**15**
9 LEDs			3500K	2709 lm	**T**	Medium Flood	**30**
			4000K	2709 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98725
Outer casing



On/Off 40W

Anod. Bk.	On/Off	**E92129**	2700K	5058 lm	**M**	Narrow Spot	**08**
Anod. Bk.	0-10V	**E83532**	3000K	5058 lm	**W**	Spot	**15**
18 LEDs			3500K	5418 lm	**T**	Medium Flood	**30**
			4000K	5418 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98726
Outer casing

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline_F Anti-glare | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Drive over Max. 11,203lbs | 13W/ft



On/Off 12W

Anod. Bk.	On/Off	**E92049**	2700K	1716 lm	**M**	Spot	**15**
Anod. Bk.	0-10V	**E83533**	3000K	1716 lm	**W**	Medium Flood	**30**
11 LEDs			3500K	1716 lm	**T**	Flood	**60**
			4000K	1837 lm	**N**	Elliptical	**25**

Installation accessories

E98724
Outer casing



On/Off 20W

Anod. Bk.	On/Off	**E92050**	2700K	2808 lm	**M**	Spot	**15**
Anod. Bk.	0-10V	**E83534**	3000K	2808 lm	**W**	Medium Flood	**30**
18 LEDs			3500K	2808 lm	**T**	Flood	**60**
			4000K	3006 lm	**N**	Elliptical	**25**

Installation accessories

E98725
Outer casing



On/Off 40W

Anod. Bk.	On/Off	**E92051**	2700K	5616 lm	**M**	Spot	**15**
Anod. Bk.	0-10V	**E83535**	3000K	5616 lm	**W**	Medium Flood	**30**
36 LEDs			3500K	5616 lm	**T**	Flood	**60**
			4000K	6012 lm	**N**	Elliptical	**25**

Installation accessories

E98726
Outer casing

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin





index
technical information

Archiline_F RGBW DMX | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Drive over Max. 11,203lbs | 14.9 W/ft



13W CRI80

Anod.Bk. **E92083**	RGBW natural white	**Q**	Spot	**15**
3 x 4 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**60**
			Elliptical	**25**
			Asymmetric	**27**

Installation accessories

E98724
Outer casing



22W CRI80

Anod.Bk. **E92084**	RGBW natural white	**Q**	Spot	**15**
5 x 4 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**60**
			Elliptical	**25**
			Asymmetric	**27**

Installation accessories

E98725
Outer casing



44W CRI80

Anod.Bk. **E92093**	RGBW natural white	**Q**	Spot	**15**
10 x 4 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**60**
			Elliptical	**25**
			Asymmetric	**27**

Installation accessories

E98726
Outer casing

Cables power+DMX

E98660	**E98661**	**E98662**	**E98663**	**E98986**
39.4 in feed cable all in one power + DMX M+F 6 pin shield	196.9 in feed cable all in one power + DMX M+F 6 pin shield	39.4 in extension all in one power + DMX M+F 6 pin shield	196.9 in extension all in one power + DMX M+F 6 pin shield	DMX 120Ω terminator

index
technical information

Archiline_FL | Linear profiles | 120-277V | topLED | Wet location IP67 | Integral Driver | Drive over Max. 11,203lbs | 3.5W/ft



3.5W

Anod.Bk.	On/Off	**E92138**	2700K	458 lm	**M**	General	**00**
Anod.Bk.	0-10V	**E83526**	3000K	483 lm	**W**		
			3500K	483 lm	**T**		
			4000K	504 lm	**N**		

Installation accessories

E98724
Outer casing



6W

Anod.Bk.	On/Off	**E92139**	2700K	785 lm	**M**	General	**00**
Anod.Bk.	0-10V	**E83527**	3000K	828 lm	**W**		
			3500K	828 lm	**T**		
			4000K	864 lm	**N**		

Installation accessories

E98725
Outer casing



12W

Anod.Bk.	On/Off	**E92142**	2700K	1570 lm	**M**	General	**00**
Anod.Bk.	0-10V	**E83528**	3000K	1656 lm	**W**		
			3500K	1656 lm	**T**		
			4000K	1728 lm	**N**		

Installation accessories

E98726
Outer casing

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline_FL RGBW DMX | Linear profiles | 120-277V | topLED | Wet location IP67 | Integral Driver | Drive over Max. 11,203lbs | 8.5W/ft

RGBW
Quad-chip LED



8.5W CRI80

Anod.Bk.	**E92143**	RGBW natural white	**Q**	General	**00**
		RGBW warm white	**V**		

Installation accessories

E98724
Outer casing



14W CRI80

Anod.Bk.	**E92144**	RGBW natural white	**Q**	General	**00**
		RGBW warm white	**V**		

Installation accessories

E98725
Outer casing



24W CRI80

Anod.Bk.	**E92145**	RGBW natural white	**Q**	General	**00**
		RGBW warm white	**V**		

Installation accessories

E98726
Outer casing

Cables power+DMX

E98660	**E98661**	**E98662**	**E98663**	**E98986**
39.4 in feed cable all in one power + DMX M+F 6 pin shield	196.9 in feed cable all in one power + DMX M+F 6 pin shield	39.4 in extension all in one power + DMX M+F 6 pin shield	196.9 in extension all in one power + DMX M+F 6 pin shield	DMX 120Ω terminator

index
technical information

Note: Source lumens shown

Archiline_A | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Walk over | 11.5W/ft



13W

Anod. Al.	On/Off	**E92132**	2700K	1686 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E83536**	3000K	1686 lm	**W**	Spot	**15**
6 LEDs			3500K	1686 lm	**T**	Medium Flood	**30**
			4000K	1806 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98671
Outer casing



20W

Anod. Al.	On/Off	**E92134**	2700K	2529 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E83537**	3000K	2529 lm	**W**	Spot	**15**
9 LEDs			3500K	2529 lm	**T**	Medium Flood	**30**
			4000K	2709 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories



E98672
Outer casing



40W

Anod. Al.	On/Off	**E92136**	2700K	5058 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E83538**	3000K	5058 lm	**W**	Spot	**15**
18 LEDs			3500K	5058 lm	**T**	Medium Flood	**30**
			4000K	5418 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98673
Outer casing



59W

Anod. Al.	On/Off	**E81590**	2700K	7171 lm	**M**	Narrow Spot	**08**
Anod. Al.	0-10V	**E83539**	3000K	7171 lm	**W**	Spot	**15**
27 LEDs			3500K	7171 lm	**T**	Medium Flood	**30**
			4000K	7667 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E99760
Outer casing

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline_A Anti-glare | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Walk over | 11.5W/ft



12W

Anod. Al.	On/Off	**E92052**	2700K	1716 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83540**	3500K	1716 lm	**T**	Flood	**60**
			4000K	1837 lm	**N**	Elliptical	**25**

11 LEDs

Installation accessories

E98671
Outer casing



20W

Anod. Al.	On/Off	**E92054**	2700K	2808 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83541**	3000K	2808 lm	**W**	Medium Flood	**30**
			3500K	2808 lm	**T**	Flood	**60**
			4000K	3006 lm	**N**	Elliptical	**25**

18 LEDs

Installation accessories



E98672
Outer casing



40W

Anod. Al.	On/Off	**E92056**	2700K	5616 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83542**	3000K	5616 lm	**W**	Medium Flood	**30**
			3500K	5616 lm	**T**	Flood	**60**
			4000K	6012 lm	**N**	Elliptical	**25**

36 LEDs

Installation accessories

E98673
Outer casing

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline_A RGBW DMX | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Walk over | 11.5W/ft



13W CRI80

Anod. Al. **E92100**	RGBW natural white	**Q**	Spot	**15**
3 x 4 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**60**
			Elliptical	**25**
			Asymmetric	**27**

Installation accessories



E98671
Outer casing



22W CRI80

Anod. Al. **E92104**	RGBW natural white	**Q**	Spot	**15**
5 x 4 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**60**
			Elliptical	**25**
			Asymmetric	**27**

Installation accessories



E98672
Outer casing



44W CRI80

Anod. Al. **E92108**	RGBW natural white	**Q**	Spot	**15**
10 x 4 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**60**
			Elliptical	**25**
			Asymmetric	**27**

Installation accessories



E98673
Outer casing

Cables power+DMX

E98660	**E98661**	**E98662**	**E98663**	**E98986**
39.4 in feed cable all in one power + DMX M+F 6 pin shield	196.9 in feed cable all in one power + DMX M+F 6 pin shield	39.4 in extension all in one power + DMX M+F 6 pin shield	196.9 in extension all in one power + DMX M+F 6 pin shield	DMX 120Ω terminator

index
technical information

Archiline_I | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Walk over | 11.5W/ft



13W

Steel	On/Off	**E92124**	2700K	1686 lm	**M**	Narrow Spot	**08**
Steel	0-10V	**E83543**	3000K	1686 lm	**W**	Spot	**15**
6 LEDs			3500K	1806 lm	**T**	Medium Flood	**30**
			4000K	1806 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98671
Outer casing



20W AC

Steel	On/Off	**E92125**	2700K	2529 lm	**M**	Narrow Spot	**08**
Steel	0-10V	**E83544**	3000K	2529 lm	**W**	Spot	**15**
12 LEDs			3500K	2709 lm	**T**	Medium Flood	**30**
			4000K	2709 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98672
Outer casing



40W

Steel	On/Off	**E92126**	2700K	5058 lm	**M**	Narrow Spot	**08**
Steel	0-10V	**E83545**	3000K	5058 lm	**W**	Spot	**15**
18 LEDs			3500K	5418 lm	**T**	Medium Flood	**30**
			4000K	5418 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Installation accessories

E98673
Outer casing

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline_I Anti-glare | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Walk over | 11.5W/ft



12W

Steel	On/Off	**E92046**	2700K	1716 lm	**M**	Spot	**15**
Steel	0-10V	**E83546**	3000K	1716 lm	**W**	Medium Flood	**30**
11 LEDs			3500K	1716 lm	**T**	Flood	**60**
			4000K	1837 lm	**N**	Elliptical	**25**

Installation accessories

E98671
Outer casing



20W

Steel	On/Off	**E92047**	2700K	2808 lm	**M**	Spot	**15**
Steel	0-10V	**E83547**	3000K	2808 lm	**W**	Medium Flood	**30**
18 LEDs			3500K	2808 lm	**T**	Flood	**60**
			4000K	3006 lm	**N**	Elliptical	**25**

Installation accessories

E98672
Outer casing



40W

Steel	On/Off	**E92048**	2700K	5616 lm	**M**	Spot	**15**
Steel	0-10V	**E83548**	3000K	5616 lm	**W**	Medium Flood	**30**
36 LEDs			3500K	5616 lm	**T**	Flood	**60**
			4000K	6012 lm	**N**	Elliptical	**25**

Installation accessories

E98673
Outer casing

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

GRUPPOUNICA
PALAZZO MOLA

Archiline_I RGBW DMX | Linear profiles | powerLED | 120-277V | Wet location IP67 | Integral Driver | Walk over | 14.9W/ft

RGBW



13W CRI80

Steel	E92080	RGBW natural white	Q	Spot	15
3 x 4 LEDs		RGBW warm white	V	Medium Flood	30
				Flood	60
				Elliptical	25
				Asymmetric	27

Installation accessories



E98671
Outer casing



22W CRI80

Steel	E92081	RGBW natural white	Q	Spot	15
5 x 4 LEDs		RGBW warm white	V	Medium Flood	30
				Flood	60
				Elliptical	25
				Asymmetric	27

Installation accessories

E98672
Outer casing



44W CRI80

Steel	E92082	RGBW natural white	Q	Spot	15
10 x 4 LEDs		RGBW warm white	V	Medium Flood	30
				Flood	60
				Elliptical	25
				Asymmetric	27

Installation accessories

E98673
Outer casing

Cables power+DMX

E98660	E98661	E98662	E98663	E98986
39.4 in feed cable all in one power + DMX M+F 6 pin shield	196.9 in feed cable all in one power + DMX M+F 6 pin shield	39.4 in extension all in one power + DMX M+F 6 pin shield	196.9 in extension all in one power + DMX M+F 6 pin shield	DMX 120Ω terminator

index
technical information

Archiline PRO_I | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | Walk over | 26W/ft



46W CRI80

Steel	On/Off	**E81673**	2700K	5243 lm	**M**	Spot	**15**
Steel	0-10V	**E83701**	3000K	5243 lm	**W**	Flood	**30**
9 LEDs			3500K	5243 lm	**T**	Medium Flood	**60**
			4000K	5660 lm	**N**	Elliptical	**25**
Steel	On/Off	**E81677**	2700K	5243 lm	**M**	Narrow Spot	**06**
Steel	0-10V	**E83702**	3000K	5243 lm	**W**		
9 LEDs			3500K	5243 lm	**T**		
			4000K	5660 lm	**N**		

Installation accessories

99771
Outer casing

Cables On/Off

E99057
78.7 in power supply cable F 3 pin

E98147
196.9 in extension M+F 3 pin

E98146
393.7 in extension M+F 3 pin

Cables 0-10V

E99826
39.4 in power supply cable + 0-10V dimming F 5 pin

E99822
196.9 in power supply cable + 0-10V dimming F 5 pin

E99823
39.4 in extension cable for power + 0-10V dimming M+F 5 pin

E99824
196.9 in extension cable for power + 0-10V dimming M+F 5 pin

E99825
393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline PRO_I RGBW DMX | Linear profiles | powerLED | 120-277V | Wet location IP67 | Integral Driver | Walk over | 26W/ft



RGBW
Quad-chip LED

44W CRI80

Steel **E81675**	RGBW natural white	**Q**	Spot	**15**
9 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**45**
			Elliptical	**25**
Steel **E81679**	RGBW natural white	**Q**	Narrow Spot	**06**
9 LEDs	RGBW warm white	**V**		

Installation accessories



E99771
Outer casing



86W CRI80

Steel **E81676**	RGBW natural white	**Q**	Spot	**15**
18 LEDs	RGBW warm white	**V**	Medium Flood	**30**
			Flood	**45**
			Elliptical	**25**
Steel **E81680**	RGBW natural white	**Q**	Narrow Spot	**06**
18 LEDs	RGBW warm white	**V**		

Installation accessories

E99830
Outer casing

Cables power+DMX

E98660	**E98661**	**E98662**	**E98663**	**E98986**
39.4 in feed cable all in one power + DMX M+F 6 pin shield	196.9 in feed cable all in one power + DMX M+F 6 pin shield	39.4 in extension all in one power + DMX M+F 6 pin shield	196.9 in extension all in one power + DMX M+F 6 pin shield	DMX 120Ω terminator

index
technical information

Archiline_F / _FL | Outer casing for trimless luminaires for floor-mounted recessed installation



Anod. Bk.	12.7 in x Archiline_F / _FL	**E98724**
Anod. Bk.	20.2 in x Archiline_F / _FL	**E98725**
Anod. Bk.	39.5 in x Archiline_F / _FL	**E98726**

These outer casings allow to create a continuous run

Installation accessories

E98957
The tool you need to extract Archiline from the Outer casing.

Anodization
Anodization is carried out in electrochemically controlled conditions, and creates a layer of oxide on the surface of the aluminum. This has excellent levels of adherence, compactness, hardness, and corrosion resistance.

Drive-over capability
The housings of the Archiline_F and FL versions have tempered glass, 0.47-inch ceramic powder coating, and will support a weight of up to five tonnes.





Archiline_A / _I | Outer casing for luminaires with trim, for floor-mounted recessed installation



Anod. Bk.	14in x Archiline_A / _I	**E98671**
Anod. Bk.	21.5 in x Archiline_A / _I	**E98672**
Anod. Bk.	40.8 in x Archiline_A / _I	**E98673**
Anod. Bk.	60.1 in x Archiline_A / _I	**E99760**



Galvanization
The housings of the Archiline_A and I versions are galvanized for improved corrosion resistance and durability.

Drive-over capability
The flange of the Archiline_A is integrated into the extrusion, forming a more durable single unit that can support a weight of up to 1.5 tons.





index
technical information

archiline_W range

Archiline_W

Archiline_W Pro

	_W	**_W** **Anti-glaring**	**_W** **RGBW**
12.6 in	13W	12W	13W
14 in	-	-	-
20.3 in	-	-	-
24.4 in	24W	24W	26W
36.2 in	37.5W	36W	40W
39.4 in	-	-	-
48 in	48.5W	48.5W	53W
Finish	■	■	■
powerLED	3000K 3500K 4000K	3000K 3500K 4000K	RGBW+W RGBW+N
Optics	Narrow Spot Spot Medium Flood Flood Elliptical Asymmetric	Spot Medium Flood Flood Elliptical	Spot Medium Flood Flood Elliptical Asymmetric
Driver	120/277VAC On/Off, 0-10V	120/277VAC On/Off, 0-10V	120/277VAC DMX

A wide range of applications

Archiline_W is a linear element for installation on the wall itself. It combines the functions of a spot with the shape and size of an outdoor bar.

The body is made from 10-micron- Anodized 6060 extruded aluminum alloy.

Archiline_W has an adjustable graduated stainless steel bracket that fixes to a wall or ceiling, and the distance from the wall is also adjustable.



DMX 512 | DALI | IK10 | IP67 | RGBW Quad-chip LED

The perfect mix

Combined-optic RGBW technology makes color mixing better and more uniform. This takes place within the optics, using treated lenses optimized for maximum efficiency and high-performance RGBW LEDs. One diode combines pure warm or natural white and red, green and blue, mixing the colors better than traditional systems and creating an infinite variety of shades, as well as obtaining pure white without the influence of the RGB. The optical compartment is screenprinted in black, with dark-light screening giving perfect control over glare, sectioning the beam to eliminate the direct outward component and lighting only the wall.

Perfect mixing



State-of-the-art engineering: Archiline_W PRO

The PRO version is the star of the Archiline range, made entirely from dedicated components, including the powerLED diode sources and extremely high-performance integrated drivers. Archiline_W PRO has an efficiency of 100 lm/W, developing a luminous flux of over 3400 lumens per foot! It is therefore strongly recommended for very high walls, thanks partly to its optics covered with 0.2-inch extra-clear glass, black screenprinted edges and high-efficiency elliptical, narrow or flood beam. The 6-degree-optic version will project a beam to a height of 164 feet! Available in an ON/OFF or RGBW version with DMX dimmer protocol. In this model, the power tension and DMX signal both pass through the connector.

Archiline_W | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | 11.5W/ft











13W

Anod. Al.	On/Off	**E92112**	2700K	1686 lm	**M**	Narrow Spot	**06**
Anod. Al.	0-10V	**E83549**	3000K	1686 lm	**W**	Spot	**15**
6 LEDs			3500K	1686 lm	**T**	Medium Flood	**30**
			4000K	1806 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

24W

Anod. Al.	On/Off	**E92114**	2700K	3093 lm	**M**	Narrow Spot	**06**
Anod. Al.	0-10V	**E83550**	3000K	3093 lm	**W**	Spot	**15**
11 LEDs			3500K	3093 lm	**T**	Medium Flood	**30**
			4000K	3307 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Accessories

E98675
Anti-glare flaps

38W

Anod. Al.	On/Off	**E92118**	2700K	4780 lm	**M**	Narrow Spot	**06**
Anod. Al.	0-10V	**E83551**	3000K	4780 lm	**W**	Spot	**15**
17 LEDs			3500K	4780 lm	**T**	Medium Flood	**30**
			4000K	5111 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Accessories

E98676
Anti-glare flaps

49W

Anod. Al.	On/Off	**E92120**	2700K	6185 lm	**M**	Narrow Spot	**06**
Anod. Al.	0-10V	**E83552**	3000K	6185 lm	**W**	Spot	**15**
22 LEDs			3500K	6185 lm	**T**	Medium Flood	**30**
			4000K	6614 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Accessories

E98677
Anti-glare flaps

59W

Anod. Al.	On/Off	**E81513**	2700K	7437 lm	**M**	Narrow Spot	**06**
Anod. Al.	0-10V	**E83553**	3000K	7437 lm	**W**	Spot	**15**
28 LEDs			3500K	7437 lm	**T**	Medium Flood	**30**
			4000K	7951 lm	**N**	Flood	**60**
						Elliptical	**25**
						Asymmetric	**27**

Accessories

E99748
Anti-glare flaps

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline_W Anti-glare | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | 11.5W/ft



12W

Anod. Al.	On/Off	**E92038**	2700K	1686 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83554**	3000K	1686 lm	**W**	Medium Flood	**30**
11 LEDs			3500K	1686 lm	**T**	Flood	**60**
			4000K	1806 lm	**N**	Elliptical	**25**

24W

Anod. Al.	On/Off	**E92040**	2700K	3093 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83555**	3000K	3093 lm	**W**	Medium Flood	**30**
22 LEDs			3500K	3093 lm	**T**	Flood	**60**
			4000K	3307 lm	**N**	Elliptical	**25**

Accessories

E98675
Anti-glare flaps

36W

Anod. Al.	On/Off	**E92042**	2700K	4780 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83556**	3000K	4780 lm	**W**	Medium Flood	**30**
33 LEDs			3500K	4780 lm	**T**	Flood	**60**
			4000K	5111 lm	**N**	Elliptical	**25**

Accessories

E98676
Anti-glare flaps

49W

Anod. Al.	On/Off	**E92044**	2700K	6870 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83557**	3000K	6870 lm	**W**	Medium Flood	**30**
44 LEDs			3500K	6870 lm	**T**	Flood	**60**
			4000K	7346 lm	**N**	Elliptical	**25**

Accessories

E98677
Anti-glare flaps

Cables On/Off

E99057
78.7 in power supply cable F 3 pin

E98147
196.9 in extension M+F 3 pin

E98146
393.7 in extension M+F 3 pin

Cables 0-10V

E99826
39.4 in power supply cable + 0-10V dimming F 5 pin

E99822
196.9 in power supply cable + 0-10V dimming F 5 pin

E99823
39.4 in extension cable for power + 0-10V dimming M+F 5 pin

E99824
196.9 in extension cable for power + 0-10V dimming M+F 5 pin

E99825
393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline_W RGBW DMX | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | 11.5W/ft



13W

Steel	E92070	RGBW natural white	Q	Spot	15
		RGBW warm white	V	Medium Flood	30
				Flood	60
				Elliptical	25
				Asymmetric	27



26W

Steel	E92072	RGBW natural white	Q	Spot	15
		RGBW warm white	V	Medium Flood	30
				Flood	60
				Elliptical	25
				Asymmetric	27

Accessories

E98675
Anti-glare flaps



40W

Steel	E92074	RGBW natural white	Q	Spot	15
		RGBW warm white	V	Medium Flood	30
				Flood	60
				Elliptical	25
				Asymmetric	27

Accessories

E98676
Anti-glare flaps



53W

Steel	E92078	RGBW natural white	Q	Spot	15
		RGBW warm white	V	Medium Flood	30
				Flood	60
				Elliptical	25
				Asymmetric	27

Accessories

E98677
Anti-glare flaps

Cables power+DMX

E98660	E98661	E98662	E98663	E98986
39.4 in feel cable all in one power + DMX M+F 6 pin shield	196.9 in feel cable all in one power + DMX M+F 6 pin shield	39.4 in extension all in one power + DMX M+F 6 pin shield	196.9 in extension all in one power + DMX M+F 6 pin shield	DMX 120Ω terminator

index
technical information

Flap

The flap fixt e is made up of two directional flaps and it has been designed to shape light when the luminaire is used as a spotlight. Please note that light emission is not reduced, but shaped only. This accessory is made of black Anodized aluminum.

type	suitable for	
Anod. Bk.	Archiline_W 24.4 in	**E98675**



type	suitable for	
Anod. Bk.	Archiline_W 36.2 in	**E98676**



type	suitable for	
Anod. Bk.	Archiline_W 48.1 in	**E98677**



Archiline PRO_W | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | 27.5W/ft



32W

Anod. Al.	On/Off	**E90458**	2700K	3629 lm	**M**	Spot	**15**
Anod. Al.	0-10V	**E83703**	3000K	3629 lm	**W**	Flood	**30**
			3500K	3629 lm	**T**	Elliptical	**25**
			4000K	3917 lm	**N**		
Anod. Al.	On/Off	**E81447**	2700K	3629 lm	**M**	Narrow Spot	**06**
Anod. Al.	0-10V	**E83704**	3000K	3629 lm	**W**		
			3500K	3629 lm	**T**		
			4000K	3917 lm	**N**		

Cables On/Off

E99057	**E98147**	**E98146**
78.7 in power supply cable F 3 pin	196.9 in extension M+F 3 pin	393.7 in extension M+F 3 pin

Cables 0-10V

E99826	**E99822**	**E99823**	**E99824**	**E99825**
39.4 in power supply cable + 0-10V dimming F 5 pin	196.9 in power supply cable + 0-10V dimming F 5 pin	39.4 in extension cable for power + 0-10V dimming M+F 5 pin	196.9 in extension cable for power + 0-10V dimming M+F 5 pin	393.7 in extension cable for power + 0-10V dimming M+F 5 pin

index
technical information

Archiline PRO_W RGBW DMX | Linear profiles | 120-277V | powerLED | Wet location IP67 | Integral Driver | 22W/ft



32W

Steel	**E90459**	RGBW natural white	**Q**	Spot	**15**
		RGBW warm white	**V**	Medium Flood	**30**
				Medium Flood	**45**
				Elliptical	**25**
Steel	**E81450**	RGBW natural white	**Q**	Narrow Spot	**06**
		RGBW warm white	**V**		



38W

Steel	**E90462**	RGBW natural white	**Q**	Spot	**15**
		RGBW warm white	**V**	Medium Flood	**30**
				Medium Flood	**45**
				Elliptical	**25**
Steel	**E81451**	RGBW natural white	**Q**	Narrow Spot	**06**
		RGBW warm white	**V**		



76W

Steel	**E90463**	RGBW natural white	**Q**	Spot	**15**
		RGBW warm white	**V**	Medium Flood	**30**
				Medium Flood	**45**
				Elliptical	**25**
Steel	**E81452**	RGBW natural white	**Q**	Narrow Spot	**06**
		RGBW warm white	**V**		

Cables power+DMX

E98662	**E98663**	**E98662**	**E98663**	**E98986**
39.4 in feed cable all in one power + DMX M+F 6 pin shield	196.9 in feed cable all in one power + DMX M+F 6 pin shield	39.4 in extension all in one power + DMX M+F 6 pin shield	196.9 in extension all in one power + DMX M+F 6 pin shield	DMX 120Ω terminator

index
technical information

PESTALOZZI

GIRARD

dirigo

The Dirigo series is a new lighting concept for outdoor spaces. Available as single elements or modules to create continuous lines, it is a ground profile designed to illuminate walkways and other foot traffic areas, and be placed along paths and walls to mark out routes. It can be safely walked on, and its distinctive and award-winning design features a hidden light source that creates controlled, ground-hugging and glare-free illumination.

Materials
Aluminum or AISI 316L stainless steel body

dirigo lighting concept

Concept

Invisible during the day. Main actor during the night. Dirigo creates lighting paths through an elegant opposite plans game, hiding the source. Its peculiar profile's section makes the fixture compact and solid, perfectly integrated in all outdoor contexts.

Technology and materials

Dirigo series available in brushed stainless steel AISI 316L or anodized extruded aluminum with polyester powder pre-coating antioxide treatment.

Dirigo FL (Full Light): Single standalone module (39.4 inch)

Grazing light

The internal Led source gradient was studied for the best lighting distribution, along the pathways.



Range

Dirigo is available as single module or prepared for continuous line installation.

Dirigo FL (Full Light): Single standalone module (39.4 inch)

Sealed profile with light unit and end caps. Requires remote 24VDC driver (s) ordered separately.

Dirigo M (Modular): For continuous installations

Continuous LED strips up to 16.4 feet. Feeds from either end. Minimal light interuption when joining multiple modules beyond 16.4'. Mechanical connection between profiles. Requires remote 24VDC driver (s) ordered separately.

Complete element version

System

**Dirigo Profiles are not field cutable.
Please consult factory for custom Dirigo M2 (Aluminum) lengths.
Dirigo M1 (Stainless Steel) is not customizable.

Robust design

The opposing level structure of Dirigo's single profile makes this appliance particularly sturdy and resistant. The absence of raw edges makes it ideal for public and private outdoor applications.
Dirigo can be walked on and is extremely safe for users.



Dirigo_FL1 Stainless Steel | Linear profiles | stripLED | Wet location | Driver remote | Walk over | 4.4 W/ft



CRI 80

Steel	**E64590**	3000K	900 lm	**W**	General	**00**

Dirigo_FL2 Aluminum | Linear profiles | stripLED | Wet location | Driver remote | Walk over | 4.4W/ft



CRI 80

Anthrachite	**E64643**	3000K	900 lm	**W**	General	**00**
Grey	**E64642**				
DarkBrown	**E64594**				

index
technical information

* Only available in straight runs

Dirigo_M1 Stainless Steel MASTER | Linear profiles



Grey	**E64591**	39.8 in

Master

To be completed with dedicated installation accessories, lighting unit and remote driver

Dirigo_M1 Stainless Steel SECONDARY | Linear profiles



Grey	**E64648**	39.4 in

Secondary

To be completed with dedicated installation accessories, lighting unit and remote driver

ACCESSORIES AND CONFIGURATION



E64592
End caps set

Stainless steel
2 pcs



E64593
Junction set

Stainless steel
1 pc



E62403
Lighting unit

LED strip 4.4W/ft, 3000K, 196.9", with 12" Female connector

E62403N
Lighting unit

LED strip 4.4W/ft, 4000K, 196.9", with 12" Female connector

E89629
Connection cable

Feed cable 39.4", with Male connector

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location



Typical Dirigo M1 configuration
(BOM shown for 3000K)

index
technical information

Dirigo_M2 Aluminum MASTER | Linear profiles



Anthrachite	**E64645**	39.8 in
Grey	**E64644**	39.8 in
DarkBrown	**E64595**	39.8 in

Master

To be completed with dedicated installation accessories, lighting unit and remote driver
* At least Master profile is required per run

Dirigo_M2 Aluminum SECONDARY | Linear profiles



Anthrachite	**E64602**	12 in
Grey	**E64604**	12 in
DarkBrown	**E64600**	12 in
Anthrachite	**E64603**	20 in
Grey	**E64605**	20 in
DarkBrown	**E64601**	20 in
Anthrachite	**E64647**	78.7 in
Grey	**E64646**	78.7 in
DarkBrown	**E64597**	78.7 in

Secondary

To be completed with dedicated installation accessories, lighting unit and remote driver

Dirigo_M2 Aluminum IN-corner | Linear profiles



Anthrachite	**E64664**	19.7 x 19.7 in
Grey	**E64665**	19.7 x 19.7 in
DarkBrown	**E64666**	19.7 x 19.7 in

To be completed with dedicated installation accessories, lighting unit and remote driver

Dirigo_M2 Aluminum OUT-corner | Linear profiles



Anthrachite	**E64667**	19.7 x 19.7 in
Grey	**E64668**	19.7 x 19.7 in
DarkBrown	**E64669**	19.7 x 19.7 in

To be completed with dedicated installation accessories, lighting unit and remote driver

index
technical information

ACCESSORIES AND CONFIGURATION REQUIRED



End caps set

Aluminum
2 pcs

Anthrachite	**E64641**
Grey	**E64640**
DarkBrown	**E64589**



Junction caps

Aluminum
1 pc

Anthrachite	**E64661**
Grey	**E64663**
DarkBrown	**E64662**



E62403
Lighting unit

LED strip 4.4W/ft, 3000K, 196.9", with 12" Female connector

E62403N
Lighting unit

LED strip 4.4W/ft, 4000K, 196.9", with 12" Female connector

E89629
Connection cable

Feed cable 39.4", with Male connector

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location



Typical Dirigo M2 configuration
(BOM shown for Dark Brown finish, 3000K)

index
technical information

accent lighting range index

click images to open product pages

Eyelet65

Eyelet65_R

N6

Eyelet65_Q

N6

Periskop

Periskop

N11

Periskop Narrow

N11

Periskop RGBW

N11

Iris67

Iris67

N17

Iris67 Elliptical

N18





Accent Lighting

N4

eyelet65

Aquastop®

Flower-filled corners and pot-grown shrubs can take on an unexpected beauty with the right lighting.
Eyelet65's extremely small size, user-friendly adjustable bracket and soft, pure beam make it the ideal small light for those garden vignettes, and it also uses AquaStop® water and moisture protection technology.

Materials
Aluminum body

Eyelet65_R | Accent lighting | powerLED | Wet location | Driver remote | Tiltable | 2W 630mA



White	**E91214**	2700K	219 lm	**M**	Spot	**15**
Black	**E91215**	3000K	233 lm	**W**	Medium Flood	**30**
Grey	**E91216**	4000K	249 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for1-16 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Accessories

E98624
Pegs

E98669
Pegs

E99746
Snoot

Eyelet65_Q | Accent lighting | powerLED | Wet location | Driver remote | Tiltable | 2W 630mA



White	**E91217**	2700K	219 lm	**M**	Spot	**15**
Black	**E91219**	3000K	233lm	**W**	Medium Flood	**30**
Grey	**E91220**	4000K	249 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for1-16 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-32 fixtures

Accessories

E98624
Pegs

E98669
Pegs

E99746
Snoot

Eyelet65 with integrated snoot accessory

index
technical information

periskop

Aquastop®

The Periskop outdoor spot is perfect for highlighting individual items. The recessed lens ensures maximum visual comfort, and the aluminum bracket allows the body to be rotated by around 180 degrees to get the end result just right. Periskop is available with spot, flood, and medium flood optics, which can be integrated with accessories to control the beam.

Materials
Aluminum body
Extra-clear tempered glass diffuser

periskop range

		1.8 in	3 in	4.3 in	6.4 in
Periskop	**Power**	6W	8W	17W	33 - 50W
	Accessories	-	◤ ■ ⊛ ⬯	◤ ■ ⊛ ⬯	◤ ■ ⊛ ⬯
	Optics	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood	Spot Medium Flood Flood
Periskop Narrow	**Power**	6W	9W	18W	48W
	Accessories	-	◤	◤	◤
	Optics	Narrow Spot	Narrow Spot	Narrow Spot	Narrow Spot
Finish		□ ■ ■ ■	□ ■ ■ ■	□ ■ ■ ■	□ ■ ■ ■
CCT		2700K 3000K 4000K RGB (4.5 W)	2700K 3000K 4000K RGBW (8 W)	2700K 3000K 4000K RGBW (18 W)	2700K 3000K 4000K RGBW (45 W)
Driver		0-10 V	0-10 V	0-10 V	0-10 V

periskop accessories

Outdoor accessories - Anti-glare

Anti-glare accessories are conceived to reduce light glare.
These accessories are made of black painted aluminum.





Indoor accessories - Honeycomb louvre and elliptic filter

The honeycomb louvre accessory was conceived to reduce light glaring. The elliptic filter allows to create ovalized projections. Available upon request only.

E81168W08



Photometric curve



Light beam



25 LUX | 100 LUX | 250 LUX | 300 LUX | 500 LUX | 1000 LUX



Floor plan

Periskop | Accent lighting | powerLED | Wet location | Driver remote | Tilatble | 6W 500mA



CRI 80

White	**E90519**	2700K	659 lm	**M**	Spot	**15**
Black	**E90520**	3000K	659 lm	**W**	Medium Flood	**30**
Grey	**E90521**	4000K	711 lm	**N**	Flood	**60**
DarkBrown	**E90522**					

Accessories

E98624
Steel Pegs

E99802
Tree belt
List Diameter of strap;
maximum tree size

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive
30W for 1-3 fixtures

SOLO50W-500
0-10V EldoLED SOLOdrive
50W for1-6 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive
100W for 1-12 fixtures

Periskop Narrow | Accent lighting | powerLED | Wet location | Driver remote | Tiltable | 6W 500mA



CRI 80

White	**E81788**	2700K	659 lm	**M**	Narrow Spot	**08**
Black	**E81789**	3000K	659 lm	**W**		
Grey	**E81790**	4000K	711 lm	**N**		
DarkBrown	**E81791**					

Accessories

E98624
Steel Pegs

E99802
Tree belt
List Diameter of strap;
maximum tree size

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive
30W for 1-3 fixtures

SOLO50W-500
0-10V EldoLED SOLOdrive
50W for1-6 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive
100W for 1-12 fixtures

Periskop RGB | Accent lighting | powerLED | Wet location | Driver remote | Tiltable | 4.5W 500mA

RGB



CRI 80

White	**E95068**	RGB	**Z**	Spot	**15**
Black	**E95126**			Flood	**60**
Grey	**E95141**				
DarkBrown	**E95330**				

Accessories

E98624
Steel Pegs

E99802
Tree belt
List Diameter of strap;
maximum tree size

Power supply options (remote only)

PWR50W - 500

DMX driver,
EldoLED POWERdrive 50W Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately
50W for 1 Fixture

index
technical information

Periskop | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 6.5W 700mA



CRI 80

White	E95346	2700K	770 lm	M	Spot	15
Black	E95347	3000K	770 lm	W	Medium Flood	30
Grey	E95348	4000K	831 lm	N	Flood	60
DarkBrown	E95349					

Power supply options (remote only)

ECO30W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-700
0-10V EldoLED SOLOdrive 50W for1-6 fixtures

SOLO100W-700
0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Accessories

E98549
Pegs

E99802
Tree belt
List Diameter of strap; maximum tree size

E98966
Anti-glare screen

E98969
Anti-glare pipe

On request
Honey-comb

On request
Elliptical filter

Periskop Narrow | Accent lighting | powerLED | Wet location | Driver remote | Tiltable | 8W 700mA



CRI 80

White	E81160	2700K	854 lm	M	Narrow Spot	08
Black	E81161	3000K	854 lm	W		
Grey	E81162	4000K	922 lm	N		
DarkBrown	E81163					

Power supply options (remote only)

ECO30W-700
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-700
0-10V EldoLED SOLOdrive 50W for1-4 fixtures

SOLO100W-700
0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Accessories

E98549
Pegs

E99802
Tree belt
List Diameter of strap; maximum tree size

E98966
Anti-glare screen

Periskop RGBW | Accent lighting | powerLED | Wet location | Driver remote | Tiltable | 8W 630mA



RGBW

CRI 80

White	E81493	RGBW natural white	Q		Narrow Spot	06
Black	E81494	RGBW warm white	V		Spot	15
Grey	E81495				Flood	45
DarkBrown	E81496					

Accessories

E98549
Pegs

E99802
Tree belt
List Diameter of strap; maximum tree size

E98966
Anti-glare screen

Power supply options (remote only)

PWR50W - 630

DMX driver,
EldoLED POWERdrive 50W Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately 50W for 1 Fixture

index
technical information

Periskop | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 18W



CRI 80

White	E95366	2700K	2349 lm	M	Spot	15
Black	E95368	3000K	2510 lm	W	Medium Flood	30
Grey	E95370	4000K	2510 lm	N	Flood	60
DarkBrown	E95378					

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-500
0-10V EldoLED SOLOdrive 50W for1-2 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Accessories

E98549
Pegs

E99802
Tree belt
List Diameter of strap; maximum tree size

E98967
Anti-glare screen

E98970
Anti-glare pipe

On request
Anti-glare pipe

On request
Elliptical filter

Periskop Narrow | Accent lighting | 3 x powerLEDs | Wet location | Driver remote | Tiltable | 18W DC - 20W AC



CRI 80

White	E81164	2700K	1977 lm	M	Narrow Spot	08
Black	E81165	3000K	1977 lm	W		
Grey	E81166	4000K	2133 lm	N		
DarkBrown	E81167					

Power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-500
0-10V EldoLED SOLOdrive 50W for1-2 fixtures

SOLO100W-500
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Accessories

E98549
Pegs

E99802
Tree belt
List Diameter of strap; maximum tree size

E98967
Anti-glare screen

Periskop RGBW | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 18W 500mA



RGBW

CRI 80

White	E81497	RGBW warm white	V	Spot	15
Black	E81498			Medium Flood	30
Grey	E81499			Flood	60
DarkBrown	E81500				

Accessories

E98549
Pegs

E99802
Tree belt
List Diameter of strap; maximum tree size

E98967
Anti-glare screen

Power supply options (remote only)

PWR50W - 500

DMX driver,
EldoLED POWERdrive 50W Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately
50W for 1 Fixture

index
technical information

Periskop | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable



30W DC - CRI 80

White	**E81367**	2700K	3991 lm	**M**	Spot	**20**
Black	**E81368**	3000K	4270 lm	**W**	Medium Flood	**30**
Grey	**E81369**	4000K	4588 lm	**N**	Flood	**60**
DarkBrown	**E81370**					

46W DC - CRI 80

White	**E80383***	2700K	6153 lm	**M**	Spot	**20**
Black	**E80384***	3000K	6153 lm	**W**	Medium Flood	**30**
Grey	**E80385***	4000K	7074 lm	**N**	Flood	**60**
DarkBrown	**E80386***					

Power supply options (remote only)

SOLO50W-840

0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO100W-840

0-10V EldoLED SOLOdrive 50W for1-2 fixtures

SOLO100W-1300*

0-10V EldoLED SOLOdrive 100W for 1 fixture

Accessories

E98549
Pegs

On request
Tree belt
List Diameter of strap; maximum tree size

E98968
Anti-glare screen

E98971
Anti-glare pipe

On request
Anti-glare pipe

On request
Elliptical filter

Periskop Narrow | Accent lighting | 9 x powerLEDs | Wet location | Driver remote | Tiltable | 46W



CRI 80

White	**E81168**	2700K	5243 lm	**M**	Narrow Spot	**08**
Black	**E81169**	3000K	5243 lm	**W**		
Grey	**E81170**	4000K	5660 lm	**N**		
DarkBrown	**E81171**					

Power supply options (remote only)

SOLO100W-1300

0-10V EldoLED SOLOdrive 100W for 1 fixture

Accessories

E98549
Pegs

On request
Tree belt
List Diameter of strap; maximum tree size

E98968
Anti-glare screen

index
technical information

iris67

Iris67's adjustable ring nut lets you set the beam width anywhere between 8 and 50 degrees, and it also swivels horizontally by 220 degrees. It is perfect for garden plants, since the light can be adjusted as they grow, and the variable focus illuminates only the required area.

Materials
Aluminum body

IP67 versatile spotlight

Aesthetically pleasing with minimal forms, Iris67 introduces the possibility of professionally managing the light beam in an outdoor environment, allowing a broad spectrum of lighting situations applicable to decorative elements (statues, installations) and high plants. A device for advanced lighting, IP67 and entirely in aluminum: the concrete and reliable design of Iris67 guarantees maximum protection against atmospheric agents, water (with the exception of immersion) and microscopic particles.

Adjustable optics

Iris_67 allows the light beam to be adapted to the directing needs in outdoor settings in order to adapt to the growth of high trees and/or the enhancement of urban décor elements with different heights and dimensions. Thanks to the graduated focus-on-board ring nut, the beam aperture can be calibrated, variable depending on the selected model, making the directing operation simple and precise. The blocking system of the facilitated focus allows obtaining an opening precisely corresponding to the gradient indicated along the ring nut.

Dynamic optical range

The Elliptic version is the feather in the cap of the Iris67 family, a new product for 2019 that expands the potential of a highly professional outdoor spotlight. In addition to allowing adjustment of the beam aperture, Iris67 Elliptic lets you act on a second ring nut to control the movement of a specific filter placed at the end of the device. Increasing or decreasing the distance of the filter from the main lens, we can change the shape of the light beam, thereby obtaining a perfect elliptical lighting for very high plants or vertical urban elements (for example, signs).



Iris67 | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 6W 630mA



CRI 80

White	**E92230**	2700K	685 lm	**M**	15°-45°	**85**
Black	**E92231**	3000K	685 lm	**W**		
Grey	**E92232**	4000K	739 lm	**N**		

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for1-6 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

E84890
9.84 in Steel Pegs

E98112
27.56 in Steel Pegs

Iris67 | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 13W 350mA



CRI 80

White	**E97318**	2700K	1724 lm	**M**	15°-62°	**85**
Black	**E97319**	3000K	1724 lm	**W**		
Grey	**E97320**	4000K	1854 lm	**N**		

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for1-2 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

E84890
9.84 in Steel Pegs

E98112
27.56 in Steel Pegs

Iris67 | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 20W 580mA



CRI 80

White	**E97321**	2700K	2714 lm	**M**	16°-52°	**85**
Black	**E97322**	3000K	2900 lm	**W**		
Grey	**E97323**	4000K	2900 lm	**N**		

Power supply options (remote only)

ECO30W-580
0-10V EldoLED ECOdrive 30W for 1 fixture

SOLO50W-580
0-10V EldoLED SOLOdrive 50W for1-2 fixtures

SOLO100W-580
0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

E84890
9.84 in Steel Pegs

E98112
27.56 in Steel Pegs

Iris67 | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 30W 840mA



CRI 80

White	**E97324**	2700K	4220 lm	**M**	15°-56°	**85**
Black	**E97325**	3000K	4535 lm	**W**		
Grey	**E97326**	4000K	4535 lm	**N**		

Power supply options (remote only)

SOLO50W-840
0-10V EldoLED SOLOdrive 50W for1 fixture

SOLO100W-840
0-10V EldoLED SOLOdrive 100W for 1-2 fixtures

E84890
9.84 in Steel Pegs

E98112
27.56 in Steel Pegs

index
technical information

Iris67 Elliptic | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 6W 630mA



CRI 80

White	**E81720**	2700K	685 lm	**M**	15°-45°	**88**
Black	**E81721**	3000K	685 lm	**W**	
Grey	**E81722**	4000K	739 lm	**N**	

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630		
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures	**E84890** 9.84 in Steel Pegs	**E98112** 27.56 in Steel Pegs

Iris67 Elliptic | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 13W 350mA



CRI 80

White	**E81723**	2700K	1636 lm	**M**	15°-62°	**88**
Black	**E81724**	3000K	1520 lm	**W**	
Grey	**E81725**	4000K	1520 lm	**N**	

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350		
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures	**E84890** 9.84 in Steel Pegs	**E98112** 27.56 in Steel Pegs

Iris67 Elliptic | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 20W 580mA



CRI 80

White	**E81726**	2700K	2572 lm	**M**	16°-52°	**88**
Black	**E81727**	3000K	2572 lm	**W**	
Grey	**E81728**	4000K	2396 lm	**N**	

Power supply options (remote only)

ECO30W-580	SOLO50W-580	SOLO100W-580		
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures	**E84890** 9.84 in Steel Pegs	**E98112** 27.56 in Steel Pegs

Iris67 Elliptic | Accent lighting | arrayLED | Wet location | Driver remote | Tiltable | 30W 840mA



CRI 80

White	**E81729**	2700K	4220 lm	**M**	15°-56°	**88**
Black	**E81730**	3000K	3945 lm	**W**	
Grey	**E81731**	4000K	3945 lm	**N**	

Power supply options (remote only)

SOLO50W-840	SOLO100W-840		
0-10V EldoLED SOLOdrive 50W for1 fixture	0-10V EldoLED SOLOdrive 100W for 1-2 fixtures	**E84890** 9.84 in Steel Pegs	**E98112** 27.56 in Steel Pegs

index
technical information

light effects range index

click images to open product pages

Arcada

Arcada

O7

Myia

Myia

O10

Loop66

Loop66

O12

Paseo_Pixel

Paseo_Pixel
RGB

O17

arcada

Arcada is designed for windows, arches and architraves, and can also be used to highlight doorways, statues, and reliefs. The light distribution reflects the fact that the ends of the diffuser are much shorter than the sides, creating a clearly defined arch shape.
The indirect lighting neatly follows the underside of the arch, without producing glare or light pollution.

Materials
Aluminum body

HOTEL MILANO MANIN
HOTEL MANIN
MILANO

Arcada | Arc light | powerLED | Wet location | Diver remote | Titable | 4.5W 350mA



CRI 80

White	**E95454**	2700 K	544 lm	**M**	Radial	**18**
Black	**E95612**	3000 K	580 lm	**W**		
Grey	**E95619**	4000 K	620 lm	**N**		

Power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-350
0-10V EldoLED SOLOdrive 50W for1-6 fixtures

SOLO100W-350
0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

Arcada | Arc light | powerLED | Wet location | Driver remote | Tiltable | 8W 630mA



CRI 80

White	**E95458**	2700 K	876 lm	**M**	Radial	**18**
Black	**E95616**	3000 K	932 lm	**W**		
Grey	**E95623**	4000 K	996 lm	**N**		

Power supply options (remote only)

ECO30W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures

SOLO50W-630
0-10V EldoLED SOLOdrive 50W for1-4 fixtures

SOLO100W-630
0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Arcada | Arc light | powerLED | Wet location | Driver remote | Tiltable | 8W 220mA.



RGB

CRI 80

White	**E95749**	RGB	**Z**	Radial	**18**
Black	**E95750**				
Grey	**E95751**				

Power supply options (remote only)

PWR50W-220

DMX driver, EldoLED POWERdrive 50W
Factory pre-programmed or RDM programmable, DMX control not included/Ordered separately
for 1-3 Fixtures

E95458N18



Photometric curve



Light beam



25 LUX | 100 LUX | 200 LUX | 350 LUX | 500 LUX



Floor plan

NYX HOTEL

myia

Myia is an innovative way of adding a touch of class to walls and facades. Designed for Linea Light Group by Okapi Light, its distinctive shape is aesthetically and functionally suited to angular structures.
It creates a perfectly homogeneous straight beam, both vertically and horizontally, and can be used to produce creative, high-impact effects.

Materials
Aluminum body

Myia | Wall light | powerLED | Wet location | Driver remote | 9W 630mA



CRI 80

White	**E91596**	2700 K	760 lm	**M**	Wide Flood	**90**
Black	**E91597**	3000 K	760 lm	**W**		
Grey	**E91598**	4000 K	821 lm	**N**		

Power supply options (remote only)

ECO30W-630

0-10V EldoLED ECOdrive 30W for 1-2 fixtures

SOLO50W-630

0-10V EldoLED SOLOdrive 50W for1-4 fixtures

SOLO100W-630

0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

Private Villa | Athens, Greece

index
technical information

loop66

The Loop outdoor IP66 light illuminates walls and facades with four very narrow perpendicular beams using a five-degree optic.
The integrated driver is resinated into the body.

Materials
Aluminum body

Loop66 | Wall light | powerLEDs | Wet location | Driver remote | 25W



CRI 80

White	**E97065**	2700 K	2628 lm	**M**	Narrow Spot **05**
Black	**E97066**	3000 K	2796 lm	**W**	
Grey	**E97067**	4000 K	2988 lm	**N**	
DarkBrown	**E97357**				

Power supply options (remote only)

SOLO50W-630

0-10V EldoLED SOLOdrive 50W for1 fixture

SOLO100W-630

0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

Euroluce 2015 | Milan, Italy



index
technical information

paseo_PIXEL RGB

Paseo linear lights use RGB pixel technology to create dynamically animated scenes. Used alone or combined with Pixie, Paseo RGB pixel bars are the ideal solution for large or small installations.
The power and DMX signal cables exit from the bottom of the bar, so it can be combined into continuous lines.

Materials
Polycarbonate body

Paseo_PIXEL RGB DMX 24V | 24V | topLED | Wet location | Driver remote



RGB Pixel



22.7 in - 10W

Opaline	**E81337**	RGB	**Z**	General	**00**

45.4 in - 20W

Opaline	**E81338**	RGB	**Z**	General	**00**

Power supply options (remote only)

OT96-JBX

Osram, Non-Dim, 96W, 24VDC, 120-277VAC, Wet Location

Cables

E99216	**E89190**	**E98437**	**E98149**	**E89188**	**E89189**
59.1 in power cable F 4 pin M12	196.9 in power cable F 4 pin M12	39.4 in Extension for power cable M+F 4 pin M12	196.9 in Extension for power cable M+F 4 pin M12	393.7 in Extension for power cable M+F 4 pin M12	196.9 in DMX cable M 5 pin M12
E89186	**E98494**	**E98493**	**E98994**	**E98993**	**E89187**
196.9 in DMX cable M 5 pin M12 + M 3 pin XLR	196.9 in DMX cable M 5 pin M12 + F 3 pin XLR	196.9 in DMX cable M 5 pin M12 + M 5 pin XLR	39.4 in DMX extension M+F	196.9 in DMX extension M+F	393.7 in DMX extension M+F

Installation accessories (ordered separately)

491
Outer casings and fixing systems

index
technical information

Paseo_PIXEL RGB
Lighting performance & engineering

The i-LèD Paseo PIXEL RGB bar redefines the surrounding landscape through the creation of dynamic lighting effects. Every single RGB LED can be controlled individually, the available versions are Paseo PIXEL RGB 22.7 inch with 32 RGB full-color LEDs, or Paseo PIXEL RGB 454 inch with 64 RGB full-color LEDs.



To guarantee a top-level flexibility and an outstanding efficacy in terms of control, a single product allows for multiple resolutions; it is possible to vary the LED and Pixel ratio based on the size of the installation.

Pixel is the RGB element that can be individually controlled. At its maximum resolution, the 45.4 inch Paseo_PIXEL RGB will have 64 independent pixels, whilst the 22.7 inch one will have 32 independent pixels. At its minimum resolution, 45.4 inch Paseo_PIXEL RGB will be made up of 4 independent pixels, whilst the 22.7 inch one will be made up of 2 independent pixels.

The resolution setting can be made through the RDM* (Remote Device Management), a system permitting the bidirectional communication of lights. The device recommended for this kind of operation is Enttec Pro Mk2.


2 LEDs x Pixel


16 LEDs x Pixel

The table in the following page sums up all the possible resolutions.

What is RDM*?
Remote-Device-Management

It is an extension of a DMX512 protocol that permits a bidirectional control of the information, by means of a feedback from the lighting devices.



It should be highlighted that a single DMX signal controls maximum 512 channels, such a grouping is normally called universe.

When looking at the table, and considering the extensive use of the DMX channels with resolutions of 1, 2 and 4 LEDs per pixel, you can notice that i-LèD has developed a system that allows to manage 4 DMX universes with the same signal line. The solution, named DMX2048, requires a specific i-LèD.

Example	22.7 in (32 LEDs RGB)	45.4 in (64 LEDs RGB)	Pixel-Pitch
1 LED x Pixel	32 PIXEL RGB / 96 DMX CHANNELS	64 PIXEL RGB / 192 DMX CHANNELS	0.7 in
2 LEDs x Pixel	16 PIXEL RGB / 48 DMX CHANNELS	32 PIXEL RGB / 96 DMX CHANNELS	1.4 in
4 LEDs x Pixel	8 PIXEL RGB / 24 DMX CHANNELS	16 PIXEL RGB / 48 DMX CHANNELS	2.8 in
8 LEDs x Pixel	4 PIXEL RGB / 12 DMX CHANNELS	8 PIXEL RGB / 24 DMX CHANNELS	5.7 in
16 LEDs x Pixel	2 PIXEL RGB / 6 DMX CHANNELS	4 PIXEL RGB / 12 DMX CHANNELS	11.3 in

Resolution and Pixel-Pitch

Changing the Resolution of a Paseo_PIXEL means substantially altering the size of Pixel and Pixel-Pitch. Large Pixel-Pitches are used in installations where accent lighting is required or in general entertainment applications, to create Wall Washing effects or highly scenic compositions that enhance the edges, depth, and characteristics of the building. With regard to applications capable of playing videos or images, Pixel size is determined by the maximum and minimum viewing distance and the resolution of the video itself.

Graphics

Graphics reproduced on Paseo_PIXEL RGB lines



Resolution



It is possible to keep the Pixel-Pitch size just like the Lines distance between the Paseo_PIXEL, however, as you can see in the picture, a great result can be obtained by extending the lines much more. The human eye can correctly distinguish the images thanks to the high density of horizontal Pixels. In the example, a double Lines distance has been used as compared to the Pixel-Pitch. The same goes when the Paseo_PIXEL are directed in a vertical position. It is important to keep, however, a high density of Pixels along one direction and "dilute" it along the other.

Some guidelines for the Pixel-Pitch sizing are reported hereunder:

The following calculations and examples are general guidelines to determine the minimum and maximum viewing distances when you wish to play a low-resolution video with the Paseo_Pixel RGBs.

- To determine the minimum viewing distance, multiply the size of the Pixel-Pitch times 100 units. For example, if the Pixel-Pitch is 1.4 inch, the minimum viewing distance is equal to 141.7 inch.

- To determine the maximum viewing distance for discernible videos, it is necessary to multiply the height of the screen by 20 units of distance. For example, if the screen is 98.4 feet high, the maximum recognizable viewing distance for the video will be 1968.5 feet.

- LED display videos can be viewed despite the maximum viewing distance for the discernible videos. To determine the maximum viewing distance for a suitable visual impact, multiply the height of the screen by 50 units of distance. For example, if the screen is 656.2 feet high, it will continue to create a visual impact up to 3280.8 feet.

However, it is possible to obtain a good visual impact up to 50 times the height of the screen also by overcoming the maximum viewing distance mentioned in the previous point.

pixel technology connection examples

Example of standard DMX512 connection:

For relatively simple projects with low densities of Pixels, we recommend using the Artnet/DMX controller. These controllers feature 2, 4, 8 or 16 DMX ports. Each port/output can control up to maximum 160 pixels and the overall length of the cable shall not exceed 984.3 feet (including the Paseo profiles).
The frame rate of the animation supported is equal to 40 frames per second.



Artnet III / sACN -Ethernet-

Artnet III and sACN are two protocols used to transmit the DMX signal to the Ethernet network, they are very widespread in the entertainment lighting sector.

ATTENTION
A typical example of possible configuration, it can vary according to the characteristics of the structure where a system is installed. To all our clients we offer full support and assistance from design to after sales to ensure the best possible service.

For each line it is possible to connect a number of **Paseo_PIXEL RGBs** in the following configuration:

Version	1 LED per pixel max connectable Paseo	2 LEDs per pixel max connectable Paseo	4 LEDs per pixel max connectable Paseo	8 LEDs per pixel max connectable Paseo	16 LEDs per pixel max connectable Paseo
22.7 in (32 LEDs)	5x	10x	21x	42x	85x
45.4 in (64 LEDs)	2x	5x	10x	21x	42x

For each DRIVER (switching driver 96W) the maximum number of Paseo_PIXEL that can be connected to the same power supply/signal line varies according to the power of the Paseo_PIXEL used. It is also possible to have mixed connection solutions among Paseo_PIXEL with different powers, as long as the 96W limit per power supply channel is not exceeded.

Example of connection with an own DMX2048 system:

For complex projects with high densities of pixels, we recommend using a “PIXEL controller”. This controller is equipped with 4 or 16 RS-485 ports (DMX 2048). Each port/output can control up to maximum 640 pixels and the overall length of the cable shall not exceed 262.5 feet (including the paseo profiles).

The frame rate of the animation supported is equal to 40 frames per second. The use of the DMX2048 system for structured systems makes the installation of the Paseo PIXELs much easier and cheaper. Compared to the DMX512 solution, the resolution of the Paseo PIXELs being the same, it is possible to control four times the amount of the devices with the same cable. Therefore, it is possible to cover four times the linear distance.



Artnet III / sACN -Ethernet-

Artnet III and sACN are two protocols used to transmit the DMX signal to the Ethernet network, they are very widespread in the entertainment lighting sector.

ATTENTION
A typical example of possible configuration, it can vary according to the characteristics of the structure where a system is installed. To all our clients we offer full support and assistance from design to after sales to ensure the best possible service.

For each signal line, it is possible to manage maximum **640 PIXEL RGBs.**
The length of the cable from the controller to the first **Paseo_PIXEL** shall not exceed **1377,95 inch.**

Version	1 LED per pixel max connectable Paseo	2 LEDs per pixel max connectable Paseo	4 LEDs per pixel max connectable Paseo	8 LEDs per pixel max connectable Paseo	16 LEDs per pixel max connectable Paseo
22.7 in (32 LEDs)	20x	To be used with the 45,35 in version. The total 22,68 in Paseo_ Pixel RGBs is 10x	To be used with the 45,35 in version. Connect maximum 10x 22,68 in Paseo_Pixel RGBs every 45,35 in 15x. The total 22,68 in Paseo_Pixel RGBs is 20x	To be used with the 45,35 in version. Connect maximum 10x 22,68 in Paseo_Pixel RGBs every 45,35 in 15x. The total 22,68 in Paseo_Pixel RGBs is 40x	To be used with the 45,35 in version. Connect maximum 10x 22,68 in Paseo_Pixel RGBs every 45,35 in 15x. The total 22,68 in Paseo_Pixel RGBs is 80x
45.4 in (64 LEDs)	10x	20x	40x	80x	160x

For each DRIVER (switching driver 96W) the maximum number of Paseo_PIXEL that can be connected to the same power supply/signal line varies according to the power of the Paseo_ PIXEL used. It is also possible to have mixed connection solutions of Paseo_PIXEL with different powers, as long as the 640-pixel limit per signal line and the 96W limit per +24V power supply line are not exceeded.

Your Light

Future Proof

LED Strips index

click images to open product pages

Ribbon

Ribbon

P4

Dropper

Dropper

P6

Silicone _C

Silicone _C

P7

Rubber

Rubber

P38

ribbon | dropper | silicone _C



The Ribbon range comprises a variety of strip solutions with flexible adhesive circuits.
Dropper is a flexible IP50 strip with the top covered in silicone, a protected diode, and an adhesive base.
The real strength of Silicone_C lies in its IP66 protection, thanks to silicone sheathing that makes it completely water and dust resistant while maintaining a flexible circuit.

Ribbon 36 LEDs/ft | LED strip | Dry location | stripLED 2.9 W/ft 24 V



Cable 11.8 in supplied with product;
Female end connector

CRI 80

196.9 in	**E98451**	3500 K	3625 lm

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Ribbon 73 LEDs/ft | LED strip | Dry location | stripLED 5.9 W/ft 24 V





Cable 11.8 in supplied with product;
Female end connector

CRI 80

196.9 in	**E98084**	2700 K	7200 lm
196.9 in	**E98570**	3000 K	7250 lm
196.9 in	**E98083**	4000 K	7400 lm

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

index
technical information

Ribbon Slim 36 LEDs/ft | LED strip | Dry location | stripLED 3.7 W/ft 24 V





Cable 11.8 in supplied with product;
Female end connector

CRI 80

196.9 in	**E84219**	2700 K	4900 lm
196.9 in	**E84220**	3000 K	4900 lm
196.9 in	**E84221**	4000 K	4900 lm

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Ribbon Dynamic 18+18 LEDs/ft | LED strip | Dry location | stripLED 5.9 W/ft 24 V





3000-6000K

DYNAMICWHITE

Cable 11.8 in supplied with product;
Female end connector

CRI 80

196.9 in	**E98548**	3000 - 6000 K

Power supply options (remote only)

EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/ order separately.

Ribbon RGB 18 LEDs/ft | LED strip | Dry location | stripLED 4.4 W/ft 24 V



RGB

Cable 11.8 in supplied with product;
Female end connector

CRI 80

196.9 in	**E98017**	RGB

Power supply options (remote only)

EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/ order separately.

Ribbon RGBW 18 LEDs/ft | LED strip | Dry location | stripLED 5.9 W/ft 24 V



RGBW

Cable 11.8 in supplied with product;
Female end connector

CRI 80

196.9 in	**E99643**	RGBW - 3000 K

Power supply options (remote only)

EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/ order separately.

index
technical information

Dropper 36 LEDs/ft | LED strip | Damp location | stripLED 2.9 W/ft 24 V





CRI 80

196.9 in	**E98572**	3000 K	3610 lm
196.9 in	**E98574**	4000 K	3700 lm

Cable 11.8 in supplied with product;
Female end connector

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Dropper RGB 18 LEDs/ft | LED strip | Damp location | stripLED 4.4 W/ft 24 V





CRI 80

196.9 in	**E98025**	RGB

Cable 11.8 in supplied with product;
Female end connector

RGB

Power supply options (remote only)

EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/ order separately.

index
technical information

Silicone_C 36 LEDs/ft | LED strip | Wet location | stripLED 4.4 W/ft 24 V





Cable 11.8 in supplied with product;
Female end connector

CRI 80 - 4.4 W/ft

196.9 in	**E62403**	7230 lm	3000 K
196.9 in	**E62403N**	7495 lm	4000 K

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Silicone_C Basic RGB 18 LEDs/ft | LED strip | Wet location | stripLED 4.4 W/ft 24 V





Cable 78.7 in supplied with product;
Female end connector

CRI 80

196.9 in	**E98033**	RGB

Power supply options (remote only)

EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/ order separately.

Silicone_C | Fixing kit



features		suitable for	
1 x	Glue	196.9 in Silicone_C	**E98373**
20 x	Brackets		
40 x	M3x25 screws		
10 x	Caps		

Silicone_C | Fixing brackets

features		suitable for	
10 x	Brackets	196.9 in Silicone_C	**E89223**
20 x	M3x25 screws		

index
technical information

LED Strips | IP66 cable

connector	sec. Ø	available for	in	
1 M	0.08 x 0.03 in^2	Silicone_C mono	39.4 in	**E89629**

RGB Strips | IP66 cable

connector	sec. Ø	available for	in	
1 M	0.16 x 0.01 in^2	Silicone_C RGB	78.7 in	**E89630**

index

Low surface profile | Indoor LED Strips

Compatible with
Ribbon - Ribbon slim
Dropper

type	L in		
Anod. Al.	78.7 in	Profile	**E98891**
Transp.	78.7 in	Diffuser	**E98941**
Satinized	78.7 in	Diffuser	**E98942**
Opaline	78.7 in	Diffuser	**E98943**
	2 x	Caps	**E98892**
	5 x	Brackets	**E98944**

KIT composition

1 x	E98891-E98943-E98892-E98944	**E98954**
10 x	E98891-E98943	**E98955**

High surface profile | Indoor LED Strips



Compatible with
Ribbon - Ribbon slim
Dropper
Silicone_C

type	L in		
Anod. Al.	78.7 in	Profile	**E98893**
Transp.	78.7 in	Diffuser	**E98941**
Satinized	78.7 in	Diffuser	**E98942**
Opaline	78.7 in	Diffuser	**E98943**
	2 x	Caps	**E98894**
	5 x	Brackets	**E98944**

index

Square surface profile | Indoor LED Strips





Compatible with
Ribbon - Ribbon slim
Dropper

type	L in		
Anod. Al.	78.7 in	Profile	**E98929**
Opaline	78.7 in	Diffuser	**E98930**
	2 x	Caps	**E98932**
	5 x	Brackets	**E98931**

Corner profile | Indoor LED Strips



Compatible with
Ribbon - Ribbon slim
Dropper

type	L in		
Anod. Al.	78.7 in	Profile	**E98903**
Transp.	78.7 in	Diffuser	**E98941**
Satinized	78.7 in	Diffuser	**E98942**
Opaline	78.7 in	Diffuser	**E98943**
	2 x	Caps	**E98905**
	5 x	Brackets	**E98904**

index

Small recessed profile | Indoor LED Strips





Compatible with
Ribbon - Ribbon slim
Dropper

type	L in		
Anod. Al.	78.7 in	Profile	**E98895**
Transp.	78.7 in	Diffuser	**E98941**
Satinized	78.7 in	Diffuser	**E98942**
Opaline	78.7 in	Diffuser	**E98943**
	2 x	Caps	**E98896**
	5 x	Brackets	**E98944**

KIT composition

1 x	E98895-E98943-E98896-E98944	**E98965**

Recessed profile | Indoor LED Strips



Compatible with
Ribbon - Ribbon slim
Dropper
Silicone_C

type	L in		
Anod. Al.	78.7 in	Profile	**E98897**
Transp.	78.7 in	Diffuser	**E98898**
Satinized	78.7 in	Diffuser	**E98899**
Opaline	78.7 in	Diffuser	**E98900**
	2 x	Caps	**E98902**
	5 x	Brackets	**E98901**

False-ceilings integrated profile | Indoor LED Strips







Compatible with
Ribbon - Ribbon slim
Dropper
Silicone_C

type	L in		
Anod. Al.	78.7 in	Profile	**E98906**
Transp.	78.7 in	Diffuser	**E98898**
Satinized	78.7 in	Diffuser	**E98899**
Opaline	78.7 in	Diffuser	**E98900**
	2 x	Caps	**E98907**

index

Plaster In linear profile | Indoor LED Strips



type	L in		
Anod. Al.	78.7 in	Profile	**E98916**
Opaline	78.7 in	Diffuser	**E98917**
	2 x	Caps	**E98918**



Compatible with
Ribbon - Ribbon slim
Dropper

Plaster In corner profile | Indoor LED Strips



type	L in		
Anod. Al.	78.7 in	Profile	**E98919**
Opaline	78.7 in	Diffuser	**E98917**
	2 x	Caps	**E98920**



Compatible with
Ribbon - Ribbon slim
Dropper

Plaster In side profile | Indoor LED Strips



type	L in		
Anod. Al.	78.7 in	Profile	**E98921**
Opaline	78.7 in	Diffuser	**E98917**
	2 x	Caps	**E98922**



Compatible with
Ribbon - Ribbon slim
Dropper

index

High slim surface profile | Indoor LED Strips



Compatible with
Ribbon slim

type	L in		
Anod. Al.	78.7 in	Profile	**E98908**
Opaline	78.7 in	Diffuser	**E98909**
	2 x	Caps	**E98911**
	5 x	Brackets	**E98910**

Square slim surface profile | Indoor LED Strips





Compatible with
Ribbon slim

type	L in		
Anod. Al.	78.7 in	Profile	**E98912**
Opaline	78.7 in	Diffuser	**E98913**
	2 x	Caps	**E98915**
	5 x	Brackets	**E98914**

Low slim surface profile | Indoor LED Strips



Compatible with
Ribbon slim

type	L in		
Anod. Al.	78.7 in	Profile	**E98885**
Transp.	78.7 in	Diffuser	**E98886**
Satinized	78.7 in	Diffuser	**E98887**
Opaline	78.7 in	Diffuser	**E98888**
	2 x	Caps	**E98890**
	5 x	Brackets	**E98889**

index

Flat surface profile | Indoor LED Strips

type	L in		
Anod. Al.	78.7 in	Profile	**E98937**
Opaline	78.7 in	Diffuser	**E98938**
	2 x	Caps	**E98940**
	5 x	Brackets	**E98939**

Compatible with
Ribbon - Ribbon slim

Surface profile | Indoor LED Strips



type	L in		
Anod. Al.	78.7 in	Profile	**E98419**
Opaline	78.7 in	Diffuser	**E98395**
	2 x	Caps	**E98418**
	5 x	Brackets	**E98420**

Compatible with
Ribbon - Ribbon slim
Dropper
Silicone_C

Slim profile kit | Indoor LED Strips



type	L in		
Anod. Al.	78.7 in		**E63560L02**

Compatible with
Ribbon
Dropper

Heat sink | Indoor LED Strips



type	L in		
Anod. Al.	78.7 in	Dissipatore - Heat sink	**E98956**

Compatible with
Ribbon - Ribbon slim
Dropper
Silicone_C

index



AUTOMHA
A07

RUBBER





rubber

It is light that becomes alive and plays in three-dimensionality, as it bends, and turns upside down.

Rubber is a tangible sign towards a new conception of light.

rubber

It is light that becomes alive and plays in three-dimensionality, as it bends, and turns upside down.

Rubber is a tangible sign towards a new conception of light.

rubber line up

	Dimensions	Length	Finish	W/ft	CCT	Optic	IP	Cutting Length
Rubber 3D	0.55x0.55	39.3 196.9	White Concrete	3	2700K 3000K 4000K RGBW	Diffused emission	IP67	1.8
Rubber 3D Optic	0.55x0.55	39.3 59 118	White Black	6.7	2700K 3000K 4000K	Spot 15° Flood 26°	IP67	6.6
Rubber 2D **(Side bend)**	0.55x0.55	39.3 196.9	White	3	2700K 3000K 4000K	Diffused emission	IP67	2
Rubber 2D Mini **(Side bend)**	0.2x0.5	39.3 196.9 393.8	White	1.5	2700K 3000K 4000K	Diffused emission	IP67	2
Rubber 2D RGBW** **(Top bend)**	0.77x0.75	39.3 196.9	White	5.8	2700K 3000K 4000K	Diffused emission	IP67	3.94

* Available for shipping Q2 2022. Not ETL listed for habitable pools. Factory cuttable, ONLY in 2 in. increments.
**Due to its LED configuration the product might show some LED imaging depending on the viewing angle.

RUBBER SPEAKS ONLY ONE LANGUAGE

PRODUCT FEATURES



5 warranty

5 years warranty

ICs Regulator

≤3 MAC ADAM

Step MacAdam ≤ 3

118 in

Submerged up to 118 in

Reverse polarity protection

Possibility of cutting

UV resistance

Self-dissipation

Salt water resistance

Chlorine resistance

Made in Italy



2D

2 Axis Movement

3D

3 Axis Movement

0.2in

Minimum Dimensions (2D Mini)

IK10

Index of protection against mechanical impact

Solvent resistance

IP67

Minimum degree of protection from external agents IP67

RGBW

RGBW Technology

PIXEL

PIXEL Technology (Coming Soon)

MADE IN ITALY

Linea Light Group is a manufacturing organization which, along with its industrial capacity, has skilfully preserved a measure of that manual craftsmanship which has always characterized “Made in Italy” products. From conception to creation and all the way to assembly, our products are the combination of high technology, research and know-how, a recipe that has made Italian companies unique the world over. Alongside our traditional machines, we have placed new and high-performance units, allowing us to complete all the processes that have made our products unique in-house. We have gone beyond manufacturing: a perfect product must also be tested and certified. This is why Linea Light Group has its own in-house laboratory. Here, various quality, heat resistance and impact tests can be carried out, as well as ensuring that the uplights are able to withstand the weight of vehicle traffic and verifying the IP classes of our submersible products.



GUARANTEED QUALITY

The Rubber fixtures are certified and guaranteed for 5 years. The various types, color temperatures and power, thanks to a short and controlled supply chain totally Made in Italy, are available immediately. The company is ISO 9001 certified. The materials and components used for the creation of our products are guaranteed by international certifying bodies and are marked and tested in accordance with ICE/EN standards.



MATERIALS

All the material used to create Rubber are of very high quality. Rubber has a PVC structure and the diffuser is a polyurethane resin, which guarantees maximum flexibility and versatility thanks to the quality of the raw materials used. Raw materials that are predisposed to resist ageing and yellowing over time. The copper used for the PCB circuits, which is 99.9% pure, guarantees the perfect continuity of the electronic connections. The Rubber range is, by its very nature, self-dissipating. It does not need additional cooling bodies or systems and it has a reversed polarity system that acts as a guarantee and protection in the event of incorrect connection.

SELF-DISSIPATION

The circuit is specifically designed to allow rapid passage of the heat from one layer to another. This factor, combined with the use of high efficiency components, helps dissipate the heat generated and guarantees a high level of self-dissipation for the product, allowing the operating temperature to be controlled. Therefore, Rubber can be applied on multiple surfaces to create all kinds of lighting installations.

ICS REGULATORS

Thanks to special integrated circuits, Rubber guarantees uniform lighting along the entire length of the product. A specific chip intervenes upon a voltage drop, typical when there are extended circuits, preventing drops in the luminous flow. Thanks to these innovations, Rubber perfectly maintains lumen values from the start to the end of the circuit.



Competitor's products without ICS Regulator



Rubber with ICS Regulator

GLOW WIRE TEST

This is a fundamental safety test, the purpose of which is to simulate the effect of thermal stress that can be produced by electrical overheating in order to assess the risk of fire. The test anticipates the contact of an incandescent wire with the insulated parts of the product in order to assess how the material behaves under thermal stress in normal operating conditions. The minimum temperature required by current regulations is 1202°F. Our products have been tested and verified at 1760°F to provide the maximum guarantee in terms of safety, which demonstrates the quality of the material Linea Light Group selects for use.



RESISTANCE TO SALT WATER AND SOLVENTS

A series of tests are conducted which are fundamental for examining and analysing the way the product behaves in extreme environments, such as the salt spray test, with isopropyl alcohol. The purpose of these tests is to understand the behaviour of the materials in high salinity level areas and in contact with aggressive solvents. The success of these tests makes it possible to be able to guarantee a product that can be installed in every outside environment.

RESISTANCE TO ULTRAVIOLET RAYS

Rubber is made up of different materials: the structure is made in PVC, whereas the diffuser is in polyurethane resin. Like all plastic materials, these are also subject to chromatic and physical variations over time. For this reason, Linea Light Group has selected specific materials that prevent these side effects. The purpose of the UV rays test is to predict ageing in the products.



CURVATURE RADIUS

Products in the Rubber range boast unique flexibility. The materials used permit formal, sinuous solutions to be created which had been unthinkable until now. Thanks to their intrinsic flexibility it is possible to achieve minimum radius of just 5.9" and 9.9". For a professional, this means being able to design freely, without any restrictions: every creation on paper can be faithfully produced.


Rubber 3D
White finish
Rubber 3D
Concrete
finish
Rubber 3D
White finish
RGBW
Rubber 3D
White finish
PIXEL


Rubber 3D
White finish
Rubber 3D
White finish
RGBW
Rubber 3D
Optic
White finish
Rubber 3D
Optic
Black finish
Rubber 2D
Mini
(Side bend)
White finish
Rubber 2D
(Side bend)
White finish

Rubber 3D

3D

Rubber 3D is unique in its kind. Thanks to the patented structure of the internal circuit, the product can bend on all axes and make new installation methods and application concepts possible. There is no limit to imagination: organic and fluid curved structures with abrupt direction changes are no longer a problem, thanks to the unrestricted flexibility of Rubber 3D. The input/output cables permit the connection of multiple fixtures in series, maintaining uniform and constant light for the entire overall length of the installation, without interruptions in the junction points. Minimum curvature radius: 9.9".



3D

IP67

The entire Rubber range is IP67 certified, in" other words"high protection against solid bodies and"dust, combined with total protection against" rain, liquids, water splashes and temporary" submersion in fresh water. IP67 protection" means that Rubber can be installed in outdoor" environments with high humidity, frequent" inclement weather or in settings subject to sand" and dust.

IP67

Concrete Finish

Rubber 3D with Concrete Finish astonishes, thanks to the way it integrates perfectly with the architecture. The product stands out for its cement gray finish, both in the profile and in the transmitting surface which, nevertheless, leads to absolutely no variation in the light tones. Along with high performance that is qualitatively unaltered, the finish lets Rubber blend in, camouflaging itself so that it is only noticed if it is on, thanks to the soft and clean emission. Rubber 3D Concrete Finish maintains a high grade of protection (IP67), is not adversely affected by exposure to ultraviolet rays, chlorine or saline environments and preserves its aesthetic (does not discolor) and technical properties (does not lose efficiency) over time.



• Binning Product Rubber 3D Concrete Finish.

Color temperature

With Linea Light Group, the designer has a choice of 3 color temperatures: 2700K, 3000K and 4000K for complete design versatility. A very important factor that influences the quality if an LED source is the step of the MacAdam ellipse which is attributed to them. Linea Light Group with its LED sources has always guaranteed a ≤ 3 step, which ensures the maintenance of the light tone within a defined range and with a color temperature that remains constant over time.

≤3 MAC ADAM

CRI85

Perfect RGBW blend

Thanks to RGBW technology, where the colors are combined inside the polyurethane resin layer, the individual RGBW LEDs are always high performance. The white at 3000K and the three RGB colors (red, green and blue) are combined in a single diode. This solution guarantees the best color blend and results in an infinite variety of chromatic shades, as well as the possibility of obtaining shades of white without the influence of the RGB colors.



RGBW

PIXEL

Rubber 3D PIXEL RGBW allows the creation of dynamic lighting effects, thanks to the i-LèD PIXEL technology allocated internally. The high definition of the pixel pitch, in other words, the space that defines the resolution of the final pixel (4.7") allows the creation of dynamic light scenarios visible from significant distances, typical in buildings where “Architainment light” is anticipated.



PIXEL

Rubber 3D

IP67 C.V.

3D



Male + Female 9.8"
feed cables





*See mounting instructions for field cutting

w	Type	CCT	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered)	LEDs/ft	Length	Min. bending Radius
E80394	White	2700 K	85	24V	3 W	309	139	39.6	39.4 in.	9.9 in.
E80395	White	3000 K	85	24V	3 W	333	153	39.6	39.4 in.	9.9 in.
E80396	White	4000 K	85	24V	3 W	361	204	39.6	39.4 in.	9.9 in.
E80397	White	2700 K	85	24V	3 W	311	139	39.6	196.8 in.	9.9 in.
E80398	White	3000 K	85	24V	3 W	335	154	39.6	196.8 in.	9.9 in.
E80399	White	4000 K	85	24V	3 W	363	205	39.6	196.8 in.	9.9in

Code	Type	CCT	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered)	LEDs/ft	Length	Min. bending Radius
E82208	Concrete	3000 K	85	24V	3 W	333	76	132	39.4 in.	9.9 in.
E82211	Concrete	3000 K	85	24V	3 W	335	72	132	196.8 in.	9.9 in.

Electronics

OT96-D010
Dry location 96W 24V
0-10V 10% dimmable

OT96-JBX
Wet location 96W 24V
Non-dim

LUT96-L3D0
Dry location 96W 24V
EcoSystem/3-wire 0.1% dimmable

index
technical information

Profile

E99549
Linear profil
Length 39.4 in
IK10 Anod. Al.



E83034
Linear profile with cable ru
Length 39.4 in
IK10 Anod. Al.



E99536
Clip with toothed spring
Length 2 in
Anod. Al.



E99537
Clip with toothed spring with cable run
Length 2 in
Anod. A

Cables

E99688 female connector
E99689 male connector
78.7 in

Rubber 3D*

IP67 C.V.

3D



Male + Female 9.8"
feed cables





Code	Type	CCT	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered)	LEDs/ft	Length	Min. bending Radius
E80403	White	3000 K	85	24V	5 W	332	49	39.6	39.4 in..	9.9 in.
		Red				29	13			
		Green				96	43			
		Blue				22	10			
E80404	White	3000 K	85	24V	5 W	110	49	39.6	196.8 in.	9.9 in.
		Red				29	13			
		Green				96	43			
		Blue				22	10			

* Available for shipping Q2 2022

Electronics

EL96-DMX

Dry location 96W 24V
RGBW Sequencer, DMX
dimmable

index
technical information

Profile

E99549
Linear profil
Length 39.4 in

IK10 Anod. Al.



E83034
Linear profile with cable ru
Length 39.4 in

IK10 Anod. Al.



E99536
Clip with toothed spring
Length 2 in

Anod. Al.



E99537
Clip with toothed spring with cable run
Length 2 in

Anod. Al.

Cables

E99692 female con. RGBW
E99693 male con. RGBW
78.7 in

Rubber 3D Optic

Optics

Rubber 3D Optic has an optics system specifically designed by the Linea Light Group R&D office to adapt to the reduced dimensions of the circuit and the stress due to the flexibility and the curvature radius. The TIR (Total Internal Reflection) optics reduce the secondary beams, increasing emission precision for an outstanding wall grazing effect. Once precision-positioned on the LED, the optics are stabilized by the cast polyurethane resin, becoming one with the adjustable body of Rubber 3D Optic. This procedure makes it possible to always maintain maximum technical lighting performance. Minimum curvature radius: 9.9".

TIR Optic

Black & White Finish

Available in white or black finish, color choice is not only a question of aesthetics, but it implies differences on a light emission level as well. Rubber 3D Optic with Black Finish has excellent glare control and extremely high performance emission, similar to that of a linear system, designed to obtain wall grazing effects even on significantly tall façades. Rubber 3D Optic with White Finish maintains the high performance of Rubber 3D Optic with the characteristic of also being illuminated outside the optics group, thereby generating an architectural lighting effect along the entire profile.

More than just an installation

1. Wall Grazing on curved wall
2. Colonnade lighting
3. Lighting of flowerbeds and parks
4. Lighting complex geometries
5. Walkway lighting
6. Cove light



Colonnade lighting with traditional Spot lights

Product installed: Spot | Optic 15°
Installation distance: on column
Number of devices: 4
Columns diameter: 19.7 in.
Interdistance columns: 7 ft
Wall column distance: 9 ft

Walkway lighting:
100lux medium



Colonnade lighting with Rubber 3D Optic

Product installed: Rubber 3D Optic
White Finish | Optic 20°
Installation distance: 3.9 in.
Rubber Length: 88.5 in.
Columns diameter: 19.6 in.
Interdistance columns: 7 ft
Wall column distance: 9 ft

Walkway lighting:

200lux medium and luminous homegeneity





Cove Light

Product installed: Rubber 3D Optic
White Finish | Optic 20°
Installation distance: 3.9 in.
Wall length: 107 ft
Walkway lighting:
250lux medium



Lighting of complex geometries

Product installed: Rubber 3D Optic
White Finish | Optic 20°
Installation distance: 3.9 in.
Rubber Length: 500 inPylon section: elliptical

Walkway lighting:
110lux average in an area
of 13 ft from the pylon

Rubber 3D Optic

IP67 C.V.

3D



Male + Female 9.8" feed cables





*See mounting instructions for field cutting

Code	Type	CCT	Code	Optics	Code	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered) *	LEDs/ft	Length	Min. bending Radius
E82216	White	2700 K	**M**	Elliptic / spot	**20**	85	24V	6.7 W	662	535	10.8	39.4 in.	9.9 in.
		3000 K	**W**	Elliptic / floo	**30**				697	563			
		4000 K	**N**						732	592			
E82217	White	2700 K	**M**	Elliptic / spot	**20**	85	24V	6.7 W	667	536	10.8	59 in.	9.9 in.
		3000 K	**W**	Elliptic / floo	**30**				702	564			
		4000 K	**N**						737	592			
E82218	White	2700 K	**M**	Elliptic / spot	**20**	85	24V	6.7 W	666	522	10.8	118.1 in.	9.9in.
		3000 K	**W**	Elliptic / floo	**30**				701	550			
		4000 K	**N**						736	577			

Code	Type	CCT	Code	Optics	Code	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered) *	LEDs/ft	Length	Min. bending Radius
E82219	Black	2700 K	**M**	Elliptic / spot	**20**	85	24V	6.7 W	662	535	10.8	39.4 in.	9.9 in.
		3000 K	**W**	Elliptic / floo	**30**				697	563			
		4000 K	**N**						732	592			
E82220	Black	2700 K	**M**	Elliptic / spot	**20**	85	24V	6.7 W	667	536	10.8	59 in.	9.9 in.
		3000 K	**W**	Elliptic / floo	**30**				702	564			
		4000 K	**N**						737	592			
E82221	Black	2700 K	**M**	Elliptic / spot	**20**	85	24V	6.7 W	666	522	10.8	118.1 in.	9.9in.
		3000 K	**W**	Elliptic / floo	**30**				701	550			
		4000 K	**N**						736	577			

* Delivered lm calculated with Optic 20

Electronics

OT96-D010
Dry location 96W 24V
0-10V 10% dimmable

OT96-JBX
Wet location 96W 24V
Non-dim

LUT96-L3D0
Dry location 96W 24V
EcoSystem/3-wire 0.1% dimmable

index
technical information

Profile

E99549
Linear profil
Length 39.4 in
Anod. Al.



E83034
Linear profile with cable ru
Length 39.4 in
Anod. Al.



E99536
Clip with toothed spring
Length 2 in
Anod. Al.



E99537
Clip with toothed spring with cable run
Length 2 in
Anod. Al.

Cables

E99688 female connector
E99689 male connector
78.7 in

Rubber 2D (Side bend)

2D

Rubber 2D and the new Rubber 2D Mini complete the Rubber family, expanding the range of choices. Rubber 2D is extremely flexible and can bend all the way to cover a very narrow radius, perfectly adapting to the sinuous profiles, and following curves and reverse curves. Rubber 2D is available up to 196.8 in. length maximum per single roll and can be cut every 2, allowing great composition adaptability. IP67 guarantees various outdoor installation environments. Thanks to the connection with in/out cables, the light is uniform and constant along its entire length, even at the junction points. Minimum curvature radius: 9.9".

2D ↔

Sancta sanctorum | Biella, Italy

Rubber 2D (Side bend)

IP67 ≤3 SDCM C.V.

2D ↔



Male + Female 9.8"
feed cables





*See mounting instructions for field cutting

Code	Type	CCT	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered)	LEDs/ft	Length	Min. bending Radius
E80409	White	2700 K	85	24V	3 W	321	132	42	39.4 in.	9.9 in..
E80410	White	3000 K	85	24V	3 W	347	143	42	39.4 in.	9.9 in.
E80411	White	4000 K	85	24V	3 W	375	154	42	39.4 in.	9.9 in.
E80412	White	2700 K	85	24V	3 W	323	133	42	196.8 in.	9.9 in.
E80413	White	3000 K	85	24V	3 W	349	144	42	196.8 in.	9.9 in.
E80414	White	4000 K	85	24V	3 W	377	155	42	196.8 in.	9.9 in.

Electronics

OT96-D010
Dry location 96W 24V
0-10V 10% dimmable

OT96-JBX
Wet location 96W 24V
Non-dim

LUT96-L3D0
Dry location 96W 24V
EcoSystem/3-wire 0.1% dimmable

index
technical information

Profile

E99549
Linear profil
Length 39.4 in

IK10 Anod. Al.



E83034
Linear profile with cable ru
Length 39.4 in

IK10 Anod. Al.



E99536
Clip with toothed spring
Length 2 in

Anod. Al.



E99537
Clip with toothed spring with cable run
Length 2 in

Anod. Al.

Cables

E99688 female connector
E99689 male connector
78.7 in

Rubber 2D Mini (Side bend)

Rubber 2D Mini

Like the standard 0.5 model, the Mini version is also an ideal solution for curves and reverse curves that demand bending on a single axis, combining flexible installation with high performance. IP67 certified, it differs from any other Rubber with its extremely reduced dimensions. Rubber 2D Mini packs in just 0.2" a custom designed circuit that allows extremely high performance to be achieved with very thin light for discrete and elegant linear effects. Just like the internal electronics, the accessories, clips and profiles are also specifically designed for the minimum bulk of the strip. Minimum curvature radius: 5.9".

2D

0.2in



Rubber 2D Mini (Side bend)

IP67 C.V.

2D

Cables Length 9.9 in





*See mounting instructions for field cutting

Code	Type	CCT	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered)	LEDs/ft	Length	Min. bending Radius
E82147	White	2700 K	85	24V	1.5 W	155	39	42	39.4 in.	5.9 in.
E82148	White	3000 K	85	24V	1.5 W	165	42	42	39.4 in.	5.9 in.
E82149	White	4000 K	85	24V	1.5 W	180	46	42	39.4 in.	5.9 in.
E82150	White	2700 K	85	24V	1.5 W	155	37	42	196.8 in.	5.9 in.
E82151	White	3000 K	85	24V	1.5 W	168	41	42	196.8 in.	5.9 in.
E82152	White	4000 K	85	24V	1.5 W	181	44	42	196.8 in.	5.9 in.
E82153	White	2700 K	85	24V	1.5 W	155	35	42	393.8 in.	5.9 in.
E82154	White	3000 K	85	24V	1.5 W	168	38	42	393.8 in.	5.9 in.
E82155	White	4000 K	85	24V	1.5 W	181	41	42	393.8 in.	5.9 in.

Electronics

OT96-D010

Dry location 96W 24V
0-10V 10% dimmable

OT96-JBX

Wet location 96W 24V
Non-dim

LUT96-L3D0

Dry location 96W 24V
EcoSystem/3-wire 0.1% dimmable

index
technical information

Profile



E82846
Linear profil
Length 39.4 in

Anod. Al.



E82847
Clip
Length 2 in

Anod. Al.

Cables

E99688 female connector
E99689 male connector
78.7 in

Rubber 2D (Top bend)*

IP67 C.V.

2D



Male + Female 9.8"
feed cables





*See mounting instructions for field cutting

Code	Type	CCT	CRI	V	W/ft	lm/ft (Source)	lm/ft (Delivered)	LEDs/ft	Length	Min. bending Radius
E82203	White	3000 K	85	24V	5.8 W	211		18.3	39.4 in..	9.9 in.
		Red				45				
		Green				88				
		Blue				23				
E82204	White	3000 K	85	24V	5.8W	211		18.3	196.8 in.	9.9 in.
		Red				45				
		Green				88				
		Blue				23				

* Due to its LED configuration the product might show some LED imaging depending on the viewing angle

Electronics

EL96-DMX

Dry location 96W 24V
RGBW Sequencer, DMX
dimmable

index
technical information

Profile

E99549
Linear profil
Length 39.4 in

IK10 Anod. Al.



E83034
Linear profile with cable ru
Length 39.4 in

IK10 Anod. Al.



E99536
Clip with toothed spring
Length 2 in

Anod. Al.



E99537
Clip with toothed spring with cable run
Length 2 in

Anod. Al.

Cables

E99692 female con. RGBW
E99693 male con. RGBW
78.7 in

Rubber | Linear profile



		description
E99549	Anod. Al.	39.3 x 0.71 x 0.75 in.

suitable for: Rubber 2D / 3D
Not suitable for concrete applications

Rubber | Linear profile

		description
E80418	PVC	39.3 x 0.71 x 0.75 in.

suitable for: Rubber 2D / 3D
Suitable for concrete applications
Only suitable for uplight applications

Rubber | Linear profile with cable run



		description
E83034	Anod. Al.	39.3 x 1.54 x 0.75 in.

suitable for: Rubber 2D / 3D
Not suitable for concrete applications

Rubber | Linear profile with cable run



		description
E80419	PVC	39.3 x 1.54 x 0.75 in.

suitable for: RuRubber 2D / 3D
Suitable for concrete applications
Only suitable for uplight applications

Rubber mini | Linear profile



		description
E82846	Anod. Al.	39.3 x 0.79 x 0.39 in.

suitable for: Rubber 2D Mini
Not suitable for concrete applications

Rubber | Linear profile

		description
E99541	Anod. Al.	41.1 x 0.75 x 0.64 in.

suitable for: Rubber 2D / 3D
Not suitable for concrete applications

Rubber | Clip with toothed spring

		description
E99536	Anod. Al.	1.9 x 0.91 x 0.83 in.

suitable for: Rubber 2D / 3D
Not suitable for concrete applications

Rubber | Clip with toothed spring with cable run

		description
E99537	Anod. Al.	1.9 x 1.61 x 0.83 in.

suitable for: Rubber 2D / 3D
Not suitable for concrete applications

Rubber | Clip

		description
E80733	PVC	1.9 x 0.71 x 0.75 in.

suitable for: Rubber 2D / 3D
Not suitable for concrete applications
Only suitable for uplight applications

Rubber | Clip with cable run

		description
E80734	PVC	1.9 x 1.54 x 0.75 in.

suitable for: Rubber 2D / 3D
Not suitable for concrete applications
Only suitable for uplight applications

Rubber mini | Clip with toothed spring

		description
E82847	Anod. Al.	1.9 x 0.79 x 0.39 in.

suitable for: Rubber 2D Mini
Not suitable for concrete applications

index
technical information

Rubber | Cap kits

	description
E99539	

suitable for: Rubber 2D / Rubber 3D

Rubber | Cap kits

	description
E99538	

suitable for: Rubber 2D Mini

Rubber | Preparation Kit for concrete pouring

	description
E99521	39.37 in.

suitable for: Rubber 2D / Rubber 3D

Rubber | Cable with female connector

	description
E99688	78.7 in. 2x #22AWG

suitable for: Rubber 2D / Rubber 3D

Rubber | Cable with male connector

	description
E99689	78.7 in. 2x #22AWG

suitable for: Rubber 2D / Rubber 3D

Rubber | Cable with female connector RGBW

	description
E99692	78.7 in. 5x #22AWG

suitable for: Rubber 3D RGBW

Rubber | Cable with male connector RGBW

	description
E99693	78.7 in. 5x #22AWG

suitable for: Rubber 3D RGBW

index
technical information

Cables

Power cable & 0-10V | 24V DC

connectors	sec. Ø	suitable for	L ft	
F 5 pin M12	5 x 20 awg	Thin 66 RGBW	16.4	**E89362**
		Paseo		
		Xenia		

Extension power cable & 0-10V | 24V DC

connectors	sec. Ø	suitable for	L ft	
M + F 5 pin M12	5 x 20 awg	Thin 66 RGBW	32.8	**E89361**
		Paseo		
		Xenia		

Power cable | 120V AC - 24V DC

connectors	sec. Ø	suitable for	L ft	
F. 4 pin M12	4 x 20 awg	Paseo	4.9	**E99216**
		Xenia	16.4	**E89190**
		Thin 66		

Power cable | 120V AC - 24V DC

connectors	sec. Ø	suitable for	L ft	
M 4 pin M12	4 x 20 awg	Paseo	4.9	**E98476**
		Xenia	16.4	**E98477**
		Thin 66		

Extension power cable | 120V AC - 24V DC

connectors	sec. Ø	suitable for	L ft	
M + F 4 pin M12	4 x 20 awg	Paseo	3.3	**E98437**
		Xenia	16.4	**E98149**
		Thin 66	32.8	**E89188**

Power cable | 120V AC

connectors	sec. Ø	suitable for	L ft	
F 3 pin	3 x 15 awg	Archiline	6.6	**E99057**

Power cable | 120V AC

connectors	sec. Ø	suitable for	L ft	
M 3 pin	3 x 15 awg	Archiline	6.6	**E99056**

Extension power cable | 120V AC

connectors	sec. Ø	suitable for	L ft	
M / F 3 pin	3 x 15 awg	Archiline	16.4	**E98147**
			32.8	**E98146**

Power cable | 24V DC

connectors	sec. Ø	suitable for	L ft	
M 2 pin	2 x 15 awg	Archicove	0.8	**E98879**

Extension power cable | 24V DC

connectors	sec. Ø	suitable for	L ft	
M / F 2 pin	2 x 15 awg	Archicove	3.3	**E98878**

Power cable | 120V AC

connectors	sec. Ø	suitable for	L ft	
M 2 pin	2 x 18 awg	Archicove	0.8	**E98713**

Extension power cable | 120V AC

connectors	sec. Ø	suitable for	L ft	
M / F 2 pin	2 x 18 awg	Archicove	3.3	**E98716**

Power cable + DMX cable

connectors	sec. Ø	suitable for	L ft	
M 5 pin	2 x 15 awg + 2 x 24 awg + shield	Archicove	0.8	**E98715**

Extension power cable + DMX cable

connectors	sec. Ø	suitable for	L ft	
M / F 5 pin	2 x 15 awg + 2 x 24 awg + shield	Archicove	3.3	**E98718**

Cables

DMX cable

connectors	sec. Ø	suitable for	L ft	
M 5 pin M12 + M 5 pin XLR	2 x 15 awg + 2 x 24 awg + shield	Archicove	16.40	**E98987**

DMX cable

connectors	sec. Ø	suitable for	L ft	
M 5 pin M12	2 x 23 awg + shield	Paseo Xenia	16.40	**E89189**

DMX cable

connectors	sec. Ø	suitable for	L ft	
M 5 pin M12 + M 3 pin XLR	2 x 23 awg + shield	Paseo Xenia	16.40	**E89186**

DMX cable

connectors	sec. Ø	suitable for	L ft	
M 5 pin M12 + F 3 pin XLR	2 x 23 awg + shield	Paseo Xenia	16.40	**E98494**

DMX cable

connectors	sec. Ø	suitable for	L ft	
M 5 pin M12 + M 5 pin XLR	2 x 23 awg + shield	Paseo Xenia	16.40	**E98493**

Extension DMX cable

connectors	sec. Ø	suitable for	L ft	
M / F 5 pin M12	2 x 23 awg + shield	Paseo	32.81	**E89187**
			16.40	**E98993**
			3.28	**E98994**

ALLinONE Power and DMX cable | 120V AC - 48V DC

connectors	sec. Ø	suitable for	L ft	
F 6 pin	3 x 15 awg + 2 x 24 awg + shield	Archiline RGBW	3.28	**E98660**
			16.40	**E98661**

ALLinONE extension power and DMX cable | 120V AC - 48V DC

connectors	sec. Ø	suitable for#	L ft	
M / F 6 pin	3 x 15 awg + 2 x 24 awg + shield	Archiline RGBW	3.28	**E98662 #**
			16.40	E98663

cables

application	type	voltage	insulation	Ø	nomenclature	sec. awg	cable color	core color	cable gland	temperature	ref. emc	
indoor	--	high	FEP + PVC	0.2 in	--	3 x 21 awg	○	○○○	--	90°C	BV37T	**E99348**
indoor	--	high	PE	0.3 in	--	2 x 18 awg	○	●●	PG7	--	RZ21B	**E99349**
indoor	--	high	FEP + PVC	0.2 in	--	2 x 24 awg	○	○○	--	90°C	BT20Q	**E99350**
indoor	RGB	low	PVC + PVC	0.3 in	--	6 x 20 awg	●	○●●● ●●	PG7	--		**E84874**
outdoor	MONO	low	FEP + PCP	0.2 in	--	2 x 24 awg	●	●●	--	70-90°C	NT20N	**E99237**
outdoor	MONO	low	GUM	0.3 in	--	2 x 18 awg	●	●●	PG7	--	NIV1N	**E84888**
outdoor	MONO	low	GUM + PCP	0.3 in	H07RN8-F	2 x 18 awg	●	●●	PG9	60-90°C	NHV1N	**E84875**
outdoor	MONO	low	PVC + PVC	0.2 in	--	2 x 26 awg	●	●●	--	90°C	RL29N	**E99351**
outdoor	MONO	low	FEP + PCP	0.2 in	--	4 x 24 awg	●	●●●●	--	70-90°C	NTQ0N	**E99352**
indoor outdoor	MONO	low	FEP + FEP	0.1 x 0.1 in	--	2 x 24 awg	●●	●●	--	180°C	TT20A	**E84892**
outdoor	--	high	GUM + PCP	0.2 in	H05RN-F	2 x 20 awg	●	●●	PG7	60-90°C	NC27N	**E99353**
outdoor	--	high	GUM + PCP	0.3 in	H05RN-F	2 x 18 awg	●	●●	PG7	60-90°C	NC21N	**E99229**
outdoor	--	high	GUM + PCP	0.3 in	H05RN-F	3 x 18 awg	●	●●◐	PG7	60-90°C	NC31N	**E84887**
outdoor	--	high	GUM + PCP	0.3 in	H07RN-F	3 x 18 awg	●	●●◐	PG9	60-90°C	NN31N	**E84863**
outdoor underwater	MONO	low	NEOPRENE	0.2 in	--	2 x 24 awg	●	●●	--	70-90°C	NT20N	**E99002**
outdoor underwater	MONO	low	NEOPRENE	0.3 in	--	3 x 18 awg	●	●●◐	PG9	--	ONT1N	**E84876**
outdoor underwater	RGB	low	NEOPRENE	0.4 in	--	7 x 18 awg	●	○●●● ●●◐	PG9	--	NIB1N	**E84864**

Extension cables

application	voltage	insulation	sec. awg	color	temperature	
indoor	low	PVC	3 x 24 awg	●●●	90°C	**E84866**
indoor	low	PVC	3 x 24 awg	●●●	90°C	**E84867**
indoor	low	PVC	3 x 24 awg	●●●	90°C	**E84872**
indoor	low	PVC	3 x 24 awg	●○●	90°C	**E84873**

The conductor cables to utilize for installing our outdoor fixtures has to be NEOPRENE H07 that respond to technical requests of EN60598 sez. 5.2.2:

- Temperature of use 90°C
- Type of conductor red copper wire
- Execution tension 450/750V
- Nomenclature H07RN-F
- Conforming of the normative CEI 20-19
- Conforming on the requests of directive B.T.73/23CEE e 93/68CEE

The cable is suitable for humid and dry outdoor ambient; Water resist, on erosion, on frequent flexions.
The cable resist on temperature up to –25°C without any superficial crackles; is necessary to protect it anyway even on surface that is use for pathways or drive over in order to prevent curving at 30°.

Cables | DMX

connectors	sec. Ø	L ft	
F 3 pin XLR	2 x 23 awg + shield	1	**E84895**
		16.4	**E84994**

Extension cables | DMX

connectors	sec. Ø	L ft	
M + F 3 pin XLR	2 x 23 awg + shield	1	**E84871**
		16.4	**E84885**

Connectors | DMX

connectors	sec. Ø	L ft	
XLR		3 M	**E84869**
		3 F	**E84870**
		5 M	**E99346**
		5 F	**E99379**

.....	GND	1
———	B	2
———	A	3



.....	GND	1
———	B	2
———	A	3
		4
		5



Connector | DMX 120 Ω Terminator

*accessory to be installed obligatorily at the end of each continuous row of appliances.

suitable for	input	output	
*Paseo RGBW *Paseo_PIXEL RGB *Xenia 2.0 RGBW	Bus DMX 512	120 Ohm	**E89365**

Connector | DMX 120 Ω Terminator

*accessory to be installed obligatorily at the end of each continuous row of appliances.

suitable for	input	output	
*Archiline RGBW	Bus DMX 512	120 Ohm	**E98986**

Connector splitter | ALLinONE splitter power/DMX



Start splitter

suitable for	input	output	
Archiline RGBW	1 3 x 15 awg (for power supply) 2 2 x 23 awg (for DMX) +shiel	3 ALLinONE F 3 x 15 awg + 2 x 24 awg +shield	**E98985**



Continuity splitter A

suitable for	input	output	
Archiline RGBW	1 ALLinONE M 3 x 15 awg + 2 x 24 awg +shield 2 3 x 15 awg (for power supply)	3 ALLinONE F 3 x 15 awg + 2 x 24 awg +shield	**E99390**

Continuity splitter B

input	output	
1 ALLinONE M 3 x 15 awg + 2 x 24 awg +shield 2 3 x 15 awg (for power supply)	3 ALLinONE F 3 x 15 awg + 2 x 24 awg +shield	**E98999**



Outer casings

type	suitable for	
PVC	Elin 0.5W - 1W	**E84335**

type	suitable for	
PVC	Envelope Vand	**E84336**

type	suitable for	
PVC	Illmat	**E84337**

type	suitable for	
PVC	Quara_R - Quara_Q Quara65_R - RI - F Quara65_Q - QI Cut	**E84338**

type	suitable for	
PVC	Ture 2W Gude 1.6 inch	**E84901**

type	suitable for	
PVC	Bibok 1W Elin 5W	**E84916**



type	suitable for	
PVC	Eibok Ture 1.5W - 2W Gude 0.78 inch	**E84917**

type	suitable for	
PVC	Ture - Gude	**E84954**

type	suitable for	
PVC	Envelope Sand	**E84915**

Outer casings



type	suitable for	
PVC	Quara65_QI 4W	**E98050**



type	suitable for	
PVC	Envelope_W R	**E98111**

type	suitable for	
PVC	Laella	**E98950**

Accessories



Thickness **E60830**



Glass **E60860**



Peg **E64758**

Compass Key **E84992**



IP68 connector **E89548**



how to read products



D

SueloPRO_RX | Up-Light | powerLED | Wet location | Driver remote | Driver over | 7.2W

C.C. - 630 mA

A

Steel Alu **E80561**	2700K	[illegible]	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
HC Steel Alu **E80562**	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**
DL B **E80563**					

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdriver 30W for 1-3 fixtures	0-10V EldoLED ECOdriver 50W for 1-4 fixtures	0-10V EldoLED ECOdriver 100W for 1-8 fixtures

C.V. - 24V

Steel Alu **E80567**	2700K	877 lm	**M**	Narrow Spot	**06**
	3000K	945 lm	**W**	Spot	**15**
HC Steel Alu **E80568**	4000K	1013 lm	**N**	Medium Flood	**30**
				Flood	**60**
DL Steel Alu **E80569**					

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E98121 Outer casing for wall-mounted installation

Suelo_RXJ | Up-Light | powerLED | Wet location | Driver remote | Adjustable | Driver over | 7.2W

C.C. - 630 mA

Steel Alu **E80577**	2700K	709 lm	**M**	Medium Flood	**20**
	3000K	760 lm	**W**	Medium Flood	**30**
	4000K	821 lm	**N**	Flood	**60**

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdriver 30W for 1-3 fixtures	0-10V EldoLED ECOdriver 50W for 1-4 fixtures	0-10V EldoLED ECOdriver 100W for 1-8 fixtures

C.V. - 24V

Steel Alu **E80579**	2700K	709 lm	**M**	Medium Flood	**20**
	3000K	760 lm	**W**	Medium Flood	**30**
	4000K	821 lm	**N**	Flood	**60**

C

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

E98121 Outer casing for wall-mounted installation

Guide to the composition of the finished part number

A

1st product code — 2nd temperature code — 3rd optics code*

C.C. - 630 mA

Steel Alu **E80577**	2700K	709 lm	**M**	Medium Flood	**20**
	3000K	760 lm	**W**	Medium Flood	**30**
	4000K	821 lm	**N**	Flood	**60**

E80577M20

B

Control

Product code

Temperature color

SueloPRO_RX | Up-Light | powerLED | Wet location | Driver remote | Driver over | 7.2W



C.C. - 630 mA

	Steel Alu **E80561**	2700K	877 lm	**M**	Narrow Spot	**06**
		3000K	945 lm	**W**	Spot	**15**
HC	Steel Alu **E80562**	4000K	1013 lm	**N**	Medium Flood	**30**
					Flood	**60**
DL	Steel Alu **E80563**					

Power supply options (remote only)

ECO30W-630	**SOLO50W-630**	**SOLO100W-630**
0-10V EldoLED ECOdriver 30W for 1-3 fixtures	0-10V EldoLED ECOdriver 50W for 1-4 fixtures	0-10V EldoLED ECOdriver 100W for 1-8 fixtures

Optics

Finishing

Internal configuration

Product measurements

Product image

Source nominal lumen

Luminous emission and other product info

C

Recessed casing dimensional

Recessed casing code

DL Steel Alu **E80569**

Power supply options (remote only)

OT96-D010	**OT96-JBX**
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 1; Wet location

Electronics information

Recessed casings

E98121
Outer casing for wall-mounted installation

D

Suelo_RXJ | Up-Light | powerLED | Wet location | Driver remote | Adjustable | Driver over | 7.2W

Family

Chapter

L.E.D type

IP gradation

Driver type

Product type

load capacity

Product power

how to read products



Edith_S | Ceiling luminaires | topLED | Damp Location | Driver remote | 30W 840mA

CRI 80

White	E96471	3000 K	4293 lm	W	General 00
		3500 K	4293 lm	T	
		4000 K	4495 lm	N	

4.4

23.4

Power supply options (remote only)

SOLO50W-840	SOLO100W-840
0-10V EldoLED ECOdriver 50W for 1 fixture	0-10V EldoLED ECOdriver 100W for 1-2 fixtures

A

E96471W00

Photometric curve | Light beam | 100 LUX | 150 LUX | 175 LUX | 200 LUX | 250 LUX | 300 LUX | 350 LUX | Floor plan

Endress+Hauser Italia | Milan, Italy

165 inter-lux.com MAESTRO 2.2

Photometry

Graphic representation of the solid photometric



Photometric curve

Application

Graphic representation of the installation prospectus of the product and its emission



Light beam

Isolux

Graphic representation of the distribution of the luminaires in a typical environment with reflection coefficients equal to 70% ceiling, 50% wall and 20% floor



Floor plan

Flat graphic representation of the distribution of the quoted luminaires in the typical environment



Floor plan

finishes materials



White | RAL 9003 embossed

Grey | RAL 9006 embossed

Satin finish



Anodized aluminum

Steel



Brushed nickel

Chrome



Anodized Black

Gray Black | RAL 7021 embossed

Black | RAL 9005 embossed

Transparent PMMA

Opaline PMMA

Gold

Rose gold

Brushed brass

Bronze

Sand

index

"Linea Light Group" reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information in the catalogue are binding for **"Linea Light Group"**. **"Linea Light Group"** will not be held liable for any illustration, text and/or translation errors. More product characteristics are contained in the relative technical data sheets and instruction sheets. This catalogue is protected by copyright (law 22/04/1941 No. 633 and law 14/12/1942 No. 1485: this prohibits any reproduction, total or even partial).
All values indicated in the catalogue are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

linea light group

inter•lux