

Archiline Aluminum Frame RGBW



General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm), Aluminum finish

Trim: 6060 Anodized Aluminum. Extra clear glass - Tempered

Mounting/Housing: Galvanized Steel (required for in ground installations).

Drive-over: Walk-Over only.

Dimensions/Weight: 14.6" (3.31 lbs) – 22.1" (6.17 lbs) – 41.4" (10.6 lbs)

Driver: Integral, 120-277V + DMX interface.

Wattages: 14.5W (14.6") – 24.5W (22.1") – 49W (41.4")

Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).

Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed. Available in Spot – Flood – Wide Flood – Elliptic, Asymmetric Wall Washer.

Color temperatures: RGBW with 3000K Warm White – RGBW with 4000K Neutral White.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.




14.6" (14.5W)
22.1" (24.5W)
41.4" (49W)

Nominal Lumens RGB/RGBW	14.6"	22.1"	41.4"
Red	177	295	590
Green	291	475	950
Blue	105	175	350
White 3K/4K	462 / 495	770 / 825	1540 / 1650

Ordering Information										
Product	Mounting/ Frame	Type	Length	Wattage	Operation	Color Temp	Optic	+	Housing (Required) ¹	Cables ¹
AR = Archiline	RAF = Recessed Aluminum Frame	F = Fixed	15 = 14.6" 22 = 22.1" 41 = 41.4"	15 = 14.5W 25 = 24.5W 49 = 49W	IDMX = Integral w/DMX interface	R3 = RGBW (3K) R4 = RGBW (4K)	SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer WW = Wall Washer		E98671 (15) E98672 (22) E98673 (41)	E98660 E98661 E98662 E98663 E98986

¹ See page 2

14.6" 14.5W IDMX




HOUSING

E98671

Outer Housing



22.1" 22.1W IDMX




HOUSING

E98672

Outer Housing



41.4" 49W IDMX



HOUSING

E98673

Outer Housing



Cables power+DMX

E98660

39.4" feed cable
all in one
power + DMX
M+F 6 pin shield

E98661

196.9" feed cable
all in one
power + DMX
M+F 6 pin shield

E98662

39.4" extension
all in one
power + DMX
M+F 6 pin shield

E98663

196.9" extension
all in one
power + DMX
M+F 6 pin shield

E98986

DMX 1200
terminator