

Archiline Frameless Frosted



General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (15 µm), Black finish

Trim: Frameless, ideal for continuous runs. Anti-slip, Tempered Glass.

Mounting/Housing: Anodized Black (15 µm) Aluminum 6060 housing (required for in ground installations).

Drive-over: Up to 11,023 lbs.

Dimensions/Weight: 12.6" (3.31 lbs) – 20.1" (6.17 lbs) – 39.4" (10.6 lbs)

Driver: Integral, 120-277V Dimmable 0-10V or Non-Dim.

Wattages: 5W (12.6") – 8.6W (20.1") – 14.3W (39.4")

Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).

Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed Frosted.

Color temperatures: 2700K – 3000K – 3500K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



12.6" (5W)
20.1" (8.6W)
39.4" (14.3W)


Delivered Lumens	12.6"	20.1"	39.4"
General	96	146	291

*Values shown for 3000K

Ordering Information										
AR	RF	FR			ID			GE		
Product	Mounting/ Frame	Type	Length	Wattage	Operation	Color Temp	Optic	+	Housing (Required) ¹	Cables ¹
AR = Archiline	RF = Recessed Frameless	FR = Frosted	12 = 12.6"	5 = 5W	ID = Integral (0-10V dim)	27 = 2700K	GE = General Illumination		E98724 (12) E98725 (20) E98726 (39)	E99826 E99822 E99823 E99824 E99825
			20 = 20.1"	9 = 8.6W		30 = 3000K				
			39 = 39.4"	14 = 14.3W		35 = 3500K 40 = 4000K				

¹ See page 2

12.6" 5W ID




HOUSING

E98724

Outer Housing
12.68" L x 2.95" W x 5.51" H



20.1" 8.6W ID




HOUSING

E98725

Outer Housing
20.20" L x 2.95" W x 5.51" H



39.4" 14.3W ID



HOUSING

E98726

Outer Housing
39.49" L x 2.95" W x 5.51" H



Cables 0-10V

E99826

39.4" power supply cable
+0-10V dimming
F 5 pin

E99822

196.9" power supply cable
+0-10V dimming
F 5 pin

E99823

39.4" extension cable for power
+0-10V dimming
M+F 5 pin

E99824

196.9" extension cable for power
+0-10V dimming
M+F 5 pin

E99825

393.7" extension cable for power
+0-10V dimming
M+F 5 pin