

# Archiline Frameless RGBW



**General:** Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

**Fixture Body:** Corrosion resistant 6060 Aluminum, Anodized (15 µm), Black finish

**Trim:** Frameless, ideal for continuous runs. Extra clear glass - Tempered

**Mounting/Housing:** Anodized Black (15 µm) Aluminum 6060 housing (required for in ground installations).

**Drive-over:** Up to 11,023 lbs.

**Dimensions/Weight:** 12.6" (3.31 lbs) – 20.1" (6.17 lbs) – 39.4" (10.6 lbs)

**Driver:** Integral, 120-277V + DMX interface.

**Wattages:** 14.5W (12.6") – 24.5W (20.1") – 49W (39.4")

**Cable:** Fixture comes with 0.66' of cable (Power cable required, ordered separately).

**Safety features:** Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

**IP rating:** IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

**IK rating:** IK 10

**ETL Certification:** ETL, wet location

**Optics:** Fixed. Available in Spot – Flood – Wide Flood – Elliptic, Asymmetric Wall Washer.

**Color temperatures:** RGBW with 3000K Warm White – RGBW with 4000K Neutral White.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.




12.6" (14.5W)  
20.1" (24.5W)  
39.4" (49W)

Nominal Lumens RGB/RGBW	12.6"	20.1"	39.4"
Red	177	295	590
Green	291	475	950
Blue	105	175	350
White 3K/4K	462 / 495	770 / 825	1540 / 1650

Ordering Information										
AR	RF	F			IDMX					
Product	Mounting/ Frame	Type	Length	Wattage	Operation	Color Temp	Optic	+	Housing (Required) <sup>1</sup>	Cables <sup>1</sup>
AR = Archiline	RF = Recessed Frameless	F = Fixed	12 = 12.6"	15 = 14.5W	IDMX = Integral w/DMX interface	R3 = RGBW (3K) R4 = RGBW (4K)	SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer WW = Wall Washer		E98724 (12)	E98660
			20 = 20.1"	25 = 24W					E98725 (20)	E98661
			39 = 39.4"	49 = 49W					E98726 (39)	E98662 E98663 E98986

<sup>1</sup> See page 2

## 12.6" 14.5W IDMX




### HOUSING

#### E98724

Outer Housing  
12.68" L x 2.95" W x 5.51" H



## 20.1" 24.5W IDMX




### HOUSING

#### E98725

Outer Housing  
20.20" L x 2.95" W x 5.51" H



## 39.4" 49W IDMX



### HOUSING

#### E98726

Outer Housing  
39.49" L x 2.95" W x 5.51" H



### Cables power+DMX

E98660	E98661	E98662	E98663	E98986
39.4" feed cable all in one power + DMX M+F 6 pin shield	196.9" feed cable all in one power + DMX M+F 6 pin shield	39.4" extension all in one power + DMX M+F 6 pin shield	196.9" extension all in one power + DMX M+F 6 pin shield	DMX 1200 terminator