

# Archiline PRO Wall RGBW

inter•lux



**General:** Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

**Fixture Body:** Corrosion resistant 6060 Aluminum, Anodized (20 µm), Aluminum finish

**Trim:** Frameless, ideal for continuous runs. Extra clear glass - Tempered

**Mounting:** 316 Marine Grade Steel adjustable bracket.

**Dimensions/Weight:** 14" (6.39 lbs) – 20.3" (7.50 lbs) – 40" (13.67 lbs)

**Driver:** Integral, 120-277V + DMX interface.

**RGBW Color Mixing:** 14" (6x Quad-Chip powerLEDs) / 20.3" (9x Quad-Chip powerLEDs) / 40" (18x Quad-Chip powerLEDs)

**Wattages:** 30W (14") – 44W (20.3") – 86W (40")

**Cable:** Fixture comes with 0.56' of cable (Power cable required, ordered separately).

**Safety features:** Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

**IP rating:** IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

**IK rating:** IK 10

**ETL Certification:** ETL, wet location

**Optics:** Fixed. Available in Narrow Spot – Spot – Flood – Wide Flood – Elliptic. Archiline PRO comes with Dark Light (Anti-glare) system as a standard feature.

**Color temperatures:** RGBW with 3000K Warm White – RGBW with 4000K Neutral White.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



14" (30W)

20.3" (44W)

40" (86W)


Nominal Lumens RGB/RGBW	14"	20.3"	40"
Red	270	405	702
Green	522	783	1404
Blue	84	126	216
White 3K/4K	474 / 594	711 / 891	1260 / 1566

Ordering Information								
ARP	W	DL			IDMX			
Product	Mounting/ Frame	Type	Length	Wattage	Operation	Color Temp	Optic	+ Cables <sup>1</sup>
ARP = Archiline PRO	W = Wall	DL = DarkLight	14 = 14"	30 = 30W	IDMX = Integral w/DMX interface	R3 = RGBW (3K) R4 = RGBW (4K)	NSP = Narrow Spot SP = Spot FL = Flood MFL = Medium Flood EL = Elliptic/Graze	E98660
			20 = 20.3"	44 = 44W				E98661
			40 = 40"	86 = 86W				E98662 E98663 E98986


<sup>3</sup> See page 2




14" 30W IDMX



20.3" 44W IDMX



40" 86W IDMX



Cables power+DMX

E98660	E98661	E98662	E98663	E98986
39.4" feed cable all in one power + DMX F 6 pin to bare leads	196.9" feed cable all in one power + DMX F 6 pin to bare leads	39.4" extension all in one power + DMX M+F 6 pin	196.9" extension all in one power + DMX M+F 6 pin	DMX 120Ω terminator