

Archiline Stainless Steel Frame RGBW

inter•lux



General: Archiline is a family of high-output, low glare linear LED in-grade and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The PRO version reaches up to 150', making it perfect for tall buildings and towers. Available in Frameless (Drive-Over), Aluminum or Stainless-Steel frame, with a broad range of optics, from Narrow Spot to Asymmetric Wall Washer and Elliptic. Its unique Dark Light (anti-glare) system provides a must-see quiet illumination, while losing almost no output.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (15µm), Black finish

Trim: 316 Marine Grade Stainless Steel, Brushed. Extra clear glass - Tempered

Mounting/Housing: Galvanized Steel (required for in ground installations).

Drive-over: Walk-Over only.

Dimensions/Weight: 14.8" (3.31 lbs) – 22.2" (6.17 lbs) – 41.6" (10.6 lbs)

Driver: Integral, 120-277V + DMX interface.

RGBW Color Mixing: 14.8" (3x4 LEDs) / 22.2" (5x4 LEDs) / 41.5" (10x4 LEDs)

Wattages: 14.5W (14.8") – 24.5W (22.2") – 49W (41.6")

Cable: Fixture comes with 0.66' of cable (Power cable required, ordered separately).

Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed. Available in Spot – Flood – Wide Flood – Elliptic, Asymmetric Wall Washer.

Color temperatures: RGBW with 3000K Warm White – RGBW with 4000K Neutral White.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



14.8" (14.5W)

22.2" (24.5W)

41.6" (49W)


Nominal Lumens RGB/RGBW	14.8"	22.2"	41.6"
Red	177	295	590
Green	291	475	950
Blue	105	175	350
White 3K/4K	462 / 495	770 / 825	1540 / 1650

Ordering Information										
AR	RSF	F			IDMX			+		
Product	Mounting/ Frame	Type	Length	Wattage	Operation	Color Temp	Optic		Housing (Required) ¹	Cables ¹
AR = Archiline	RSF = Recessed Stainless Steel Frame	F = Fixed	15 = 14.8"	15 = 14.5W	IDMX = Integral w/DMX interface	R3 = RGBW (3K) R4 = RGBW (4K)	SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer WW = Wall Washer		E98671 (15) E98672 (22) E98673 (42)	E98660
			22 = 22.2"	25 = 24.5W						E98661
			42 = 41.6"	49 = 49W						E98662 E98663 E98986

¹ See page 2



14.8" 14.5W IDMX




HOUSING

E98671
Outer Housing



22.2" 24.5W IDMX




HOUSING

E98672
Outer Housing



41.6" 49W IDMX



HOUSING

E98673
Outer Housing



Cables power+DMX

E98660	E98661	E98662	E98663	E98986
39.4" feed cable all in one power + DMX F 6 pin to bare leads	196.9" feed cable all in one power + DMX F 6 pin to bare leads	39.4" extension all in one power + DMX M+F 6 pin	196.9" extension all in one power + DMX M+F 6 pin	DMX 1200 terminator