

Beret Round Frosted



General: Beret is a small and shallow in-grade suitable to illuminate outdoor architectural details such as columns or walls. Beret can also be used as a way finder, or to illuminate landscape details.

Fixture Body: Different options like Brass (Powder Coated, Chrome or Nickel finished), Steel.

Trim/Diffuser: Semi-Flush trim. Diffused glass.

Mounting/Casing: Black, ABS casings available for both Concrete or Tile installation.

Drive-over: Walk-over only.

Dimension/Weight: 1.4" (0.14 lbs)

Driver: Remote, Constant Current. 120-277V Dimmable 0-10V or Non-Dim.

CC features: Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

Wattage: 1W & 2W (1.4")

Cable: Fixture comes with 3.28' of power cable and built-in Aquastop® (anti-wicking) system

IP rating: IP66 for protection against dust and powerful water jets from any angle.

IK rating: IK 05

ETL Certification: ETL, wet location

Optics: Fixed, with General distribution (Frosted).

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



1.4" (1W)

1.4" (2W)

Delivered Lumens*	1W	2W
GE	28	45

*Values shown for 3000K

Ordering Information							(Required) ²		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
BER = Beret	RSFWH = Round Semi-Flush White ¹ RSFGR = Round Semi-Flush Grey ¹ RSFCH = Round Semi-Flush Chrome RSFNI = Round Semi-Flush Nickel RSFST = Round Semi-Flush St. Steel RSFBR = Round Semi-Flush Brass	FR = Fixed Frosted	1.4 = 1.4"	1 CC = 1W / Constant Current (350mA) 2 CC = 2W / Constant Current 630mA)	27 = 2700K 30 = 3000K 40 = 4000K	GE = General	+	E84915 (1W) E84336 (1W) E84918 (2W)	ECO30W-XXX SOLO50W-XXX SOLO100W-XXX

¹ 1W ONLY

² See page 2

Beret Round Frosted

1.4" 1W



Housing

E84915
Recessed Housing



E84336
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures

1.4" 2W



Housing

E84918
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures