Elin RGB









General: Elin is part of our Crystals collection. A series of small spot lights with crystal diffusers made in different shapes, some clear and some diffused but all of them with the goal to create a unique effect in the space.

Fixture Body: Brass (Chromium Plated).

Diffuser: Clear Glass.

Trim: Bezel.

Mounting: Semi-Recessed ceiling.

Dimensions/Weight: 0.8"@0.5W (0.03 lbs) - 0.8"@1W (0.11 lbs) - 0.8"@1.5W (0.15 lbs)

Driver: Remote, DMX 24VDC Constant Voltage, Dimmable.

Operation: Constant Voltage (CV).

Wattage: 0.5W (0.8")

Cable: Fixture comes with 0.39' of power cable.

IP rating: IP20. Fixture is protected against solid objects greater than 0.04". Not suitable for

Outdoor applications or any contact with water.

ETL Certification: ETL, dry location Optics: Fixed, General distribution.

Color temperatures: Color changing RGB.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



0.8" (0.5W)

Delivered Lumens*	0.8"
Red	3
Green	5
Blue	3

^{*}Values shown for 3000K

Ordering Information									
ELI	SFCH	D	08	0.5 - CVDMX	RGB	GE		E84916	EL96-DMX
Product	Trim/Film	Туре	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing ¹	Driver ¹
ELI = Elin	SFCH = Semi-Flush Chrome	D = Diamond Shaped Crystal	08 = 0.8"	0.5 CVDMX = 0.5W / Remote DMX 24VDC	RGB = RGB	GE = General distribution		E84916	EL96-DMX

¹ N/A for CV 1 See page 2






Elin RGB



0.8" 0.5W CVDMX



Housing

E84916

Recessed Housing



C.V. Power supply options

EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/order separately.



