


Giotto Pendant


FIXED

GIO-RWH-F-...-NSP...			
Delivered Lumens - Narrow Spot			
		Diameter [Wattage]	
		17 [4 CC]	17 [6 CC]
CCT	92-27-	33	-
	92-30-	36	48
	92-35-	36	48
	92-40-	39	52
Polar Plot / Cone Of Light Multiplier			
		17 [4 CC]	17 [6 CC]
		0.75	1.00




CONE OF LIGHT - 6W 3000K Narrow Spot GIO-RWH-F-17-6-CC-92-30-NSP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	267	0.5
4	67	1.0
6	30	1.5
8	17	2.0
10	11	2.5
12	7	3.0
14	5	3.5
16	4	4.0
18	3	4.5
20	3	5.0

GIO-RWH-F-...-FL...			
Delivered Lumens - Flood			
		Diameter [Wattage]	
		17 [4 CC]	17 [6 CC]
CCT	92-27-	95	129
	92-30-	103	139
	92-35-	103	139
	92-40-	111	150
Polar Plot / Cone Of Light Multiplier			
		17 [4 CC]	17 [6 CC]
		0.74	1.00



CONE OF LIGHT - 6W 3000K Flood GIO-RWH-F-17-6-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	124	1.3
4	31	2.5
6	14	3.8
8	8	5.1
10	5	6.3
12	3	7.6
14	3	8.9
16	2	10.2
18	2	11.4
20	1	12.7

GIO-RWH-F-...-WFL...			
Delivered Lumens - Wide Flood			
		Diameter [Wattage]	
		17 [4 CC]	17 [6 CC]
CCT	92-27-	66	90
	92-30-	71	96
	92-35-	71	96
	92-40-	77	104
Polar Plot / Cone Of Light Multiplier			
		17 [4 CC]	17 [6 CC]
		0.74	1.00



CONE OF LIGHT - 6W 3000K Wide Flood GIO-RWH-F-17-6-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	41	2.0
4	10	4.1
6	5	6.1
8	3	8.2
10	2	10.2
12	1	12.3
14	1	14.3
16	1	16.4
18	1	18.4
20	0	20.5


*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

** Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.

Giotto Pendant

PENDANT


GIO-RWH-P-...-FL...		
Delivered Lumens - Flood		
Diameter [Wattage]		
24x10 [8 CC]		
CCT	92-27-	151
	92-30-	161
	92-35-	161
	92-40-	174
Polar Plot / Cone Of Light Multiplier		
24x10 [8 CC]		
1.00		



Beam Angle (0-180) = 35.2
Beam Angle (90-270) = 35.0

CONE OF LIGHT - 7.5W 3000K Flood		
GIO-RWH-P-24x10-8-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	143	1.3
4	36	2.5
6	16	3.8
8	9	5.1
10	6	6.3
12	4	7.6
14	3	8.9
16	2	10.2
18	2	11.4
20	1	12.7

GIO-RWH-P-...-WFL...		
Delivered Lumens - Wide Flood		
Diameter [Wattage]		
24x10 [8 CC]		
CCT	92-27-	103
	92-30-	110
	92-35-	110
	92-40-	119
Polar Plot / Cone Of Light Multiplier		
24x10 [8 CC]		
1.00		



Beam Angle (0-180) = 54.2
Beam Angle (90-270) = 54.0

CONE OF LIGHT - 7.5W 3000K Wide Flood		
GIO-RWH-P-24x10-8-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	47	2.0
4	12	4.1
6	5	6.1
8	3	8.2
10	2	10.2
12	1	12.3
14	1	14.3
16	1	16.4
18	1	18.4
20	0	20.5

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

** Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.